Koken®

Koken TOOL CO., LTD.

INDEX

Z-SERIES P20–34

HAND
MANUALES P36–136

TITANIUM
DE TITANIO P138

ACCESSORIES
ACCESORIOS P140-176

Reproduction in whole or in part without proper and prior authorization is prohibited.

Se prohíbe la reproducción total o parcial sin la debida autorización previa.

Specifications or design of any product in this catalogue are subject to change without notice.

Las especificaciones o el diseño de cualquiera de los productos de este catálogo están sujetos a cambio sin previo aviso.

SCREWDRIVERS
DESTORNILLADORES P178-182

PLASTIC PROTECTOR
PROTECTORES PLÁSTICOS P260-262

IMPACT
DE IMPACTO P184-242

AUTOMOTIVE P264-284

SLEEVE-DRIVE P244-252

CONSTRUCTION
CONSTRUCCIÓN P286-296

INDUSTRIAL
INDUSTRIALES P254-258

RENEWAL KITS
JUEGOS DE PIEZAS DE REPUESTO P298-301

4763-125

■ TEST AND LABORATORY



Ko-ken uses a variety of test equipment. Strength is measured by the Static Load Test Machine that can measure torque load up to 5,000Nm. Durability is measured by the Cyclic Test Machine and corrosion resistance testing is done by the Salt Spray Test Machine. The test results are used to improve our standard products and assist with new product design and development.



■ DESIGN AND DEVELOPMENT

The 3D-CAD is used to improve standard products, designing new products and making customized items for special requirements. Trial products are regularly developed, manufactured and tested to improve the durability, appearance and functionality of all tools produced by Ko-ken.

■ FORGING

The Forming machines are used for the forging process. These machines can produce mass quantities of sockets and parts with high accuracy that ordinary drop forging machines can not achieve. On the other hand, ordinary forging machines are also used for small production runs.

■ TURNING

The forged steel is turned into required shapes and dimensions. The MC (Machining Center) operates with extraordinary speed and precision. The article number, size, logo, production number, and MADE IN JAPAN are marked on the products after the turning process has been completed.



■ HEAT TREATMENT



To make the tools stronger and more durable, proper heat treatment is critically important. The temperature and the time of the heat treatment are strictly regulated by a very accurate control device.

■ INSPECTION



Our products are periodically checked at each production process by inspection devices. Highly accurate 3-D measuring instruments are used to inspect and check dimensions.

FLAT DRIVE®

Flat Drive is designed to guarantee a flat surface contact between the socket and the bolt/nut.
The Flat contact reduces wear and allows to transmit a higher torque value.
The Flat Drive System is also used for the square drive end as well as the hexagonal or bi-hexagonal openings of the socket.

El diseño de Contacto Plano garantiza una superficie de contacto plana entre el vaso y el perno/tuerca. El contacto plano reduce el desgaste y permite transmitir un par mayor.
El Sistema de Contacto Plano se utiliza tanto para el extremo del cuadrado conductor como para la boca hexagonal o bi-hexagonal del vaso.

SOCKETS

SURFACE DRIVE



Surface drive sockets are designed to retain contact with flat sides of nut to transmit high torque and reduce nut wear.
These sockets are ideal for use on polished nuts, aluminum nuts and nuts with worn out points.

Los vasos de contacto curvo se diseñan para mantener el contacto con las caras planas de la tuerca y transmitir un alto par reduciendo el desgaste de la tuerca.
Estos vasos son ideales para utilizarse en tuercas pulidas, tuercas de aluminio y tuercas con puntas desgastadas.

NUT GRIP®

Twin balls at the 6-point opening hold bolt/nut tightly for safe and reliable work.



El perno/tuerca se sujeta firmemente por medio de dos bolas en la boca hexagonal para un trabajo seguro y fiable.

PATHFINDER®

The beveled flats of the 6-point opening of the PATHFINDER socket engage the nut almost immediately. PATHFINDER sockets are ideal for use with power tools in automatic assembly processes, as the power tool does not have to be totally stopped for the socket to engage the nut.

Las caras biseladas de la boca hexagonal del vaso GUÍA acoplan el vaso inmediatamente.
Los vasos GUÍA son ideales para su utilización con herramientas mecánicas en procesos de montaje automáticos, ya que no es necesario que la herramienta esté completamente parada para acoplar el vaso a la tuerca.

RATCHET HANDLE



S.O.D.H-System®

Two dogs are located in the ratchet body so that the dogs and springs are held securely in place while allowing the reversing lever and dog to switch smoothly.
The torque load on the gear it is transmitted vertically to the dog, and in turn, down the ratchet handle. This mechanism locks gears tightly in place while torque is being applied, thus avoiding any gear slippage.

Los dos trinquetes del cuerpo de la llave de carraca y sus muelles están dispuestos en el cuerpo de la llave de forma que se mantienen firmemente en posición permitiendo un cambio suave de la palanca de inversión y del trinquete.
El par sobre la rueda dentada se transmite verticalmente al trinquete, y al mismo tiempo al mango de la llave de carraca. Este mecanismo bloquea firmemente los dientes mientras se aplica el par, evitando así el deslizamiento de los mismos.

Two-Step Dog

Two flats hold two teeth of the ratchet gear, thus increasing the maximum torque load of the ratchet compared with a single-step system.

Los dientes de la rueda de la llave de carraca se inmovilizan por medio de dos dientes aumentando de esta forma el par máximo de la llave en comparación con el sistema de un paso.

Three-Step Dog

Two dogs are set in the same axis, and the three teeth hold the ratchet gear.
The enlarged contact area produces about 10% higher torque value and the S.O.D.H-System provides smooth and light movements.

Se disponen dos trinquetes en el mismo eje y la rueda de la llave de carraca se bloquea por medio de tres dientes.
El aumento de la superficie de contacto produce un aumento de par de aproximadamente 10% y el sistema S.O.D.H permite movimientos suaves y sin esfuerzo.

SHAPE of HANDLE

OVAL SHAPE SHANK

Unique designed oval shape shank provides extra strength and durability.

El particular diseño de caña de sección Ovalada proporciona más resistencia y duración.

KNURLING



Ratchets and Hinge handles have knurling on the grip to ensure the tool can be held securely.
Extension bars also have 6-point knurling on the outside of the female square drive. This gives a grip to hold with your fingers as well as preventing the tool from rolling on flat surfaces.

WOBBLE-FIX

One use as a flexible extension bar permitting movement up to 15°angle and the other as a normal extension bar.

Una, como alargadera flexible que permite trabajar con un ángulo de 15°,otra,como alargadera normal.

Fix



Wobble



STUD BOLT PULLER/SETTER

STUD BOLT PULLER

The body design was changed to hexagonal shape to minimize tolerances. This shape is also effective to lessen excessive load on cages and rollers inside the body.

RATCHET PULLER

Puller for tightening stud bolts. Go-through body allows puller to grip the stud bolt at any position along the stud. Three-roller protects the bolt from damage.

STUD BOLT SETTER

Special socket for installing a stud bolt. The bolt contacts with a steel ball to prevent the bolt from sticking onto the socket. After installing the bolt, turn anti-clockwise to remove the socket.



ATTACK DRIVER®

1 BLACK FINISHED HEAD

The top of Attack Driver is manganese phosphate treated to prevent chrome peeling off the head when it is struck.



1 3 HEAT TREATMENT FOR ANTI-CRACK

Special Heat treatment is applied on the parts of Attack Driver. Hardness of Striking head is slightly softer to prevent cracking. The cam part has higher hardness to improve anti-wear.

3 SPRING

Strong spring is used to convert the striking power efficiently into twisting power.

2 BODY SHAPE

Original body shape allows stronger grip. It makes it easier to convert the striking power into twisting power.

FREE-TURN GRIP

SPINNING CROSS WRENCH

The shaft of cross wrench turns freely within the knurled grip. The cross bar is removable for easy storage in a compact space.

FLEXIBLE SPEEDER

Free-turn grip allows speedy removal or replacement of wheel nuts. It can also be used as a hinge handle to tighten or loosen the nuts.

SPINNING SLIDE T-HANDLE

The knurled grip is attached in the middle of shaft for free turning. Oval shaped cross bar prevents the bar from turning inside the shaft during use.

IMPACT WHEEL NUT SOCKET

PLASTIC PROTECTOR

A detachable plastic protector is fitted to the socket to prevent damage to the wheel when working in tight areas.
The socket size and Ko-ken Mark printed on the shaft makes it easier to see if the socket is still rotating or stopped.

EXTRA THIN-WALLED

Thin-walled shape and 110mm length gives extra reach for nuts recessed deep inside the wheel.
They are ideal for aluminum wheel nuts where access to nut is very tight. Color coded shafts make size identification easy.

SPARK PLUG SOCKET

CLIP TYPE

It is designed to grip a spark plug securely at its hexagonal part by two stainless spring clips.
Internal brass guide holds the clips in place ensuring perfect alignment of the spark plug into the threaded plughole of the cylinder head and thus preventing thread damage.
The brass guide also eliminates stress loading and possible damage to the ceramic insulator.



License

TORX® / TORXplus® & LHSTIX®

TORX®/ TORXplus® and LHSTIX® are recognized as three of the most efficient fastening systems because of their ability to transfer greater torque, reduce end load and virtually eliminate tool slippage.

TORX®/ TORXplus® y LHSTIX® están reconocidos como los tres sistemas más efectivos de fijación debido a su mayor capacidad de transmitir par, reducir el par final y eliminar completamente el deslizamiento de la herramienta.

TORX® & TORXPLUS®

TORX®

TORXplus®



TORX® and TORXplus® are registered trademark of **Acument Intellectual Properties, LLC.**
Koken TOOL CO., LTD. holds the official license to use the trademark TORX® and TORXplus®.

TORX® y TORXplus® es una marca registrada de **Acument Intellectual Properties, LLC.**
Koken TOOL CO., LTD. cuenta con licencias oficiales para el uso de la marca TORX® y TORXplus®.

LHSTIX®

LHSTIX®

Line Head Straight

LH-S series

LHSTIX® is a registered trademark of **OSG CORPORATION** System Engineering Department.
Koken TOOL CO., LTD. holds the official license to use the trademark LHSTIX®.

LHSTIX® es una marca registrada de **OSG CORPORATION** System Engineering Department.
Koken TOOL CO., LTD. cuenta con licencia oficial para uso de la marca LHSTIX®.

Registered Trademarks

Koken®

工研®

Koken TOOLS®

Koken TOOL CO., LTD.®

HIGH PERFORMANCE TOOLS OF CONVINCING QUALITY

山下工業研究所®

山下工研®

S.O.D.H-System®

Flatdrive®

ATTACK DRIVER®

HANDY-ENDY®

PATHFINDER®

Nut Grip®

LOCK NUT BUSTER®

NUT TWISTER®

BOLT TWISTER®

Aerial Photograph

Warranty

WARRANTY

The trade mark Koken is your unqualified warranty against any defect in material or workmanship. Each Koken tool is built to more than meet the requirements of its intended use and is carefully checked before leaving the factory. Any Koken tool which fails because of defective material or workmanship will be repaired or replaced through your Koken dealer, to the exclusion of any further liability.

GARANTIA

La marca Koken es la garantía incondicional contra cualquier defecto de materiales o de fabricación. Todas las herramientas Koken están fabricadas para satisfacer con creces las exigencias del uso previsto y se inspeccionan meticulosamente antes de su expedición. Las herramientas Koken que fallen por defectos de materiales o de fabricación se repararán o reemplazarán a través del distribuidor Koken correspondiente, excluyendo cualquier otra responsabilidad.

ISO9001


ISO 9001
Management System Certificate

Certificate Number : JQA-1028

Organization :
KO-KEN TOOL CO., LTD.
656 NAKANO, KAKEGAWA-CITY, SHIZUOKA, JAPAN

JQA certifies that the above organization operates the Quality Management System, within the scope of the Appendix attached, which has been assessed and found to comply with the requirements of:

ISO 9001 :2008 / JIS Q 9001 :2008

Registration Date : November 6, 1995
Last Renewal Date : January 9, 2016
Expiry Date : September 14, 2018

NOBUAKI KOBAYASHI
PRESIDENT
1-25 KANDASUDACHO, CHIYODA-KU, TOKYO, JAPAN

JAPAN QUALITY ASSURANCE ORGANIZATION

JQA

ISO 9001
Appendix

Certificate Number JQA-1028 1 / 1

Organization
KO-KEN TOOL CO., LTD.

Scope of Registration:
THE DESIGN / DEVELOPMENT AND MANUFACTURE OF SOCKET WRENCH

Registration Date November 6, 1995
Last Renewal Date January 9, 2016
Expiry Date September 14, 2018

NOBUAKI KOBAYASHI
PRESIDENT

JAPAN QUALITY ASSURANCE ORGANIZATION

JQA

GENERAL / CONSIDERACIONES GENERALES

(a) Make sure you use the right type socket, whose opening fit the nut.
Asegurarse de utilizar el tipo de vaso adecuado, con una boca que se ajuste a la tuerca.

(b) For use on electric or air IMPACT Wrenches select IMPACT Sockets only.
Con llaves mecánicas de IMPACTO, utilizar solamente Vasos de IMPACTO.

(c) When using nut runners or IMPACT Wrenches wear safety goggles.
Cuando se utilicen aprieta-tuercas mecánicos o llaves de IMPACTO, llevar siempre gafas de seguridad.

(d) Plastic or rubber handles are not intended to act as insulation.
Los mangos de goma o de plástico no están previstos para aislamiento

(e) Never substitute a HAND Socket for an INDUSTRIAL Socket or an IMPACT Socket, or an INDUSTRIAL Socket for an IMPACT Socket.
No sustituir nunca un vaso INDUSTRIALES o un vaso de IMPACTO por un vaso MANUAL, ni un vaso de IMPACTO por un vaso INDUSTRIALES.

(f) Items in this catalogue marked ⚠ can be loaded to torque values which may cause breakage. In the interest of your own safety always apply load evenly and progressively to avoid breakage and possible injury.
Los artículos de este catálogo marcados ⚠ se pueden forzar con pares que pueden causar rotura.En interés de su propia seguridad aplicar siempre el par uniforme y progresivamente para evitar la rotura y posibles lesiones.

SOCKETS / VASOS

Sockets showing cracked walls, battered points or other marks of wear are to be replaced.

Los vasos que presenten paredes agrietadas, cantos machacados u otros signos de desgaste deben reemplazarse.

HANDLES / MANGOS

A ratchet is not a hammer
Una llave de carraca no es un martillo.

Never use loose pipes or other improvised attachments on handles for increased leverage.

No utilizar nunca tubos sueltos u otras herramientas improvisadas con los mangos para aumentar el brazo de palanca.

EXTENSION BARS / ALARGADERAS

The combination of several short extensions instead of one correct sized one is to be avoided.

Debe evitarse combinar varias alargaderas cortas en lugar de una sola alargadera de longitud correcta.

ADAPTORS / ADAPTADORES

Adaptors are to be used reasonably. Be reminded that high torque potentials are reached when using a "down" adaptor, a bigger sized handle to a smaller drive socket. Always stay within safe limits.

Los adaptadores se deben utilizar razonablemente. Debe tenerse en cuenta que al utilizar adaptadores "para menor diámetro", mayor mango en un vaso conductor más pequeño, se consiguen pares superiores al necesario. Mantenerse siempre dentro de límites seguros.

Z-series

Z-Series : Feature



COMPACT

2400MZ, 3400MZ and 4400MZ are designed 5-14mm shorter than standard 2400M, 3400M and 4400M. Ideal for working in confined and tight areas.



TOLERANCE-Hexagon Opening

Ko-ken standard sockets are manufactured according to DIN/ISO standards. The tolerances of Z-Series sockets are precisely controlled to achieve a more positive fit between bolt and socket.



TOLERANCE-Square Drive

Manufacturing tolerance of Male and Female Square are precisely controlled to achieve a more secure fit between Socket and Handle.



BALL HOLDING GROOVE

Original Ball Holding system is applied on Z-series. This mechanism gives secure connection between Socket and Handle.



* A, B : Other Brand

RATCHET HANDLE

Smaller head with 36 tooth gear and light ratchet movement allow working in narrow space and confined areas.

Specifications or design of any product in this catalogue are subject to change without notice.

Las especificaciones o el diseño de cualquiera de los productos de este catálogo están sujetos a cambio sin previo aviso.

2400MZ

6-point Sockets
Vasos Hexagonales

2400MZ (mm)	D_1 (mm)	D_2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
4	6.4	11	3	14	6	10
4.5	7	11	3	14	6	10
5	7.6	11	3	14	6	10
5.5	8.2	11	3.5	14	6	10
6	8.8	11	3.5	14	6	10
7	9.9	11	3.5	14	6	10
8	11.1	11.7	4.5	15	7	10
10	13.5	12.5	7	15	8	10
11	14.7	13.2	7	15	9	10
12	15.9	14.4	7	15	11	10
13	17.1	15.6	7	15	14	10
14	18.3	16.8	7	15	16	10



RS2400MZ/12

Socket Set on Rail
Juego de Vasos en Regleta

RS2400MZ/12	12 Pieces Set/Rail 200mm	(g)
	4, 4.5, 5, 5.5, 6, 7, 8, 10, 11, 12, 13, 14	228

2300XZ

6-point Sockets, Semi-Deep
Vasos Hexagonales, Medianos

2300XZ (mm)	D_1 (mm)	D_2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
5.5	8.2	11	6	20	30	10	10
6	8.8	11	7	20	30	10	10
7	9.9	11	8	20	30	11	10
8	11.1	11.7	9	20	30	13	10
10	13.5	12.5	11	20	30	16	10
11	14.7	13.2	12	20	30	19	10
12	15.9	14.4	13	20	30	22	10
13	17.1	15.6	14	20	30	26	10
14	18.3	16.8	14	20	30	30	10



RS2300XZ/9

Socket Set on Rail
Juego de Vasos en Regleta

RS2300XZ/9	9 Pieces Set/Rail 200mm	(g)
	5.5, 6, 7, 8, 10, 11, 12, 13, 14	290

2300MZ

6-point Deep Sockets
Vasos Hexagonales Largos

2300MZ (mm)	D_1 (mm)	D_2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
4	6.4	11	5	41	50	14	10
4.5	7	11	5.5	41	50	16	10
5	7.6	11	6	41	50	16	10
5.5	8.2	11	6.5	41	50	16	10
6	8.8	11	7	41	50	17	10
7	9.9	11	8	41	50	20	10
8	11.1	11.7	9	41	50	22	10
10	13.5	12.5	11	41	50	29	10
11	14.7	13.2	12	41	50	33	10
12	15.9	14.4	13	41	50	40	10
13	17.1	15.6	14	41	50	45	10
14	18.3	16.8	16	41	50	51	10



RS2300MZ/12

Socket Set on Rail
Juego de Vasos en Regleta

RS2300MZ/12	12 Pieces Set/Rail 200mm	(g)
	4, 4.5, 5, 5.5, 6, 7, 8, 10, 11, 12, 13, 14	445

2000Z-28 • -50 Phillips Bit Sockets
Vasos con Punta Phillips



2000Z.28 (PH)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
1	11.2	12	28	9	10
2	11.2	12	28	10	10
3	11.2	12	28	10	10

2000Z.50 (PH)	D (mm)	d (mm)	H (mm)	L (mm)	(g)	(pcs.)
1	11.2	4	34	50	11	10
2	11.2	5	34	50	13	10
3	11.2	–	34	50	16	10

2005Z-25 Slotted Bit Sockets
Vasos con Punta Recta para Cabeza Ranurada



2005Z.25	T × W (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
5	1.0 × 5.5	11.2	9	25	9	10
6	1.2 × 6.5	11.2	9	25	10	10

2010MZ-25 • -50 Inhex Bit Sockets
Vasos con Punta Hexagonal



2010MZ.25 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	11.2	9	25	9	10
4	11.2	9	25	9	10
5	11.2	9	25	10	10
6	11.2	9	25	10	10

2010MZ.50 (mm)	D (mm)	d (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	11.2	4	34	50	11	10
4	11.2	5	34	50	13	10
5	11.2	6	34	50	15	10
6	11.2	–	34	50	17	10

RS20XXZ/9 Socket Set on Rail
Juego de Vasos en Regleta

RS20XXZ/9	9 Pieces Set/Rail 200mm	(g)
2000Z.28	**1, 2, 3**	213
2005Z.25	**5, 6**	
2010MZ.25	**3, 4, 5, 6**	

2025Z-28 • -50

TORX® Bit Sockets
Vasos con Punta TORX®

2025Z.28 (T)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
T10	11.2	12	28	9	10
T15	11.2	12	28	9	10
T20	11.2	12	28	9	10
T25	11.2	12	28	10	10
T27	11.2	12	28	10	10
T30	11.2	12	28	10	10
T40	11.2	12	28	11	10

2025Z.50 (T)	D (mm)	d (mm)	H (mm)	L (mm)	(g)	(pcs.)
T10	11.2	4	34	50	11	10
T15	11.2	4	34	50	11	10
T20	11.2	4.5	34	50	12	10
T25	11.2	5	34	50	13	10
T27	11.2	5	34	50	13	10
T30	11.2	5.6	34	50	15	10
T40	11.2	–	34	50	17	10



RS2025Z/7-L28
RS2025Z/7-L50

Socket Set on Rail
Juego de Vasos en Regleta

RS2025Z/7-L28	7 Pieces Set/Rail 200mm	(g)
T10, T15, T20, T25, T27, T30, T40		195

RS2025Z/7-L50	7 Pieces Set/Rail 200mm	(g)
T10, T15, T20, T25, T27, T30, T40		220

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

2725Z
2725Z-160

Reversible Ratchet
Llave de Carraca Reversible



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
2725Z	20.5	17.1	9.5	114	79	2
New 2725Z-160	20.5	17.1	9.5	160	120	1

* Renewal Kits → **2725RK** ➔P298

2726Z
2726Z-160

Flexible Ratchet, Reversible (Short)
Llave de Carraca Flexible, Reversible (Corta)



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
2726Z	20.5	17.1	9.5	114	103	2
New 2726Z-160	20.5	17.1	9.5	160	150	1

* Renewal Kits → **2725RK** ➔P298

2760Z

Extension Bars
Alargaderas



2760Z	D (mm)	L (mm)	(g)	(pcs.)
50	11.5	50	21	10
100	11.5	100	39	10
150	11.5	150	58	10

2771Z

Universal Joint
Articulación Universal



	D (mm)	L (mm)	(g)	(pcs.)
2771Z	11.7	29.9	15	10



2772Z

Universal Joint
Articulación Universal



	D (mm)	L (mm)	(g)	(pcs.)
New 2772Z	11.7	46	26	10



2756Z
2756Z-3/8

Quick Spinner
Disco de Giro Rápido

2756Z-3/8

	D (mm)	L (mm)	(g)	(pcs.)
2756Z	20.3	18	15	10
2756Z-3/8	20.3	21.5	24	10



P2285Z Socket Set / Juego de Vasos

P2285Z	26 Pieces Set/⚖=660g
PLASTIC CASE:W245×H120×T45	
Sockets	Accessories
2400MZ 6-pt. Sockets 4, 4.5, 5, 5.5, 6, 7, 8, 10, 11,12, 13, 14	**2725Z**
2000Z.28 1, 2, 3	**2756Z**
2005Z.25 5, 6	**2771Z**
2010MZ.25 3, 4, 5, 6	**2760Z-50**
	2760Z-150

2285ZE Socket Set / Juego de Vasos

2285ZE	10 Pieces Set/⚖=300g
Rail 200mm/PLASTIC BAG	
Sockets	Accessories
2400MZ 6-pt. Sockets 5.5, 6, 7, 8, 10, 12, 13, 14	**2725Z**
	2756Z

2286Z Socket Set / Juego de Vasos

New 2286Z	17 Pieces Set/⚖=780g
BLACK METAL CASE:W240×H100×T32mm	
Sockets	Accessories
2400MZ 6-pt. Sockets 4, 5, 5.5, 6, 7, 8, 10, 11, 12, 13, 14	**2725Z**
	2756Z
	2771Z
	2760Z-50
	2760Z-100
	2760Z-150

3400MZ

6-point Sockets
Vasos Hexagonales



3400MZ (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
5.5	8.5	17	3.5	19	16	10
6	9.1	17	3.5	19	17	10
7	10.3	17	3.5	19	17	10
8	11.5	17	4.5	20	17	10
10	14	17	4.5	20	18	10
11	15.3	17	5.5	21	18	10
12	16.5	17	5.5	21	19	10
13	17.8	17	8.5	21	19	10
14	19	17	8.5	21	20	10
15	20.2	18.2	8.5	21	24	10
16	21.3	19.3	8.5	21	28	10
17	22.5	20.5	8.5	21	32	10
18	23.6	21.6	9.5	22	38	10
19	24.8	22.8	9.5	22	41	10
21	27	25	10.5	23	51	10
22	28.3	26.3	10.5	23	58	10

3400MZ is designed 5-9mm shorter than standard 3400M.
Ideal for working in confined and tight areas.

RS3400MZ/8
RS3400MZ/12

Socket Set on Rail
Juego de Vasos en Regleta

RS3400MZ/8	8 Pieces Set/Rail 200mm	(g)
8, 10, 11, 12, 13, 14, 17, 19		320

RS3400MZ/12	12 Pieces Set/Rail 300mm	(g)
7, 8, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19		490

3300XZ

6-point Sockets, Semi-Deep
Vasos Hexagonales, Medianos



3300XZ (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
7	10.3	17	8	23	35	23	10
8	11.5	17	9	23	35	24	10
10	14	17	11	23	35	26	10
11	15.3	17	12	23	35	28	10
12	16.5	17	13	23	35	29	10
13	17.8	17	14	23	35	32	10
14	19	17	16	23	35	34	10
15	20.2	18.2	16	23	35	40	10
16	21.3	19.3	16.5	23	35	45	10
17	22.5	20.5	16.5	23	35	50	10
18	23.6	21.6	16.5	23	35	56	10
19	24.8	22.8	18	23	35	60	10

RS3300XZ/8
RS3300XZ/12

Socket Set on Rail
Juego de Vasos en Regleta

RS3300XZ/8	8 Pieces Set/Rail 200mm	(g)
8, 10, 11, 12, 13, 14, 17, 19		420

RS3300XZ/12	12 Pieces Set/Rail 300mm	(g)
7, 8, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19		630





Manufacturing tolerance is precisely controlled to achieve a secure fitting.



BALL HOLDING GROOVE

Original Ball Holding system is applied on Z-series. This mechanism gives secure connection between Socket and Handle.

3300MZ

6-point Deep Sockets
Vasos Hexagonales Largos

3300MZ (mm)	D_1 (mm)	D_2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
7	10.3	17	8	41.5	55	29	10
8	11.5	17	9	41.5	55	34	10
10	14	17	11	41.5	55	43	10
11	15.3	17	12	41.5	55	45	10
12	16.5	17	13	41.5	55	49	10
13	17.8	17	14	41.5	55	52	10
14	19	17	16	41.5	55	55	10
15	20.2	18.2	16	40.5	55	65	10
16	21.3	19.3	17	40.5	55	74	10
17	22.5	20.5	18	40.5	55	83	10
18	23.6	21.6	19	39.5	55	90	10
19	24.8	22.8	20	39.5	55	95	10



RS3300MZ/8
RS3300MZ/12

Socket Set on Rail
Juego de Vasos en Regleta

RS3300MZ/8 — 8 Pieces Set/Rail 200mm	(g)
8, 10, 11, 12, 13, 14, 17, 19	600

RS3300MZ/12 — 12 Pieces Set/Rail 300mm	(g)
7, 8, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19	900

RS3X00MZ/12

Socket Set on Rail
Juego de Vasos en Regleta

RS3X00MZ/12 — 12 Pieces Set/Rail 300mm		(g)
3400MZ	**8, 10, 11, 12, 13, 14, 17, 19**	550
3300MZ	**8, 10, 12, 14**	

3300CZ

Spark Plug Sockets with Spring Clips
Llaves de Bujía con Presillas

3300CZ (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
14	18.4	11	70	67	10
16	20.5	13	70	71	10
18	22.9	12	70	75	10
20.8	26.3	13.5	70	105	10

Slim & light weight body with smaller outside diameter for work in tight spaces.



3305PZ

Spark Plug Socket with Magnet, 12-pt. opening
Llaves de bujía con Imán, Boca Bihex

3305PZ (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
14	17.9	8	70	56	10
16	20	8	70	55	10

Spark Plug Socket with Magnet, 12-pt. opening: size 14mm



3010MZ-50 · -75

Inhex Bit Sockets
Vasos con Punta Hexagonal



3010MZ.50 (mm)	D (mm)	d (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	17	4	23.5	50	28	10
4	17	5	23.5	50	29	10
5	17	6	23.5	50	30	10
6	17	7	23.5	50	35	10
7	17	–	23.5	50	38	10
8	17	–	23.5	50	40	10
10	17	–	23.5	50	50	10
12	19	–	23.5	50	70	10

3010MZ.75 (mm)	D (mm)	d (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	17	6	48.5	75	33	10
4	17	6	48.5	75	35	10
5	17	6	48.5	75	36	10
6	17	7	48.5	75	41	10
7	17	7.9	48.5	75	45	10
8	17	–	48.5	75	48	10
10	17	–	48.5	75	65	10
12	19	–	48.5	75	90	10

RS3010MZ/8-L50
RS3010MZ/8-L75

Socket Set on Rail
Juego de Vasos en Regleta

RS3010MZ/8-L50	8 Pieces Set/Rail 200mm	(g)
3, 4, 5, 6, 7, 8, 10, 12		460

RS3010MZ/8-L75	8 Pieces Set/Rail 200mm	(g)
3, 4, 5, 6, 7, 8, 10, 12		530

3025Z-50 · -75

TORX® Bit Sockets
Vasos con Punta TORX®



3025Z.50 (T)	D (mm)	d (mm)	H (mm)	L (mm)	(g)	(pcs.)
T10	17	3	23.5	50	27	10
T15	17	3.5	23.5	50	28	10
T20	17	3.9	23.5	50	28	10
T25	17	4.5	23.5	50	29	10
T27	17	5	23.5	50	30	10
T30	17	5.6	23.5	50	31	10
T40	17	6.7	23.5	50	35	10
T45	17	7.83	23.5	50	38	10
T50	17	8.90	23.5	50	48	10
T55	19	11.3	23.5	50	70	10

3025Z.75 (T)	D (mm)	d (mm)	H (mm)	L (mm)	(g)	(pcs.)
T20	17	4.5	48.5	75	32	10
T25	17	5	48.5	75	33	10
T27	17	5	48.5	75	33	10
T30	17	5.6	48.5	75	35	10
T40	17	6.7	48.5	75	41	10
T45	17	7.9	48.5	75	45	10
T50	17	8.9	48.5	75	55	10
T55	19	11.3	48.5	75	80	10

RS3025Z/8-L50
RS3025Z/8-L75

Socket Set on Rail
Juego de Vasos en Regleta

RS3025Z/8-L50	8 Pieces Set/Rail 200mm	(g)
T20, T25 ,T27, T30, T40, T45, T50, T55		450

RS3025Z/8-L75	8 Pieces Set/Rail 200mm	(g)
T20, T25, T27, T30, T40, T45, T50, T55		480

TORX® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX® es una marca registrada de **Acument Intellectual Properties, LLC.**



36

2725Z-3/8

Reversible Ratchet Short
Llave de Carraca Reversible Corta

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
2725Z-3/8	20.5	20.5	9.5	114	83	2



36

3725ZS

Reversible Ratchet Short
Llave de Carraca Reversible Corta

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
3725ZS	28	24.5	13.7	100	157	2

* Renewal Kits→ 3725RK ➔P298



36

3725Z
3725Z-280

Reversible Ratchet
Llave de Carraca Reversible

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
3725Z	28	24.5	13.7	178	254	1
New 3725Z-280	28	24.5	13.7	280	360	1

* Renewal Kits→ 3725RK ➔P298



36

Flexible Head

2726Z-3/8

Flexible Ratchet, Reversible (Short)
Llave de Carraca Flexible, Reversible (Corta)

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
2726Z-3/8	20.5	20.5	9.5	114	107	2

Z-series 3/8”

3726ZS

Flexible Ratchet, Reversible (Short)
Llave de Carraca Flexible, Reversible (Corta)

36 Flexible Head



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
3726ZS	28	24.5	13.7	120	196	2

* Renewal Kits → 3725RK ➔P298

3726Z
3726Z-280

Flexible Ratchet, Reversible
Llave de Carraca Flexible, Reversible

36 Flexible Head



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
3726Z	28	24.5	13.7	178	317	1
New 3726Z-280	28	24.5	13.7	280	420	1

* Renewal Kits → 3725RK ➔P298

3768Z-250 · -400

Hinge Handle
Mango Articulado

OVAL Shank



3768Z	D (mm)	L (mm)	(g)	(pcs.)
250	20.5	250	309	2
New 400	20.5	400	500	2

* Renewal Kits → 3768ZRK ➔P300

3760Z-75 · -125 · -250

Extension Bars
Alargaderas



3760Z	D (mm)	L (mm)	(g)	(pcs.)
75	17.5	75	66	10
125	17.5	125	103	10
250	17.5	250	195	5

3771Z Universal Joint / Articulación Universal

	D (mm)	L (mm)	(g)	(pcs.)
3771Z	18	42.5	44	10





3772Z Universal Double Joint / Articulación Universal

	D (mm)	L (mm)	(g)	(pcs.)
New 3772Z	17	65	76	10





3756Z Quick Spinner / Disco de Giro Rápido

	D (mm)	L (mm)	(g)	(pcs.)
3756Z	28	25	40	10

Outside diameter is smaller compared to standard 3756.
Ideal for working in combination with 3725Z



3756ZS Quick Spinner / Disco de Giro Rápido

	D (mm)	L (mm)	(g)	(pcs.)
New 3756ZS	20.3	25	26	10

Ideal for working in combination with 2725Z-3/8 and 2726Z-3/8.



3322AZ-75 Extension Adaptor / Adaptador Alargadera

	D (mm)	L (mm)	(g)	(pcs.)
3322AZ-75	17.5	75	42	10



3322AZ-75



3286Z Socket Set / Juego de Vasos

New 3286Z — 21 Pieces Set/⚖=2,600g

BLACK METAL CASE:W415×H120×T50mm

Sockets	Accessories
3400MZ 6-pt. Sockets 7, 8, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22	3725Z 3756Z 3771Z 3768Z-250 3760Z-75 3760Z-125 3760Z-250

3285Z Socket Set / Juego de Vasos

3285Z	26 Pieces Set/⚖=2,100g
PLASTIC TRAY:W390×T180×H25	
Sockets	**Accessories**
3400MZ 6-pt. Sockets 5.5, 6, 7, 8, 10, 12, 13, 14, 17, 19, 21, 22	**3725Z**
3300MZ 6-pt. Deep Sockets 8, 10, 12, 14	**3756Z**
3300CZ Spark Plug Sockets 14, 16, 20.8	**3771Z**
	3768Z-250
	3760Z-75
	3760Z-125
	3760Z-250

3285ZA Socket Set / Juego de Vasos

3285ZA	15 Pieces Set/⚖=750g
PLASTIC TRAY:W300×T90×H25	
Sockets	**Accessories**
3400MZ 6-pt. Sockets 5.5, 6, 7, 8, 10, 12, 13, 14, 17, 19, 21, 22	**3725Z**
	3756Z
	3771Z

3285ZE Socket Set / Juego de Vasos

3285ZE	9 Pieces Set/⚖=600g
Rail 200mm/PLASTIC BAG	
Sockets	**Accessories**
3400MZ 6-pt. Sockets 8, 10, 12, 13, 14, 17, 19	**3725Z**
	3756Z

RSAL200-1/4×12 · -3/8×8 / RSAL300-3/8×12 · -1/2×10

Rail / Regleta

RSAL200	◹	RAIL (mm)	CLIP (pcs.)	⚖ (g)	(pce.)
1/4×12	1/4"	200	12	125	1
3/8×8	3/8"	200	8	130	1

RSAL300	◹	RAIL (mm)	CLIP (pcs.)	⚖ (g)	(pce.)
3/8×12	3/8"	300	12	180	1
1/2×10	1/2"	300	10	190	1

RSAL-200 · -300 · -400 / CLIP.P/5-1/4 · -3/8 · -1/2

RAIL

	RAIL (mm)	⚖ (g)	(pce.)
RSAL200	200	110	1
RSAL300	300	145	1
New **RSAL400**	400	210	1

CLIP

CLIP.P/5	◹	⚖ (g)	(pcs.)
1/4	1/4"	10	5
3/8	3/8"	13	5
1/2	1/2"	20	5

4400MZ

6-point Sockets
Vasos Hexagonales

4400MZ (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
8	12.6	20.6	4.5	26	30	10
10	15	20.6	4.5	26	31	10
12	17.5	20.6	5.5	27	32	10
13	18.7	21.5	6.5	28	40	10
14	19.8	21.5	6.5	28	40	10
16	22.3	21.5	7.5	28	43	10
17	23.6	22.5	7.5	29	49	10
18	24.8	23.7	7.5	29	56	10
19	26	24.4	9.5	29	62	10
21	28.4	26.3	10.5	29	76	10
22	29.6	27.5	11	29	83	10
24	32	29.2	12	29	96	5
27	35.7	32.2	13.5	30	124	5
30	39.3	35.2	14.5	31	156	5
32	41.7	36.8	15.5	32	178	5



RS4400MZ/10

Socket Set on Rail
Juego de Vasos en Regleta

RS4400MZ/10	10 Pieces Set/Rail 300mm	(g)
10, 12, 13, 14, 17, 19, 21, 22, 24, 27		830

4725Z

Reversible Ratchet
Llave de Carraca Reversible

36

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
4725Z	36.5	32.8	18.2	253	590	1

* Renewal Kits → **4725RK** ➡P298



4768Z-430

Hinge Handle
Mango Articulado

	D (mm)	L (mm)	(g)	(pce.)
4768Z-430	28	430	720	1

* Renewal Kits → **4768ZRK** ➡P300



4760Z-125 • -250 Extension Bars Alargaderas



4760Z	D (mm)	L (mm)	(g)	(pcs.)
125	22.5	125	180	5
250	22.5	250	340	5

4771Z Universal Joint Articulación Universal



	D (mm)	L (mm)	(g)	(pcs.)
4771Z	23.7	55.8	100	10

4756Z Quick Spinner Disco de Giro Rápido



	D (mm)	L (mm)	(g)	(pcs.)
4756Z	36.3	33.5	84	10

4285Z Socket Set Juego de Vasos

4285Z 21 Pieces Set/=4,800g

METAL CASE:W445×T190×H50

Sockets	Accessories
4400MZ 6-pt. Sockets 8, 10, 12, 13, 14, 16, 17, 18, 19, 21, 22, 24, 27, 30, 32	**4725Z** **4756Z** **4771Z** **4768Z-430** **4760Z-125** **4760Z-250**

4285ZE Socket Set Juego de Vasos

4285ZE 11 Pieces Set/=1,380g

Rail 300mm/PLASTIC BAG

Sockets	Accessories
4400MZ 6-pt. Sockets 10, 12, 13, 14, 17, 19, 21,22, 24	**4725Z** **4756Z**

Hand Sockets

1/4”

3/8”

1/2”

3/4”

1”

2400M · 2400A

6-point Sockets
Vasos Hexagonales



2400M 2405M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
3	5.5	11.2	2.6	22	7	10
3.5	6.1	11.2	3	22	7	10
4	6.7	11.2	3.5	22	8	10
4.5	7.3	11.2	4	22	8	10
5	8	11.2	5	22	8	10
5.5	8.5	11.2	5.5	22	9	10
6	9.2	11.2	5.5	22	9	10
7	10.3	11.2	6	22	9	10
8	11.2	11.7	6.9	22	11	10
9	13	12	7.3	22	12	10
10	14.3	12.9	7.7	22	15	10
11	15.5	14.3	9.3	22	18	10
12	16.8	15.5	9.3	22	23	10
13	18	16.4	9.8	22	23	10
14	19.3	17.9	11	24	30	10

2405M · 2405A

12-point Sockets
Vasos Bihexagonales



2400A 2405A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
1/8	5.7	11.2	2.7	22	7	10
5/32	6.7	11.2	3.5	22	8	10
3/16	7.8	11.2	5	22	8	10
7/32	8.5	11.2	5.5	22	9	10
1/4	9.6	11.2	5.8	22	9	10
9/32	10.3	11.2	6	22	9	10
5/16	11.2	11.7	6.9	22	11	10
11/32	12.5	11.7	7.3	22	12	10
3/8	13.7	12.5	7.7	22	15	10
7/16	15.5	14.3	9.3	22	18	10
1/2	18	16.4	9.8	22	23	10
9/16	19.3	17.9	11	24	30	10

RS2400M/11
RS2405M/11

Socket Set on Rail
Juego de Vasos en Regleta

RS2400M/11	11 Pieces Set/Rail 200mm	(g)
4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14		222

RS2405M/11	11 Pieces Set/Rail 200mm	(g)
4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14		222

RS2400A/9
RS2405A/9

Socket Set on Rail
Juego de Vasos en Regleta

RS2400A/9	9 Pieces Set/Rail 150mm	(g)
3/16, 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2		162

RS2405A/9	9 Pieces Set/Rail 150mm	(g)
3/16, 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2		162

AS2405A

12-point Sockets, AS954
Vasos Bihexagonales

SAE AS954



AS2405A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
3/16	7.7	10.9	4.5	22	8	10
7/32	8.5	10.9	4.9	22	8	10
1/4	9.4	10.9	5.3	22	8	10
9/32	10.2	10.9	5.5	22	8	10
5/16	11.3	11.7	6.4	22	10	10
11/32	12.5	12	6.8	22	10	10
3/8	13.7	12.9	6.8	22	13	10
7/16	15.6	14.3	8.8	22	17	10
1/2	17.2	16.4	8.9	22	20	10
9/16	18.8	17.9	9.1	24	27	10

Aerospace Standard SAE AS954
Norma Aeroespacial SAE AS954

RSAS2405A/10

Socket Set on Rail
Juego de Vasos en Regleta

SAE AS954

RSAS2405A/10	10 Pieces Set/Rail 150mm	(g)
3/16, 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2, 9/16		160

2410M

Surface Drive Sockets
Vasos Surface Drive (de Contacto Curvo)



2410M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
4	6.7	11.2	3.5	22	8	10
4.5	7.3	11.2	4	22	8	10
5	8	11.2	5	22	8	10
5.5	8.5	11.2	5.5	22	9	10
6	9.2	11.2	5.5	22	9	10
7	10.3	11.2	6	22	9	10
8	11.2	11.7	6.9	22	11	10
9	13	12	7.3	22	12	10
10	14.3	12.9	7.7	22	15	10
11	15.5	14.3	9.3	22	18	10
12	16.8	15.5	9.3	22	23	10
13	18	16.4	9.8	22	23	10
14	19.3	17.9	11	24	30	10

RS2410M/11

Socket Set on Rail
Juego de Vasos en Regleta

RS2410M/11	11 Pieces Set/Rail 200mm	(g)
4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14		222

2400W-BA

6-point Sockets
Vasos Hexagonales



2400W (BA)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
8	6.1	11.2	3	22	7	10
7	7.3	11.2	4	22	8	10
6	8	11.2	5	22	8	10
5	8.5	11.2	5.5	22	9	10
4	9.6	11.2	5.8	22	9	10
3	10.3	11.2	6	22	9	10
2	11.2	11.7	6.9	22	11	10
1	13	12	7.3	22	12	10
0	14.9	13.6	8	22	16	10

BA

BA		8BA	7BA	6BA	5BA	4BA	3BA	2BA	1BA	0BA
Across Flat	(ref. mm)	3.86	4.37	4.90	5.59	6.30	7.16	8.23	9.27	10.49
	(ref. inch)	0.152	0.172	0.193	0.220	0.248	0.282	0.324	0.365	0.413

RS2400W/9-BA

Socket Set on Rail
Juego de Vasos en Regleta

RS2400W/9-BA	9 Pieces Set/Rail 150mm	(g)
8, 7, 6, 5, 4, 3, 2, 1, 0		120

2415M · 2415A

Double Square Sockets
Vasos Octagonales



2415M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
New **5.5**	10.3	11.2	5.4	22	10	10
6	11	11.7	5.4	22	13	10
New **7**	12.5	11.7	6.1	22	13	10
8	14.3	12.9	6.8	22	17	10
10	17.4	16	8.2	22	27	10

2415A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
1/4	11	11.7	5.4	22	14	10
5/16	14.3	12.9	6.8	22	17	10
3/8	17.4	16	8.2	22	26	10

2425 TORX® Sockets / Vasos TORX®



2425 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
E 4	5.4	11.2	4.6	22	7	10
E 5	6.7	11.2	5.2	22	8	10
E 6	7.7	11.2	5.4	22	8	10
E 7	8.3	11.2	6.6	22	9	10
E 8	9.6	11.2	7	22	9	10
E10	11.3	12	8.2	22	10	10
New E11	12.9	12	8.7	22	13	10
New E12	14.3	12.9	9.3	23	17	10

RS2425/6 Socket Set on Rail / Juego de Vasos en Regleta

RS2425/6	6 Pieces Set/Rail 150mm	(g)
	E4, E5, E6, E7, E8, E10	85

2450MS Nut Grip Sockets **Nut Grip®** / Vasos Sujeta-tuercas **Nut Grip®**



2450MS (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
7	11.3	11.2	4	18	8	10
8	12.3	11.2	5	18	9	10
10	14.3	12.9	6	19	13	10
12	17.4	16	7	20	22	10
13	18	16.4	8	20	22	10
14	19.9	18	8.5	22	31	10

RS2450MS/6 Socket Set on Rail / Juego de Vasos en Regleta

RS2450MS/6	6 Pieces Set/Rail 150mm	(g)
	7, 8, 10, 12, 13, 14	120

2300X 6-point Sockets, Semi-Deep / Vasos Hexagonales, Medianos



2300X (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
4	6.7	11.2	4	22	32	10	10
5	8	11.2	5.5	22	32	11	10
6	9.2	11.2	7	22	32	12	10
7	10.5	11.2	8	22	32	13	10
8	11.8	11.2	9	22	32	16	10
9	13	12	10	22	32	18	10
10	14.3	12.9	11	21	32	23	10
11	15.5	14.3	12	21	32	27	10
12	16.8	15.5	13	21	32	29	10
13	18	16.4	14	21	32	32	10
14	19.3	17.9	16	20	32	37	10

RS2300X/11 Socket Set on Rail / Juego de Vasos en Regleta

RS2300X/11	11 Pieces Set/Rail 200mm	(g)
	4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14	300

2350X **Nut Grip®** Socket, Semi-Deep / Vasos Sujeta-tuercas **Nut Grip®**. Medianos



2350X (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
8	12.3	11.2	5	22	32	17	10
10	14.2	12.9	6	22	32	22	10
12	17.3	16	7	22	32	34	10
14	20	18	8.5	22	32	43	10

RS2350X/4 Socket Set on Rail / Juego de Vasos en Regleta

RS2350X/4	4 Pieces Set/Rail 150mm	(g)
New	8, 10, 12, 14	140

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

2300M · 2300A

6-point Deep Sockets
Vasos Hexagonales Largos





2300M 2305M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	5.5	11.2	3	40	50	15	10
4	6.7	11.2	4	40	50	15	10
4.5	7.3	11.2	4.5	40	50	15	10
5	8	11.2	5.5	40	50	17	10
5.5	8.5	11.2	6	40	50	17	10
6	9.2	11.2	7	40	50	20	10
7	10.5	11.2	8	40	50	25	10
8	11.8	11.2	9	40	50	25	10
9	13	12	10	40	50	30	10
10	14.3	12.9	11	39	50	34	10
11	15.5	14.3	12	39	50	43	10
12	16.8	15.5	13	39	50	50	10
13	18	16.4	14	39	50	52	10
14	19.3	17.9	16	38	50	57	10

2305M · 2305A

12-point Deep Sockets
Vasos Bihexagonales Largos



2300A 2305A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
1/8	5.7	11.2	3.5	40	50	15	10
5/32	6.7	11.2	4	40	50	15	10
3/16	7.8	11.2	5.5	40	50	17	10
7/32	8.5	11.2	6	40	50	17	10
1/4	9.8	11.2	7	40	50	25	10
9/32	10.5	11.2	8	40	50	25	10
5/16	11.8	11.2	9	40	50	25	10
11/32	12.5	11.7	10	40	50	30	10
3/8	13.7	12.5	11	40	50	34	10
7/16	15.5	14.3	12	39	50	43	10
1/2	18	16.4	14	39	50	52	10
9/16	19.3	17.9	16	38	50	57	10

RS2300M/11
RS2305M/11

Socket Set on Rail
Juego de Vasos en Regleta

RS2300M/11	11 Pieces Set/Rail 200mm	(g)
4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14		437

RS2305M/11	11 Pieces Set/Rail 200mm	(g)
4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14		437

RS2300A/9
RS2305A/9

Socket Set on Rail
Juego de Vasos en Regleta

RS2300A/9	9 Pieces Set/Rail 150mm	(g)
3/16, 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2		296

RS2305A/9	9 Pieces Set/Rail 150mm	(g)
3/16, 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2		296

2300W-BA

6-point Deep Sockets
Vasos Hexagonales Largos



2300W (BA)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
4	9.8	11.2	7	40	50	22	10
3	10.5	11.2	8	40	50	25	10
2	11.8	11.2	9	40	50	25	10
1	13	12	10	40	50	30	10
0	14.9	13.6	12	39	50	38	10

BA

BA		8BA	7BA	6BA	5BA	4BA	3BA	2BA	1BA	0BA
Across Flat	(ref. mm)	3.86	4.37	4.90	5.59	6.30	7.16	8.23	9.27	10.49
	(ref. inch)	0.152	0.172	0.193	0.220	0.248	0.282	0.324	0.365	0.413

AS2305A

12-point Deep Sockets, AS954
Vasos Bihexagonales Largos, AS954

SAE AS954



AS2305A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
3/16	7.7	10.9	4.5	40	50	17	10
7/32	8.5	10.9	4.9	40	50	17	10
1/4	9.4	10.9	5.3	40	50	19	10
9/32	10.2	10.9	5.5	40	50	18	10
5/16	11.3	11.7	6.4	40	50	23	10
11/32	12.5	12	6.8	40	50	24	10
3/8	13.7	12.8	6.8	39	50	31	10
7/16	15.6	14.2	8.8	39	50	38	10
1/2	17.2	16.2	8.9	39	50	42	10
9/16	18.8	17.1	9.1	38	50	47	10

Aerospace Standard SAE AS954
Norma Aeroespacial SAE AS954

RSAS2305A/10

Socket Set on Rail
Juego de Vasos en Regleta

SAE AS954

RSAS2305A/10	10 Pieces set/Rail 150mm	(g)
3/16, 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2, 9/16		307

2310M

Surface Drive Deep Sockets
Vasos Surface Drive (de Contacto Curvo) Largos



2310M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	5.5	11.2	3	40	50	15	10
4	6.7	11.2	4	40	50	15	10
4.5	7.3	11.2	4.5	40	50	15	10
5	8	11.2	5.5	40	50	17	10
5.5	8.5	11.2	6	40	50	17	10
6	9.2	11.2	7	40	50	20	10
7	10.5	11.2	8	40	50	25	10
8	11.8	11.2	9	40	50	25	10
9	13	12	10	40	50	30	10
10	14.3	12.9	11	39	50	34	10
11	15.5	14.3	12	39	50	43	10
12	16.8	15.5	13	39	50	50	10
13	18	16.4	14	39	50	52	10
14	19.3	17.9	16	38	50	57	10

RS2310M/11

Socket Set on Rail
Juego de Vasos en Regleta

RS2310M/11	11 Pieces set/Rail 200mm	(g)
4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14		437

2325

TORX® Deep Sockets
Vasos TORX® Largos



2325 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
E 4	5.4	12	4.6	40	50	17	10
E 5	6.8	12	5.2	40	50	20	10
E 6	8	12	5.4	40	50	20	10
E 7	8.3	12	6.6	40	50	22	10
E 8	9.8	12	7	40	50	25	10
E10	11.6	12	8.2	40	50	29	10

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

2350M

Nut Grip Deep Sockets **Nut Grip®**
Vasos Sujeta-tuercas Largos **Nut Grip®**

2350M (mm)	D_1 (mm)	D_2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
8	12.3	11.2	5	40	50	30	10
10	14.2	12.9	6	39	50	35	10
12	17.3	16	7	39	50	55	10
14	19.9	18	8.5	38	50	70	10



RS2350M/4

Socket Set on Rail
Juego de Vasos en Regleta

RS2350M/4	4 Pieces Set/Rail 150mm	(g)
New	**8, 10, 12, 14**	220

2440M · 2440A

6-point Universal Sockets
Vasos Hexagonales con Articulación Universal

2440M 2445M (mm)	D_1 (mm)	D_2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
4	6.7	13	4.8	31.5	17	10
5	8	13	5.3	32	17	10
6	9.2	13	6.1	33	18	10
7	10.5	13	6.5	33	19	10
8	11.7	13	7	34	19	10
9	13	13	7	34	20	10
10	14.2	13	8.3	35	20	10
11	15.5	13	9.5	36	21	10
12	16.7	13	10	37	21	10
13	18	13	10.5	37	26	10
14	19.2	13	10.5	37	28	10



2445M · 2445A

12-point Universal Sockets
Vasos Bihexagonales con Articulación Universal

2440A (inch)	D_1 (mm)	D_2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
1/4	9.8	13	6.5	33	18	10
5/16	11.7	13	7	34	19	10
3/8	13.7	13	8.3	35	20	10
7/16	15.5	13	9.5	36	21	10
1/2	18	13	10.5	37	26	10
9/16	19.2	13	10.5	37	28	10

2445A (inch)	D_1 (mm)	D_2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
3/16	8	13	5.3	32	18	10
1/4	9.8	13	6.5	33	18	10
9/32	10.5	13	6.5	33	19	10
5/16	11.7	13	7	34	19	10
11/32	13	13	7	34	20	10
3/8	13.7	13	8.3	35	20	10
7/16	15.5	13	9.5	36	21	10
1/2	18	13	10.5	37	26	10
9/16	19.2	13	10.5	37	28	10



RS2445A/9

Socket Set on Rail
Juego de Vasos en Regleta

RS2445A/9	9 Pieces set/Rail 150mm	(g)
	3/16, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2, 9/16	220

AS2445A

12-point Universal Sockets
Vasos Bihex con Articulación Universal

AS2445A (inch)	D_1 (mm)	D_2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
1/4	9.6	12.9	5.7	31.8	18	10
5/16	11.7	12.9	7	34.6	21	10
3/8	13.5	12.9	8.3	35.1	21	10
7/16	15.5	12.9	9.5	39.1	25	10
1/2	17.2	12.9	10.5	40.1	27	10



2440T

TORX® Universal Sockets
Vasos TORX® con Aritculación Universal



2440T (E)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
E 6	8	13	5.4	31.9	20	10
E 8	9.8	13	7	33.1	20	10
E10	11.7	13	8.2	33.6	21	10
E12	14.2	13	9.3	35.1	24	10

2441M

Nut Grip Universal Sockets **Nut Grip®**
Vasos Sujeta-Tuercas con Articulación Universal



2441M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
7	11.3	13	4	33	19	10
8	12.3	13	5	32	19	10
10	14.5	13	6	32.5	21	10
12	16.8	13	7	34	21	10
13	18	13	8	35	21	10
14	20	13	8.5	37	28	10

2430M

Universal Inhex Sockets
Vasos Hexagonales con Articulación Universal



2430M (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
3	13	5.5	40	18	10
4	13	5.5	40	18	10
5	13	6.5	40	20	10
6	13	7.5	40	21	10

2430T

TORX® Universal Sockets
Vasos TORX® con Articulación Universal



2430T (T)	D (mm)	L (mm)	(g)	(pcs.)
T 8	13	42	22	10
T 9	13	42	22	10
T10	13	42	22	10
T15	13	42	22	10
T20	13	42	22	10
T25	13	42	22	10
T27	13	42	22	10
T30	13	42	22	10

2000-28 (PH)

Phillips Bit Sockets
Vasos con Punta Phillips



2000.28 (PH)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
1	11.9	12	28	10	10
2	11.9	12	28	11	10
3	11.9	12	28	12	10
4	13.1	11	28	14	10

2000-28 (PZ)

PZ Bit Sockets
Vasos con Punta PZ



2000.28 (PZ)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
PZ1	11.9	12	28	10	10
PZ2	11.9	12	28	11	10
PZ3	11.9	12	28	12	10

2005-25

Slotted Bit Sockets
Vasos con Punta Recta para Cabeza Ranurada



2005.25	T×W (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	0.5× 3	11.9	9	25	9	10
4	0.8× 4	11.9	9	25	10	10
5	1.0× 5.5	11.9	9	25	10	10
6	1.2× 6.5	13.1	9	25	11	10
8	1.2× 8	13.1	9	25	12	10
9	1.6× 8	13.1	9	25	12	10
10	1.6×10	14.3	9	25	13	10

TORX® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX® es una marca registrada de **Acument Intellectual Properties, LLC.**

2010M-25 • -100
2010A-25

Inhex Bit Sockets
Vasos con Punta Hexagonal



2010M.25 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
1.5	11.9	9	25	9	10
2	11.9	9	25	9	10
2.5	11.9	9	25	9	10
3	11.9	9	25	9	10
4	11.9	9	25	9	10
5	11.9	9	25	10	10
6	11.9	9	25	12	10
7	13.1	8	25	12	10
8	13.1	8	25	14	10
10	14.3	8	25	17	10
New **12**	16.4	8	25	36	10

2010M.100 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
2	11.9	84	100	30	10
2.5	11.9	84	100	30	10
3	11.9	84	100	30	10
4	11.9	84	100	30	10
5	13.1	83	100	30	10
6	13.1	83	100	35	10
7	13.1	83	100	35	10
8	13.1	83	100	38	10
10	14.3	83	100	45	10
New **12**	16.4	83	100	107	10

2010A.25 (inch)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
1/8	11.9	9	25	9	10
5/32	11.9	9	25	9	10
3/16	11.9	9	25	10	10
7/32	11.9	9	25	11	10
1/4	11.9	9	25	12	10
9/32	13.1	8	25	12	10
5/16	13.1	8	25	14	10
3/8	14.3	8	25	17	10

RS2010M/7-L25
RS2010A/8-L25

Socket Set on Rail
Juego de Vasos en Regleta

RS2010M/7-L25	7 Pieces set/Rail 150mm	(g)
3, 4, 5, 6, 7, 8, 10		115

RS2010A/8-L25	8 Pieces set/Rail 150mm	(g)
1/8, 5/32, 3/16, 7/32, 1/4, 9/32, 5/16, 3/8		130

2011M-50

Ballpoint Inhex Bit Sockets
Vasos con Punta de Bola Inhex



2011M.50 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	11.9	34	50	16	10
4	11.9	34	50	17	10
5	11.9	34	50	18	10
6	11.9	34	50	18	10

Ball point bit sockets have less strength due to the special design. Make sure to use them correctly.

2020-28 • -50

XZN Bit Sockets
Vasos con Punta XZN



2020.28 (XZN)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
M4	11.9	12	28	12	10
M5	11.9	12	28	12	10
M6	11.9	12	28	13	10
M8	13.1	11	28	14	10

2020.50 (XZN)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
M4	11.9	34	50	20	10
M5	11.9	34	50	20	10
M6	11.9	34	50	22	10
M8	13.1	33	50	24	10

2025-28 • -80 (T)

TORX® Bit Sockets
Vasos con Punta TORX®



2025.28 (T)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
T 8	11.9	12	28	10	10
T 9	11.9	12	28	10	10
T10	11.9	12	28	10	10
T15	11.9	12	28	10	10
T20	11.9	12	28	11	10
T25	11.9	12	28	11	10
T27	11.9	12	28	12	10
T30	11.9	12	28	12	10
T40	11.9	12	28	13	10

2025.80 (T)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
T10	11.9	64	80	40	10
T15	11.9	64	80	40	10
T20	11.9	64	80	42	10
T25	11.9	64	80	42	10
T27	11.9	64	80	45	10
T30	11.9	64	80	45	10
T40	11.9	64	80	50	10

TORX® (T)



T		T8	T9	T10	T15	T20	T25	T27	T30	T40	T45	T50	T55	T60	T70	T80	T90	T100
S_1	(ref. mm)	2.3	2.5	2.7	3.3	3.9	4.5	5.0	5.6	6.7	7.9	8.9	11.3	13.3	15.6	17.6	20.0	22.2
S_2	(ref. mm)	1.7	1.8	2.0	2.3	2.8	3.2	3.6	4.0	4.8	5.6	6.2	8.0	9.5	11.1	12.7	14.2	15.8

RS2025/7-L28

Socket Set on Rail
Juego de Vasos en Regleta

RS2025/7-L28	7 Pieces set/Rail 150mm	(g)
	T10, T15, T20, T25, T27, T30, T40	119

2025-28 (TH)

Tamper-Resistant TORX® Bit Sockets
Vasos con Punta TORX® Indeformable



2025.28 (TH)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
T10H	11.9	12	28	10	10
T15H	11.9	12	28	10	10
T20H	11.9	12	28	11	10
T25H	11.9	12	28	11	10
T27H	11.9	12	28	12	10
T30H	11.9	12	28	12	10
T40H	11.9	12	28	13	10

RS2025/7-HOLE

Socket Set on Rail
Juego de Vasos en Regleta

RS2025/7-HOLE	7 Pieces set/Rail 150mm	(g)
	T10H, T15H, T20H, T25H, T27H, T30H, T40H	119

Tamper Resistant TORX® Bit Sockets have less strength due to special design. Make sure to use it correctly.

Los Vasos con Punta Indeformable TORX® tienen menos resistencia debido al diseño especial. Asegurarse de su correcta utilización.

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

2025-28 (IP)

TORXPLUS® Bit Sockets
Vasos con Punta TORXPLUS®

TORX plus®



2025.28 (IP)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
8IP	11.9	12	28	10	10
9IP	11.9	12	28	10	10
10IP	11.9	12	28	10	10
15IP	11.9	12	28	10	10
20IP	11.9	12	28	11	10
25IP	11.9	12	28	11	10
27IP	11.9	12	28	12	10
30IP	11.9	12	28	12	10
40IP	11.9	12	28	13	10

TORXPLUS® (IP)



IP		8IP	9IP	10IP	15IP	20IP	25IP	27IP	30IP	40IP	45IP	50IP	55IP	60IP	70IP
S_1	(ref. mm)	2.3	2.5	2.7	3.3	3.9	4.5	5.0	5.6	6.7	7.9	8.9	11.3	13.3	15.6
S_2	(ref. mm)	1.7	1.8	2.0	2.3	2.8	3.2	3.6	4.0	4.8	5.6	6.2	8.0	9.5	11.1

RS2025/7-IP

Socket Set on Rail
Juego de Vasos en Regleta

RS2025/7-IP	7 Pieces set/Rail 150mm	(g)
10IP, 15IP, 20IP, 25IP, 27IP, 30IP, 40IP		119

2025-28 (IPR)

TORXPLUS® Bit Sockets, with Hole
Vasos con Punta de Cinco Lóbulos, con agujero

TORX plus®



2025.28 (IPR)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
8IPR	11.9	12	28	10	10
9IPR	11.9	12	28	10	10
10IPR	11.9	12	28	10	10
15IPR	11.9	12	28	10	10
20IPR	11.9	12	28	11	10
25IPR	11.9	12	28	11	10
27IPR	11.9	12	28	12	10
30IPR	11.9	12	28	12	10
40IPR	13.1	12	28	13	10

TORXPLUS® (IPR)



IPR		8IPR	9IPR	10IPR	15IPR	20IPR	25IPR	27IPR	30IPR	40IPR	45IPR	50IPR	55IPR
S_1	(ref. mm)	2.2	2.4	2.6	3.1	3.6	4.1	4.7	5.2	6.3	7.4	8.4	10.6
S_2	(ref. mm)	2.0	2.2	2.4	2.8	3.3	3.8	4.3	4.8	5.7	6.7	7.6	9.7

RS2025/7-IPR

Socket Set on Rail
Juego de Vasos en Regleta

RS2025/7-IPR	7 Pieces set/Rail 150mm	(g)
10IPR, 15IPR, 20IPR, 25IPR, 27IPR, 30IPR, 40IPR		119

TORX plus® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX plus® es una marca registrada de **Acument Intellectual Properties, LLC.**

2753PS
Reversible Ratchet Short
Llave de Carraca Reversible Corta



S.O.D.H.-System · 2 Two-Step Dog · 20

* Renewal Kits → 2753RK ➡P298

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
2753PS	22	18.7	11.4	75	55	5

2753N
Reversible Ratchet
Llave de Carraca Reversible

S.O.D.H.-System · 2 Two-Step Dog · 20

* Renewal Kits → 2753RK ➡P298

2753P
Reversible Ratchet
Llave de Carraca Reversible

S.O.D.H.-System · 2 Two-Step Dog · 20

* Renewal Kits → 2753RK ➡P298

2753J
Reversible Ratchet
Llave de Carraca Reversible



S.O.D.H.-System · 2 Two-Step Dog · 20

* Renewal Kits → 2753RK ➡P298

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
2753N	22	18.7	11.4	115	90	10
2753P	22	18.7	11.4	115	87	10
2753J	22	18.7	11.4	115	77	5

2753P-160
Reversible Ratchet Long
Llave de Carraca Reversible Larga



S.O.D.H.-System · 2 Two-Step Dog · 20

* Renewal Kits → 2753RK ➡P298

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
2753P-160	22	18.7	11.4	160	107	5

2753NB

Reversible Ratchet with Quick Release Button
Llave de Carraca Reversible con botón de extracción rápida

* Renewal Kits → 2753BRK ➡P298

2753PB

Reversible Ratchet with Quick Release Button
Llave de Carraca Reversible con botón de extracción rápida

* Renewal Kits → 2753BRK ➡P298

2753JB

Reversible Ratchet with Quick Release Button
Llave de Carraca Reversible con botón de extracción rápida

* Renewal Kits → 2753BRK ➡P298



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
2753NB	22	18.7	11.4	115	90	10
2753PB	22	18.7	11.4	115	87	10
2753JB	22	18.7	11.4	115	77	5

Reversible Ratchet with quick release button has less strength compared with normal ratchet due to the technical design. Make sure to use the ratchet correctly.

2752N

Reversible Ratchet
Llave de Carraca Reversible

* Renewal Kits → 2752RK ➡P298



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
2752N	26.5	19.8	12.5	125	95	10

2774PS

Flexible Ratchet, Reversible
Llave de Carraca Flexible, Reversible

* Renewal Kits → 2753RK ➡P298

2774JS

Flexible Ratchet, Reversible
Llave de Carraca Flexible, Reversible

* Renewal Kits → 2753RK ➡P298



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
2774PS	22	18.7	11.4	116	110	5
2774JS	22	18.7	11.4	116	113	5

2774N
Flexible Ratchet, Reversible
Llave de Carraca Flexible, Reversible

S.O.D.R-System | 20 | Flexible Head

* Renewal Kits → 2753RK ➡P298

2774P
Flexible Ratchet, Reversible
Llave de Carraca Flexible, Reversible

S.O.D.R-System | 20 | Flexible Head

* Renewal Kits → 2753RK ➡P298

2774J
Flexible Ratchet, Reversible
Llave de Carraca Flexible, Reversible

S.O.D.R-System | 20 | Flexible Head

* Renewal Kits → 2753RK ➡P298



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
2774N	22	18.7	11.4	161	130	2
2774P	22	18.7	11.4	161	126	2
2774J	22	18.7	11.4	161	130	2

2755
Ratchet Adaptor
Adaptador de carraca



44

* Renewal Kits → 2755RK ➡P300

	D (mm)	L (mm)	(g)	(pcs.)
2755	26	40	80	10

2756
Quick Spinner
Disco de giro Rápido



	D (mm)	L (mm)	(g)	(pcs.)
2756	22	20	19	10

2762
Flexible Extension Bar
Alargadera Flexible



	D (mm)	L (mm)	(g)	(pcs.)
2762	13	300	90	2

2760-28 • -50 • -75 • -100 • -150 • -200 • -250 • -300 • -350 • -400 • -600

Extension Bars
Alargaderas



2760	D (mm)	L (mm)	(g)	(pcs.)
28	12.3	28	14	10
50	12.3	50	23	10
75	12.3	75	35	10
100	12.3	100	44	10
150	12.3	150	63	10
200	12.3	200	83	10
250	12.3	250	103	10
300	12.3	300	122	2
350	12.3	350	145	2
400	12.3	400	160	2
600	12.3	600	240	2

PK2760/6

Set
Juego

PK2760/6 — 6 Pieces Set/⚖=430g

PLASTIC TRAY

Extension Bars

2760 Extension Bars
28, 50, 100, 150, 200, 250

2763-28 • -50 • -75 • -100 • -150 • -200 • -250

Wobble-Fix Extension Bars
Alargaderas Articuladas-Fijas ⚠



2763	D (mm)	L (mm)	(g)	(pcs.)
28	12.3	28	14	10
50	12.3	50	23	10
75	12.3	75	33	10
100	12.3	100	43	10
150	12.3	150	62	10
200	12.3	200	80	10
250	12.3	250	100	10

PK2763/6

Set
Juego

PK2763/6 — 6 Pieces Set/⚖=420g

PLASTIC TRAY

Extension Bars

2763 Wobble-Fix Extension Bar
28, 50, 100, 150, 200, 250

Wobble-Fix Extension Bar
Two way usage : One for as a flexible extension bar to provide at 15° angle operation, the other for use as a normal extension bar. This usage is Patent.

Alargadera Articulada-Fija
Dos formas de utilización : Una como alargadera flexible para poder trabajar con un ángulo de 15° y otra para utilizarse como alargadera normal. Esta aplicación está patentada.



⚠ The Wobble-Fix Extension Bar has less strength than normal extension bar due to it's specific design with a reduced square drive. Make sure to use it correctly.

2768N

Hinge Handle
Mango Articulado

* Renewal Kits → **2768RK** ➡P300

2768P

Hinge Handle
Mango Articulado

* Renewal Kits → **2768RK** ➡P300

2768J

Hinge Handle
Mango Articulado



* Renewal Kits → **2768RK** ➡P300

	D (mm)	L (mm)	(g)	(pcs.)
2768N	14	130	86	10
2768P	14	130	70	10
2768J	14	130	73	5

2769N-150 · -220

Spin Type Handle
Mango Tipo Destornillador ⚠

2769N	ℓ (mm)	L (mm)	(g)	(pcs.)
150	50	150	68	2
220	120	220	100	2

⚠ Plastic or rubber handles are not intended to act as insulation.
Los mangos de plástico o de goma no están previstos para aislamiento.

2769NWF-150 · -220

Spin Type Handle(Wobble-Fix)
Mango Tipo Destornillador Articulados-Fijos ⚠

Wobble-Fix

2769NWF	ℓ (mm)	L (mm)	(g)	(pcs.)
150	50	150	68	2
220	120	220	100	2

Wobble-Fix Extension Bar
Two way usage : One for as a flexible extension bar to provide at 15° angle operation, the other for use as a normal extension bar. This usage is Patent.

Alargadera Articulada-Fija
Dos formas de utilización : Una como alargadera flexible para poder trabajar con un ángulo de 15° y otra para utilizarse como alargadera normal. Esta aplicación está patentada.



2769F

Spin Type Handle
Mango Tipo Destornillador



	ℓ (mm)	L (mm)	(g)	(pcs.)
2769F	78	150	90	5

2769H

Folding Socket Driver
Llave de Vaso Plegable



	L (mm)	(g)	(pcs.)
2769H	160	180	10

2770 Universal Joint
Articulación Universal

	L (mm)	(g)	(pcs.)
2770	33	20	10
2771	31	20	10







2771 Universal Joint
Articulación Universal





2780 Speed Handle
Manivela Rápida

	L (mm)	(g)	(pce.)
2780	350	250	1



2785 T-Handle
Mango Corredizo

	L (mm)	(g)	(pcs.)
2785	115	36	10



2233A Adaptor
Adaptador

	(sq.)	(sq.)	L (mm)	(g)	(pcs.)
2233A	1/4"	3/8"	22	16	10



Hand Sockets 1/4”

2201AM
Socket Set
Juego de Vasos

2201AM	25 Pieces Set/=870g
METAL CASE:W240×H100×T32mm	
Sockets	**Accessories**
2400M 6-pt. Sockets 4, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13	**2753N**
2400A 6-pt. Sockets 3/16, 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2	**2760-100**
	2769N-150
	2770
	2785

2203M · 2203A
Socket Set
Juego de Vasos

2203M	12 Pieces Set/=550g
METAL CASE:W160×H100×T28mm	
Sockets	**Accessories**
2400M 6-pt. Sockets 4, 4.5, 5, 5.5, 6, 7, 8 9, 10, 11, 13	**2769H**

2203A	10 Pieces Set/=550g
METAL CASE:W160×H100×T28mm	
Sockets	**Accessories**
2400A 6-pt. Sockets 3/16, 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2	**2769H**

2250M · 2250A
Socket Set
Juego de Vasos



2250M	16 Pieces Set/=700g
METAL CASE:W160×H100×T28mm	
Sockets	**Accessories**
2400M 6-pt. Sockets 5, 6, 7, 8, 9, 10, 11, 12	**2753N**
2415M Double Square Sockets 8, 10	**2760-50**
	2760-150
	2768N
	2770
	2785

2250A	16 Pieces Set/=700g
METAL CASE:W160×H100×T28mm	
Sockets	**Accessories**
2400A 6-pt. Sockets 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16	**2753N**
2415A Double Square Sockets 1/4, 5/16, 3/8	**2760-50**
	2760-150
	2768N
	2770
	2785

2254M
Bit Set
Juego de Puntas

2254M	12 Pieces Set/=450g
METAL CASE:W160×H100×T28mm	
Bits	**Accessories**
101P Phillips Bits 1, 2, 3	**102NA-1/4x5/16**
101S Slotted Bits 1×7, 1.2×7	**2769F**
101H Hex Bits 3, 4, 5	**101A**
	2137

2257M Socket Set Juego de Vasos

2257M	31 Pieces Set/=930g
METAL CASE:W240×H100×T32mm	
Sockets	Accessories
2400M 6-pt. Sockets 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12	**2753N**
2000.28 Bit Sockets 1, 2, 3, 4	**2760-100**
2005.25 Bit Sockets 4, 5, 6, 8, 9	**2769N-150**
2010M.25 Bit Sockets 3, 4, 5, 6, 8, 10	**2770**
	2785

2260M Socket Set Juego de Vasos

2260M	28 Pieces Set/=2,370g
METAL CASE: W370×H150×T50mm	
Sockets	Accessories
2400M 6-pt. Sockets 4, 5, 5.5, 6, 7, 8, 10, 12	**2753N**
	2760-50
	2760-100
	2769N-150
3400M 6-pt. Sockets 8, 10, 11, 12, 13, 14, 15, 17, 18, 19, 21	**3749N**
	3760-75
	3760-125
	3785
	3322A

2261M Socket Set Juego de Vasos

2261M	17 Pieces Set/=690g
METAL CASE:W192×H122×T30mm	
Sockets	Accessories
2400M 6-pt. Sockets 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12	**2753N**
	2760-50
	2760-150
	2768N
	2770
	2785

2262M Socket Set Juego de Vasos

2262M	13 Pieces Set/=470g
METAL CASE:W160×H100×T28mm	
Sockets	Accessories
2400M 6-pt. Sockets 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12	**2760-50**
	2768N

2274M · 2274A Socket Set Juego de Vasos

2274M	7 Pieces Set/=245g
PLASTIC BAG	
Sockets	
2300M 6-pt. Deep Sockets 6, 7, 8, 9, 10, 11, 12	

2274A	7 Pieces Set/=245g
PLASTIC BAG	
Sockets	
2300A 6-pt. Deep Sockets 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2	

2275 Sockets Set / Juego de Vasos

2275	19 Pieces Set/=880g

METAL CASE:W192×H122×T30mm

Sockets	Accessories
2400M 6-pt. Sockets 5.5, 6, 7, 8, 10, 12, 13	**2753N**
2000.28 Bit Sockets 1, 2, 3	**2763-50**
2005.25 Bit Sockets 6, 8	**2769N-150**
2010M.25 Bit Sockets 3, 4, 5, 6	

2276 Sockets Set with Bits and Accessories / Juego de vasos con Puntas y Accesorios

2276	19 Pieces Set/=640g

METAL CASE:W192×H122×T30mm

Bits	Accessories
108P Phillips Bits 1, 2, 3	**2753PS**
108S Slotted Bits 4, 5, 6	**2769N-150**
108H Hex Bits 3, 4, 5, 6	**2137**
108T TORX® Bits T10, T15, T20, T25, T27, T30	

2277 Sockets Set / Juego de Vasos

2277	21 Pieces Set/=1,240g

METAL CASE:W310×H90×T48mm

Sockets	Accessories
2400M 6-pt. Sockets 5.5, 6, 7, 8, 9, 10, 11, 12, 13	**2753N**
2300M 6-pt. Deep Sockets 5.5, 6, 7, 8, 9, 10, 11, 12, 13	**2763-75**
	2769N-150

2277A-12P Sockets Set / Juego de Vasos

2277A-12P	21 Pieces Set/=1,240g

METAL CASE:W310×H90×T48mm

Sockets	Accessories
2405A 12-pt. Sockets 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2, 9/16	**2753N**
2305A 12-pt. Deep Sockets 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2, 9/16	**2763-75**
	2769N-150

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

P2201AM

Sockets Set
Juego de Vasos

P2201AM	25 Pieces Set/=800g

PLASTIC CASE:W245×H120×T45mm

Sockets	Accessories
2400M 6-pt. Sockets 4, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13	**2753N**
2400A 6-pt. Sockets 3/16, 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2	**2760-100**
	2769N-150
	2770
	2785

P2251M

Sockets Set
Juego de Vasos

P2251M	18 Pieces Set/=770g

PLASTIC CASE:W245×H120×T45mm

Sockets	Accessories
2400M 6-pt. Sockets 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13	**2753N**
	2760-50
	2760-150
	2768N
	2770
	2785

P2258M

Sockets Set
Juego de Vasos

P2258M	31 Pieces Set/=860g

PLASTIC CASE:W245×H120×T45mm

Sockets	Accessories
2400M 6-pt. Sockets 4, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13	**2753N**
2000.28 Bit Sockets 1, 2, 3	**2760-100**
2005.25 Bit Sockets 4, 6	**2769N-150**
2010M.25 Bit Sockets 3, 4, 5, 6, 8	**2770**
2025.28 Bit Sockets T10, T15, T20, T25, T30	**2785**

P2281A-12P

Sockets Set
Juego de Vasos

P2281A-12P	18 Pieces Set/=770g

PLASTIC CASE:W245×H120×T45mm

Sockets	Accessories
2405A 12-pt. Sockets 1/8, 5/32, 3/16, 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2, 9/16	**2753N**
	2760-50
	2760-150
	2768N
	2770
	2785

ABS Case - PE foam insert
Caja ABS - espuma polietileno

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

3400M · 3400A

6-point Sockets
Vasos Hexagonales



3400M 3405M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
5	8.3	17.3	5	26	20	10
5.5	8.9	17.3	5.5	26	20	10
6	9.9	17.3	6	26	20	10
7	10.8	17.3	6.5	26	20	10
8	12	17.3	7	26	22	10
9	13.3	17.3	7.5	26	23	10
10	14.5	17.3	8	26	24	10
11	15.8	17.3	8.5	26	25	10
12	16.8	17.3	9	26	25	10
13	18	17	9.5	26	24	10
14	19.5	18.5	11	27	31	10
15	20.8	19.5	11.5	28	39	10
16	22	20	12	28	42	10
17	23.3	21.5	12.5	29	51	10
18	24.5	22.5	13	30	51	10
19	25.8	23.5	13.5	30	63	10
20	27	24.5	14	31	75	10
21	28	26	14.5	32	77	10
22	29.5	26.5	15	32	82	10
23	30.8	27.5	15.5	33	95	10
24	32	28.5	16	34	102	10
New **25**	33.3	29.5	16.5	34	115	10
New **26**	34.5	30.5	17	35	129	10

3405M · 3405A

12-point Sockets
Vasos Bihexagonales



3400A 3405A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
3/16	8.3	17.3	5	26	20	10
1/4	10.3	17.3	6	26	20	10
9/32	10.8	17.3	6.5	26	20	10
5/16	12	17.3	7	26	22	10
11/32	13.3	17.3	7.5	26	23	10
3/8	13.9	17.3	8	26	23	10
13/32	13.3	17.3	7.5	26	23	10
7/16	15.8	17.3	8.5	26	25	10
1/2	18	17	9.5	26	24	10
9/16	19.5	18.5	11	27	31	10
19/32	20.8	19.5	11.5	28	39	10
5/8	22	20	12	28	42	10
11/16	24.5	22.5	13	30	51	10
3/4	25.8	23.5	13.5	30	63	10
25/32	27	24.5	14	31	75	10
13/16	28	26	14.5	32	77	10
7/8	29.5	26.5	15	32	82	10
15/16	32	28.5	16	34	102	10
New **1**	34.5	30.5	17	35	132	10

FLAT DRIVE®

Flat drive is designed to guarantee a flat surface contact between the socket and the bolt/nut. The Flat contact reduces wear and allows to transmit a higher torque value. The Flat Drive System is also used for the square drive end as well as the hexagonal or bi-hexagonal openings of the socket.

El diseño de contacto plano garantiza una superficie de contacto plana entre el vaso y el perno/tuerca. El contacto plano reduce el desgaste y permite transmitir más par. El Sistema de Contacto Plano se utiliza tanto para el extremo del cuadrado conductor como para la boca del vaso Hex o Bihex.

RS3400M/8
RS3405M/8

Socket Set on Rail
Juego de Vasos en Regleta

RS3400M/8	8 Pieces Set/Rail 200mm	(g)
	8, 10, 11, 12, 13, 14, 17, 19	300

RS3405M/8	8 Pieces Set/Rail 200mm	(g)
	8, 10, 11, 12, 13, 14, 17, 19	300

RS3400M/12
RS3405M/12

Socket Set on Rail
Juego de Vasos en Regleta

RS3400M/12	12 Pieces Set/Rail 300mm	(g)
	8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19	465

RS3405M/12	12 Pieces Set/Rail 300mm	(g)
	8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19	465

RS3400A/9
RS3405A/9

Socket Set on Rail
Juego de Vasos en Regleta

RS3400A/9	9 Pieces Set/Rail 200mm	(g)
	1/4, 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4	333

RS3405A/9	9 Pieces Set/Rail 200mm	(g)
	1/4, 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4	333

3410M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
5.5	8.9	17.3	5.5	26	20	10
6	9.9	17.3	6	26	20	10
7	10.8	17.3	6.5	26	20	10
8	12	17.3	7	26	22	10
9	13.3	17.3	7.5	26	23	10
10	14.5	17.3	8	26	24	10
11	15.8	17.3	8.5	26	25	10
12	16.8	17.3	9	26	25	10
13	18	17	9.5	26	24	10
14	19.5	18.5	11	27	31	10
15	20.8	19.5	11.5	28	39	10
16	22	20	12	28	42	10
17	23.3	21.5	12.5	29	51	10
18	24.5	22.5	13	30	51	10
19	25.8	23.5	13.5	30	63	10
20	27	24.5	14	31	75	10
21	28	26	14.5	32	77	10
22	29.5	26.5	15	32	82	10
23	30.8	27.5	15.5	33	95	10
24	32	28.5	16	34	102	10

3410M

Surface Drive Sockets
Vasos Surface Drive (de Contacto Curvo)



SURFACE DRIVE

Surface drive sockets are designed to retain contact with flat sides of nut to transmit high torque and reduce nut wear. These sockets are ideal for use on polished nuts, aluminum nuts and nuts with worn out points.

Los vasos de contacto curvo se diseñan para mantener el contacto con las caras planas de la tuerca y transmitir un alto par reduciendo el desgaste de la tuerca. Estos vasos son ideales para utilizarse en tuercas pulidas, tuercas de aluminio y tuercas con puntas gastadas

RS3410M/12	12 Pieces Set/Rail 300mm	(g)
8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19		468

RS3410M/12

Socket Set on Rail
Juego de Vasos en Regleta

3400W 3405W (W)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
1/8	13.3	17.3	7.5	26	22	10
3/16	15.8	17.3	8.5	26	25	10
1/4	18	17	9.5	26	24	10
5/16	20.8	19.5	11.5	28	39	10
3/8	24.5	22.5	13	30	51	10
7/16	28	26	14.5	32	81	10
1/2	30.8	27.5	15.5	33	103	10
9/16	34.5	30.5	17	35	128	10

3400W

6-point Whitworth Sockets
Vasos Hexagonales Whitworth



3405W

12-point Whitworth Sockets
Vasos Bihexagonales Whitworth



BS W

BS・W	BS	3/16BS	1/4BS	5/16BS	3/8BS	7/16BS	1/2BS	9/16BS	5/8BS	11/16BS	3/4BS	7/8BS
	W	1/8W	3/16W	1/4W	5/16W	3/8W	7/16W	1/2W	9/16W	5/8W	11/16W	3/4W
Across Flat	(ref. mm)	8.64	11.30	13.34	15.24	18.03	20.83	23.37	25.65	27.94	30.48	33.35

RS3400W/7	7 Pieces Set/Rail 200mm	(g)
1/8, 3/16, 1/4, 5/16, 3/8, 7/16, 1/2		389

RS3405W/7	7 Pieces Set/Rail 200mm	(g)
1/8, 3/16, 1/4, 5/16, 3/8, 7/16, 1/2		389

RS3400W/7
RS3405W/7

Socket Set on Rail
Juego de Vasos en Regleta

3415M · 3415A

Double Square Sockets
Vasos Octagonales



	3415M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
New	**5.5**	10.8	17.4	5.5	26	21	10
	6	12	17.3	6	26	26	10
New	**7**	13.3	17.4	6.5	26	26	10
	8	14.5	17.3	7	26	26	10
	10	16.8	17.3	8	26	27	10
	12	20.8	19.5	9	27	43	10
New	**13**	21.9	20	9.5	27	46	10

3415A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
1/4	12	17.3	6	26	24	10
5/16	14.5	17.3	7	26	26	10
11/32	15.8	17.3	7.5	26	27	10
3/8	16.8	17.3	8	26	27	10
7/16	19.5	18.5	8.5	27	37	10
1/2	22	20	9.5	27	46	10

3425

TORX® Sockets
Vasos TORX®



3425 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
E 4	5.6	17.3	4.6	26	18	10
E 5	7	17.3	5.2	26	20	10
E 6	8.3	17.3	5.4	26	21	10
E 7	8.9	17.3	6.6	26	22	10
E 8	9.9	17.3	7	26	23	10
E10	12	17.3	8.2	26	24	10
E11	13.3	17.3	8.7	26	25	10
E12	14.5	17.3	9.3	26	26	10
E14	15.8	17.3	10.6	26	27	10
E16	18	17	11.8	26	27	10

TORX® (E)



E		E4	E5	E6	E7	E8	E10	E11	E12	E14	E16	E18	E20	E22	E24	E26	E28
S1	(ref. mm)	3.7	4.6	5.6	6.1	7.4	9.3	9.9	11.0	12.8	14.6	16.5	18.3	20.1	22.0	23.7	25.5
S2	(ref. mm)	2.7	3.3	4.0	4.3	5.3	6.8	7.1	7.9	9.2	10.5	11.9	13.2	14.8	15.7	17.5	18.3

RS3425/9

Socket Set on Rail
Juego de Vasos en Regleta

RS3425/9	9 Pieces Set/Rail 200mm	(g)
E4, E5, E6, E7, E8, E10, E12, E14, E16		239

3400LH

LHS Sockets
Vasos LHS



3400LH (LH-S)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
5S	10.8	17.3	5	26	20	10
6S	12	17.3	5.6	26	22	10
8S	15.8	17.3	6.8	26	25	10
10S	18	17	8	26	25	10
12S	22	20	9.2	28	42	10
14S	24.5	22.5	10.4	30	51	10
16S	28	26	11.6	32	77	10

RS3400LH/7

Socket Set on Rail
Juego de Vasos en Regleta

RS3400LH/7	7 Pieces Set/Rail 150mm	(g)
5S, 6S, 8S, 10S, 12S, 14S, 16S		315

TORX® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX® es una marca registrada de **Acument Intellectual Properties, LLC.**
LHstix® is a registered trademark of **OSG CORPORATION** System Engineering Department.
LHstix® es una marca registrada de **OSG CORPORATION** System Engineering Department.

3450M

Nut Grip Sockets **Nut Grip®**
Vasos Sujeta-tuercas **Nut Grip®**



3450M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
8	12	17.3	5	26	21	10
10	14.5	17.3	6	26	24	10
11	15.8	17.3	6.5	26	26	10
12	16.8	17.3	7	26	26	10
13	18	17	8	26	28	10
14	19.5	18.5	8.5	27	34	10
15	20.8	19.5	9	27	42	10
16	22	20	9	27	50	10
17	23.3	21.5	9.5	28	62	10
18	24.5	22.5	10.5	29	64	10
19	25.8	23.3	11.5	29	66	10
21	28	26	12	29	85	10
22	29.5	27	12.5	29	90	10
24	32	30	14.5	31	102	10





NUT GRIP®



Twin balls at the 6-point opening hold bolt-nut tightly for safe and reliable work.

Las dos bolas de la boca Hexagonal sujetan el perno-tuerca permitiendo un trabajo seguro y fiable.

RS3450M/8

Socket Set on Rail
Juego de Vasos en Regleta

RS3450M/8 — 8 Pieces Set/Rail 200mm	(g)
8, 10, 11, 12, 13, 14, 17, 19	310

RS3450M/10

Socket Set on Rail
Juego de Vasos en Regleta

RS3450M/10 — 10 Pieces Set/Rail 250mm	(g)
10, 11, 12, 13, 14, 15, 17, 19, 21, 22	500

3425 (2B)

TORX® Sockets **Nut Grip®**
Vasos TORX® **Nut Grip®**



3425 (2B)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
E10	12	17.3	8.2	26	23	10
E12	14.5	17.3	9.3	26	25	10
E14	15.8	17.3	10.6	26	26	10
E16	18.1	17	11.8	26	27	10
E18	19.5	18.5	12	32	41	10
E20	21.9	20	14.4	32	52	10

RS3425/4 (2B)

Socket Set on Rail
Juego de Vasos en Regleta

RS3425/4(2B) — 4 Pieces Set/Rail 150mm	(g)
E10, E12, E14, E20	150

TORX® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX® es una marca registrada de **Acument Intellectual Properties, LLC.**

3300X · 3300XA

6-point Sockets, Semi-Deep
Vasos Hexagonales, Medianos



3300X 3305X (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
8	12	17.3	9	26.5	40	34	10
9	13	17.3	10	26.5	40	36	10
10	14.5	17.3	11	26.5	40	36	10
11	16	17.2	12	26.5	40	36	10
12	16.8	17.2	13	26.5	40	36	10
13	18	17	14	26.5	40	37	10
14	20	18	16	26.5	40	46	10
15	21	20	16	25.5	40	49	10
16	22	20	17	25.5	40	51	10
17	23.5	22	18	25.5	40	61	10
18	24.5	23	19	24.5	40	68	10
19	25	24	20	24.5	40	75	10

3305X · 3305XA

12-point Sockets, Semi-Deep
Vasos Bihexagonales, Medianos



3300XA 3305XA (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
1/4	10.3	17.3	7	26.5	40	32	10
5/16	12	17.3	9	26.5	40	34	10
3/8	13.9	17.3	11	26.5	40	36	10
7/16	16	17.2	12	26.5	40	36	10
1/2	18	17	14	26.5	40	37	10
9/16	20	18.5	16	26.5	40	46	10
5/8	22	20	17	25.5	40	51	10
11/16	24.5	22.5	19	24.5	40	68	10
3/4	25	23.5	20	24.5	40	75	10

RS3300X/8
RS3305X/8

Socket Set on Rail
Juego de Vasos en Regleta

RS3300X/8	8 Pieces Set/Rail 200mm	(g)
	8, 10, 11, 12, 13, 14, 17, 19	405

RS3305X/8	8 Pieces Set/Rail 200mm	(g)
	8, 10, 11, 12, 13, 14, 17, 19	405

RS3300XA/9
RS3305XA/9

Socket Set on Rail
Juego de Vasos en Regleta

RS3300XA/9	9 Pieces Set/Rail 200mm	(g)
	1/4, 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4	460

RS3305XA/9	9 Pieces Set/Rail 200mm	(g)
	1/4, 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4	460

3350X

Nut Grip® Socket, Semi-Deep
Vasos Sujeta-tuercas **Nut Grip®**. Medianos



3350X (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
8	12	17.4	5	26.5	40	33	10
10	14.5	17.4	6	26.5	40	35	10
12	16.8	17.2	7	26.5	40	40	10
14	19.5	18.5	8.5	26.5	40	48	10

RS3350X/4

Socket Set on Rail
Juego de Vasos en Regleta

	RS3350X/4	4 Pieces Set/Rail 150mm	(g)
New		**8, 10, 12, 14**	165

3300M · 3300A

6-point Deep Sockets
Vasos Hexagonales Largos



3300M 3305M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
5.5	8.9	17.3	6.5	41.5	55	37	10
6	9.9	17.3	7	41.5	55	37	10
7	10.6	17.3	8	41.5	55	37	10
8	12	17.3	9	41.5	55	40	10
9	13	17.3	10	41.5	55	42	10
10	14.5	17.3	11	41.5	55	46	10
11	16	17.2	12	41.5	55	51	10
12	16.8	17.2	13	41.5	55	52	10
13	18	17	14	41.5	55	53	10
14	20	18	16	41.5	55	60	10
15	21	20	16	40.5	55	74	10
16	22	20	17	40.5	55	76	10
17	23.5	22	18	40.5	55	93	10
18	24.5	23	19	39.5	55	98	10
19	25	24	20	39.5	55	98	10
20	26	25	21	49.5	65	126	10
21	27	26	22	49.5	65	126	10
22	29	28	23	48.5	65	163	10
23	30	29	24	48.5	65	168	10
24	31	30	25	47.5	65	191	10
25	33	30	26	47.5	65	199	10
26	34	31	27	47.5	65	209	10
27	35	32.5	28	47.5	65	218	10

3305M · 3305A

12-point Deep Sockets
Vasos Bihexagonales Largos



3300A 3305A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
7/32	8.9	17.3	6	41.5	55	35	10
1/4	9.9	17.3	7	41.5	55	37	10
5/16	12	17.3	9	41.5	55	40	10
11/32	12.3	17.3	10	41.5	55	41	10
3/8	14	17.3	11	41.5	55	46	10
7/16	16	17.2	12	41.5	55	51	10
1/2	18	17	14	41.5	55	53	10
9/16	20	18	16	41.5	55	60	10
19/32	21	20	16	40.5	55	74	10
5/8	22	20	17	40.5	55	76	10
11/16	23.5	22	18	40.5	55	93	10
3/4	25	24	20	39.5	55	98	10
13/16	27	26	22	49.5	65	126	10
7/8	29	28	23	48.5	65	163	10
15/16	31	30	25	47.5	65	191	10

RS3300M/8
RS3305M/8

Socket Set on Rail
Juego de Vasos en Regleta

RS3300M/8	8 Pieces Set/Rail 200mm	(g)
	8, 10, 11, 12, 13, 14, 17, 19	540

RS3305M/8	8 Pieces Set/Rail 200mm	(g)
	8, 10, 11, 12, 13, 14, 17, 19	540

RS3300M/12
RS3305M/12

Socket Set on Rail
Juego de Vasos en Regleta

RS3300M/12	12 Pieces Set/Rail 300mm	(g)
	8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19	878

RS3305M/12	12 Pieces Set/Rail 300mm	(g)
	8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19	878

RS3300A/9
RS3305A/9

Socket Set on Rail
Juego de Vasos en Regleta

RS3300A/9	9 Pieces Set/Rail 200mm	(g)
	1/4, 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4	628

RS3305A/9	9 Pieces Set/Rail 200mm	(g)
	1/4, 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4	628

3300M (L120)

6-point Extra Deep Sockets
Vasos Hexagonales Extra-Largos

3305M (L120)

12-point Extra Deep Sockets
Vasos Bihexagonales Extra-Largos



3300M(L120) 3305M(L120) (mm)	D₁ (mm)	D₂ (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
8	12	17.3	9	106.5	120	85	10
10	14.5	17.3	11	106.5	120	110	10
12	16.8	17.2	13	106.5	120	116	10
13	18	17	14	106.5	120	155	5
14	20	18	16	106.5	120	166	5

3300M-Size DEEP SOCKET



3300M-Size(L120) EXTRA DEEP SOCKET



3300M/4-L120
3305M/4-L120

Socket Set
Juego de Vasos

3300M/4-L120	4 Pieces Set/⚖=477g
PLASTIC BAG	
Sockets	
3300M(L120) 6-point Extra Deep Sockets 8, 10, 12, 14	

3305M/4-L120	4 Pieces Set/⚖=477g
PLASTIC BAG	
Sockets	
3305M(L120) 12-point Extra Deep Sockets 8, 10, 12, 14	

3310M

Surface Drive Deep Sockets
Vasos Surface Drive (de Contacto Curvo) Largos



3310M (mm)	D₁ (mm)	D₂ (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
6	9.9	17.3	7	41.5	55	37	10
7	10.6	17.3	8	41.5	55	37	10
8	12	17.3	9	41.5	55	40	10
9	13	17.3	10	41.5	55	42	10
10	14.5	17.3	11	41.5	55	46	10
11	16	17.2	12	41.5	55	51	10
12	16.8	17.2	13	41.5	55	52	10
13	18	17	14	41.5	55	53	10
14	20	18	16	41.5	55	60	10
15	21	20	16	40.5	55	74	10
16	22	20	17	40.5	55	76	10
17	23.5	22	18	40.5	55	93	10
18	24.5	23	19	39.5	55	98	10
19	25	24	20	39.5	55	98	10
20	26	25	21	49.5	65	126	10
21	27	26	22	49.5	65	126	10
22	29	28	23	48.5	65	163	10
23	30	29	24	48.5	65	168	10
24	31	30	25	47.5	65	161	10

RS3310M/12

Socket Set on Rail
Juego de Vasos en Regleta

RS3310M/12	12 Pieces Set/Rail 300mm	⚖ (g)
8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19		881

3300W

6-point Deep Whitworth Sockets
Vasos Whitworth Hexagonales Largos



3300W 3305W (W)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
1/8	12.3	17.3	10	41.5	55	46	10
3/16	16	17.3	12	41.5	55	55	10
1/4	18	17	14	41.5	55	57	10
5/16	21	20	16	40.5	55	79	10
3/8	24.5	23	19	39.5	55	96	10
7/16	27	26	22	49.5	65	140	10
1/2	30	29	24	48.5	65	193	10
9/16	34	31	27	47.5	65	250	10

3305W

12-point Deep Whitworth Sockets
Vasos Whitworth Bihexagonales Largos



BS W

BS・W												
	BS	3/16BS	1/4BS	5/16BS	3/8BS	7/16BS	1/2BS	9/16BS	5/8BS	11/16BS	3/4BS	7/8BS
	W	1/8W	3/16W	1/4W	5/16W	3/8W	7/16W	1/2W	9/16W	5/8W	11/16W	3/4W
Across Flat	(ref. mm)	8.64	11.30	13.34	15.24	18.03	20.83	23.37	25.65	27.94	30.48	33.35

RS3300W/7
RS3305W/7

Socket Set on Rail
Juego de Vasos en Regleta

RS3300W/7 — 7 Pieces Set/Rail 200mm	(g)
1/8, 3/16, 1/4, 5/16, 3/8, 7/16, 1/2	719

RS3305W/7 — 7 Pieces Set/Rail 200mm	(g)
1/8, 3/16, 1/4, 5/16, 3/8, 7/16, 1/2	719

3325

TORX® Deep Sockets
Vasos TORX® Largos



3325 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
E 4	5.6	17.3	4.6	41.5	55	29	10
E 5	6.9	17.3	5.2	41.5	55	31	10
E 6	7.9	17.3	5.4	41.5	55	33	10
E 7	8.9	17.3	6.6	41.5	55	36	10
E 8	9.9	17.3	7	41.5	55	39	10
E10	11.8	17.3	8.2	41.5	55	43	10
E12	14.5	17.2	9.3	41.5	55	53	10
E14	15.7	17.2	10.6	41.5	55	57	10
E16	18	17	11.8	41.5	55	69	10

TORX® (E)



E		E4	E5	E6	E7	E8	E10	E11	E12	E14	E16	E18	E20	E22	E24	E26	E28
S1	(ref. mm)	3.7	4.6	5.6	6.1	7.4	9.3	9.9	11.0	12.8	14.6	16.5	18.3	20.1	22.0	23.7	25.5
S2	(ref. mm)	2.7	3.3	4.0	4.3	5.3	6.8	7.1	7.9	9.2	10.5	11.9	13.2	14.8	15.7	17.5	18.3

RS3325/9

Socket Set on Rail
Juego de Vasos en Regleta

RS3325/9 — 9 Pieces Set/Rail 200mm	(g)
E4, E5, E6, E7, E8, E10, E12, E14, E16	420

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

3350M

Nut Grip Deep Sockets **Nut Grip®**
Vasos Sujeta-tuercas Largos **Nut Grip®**





3350M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
8	12	17.4	5	41.5	55	50	10
10	14.5	17.4	6	41.5	55	54	10
12	16.8	17.2	7	41.5	55	58	10
13	18	17	8	41.5	55	59	10
14	19.5	18.5	8.5	41.5	55	71	10

RS3350M/5

Socket Set on Rail
Juego de Vasos en Regleta

RS3350M/5	5 Pieces set/Rail 150mm	(g)
	8, 10, 12, 13, 14	322





3350M (L120)

Extra Deep Sockets **Nut Grip®**
Vasos Extra-Largos **Nut Grip®**



3350M(L120) (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
10	14.5	17.2	6	106.5	120	110	10
12	16.8	17.2	7	106.5	120	116	10

3350M/2-L120

Socket Set
Juego de Vasos

3350M/2-L120	2 Pieces Set/=230g
PLASTIC BAG	
Sockets	
3350M(L120) Nut Grip Extra Deep Sockets 10, 12	

3300FN

Flare Nut Sockets
Llaves de vaso para entubar





3300FN (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	S (mm)	(g)	(pcs.)
8	14.5	17.3	6	53	6.4	38	10
9	16	17.3	7	53	6.8	41	10
10	16.8	17.2	7.5	53	7.2	42	10
11	18	17	8.5	53	8.3	42	10
12	20	18	9	53	8.8	50	10
13	21.1	20	9.5	62	9.4	66	10
14	22	20	10.5	62	10.5	66	10
15	23	22	11	70	11.5	82	10
16	24	23	11.5	70	12	90	10
17	25	24	12.5	80	13	110	10
18	27	25	13	80	13.5	120	10
19	28	26	14	80	14.5	130	10
22	32	29.5	16	80	16	180	10
24	34.5	31.5	17	80	17	200	10

RS3300FN/6

Socket Set on Rail
Juego de Vasos en Regleta

RS3300FN/6	6 Pieces Set/Rail 150mm	(g)
	8, 10, 12, 14, 17, 19	450

3440M · 3440A

6-point Universal Sockets
Vasos Hexagonales Universal

3440M 3445M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
8	12	19	7.3	47	50	10
9	13.3	19	7.8	47.5	50	10
10	14.5	19	8.8	48.5	64	10
11	15.8	19	9.8	49.5	66	10
12	17	19	10.3	50	67	10
13	18.3	19	11.3	51	68	10
14	19.5	19	11.3	51	69	10
15	20.8	19	12.8	53.5	70	10
16	22	19	12.8	53.5	77	10
17	23.3	19	13.8	54.5	80	10
18	24.5	19	13.8	54.5	80	10
19	25.8	19	15.8	56.5	84	10
21	28.3	19	16.8	56.5	96	10



3445M · 3445A

12-point Universal Sockets
Vasos Bihexagonales con Articulación Universal

3440A 3445A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
5/16	12	19	7.3	47	50	10
3/8	14	19	8.3	48	64	10
7/16	15.8	19	9.8	49.5	66	10
1/2	18.3	19	11.3	51	68	10
9/16	19.5	19	11.3	51	69	10
5/8	22	19	12.8	53.5	77	10
11/16	24.5	19	13.8	54.5	80	10
3/4	25.8	19	15.8	56.5	84	10



RS3440M/8
RS3440A /8

Socket Set on Rail
Juego de Vasos en Regleta

RS3440M/8	8 Pieces Set/Rail 200mm	(g)
	8, 10, 11, 12, 13, 14, 17, 19	550

RS3440A/8	8 Pieces Set/Rail 200mm	(g)
	5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4	570

3445W

12-point Whitworth Universal Socket
Vasos Whitworth Bihex con Articulación Universal

3445W (W)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
1/8	13.3	19	7.8	47.5	50	10
3/16	15.8	19	9.7	49.5	66	10
1/4	18.3	19	11.3	51	68	10
5/16	20.8	19	12.8	53.5	70	10
3/8	24.5	19	13.8	54.5	80	10
7/16	28.3	19	16.8	57.5	96	10
1/2	30.8	19	17.8	58.5	105	10



RS3445W/7

Socket Set on Rail
Juego de Vasos en Regleta

RS3445W/7	7 Pieces Set/Rail 200mm	(g)
	1/8, 3/16, 1/4, 5/16, 3/8, 7/16, 1/2	570

3440T

TORX® Universal Sockets
Vasos TORX® con Articulación Universal



3440T (E)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
E 6	7.9	19	5.4	44.9	60	10
E 8	9.9	19	7	46.5	63	10
E10	11.8	19	8.2	47.7	63	10
E12	14.5	19	9.3	48.8	68	10
E14	15.7	19	10.6	50.1	68	10
E16	18	19	11.8	51.3	70	10
E18	19.5	19	13	53.5	78	10
E20	22	19	14.4	54.9	81	10

RS3440T/8

Socket Set on Rail
Juego de Vasos en Regleta

RS3440T/8	8 Pieces Set/Rail 200mm	(g)
E6, E8, E10, E12, E14, E16, E18, E20		594

3441M

Nut Grip Universal Sockets **Nut Grip®**
Vasos Sujeta-Tuercas con Articulación Universal



3441M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
8	12	19	5	46	57	10
10	14.5	19	6	46	58	10
12	16.8	19	7	47	58	10
13	18	19	8	48	60	10
14	19.5	19	8.5	49.5	65	10

RS3441M/5

Socket Set on Rail
Juego de Vasos en Regleta

RS3441M/5	5 Pieces Set/Rail 150mm	(g)
8, 10, 12, 13, 14		320

3340M-75

Universal Deep Sockets
Vasos Largos con Articulación Universal



3340M.75 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
8	12	19	9	39	75	82	10
10	14.5	19	11	39	75	87	10
11	15.8	19	12	39	75	87	10
12	17	19	13	39	75	92	10
13	18.3	19	14	36	75	93	10
14	19.5	19	15	35	75	103	10
15	20.8	19	16	35	75	104	10
16	22	19	17	34	75	110	10
17	23.3	19	18	34	75	115	10
18	24.5	19	19	34	75	119	10
19	25.8	19	20	33	75	123	10

RS3340M/8-L75

Socket Set on Rail
Juego de Vasos en Regleta

RS3340M/8-L75	8 Pieces Set/Rail 200mm	(g)
8, 10, 11, 12, 13, 14, 17, 19		810

TORX® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX® es una marca registrada de **Acument Intellectual Properties, LLC.**

3430M

Universal Inhex Bit Sockets
Vasos Inhex con Articulación Universal



3430M (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
5	19	15.5	62	66	10
6	19	15.5	62	70	10
7	19	15.5	62	72	10
8	19	15.5	62	74	10
10	19	15.5	62	78	10
12	19	15.5	62	85	10

RS3430M/6

Socket Set on Rail
Juego de Vasos en Regleta

RS3430M/6	6 Pieces Set/Rail 150mm	(g)
5, 6, 7, 8, 10, 12		470

3117M-125 · -250

Extension Deep Sockets
Vasos con Alargadera



3117M.125 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pce.)
10	14.5	18	10	44	125	121	1
11	16	18	11	44	125	133	1
12	17	18	12	44	125	133	1
13	18	18	13	44	125	134	1
14	19.5	18	14	44	125	145	1
17	23.5	18	17	44	125	178	1
19	25	18	19	44	125	187	1
21	27	18	21	44	125	195	1
22	29	18	22	44	125	214	1

3117M.250 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pce.)
10	14.5	18	10	44	250	233	1
11	16	18	11	44	250	241	1
12	17	18	12	44	250	246	1
13	18	18	13	44	250	249	1
14	19.5	18	14	44	250	262	1
17	23.5	18	17	44	250	289	1
19	25	18	19	44	250	298	1
21	27	18	21	44	250	302	1
22	29	18	22	44	250	325	1

3000-60 (PH)

Phillips Bit Sockets
Vasos con Punta Phillips



3000 (PH)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
1	18	33.5	60	49	10
2	18	33.5	60	49	10
3	18	33.5	60	49	10
4	18	33.5	60	50	10

3000-50 (PZ)

PZ Bit Sockets
Vasos con Punta PZ



3000.50 (PZ)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
PZ1	18	23.5	50	50	10
PZ2	18	23.5	50	50	10
PZ3	18	23.5	50	50	10

3005-60

Slotted Bit Sockets
Vasos con Punta Recta para Cabeza Ranurada



3005	T×W (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
5	1.0× 5.5	18	33.5	60	47	10
8	1.2× 8	18	33.5	60	49	10
10	1.6×10	20	33.5	60	85	10

	Phillips (PH)	PZ	Slotted	HEX	HEX (ball point)	Triple Square (XZN)	TORX® (T)	TORX® (TH)	TORXPLUS® (IP)	TORXPLUS® (IPR)	Ribe-CV
1/4"	No.2000 series	No.2000(PZ) series	No.2005 series	No.2010M/A series	No.2011M series	No.2020 series	No.2025 series	No.2025(TH) series	No.2025(IP) series	No.2025(IPR) series	—
3/8"	No.3000 No.3001 series	No.3000(PZ) series	No.3005 No.3006 series	No.3010M/A No.3012M/A No.3015M series	No.3011M series	No.3020 series	No.3025 series	No.3025(TH) series	No.3025(IP) series	No.3025(IPR) series	No.3027 series
1/2"	No.4000 No.4001 series	No.4000(PZ) series	No.4005 No.4006 series	No.4010M/A No.4012M/A series	—	No.4020 series	No.4025 series	—	No.4025(IP) series	—	No.4027 series

3010M-38 · -62 · -100 · -160
3010A-50

Inhex Bit Sockets
Vasos con Punta Hexagonal



3010M.38 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	18	11.5	38	27	10
4	18	11.5	38	28	10
5	18	11.5	38	30	10
6	18	11.5	38	31	10
7	18	11.5	38	32	10
8	18	11.5	38	33	10
9	20	11.5	38	47	10
10	20	11.5	38	48	10
11	20	11.5	38	59	10
12	20	11.5	38	60	10
13	22	11.5	38	76	5
14	22	11.5	38	78	5

3010M.62 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	18	35.5	62	43	10
4	18	35.5	62	45	10
5	18	35.5	62	48	10
6	18	35.5	62	49	10
7	18	35.5	62	50	10
8	18	35.5	62	62	10
9	20	35.5	62	75	10
10	20	35.5	62	76	10
11	20	35.5	62	92	10
12	20	35.5	62	94	10
13	22	35.5	62	107	5
14	22	35.5	62	109	5

3010M.100 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	18	73.5	100	58	10
4	18	73.5	100	60	10
5	18	73.5	100	63	10
6	18	73.5	100	64	10
7	18	73.5	100	66	10
8	18	73.5	100	69	10
9	20	73.5	100	100	10
10	20	73.5	100	102	10
11	20	73.5	100	129	10
12	20	73.5	100	131	10
13	22	73.5	100	158	5
14	22	73.5	100	160	5

3010M.160 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	18	133.5	160	84	10
4	18	133.5	160	86	10
5	18	133.5	160	89	10
6	18	133.5	160	90	10
7	18	133.5	160	92	10
8	18	133.5	160	95	10
9	20	133.5	160	125	10
10	20	133.5	160	128	10
11	20	133.5	160	153	10
12	20	133.5	160	157	10
13	22	133.5	160	237	5
14	22	133.5	160	239	5

3010A.50 (inch)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
1/8	18	23.5	50	35	10
5/32	18	23.5	50	36	10
3/16	18	23.5	50	36	10
7/32	18	23.5	50	38	10
1/4	18	23.5	50	40	10
9/32	18	23.5	50	42	10
5/16	18	23.5	50	44	10
11/32	20	23.5	50	59	10
3/8	20	23.5	50	60	10
7/16	20	23.5	50	74	10
1/2	22	23.5	50	91	5

RS3010M/8-L38
RS3010M/8-L62
RS3010M/8-L100
RS3010A/8-L50

Socket Set on Rail
Juego de Vasos en Regleta

RS3010M/8-L38	8 Pieces Set/Rail 200mm	(g)
3, 4, 5, 6, 7, 8, 10, 12		322

RS3010M/8-L62	8 Pieces Set/Rail 200mm	(g)
3, 4, 5, 6, 7, 8, 10, 12		490

RS3010M/8-L100	8 Pieces Set/Rail 200mm	(g)
3, 4, 5, 6, 7, 8, 10, 12		645

RS3010A/8-L50	8 Pieces Set/Rail 200mm	(g)
1/8, 5/32, 3/16, 7/32, 1/4, 5/16, 3/8, 1/2		400

3012M-25

Inhex Sockets
Vasos con Punta de Hexagonal



3012M.25 (inch)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
New 3	18.5	5.5	10	25	22	10
New 4	18.5	5.5	10	25	22	10
New 5	18.5	6.5	10	25	22	10
New 6	18.5	7.5	10	25	23	10
New 7	18.5	10	–	25	24	10
New 8	18.5	10	–	25	25	10
New 10	18.5	10	–	25	27	10
New 12	18.5	10	–	25	30	10
14	19	10	–	25	30	10
17	19	10	–	25	30	10

3012M-52 · -62 · -75
3012A -52 · -62 · -75

Inhex Sockets
Vasos con Punta de Hexagonal



3012M/A are for hand use only.
Do not use with a power or impact wrench.

3012M.52 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	18	10	34	52	35	10
4	18	15.5	34	52	38	10
5	18	15.5	34	52	40	10
6	18	15.5	34	52	42	10
7	18	15.5	34	52	46	10
8	18.5	15.5	34	52	50	10
9	18.5	15.5	34	52	55	10
10	20	15.5	34	52	66	10
11	20	15.5	34	52	72	10
12	20	15.5	34	52	77	10
13	20	15.5	34	52	82	10
14	20	15.5	34	52	89	10

3012A.52 (inch)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
1/8	18	10	34	52	35	10
5/32	18	15.5	34	52	38	10
3/16	18	15.5	34	52	40	10
7/32	18	15.5	34	52	42	10
1/4	18	15.5	34	52	44	10
9/32	18	15.5	34	52	46	10
5/16	18.5	15.5	34	52	50	10
11/32	18.5	15.5	34	52	55	10
3/8	20	15.5	34	52	65	10
7/16	20	15.5	34	52	72	10
1/2	20	15.5	34	52	82	10
9/16	20	15.5	34	52	89	10

3012M.62 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	18	10	44	62	38	10
4	18	15.5	44	62	40	10
5	18	15.5	44	62	43	10
6	18	15.5	44	62	46	10
7	18	15.5	44	62	53	10
8	18.5	15.5	44	62	58	10
9	18.5	15.5	44	62	63	10
10	20	15.5	44	62	77	10
11	20	15.5	44	62	83	10
12	20	15.5	44	62	90	10
13	20	15.5	44	62	95	10
14	20	15.5	44	62	109	10

3012A.62 (inch)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
1/8	18	10	44	62	38	10
5/32	18	15.5	44	62	40	10
3/16	18	15.5	44	62	43	10
7/32	18	15.5	44	62	46	10
1/4	18	15.5	44	62	48	10
9/32	18	15.5	44	62	53	10
5/16	18.5	15.5	44	62	58	10
11/32	18.5	15.5	44	62	63	10
3/8	20	15.5	44	62	73	10
7/16	20	15.5	44	62	83	10
1/2	20	15.5	44	62	95	10
9/16	20	15.5	44	62	109	10

3012M.75 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	18	10	57	75	41	10
4	18	15.5	57	75	43	10
5	18	15.5	57	75	48	10
6	18	15.5	57	75	53	10
7	18	15.5	57	75	58	10
8	18.5	15.5	57	75	72	10
9	18.5	15.5	57	75	92	10
10	20	15.5	57	75	114	10
11	20	15.5	57	75	120	10
12	20	15.5	57	75	127	10
13	20	15.5	57	75	132	10
14	20	15.5	57	75	146	10

3012A.75 (inch)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
1/8	18	10	57	75	41	10
5/32	18	15.5	57	75	43	10
3/16	18	15.5	57	75	48	10
7/32	18	15.5	57	75	53	10
1/4	18	15.5	57	75	53	10
9/32	18	15.5	57	75	58	10
5/16	18.5	15.5	57	75	72	10
11/32	18.5	15.5	57	75	92	10
3/8	20	15.5	57	75	110	10
7/16	20	15.5	57	75	120	10
1/2	20	15.5	57	75	132	10
9/16	20	15.5	57	75	146	10

RS3012M/8-L52
RS3012A /8-L52

Socket Set on Rail
Juego de Vasos en Regleta

RS3012M/8-L52	8 Pieces Set/Rail 200mm	(g)
3, 4, 5, 6, 7, 8, 10, 12		394

RS3012A/8-L52	8 Pieces Set/Rail 200mm	(g)
1/8, 5/32, 3/16, 7/32, 1/4, 5/16, 3/8, 1/2		425

3011M-62 · -100 · -120 · -160

Ballpoint Inhex Sockets
Vasos con Punta de Bola Inhex



3011M.62 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	18	35.5	62	45	10
4	18	35.5	62	46	10
5	18	35.5	62	48	10
6	18	35.5	62	49	10
7	18	35.5	62	50	10
8	18	35.5	62	51	10
10	20	35.5	62	66	10
12	20	35.5	62	79	10

3011M.100 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	18	73.5	100	61	10
4	18	73.5	100	62	10
5	18	73.5	100	64	10
6	18	73.5	100	65	10
7	18	73.5	100	67	10
8	18	73.5	100	68	10

3011M.120 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	18	93.5	120	77	10
4	18	93.5	120	78	10
5	18	93.5	120	80	10
6	18	93.5	120	81	10
7	18	93.5	120	83	10
8	18	93.5	120	84	10

3011M.160 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	18	133.5	160	87	10
4	18	133.5	160	88	10
5	18	133.5	160	89	10
6	18	133.5	160	91	10
7	18	133.5	160	93	10
8	18	133.5	160	95	10

Ball point bit sockets have less strength due to the special design. Make sure to use them correctly.

3015M-62 · -100

Inhex Bit Sockets, Grip Ring
Vasos con Punta Hexagonal, Grip Ring



3015M.62 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	18	35.5	62	43	10
4	18	35.5	62	45	10
5	18	35.5	62	50	10
6	18	35.5	62	50	10
7	18	35.5	62	50	10
8	18	35.5	62	62	10
10	20	35.5	62	75	10
12	20	35.5	62	95	10

3015M.100 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
3	18	73.5	100	60	10
4	18	73.5	100	60	10
5	18	73.5	100	65	10
6	18	73.5	100	65	10
7	18	73.5	100	70	10
8	18	73.5	100	70	10
10	20	73.5	100	105	10
12	20	73.5	100	135	10

Grip Ring holds hex screws

RS3015M/8-L62
RS3015M/8-L100

Socket Set on Rail
Juego de Vasos en Regleta

RS3015M/8-L62	8 Pieces Set/Rail 200mm	(g)
	3, 4, 5, 6, 7, 8, 10, 12	500

RS3015M/8-L100	8 Pieces Set/Rail 200mm	(g)
	3, 4, 5, 6, 7, 8, 10, 12	650

3020-38 • -50 • -100 • -120

XZN Bit Sockets
Vasos con punta XZN



3020.38 (XZN)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
M 5	18	11.5	38	32	10
M 6	18	11.5	38	33	10
M 8	18	11.5	38	36	10
M10	20	11.5	38	51	10
M12	20	11.5	38	52	10
M14	22	11.5	38	74	10

3020.50 (XZN)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
M 4	18	23.5	50	35	10
M 5	18	23.5	50	37	10
M 6	18	23.5	50	39	10
M 8	18	23.5	50	40	10
M10	20	23.5	50	65	10
M12	20	23.5	50	69	10
M14	22	23.5	50	75	10

3020.100 (XZN)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
M 4	18	73.5	100	57	10
M 5	18	73.5	100	59	10
M 6	18	73.5	100	61	10
M 8	18	73.5	100	62	10
M10	20	73.5	100	99	10
M12	20	73.5	100	103	10
M14	22	73.5	100	145	5

3020.120 (XZN)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
M 4	18	93.5	120	77	10
M 5	18	93.5	120	79	10
M 6	18	93.5	120	81	10
M 8	18	93.5	120	82	10
M10	20	93.5	120	119	10
M12	20	93.5	120	123	10
M14	22	93.5	120	165	5

XZN



XZN		M4	M5	M6	M8	M10	M12	M14	M16	M18
S_1	(ref. mm)	3.6	4.8	6.1	7.3	9.7	11.5	13.3	15.7	16.9
S_2	(ref. mm)	3.1	4.1	5.1	6.1	8.1	9.7	11.2	13.2	14.2

RS3020/6-L38

Socket Set on Rail
Juego de Vasos en Regleta

RS3020/6-L38	6 Pieces Set/Rail 150mm	(g)
	M5, M6, M8, M10, M12, M14	308

RS3020/7-L50

Socket Set on Rail
Juego de Vasos en Regleta

RS3020/7-L50	7 Pieces Set/Rail 200mm	(g)
	M4, M5, M6, M8, M10, M12, M14	400

3025-38 · -50 · -140 (T)

TORX® Bit Sockets
Vasos con Punta TORX®



3025.38 (T)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
New T 8	18	11.5	38	32	10
T 9	18	11.5	38	32	10
T10	18	11.5	38	32	10
T15	18	11.5	38	33	10
T20	18	11.5	38	33	10
T25	18	11.5	38	33	10
T27	18	11.5	38	33	10
T30	18	11.5	38	33	10
T40	18	11.5	38	34	10
T45	18	11.5	38	37	10
T50	20	11.5	38	49	10
T55	20	11.5	38	57	10

3025.50 (T)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
New T 8	18	23.5	50	36	10
T 9	18	23.5	50	36	10
T10	18	23.5	50	36	10
T15	18	23.5	50	36	10
T20	18	23.5	50	36	10
T25	18	23.5	50	37	10
T27	18	23.5	50	37	10
T30	18	23.5	50	38	10
T40	18	23.5	50	39	10
T45	18	23.5	50	41	10
T50	20	23.5	50	55	10
T55	20	23.5	50	67	10

3025.140 (T)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
T 9	18	113.5	140	75	10
T10	18	113.5	140	75	10
T15	18	113.5	140	75	10
T20	18	113.5	140	75	10
T25	18	113.5	140	76	10
T27	18	113.5	140	76	10
T30	18	113.5	140	77	10
T40	18	113.5	140	78	10
T45	18	113.5	140	80	10
T50	20	113.5	140	94	10
T55	20	113.5	140	106	10

TORX® (T)



T		T8	T9	T10	T15	T20	T25	T27	T30	T40	T45	T50	T55	T60	T70	T80	T90	T100
S1	(ref. mm)	2.3	2.5	2.7	3.3	3.9	4.5	5.0	5.6	6.7	7.9	8.9	11.3	13.3	15.6	17.6	20.0	22.2
S2	(ref. mm)	1.7	1.8	2.0	2.3	2.8	3.2	3.6	4.0	4.8	5.6	6.2	8.0	9.5	11.1	12.7	14.2	15.8

RS3025/8-L38	8 Pieces Set/Rail 200mm	(g)
T10, T15, T20, T25, T27, T30, T40, T45		300

RS3025/8-L50	8 Pieces Set/Rail 200mm	(g)
T10, T15, T20, T25, T27, T30, T40, T45		320

RS3025/8-L38
RS3025/8-L50

Socket Set on Rail
Juego de Vasos en Regleta

3025.50 (T)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
T35	18	23.5	50	39	10

3025-50-T35

Bit Socket
Vasos con Punta

3025.100R (T)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
T20	18	73.5	100	38	10
T25	18	73.5	100	40	10
T27	18	73.5	100	42	10
T30	18	73.5	100	45	10
T40	18	73.5	100	52	10
T45	18	73.5	100	73	10
T50	20	73.5	100	80	10
T55	20	73.5	100	106	10



3025-100R (T)

TORX® Bit Sockets, Round Shaft
Vasos con Punta TORX®

RS3025/8-L100R	8 Pieces Set/Rail 200mm	(g)
T20, T25, T27, T30, T40, T45, T50, T55		490

RS3025/8-L100R

Socket Set on Rail
Juego de Vasos en Regleta

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

3025-50 · -160 (TH)

Tamper-Resistant TORX® Bit Sockets
Vasos con Punta TORX® Indeformable



Tamper Resistant TORX® Bit Sockets have less strength due to special design. Make sure to use it correctly.

Los Vasos con Punta Indeformable TORX® tienen menos resistencia debido al diseño especial. Asegurarse de su correcta utilización.

3025.50 (TH)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
T10H	18	23.5	50	37	10
T15H	18	23.5	50	38	10
T20H	18	23.5	50	38	10
T25H	18	23.5	50	38	10
T27H	18	23.5	50	38	10
T30H	18	23.5	50	39	10
T40H	18	23.5	50	40	10
T45H	18	23.5	50	41	10
T50H	20	23.5	50	61	10
T55H	20	23.5	50	61	10

3025.160 (TH)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
T25H	18	133.5	160	83	10
T27H	18	133.5	160	83	10
T30H	18	133.5	160	84	10
T40H	18	133.5	160	85	10
T45H	18	133.5	160	86	10
T50H	20	133.5	160	128	10
T55H	20	133.5	160	128	10

RS3025/9-HOLE

Socket Set on Rail
Juego de Vasos en Regleta



RS3025/9-HOLE	9 Pieces Set/Rail 200mm	(g)
	T10H, T15H, T20H, T25H, T27H, T30H, T40H, T45H, T50H	405

3247

Bit Socket Set
Juego de Vasos con Punta

3247	4 Pieces Set/⚖=385g
PLASTIC BAG	
Sockets	
3025.160 Tamper-Resistant TORX® Bit Sockets T27H, T30H, T40H, T50H	

3025-100R (TH)

Tamper-Resistant TORX® Bit Sockets, Round Shaft
Vasos con Punta TORX® Indeformable



3025.100R (TH)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
T20H	18	73.5	100	38	10
T25H	18	73.5	100	40	10
T27H	18	73.5	100	42	10
T30H	18	73.5	100	45	10
T40H	18	73.5	100	52	10
T45H	18	73.5	100	73	10
T50H	20	73.5	100	80	10
T55H	20	73.5	100	106	10

RS3025/8-L100RH

Socket Set on Rail
Juego de Vasos en Regleta

RS3025/8-L100RH	8 Pieces Set/Rail 200mm	(g)
	T20H, T25H, T27H, T30H, T40H, T45H, T50H, T55H	490

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

3025-50 (IP)

TORXPLUS® Bit Sockets
Vasos con Punta TORXPLUS®

TORX plus®

3025.50 (IP)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
10IP	18	23.5	50	38	10
15IP	18	23.5	50	38	10
20IP	18	23.5	50	38	10
25IP	18	23.5	50	38	10
27IP	18	23.5	50	40	10
30IP	18	23.5	50	40	10
40IP	18	23.5	50	41	10
45IP	18	23.5	50	41	10
50IP	20	23.5	50	61	10
55IP	20	23.5	50	61	10



TORXPLUS® (IP)



IP		8IP	9IP	10IP	15IP	20IP	25IP	27IP	30IP	40IP	45IP	50IP	55IP	60IP	70IP
S_1	(ref. mm)	2.3	2.5	2.7	3.3	3.9	4.5	5.0	5.6	6.7	7.9	8.9	11.3	13.3	15.6
S_2	(ref. mm)	1.7	1.8	2.0	2.3	2.8	3.2	3.6	4.0	4.8	5.6	6.2	8.0	9.5	11.1

RS3025/8-IP

Socket Set on Rail
Juego de Vasos en Regleta

RS3025/8-IP	8 Pieces Set/Rail 200mm	(g)
20IP, 25IP, 27IP, 30IP, 40IP, 45IP, 50IP, 55IP		370

RSX025/11-IP

Socket Set on Rail
Juego de Vasos en Regleta

RSX025/11-IP	11 Pieces Set/Rail 200mm	(g)
2025.28(IP)	**10IP, 15IP, 20IP, 25IP, 27IP**	480
3025.50(IP)	**30IP, 40IP, 45IP, 50IP**	
4025.60(IP)	**55IP, 60IP**	

1/4" + 3/8" + 1/2"

3025-50 (IPR)

TORXPLUS® Bit Sockets, with Hole
Vasos con Punta de Cinco Lóbulos, con agujero

TORX plus®

3025.50 (IPR)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
10IPR	18	23.5	50	38	10
15IPR	18	23.5	50	38	10
20IPR	18	23.5	50	38	10
25IPR	18	23.5	50	38	10
27IPR	18	23.5	50	40	10
30IPR	18	23.5	50	40	10
40IPR	18	23.5	50	41	10
45IPR	18	23.5	50	41	10
50IPR	20	23.5	50	61	10
55IPR	20	23.5	50	61	10



TORXPLUS® (IPR)



IPR		8IPR	9IPR	10IPR	15IPR	20IPR	25IPR	27IPR	30IPR	40IPR	45IPR	50IPR	55IPR
S_1	(ref. mm)	2.2	2.4	2.6	3.1	3.6	4.1	4.7	5.2	6.3	7.4	8.4	10.6
S_2	(ref. mm)	2.0	2.2	2.4	2.8	3.3	3.8	4.3	4.8	5.7	6.7	7.6	9.7

RS3025/9-IPR

Socket Set on Rail
Juego de Vasos en Regleta

RS3025/9-IPR	9 Pieces Set/Rail 200mm	(g)
10IPR, 15IPR, 20IPR, 25IPR, 27IPR, 30IPR, 40IPR, 45IPR, 50IPR		395

RSX025/11-IPR

Socket Set on Rail
Juego de Vasos en Regleta

RSX025/11-IPR	11 Pieces Set/Rail 200mm	(g)
2025.28(IPR)	**8IPR, 10IPR, 15IPR, 20IPR, 25IPR, 27IPR, 30IPR**	320
3025.50(IPR)	**40IPR, 45IPR, 50IPR, 55IPR**	

1/4" + 3/8"

TORX plus is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX plus es una marca registrada de **Acument Intellectual Properties, LLC.**

3027-50 • -100

Bit Sockets for Ribe Screws
Vasos con Punta Ribe



3027.50	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
M 5	18	23.5	50	38	10
M 6	18	23.5	50	38	10
M 7	18	23.5	50	38	10
M 8	18	23.5	50	39	10
M 9	20	23.5	50	40	10
M10	20	23.5	50	40	10
M12	20	23.5	50	41	10

3027.100	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
M 5	18	73.5	100	40	10
M 6	18	73.5	100	42	10
M 8	18	73.5	100	45	10
M10	20	73.5	100	52	10
M12	20	73.5	100	73	10

Ribe CV



CV		M5	M6	M7	M8	M9	M10	M12	M13	M14	M16
W	(ref. mm)	1.2	1.3	1.4	1.8	2.0	2.3	2.6	3.1	3.2	3.6
S_1	(ref. mm)	5.0	6.0	7.0	8.0	9.0	10.0	12.0	13.0	14.0	16.0
S_2	(ref. mm)	3.8	4.5	5.0	6.0	7.1	7.4	9.0	11.0	10.4	11.9

RS3027/5-L50

Socket Set on Rail
Juego de Vasos en Regleta

RS3027/5-L50	5 Pieces Set/Rail 150mm	(g)
	M5, M6, M8, M10, M12	240

3001

Phillips Bit Sockets
Vasos con Punta Phillips



3001 (PH)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
2	18	42	60	38	10
3	18	42	60	38	10
4	18	42	60	38	10

3006

Slotted Bit Sockets
Vasos con Punta Recta para Cabeza Ranurada



3006	T×W (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
5	1.0× 5	18	42	60	35	10
8	1.2× 8	18	42	60	42	10
10	1.6×10	20	42	60	50	10

3001, 3006 are for hand use only.
Do not use with a power or impact wrench.

3110M · 3110A

4-point Male Sockets
Vasos con Macho Cuadrado

3110M (mm)	□	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
6	3/8"	18	10	28	30	10
8		18	10	28	30	10
10		18	10	28	33	10
12		18	10	28	37	10

3110A (inch)	□	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
5/16	3/8"	18	10	28	30	10
3/8		18	10	28	33	10
1/2		18	10	28	37	10



3137

Bit Holder
Porta-punta

	□	D1 (mm)	D2 (mm)	L (mm)	(g)	(pcs.)
3137	3/8"	13	16.5	30	30	10



For DIN3126 C6.3 Bits



D6.3

3138

Bit Holder
Porta-punta

	□	D1 (mm)	D2 (mm)	L (mm)	(g)	(pcs.)
3138	3/8"	16	18	38	55	10



For DIN3126 C8 Bits



D8

3141

Bit Holder, extra deep for 131P-80, 131S-80, 131T-80
Porta-punta, extra-largo para 131P-80, 131S-80, 131T-80

	□	D1 (mm)	D2 (mm)	L (mm)	(g)	(pcs.)
3141	3/8"	16	18	48	60	10



2749PS-3/8

Reversible Ratchet Short
Llave de Carraca Reversible Corta



S.O.D.H-System 24

* Renewal Kits → **2749RK-3/8** ➡P298

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
2749PS-3/8	25	21.9	11.2	75	70	10

2749N-3/8

Reversible Ratchet
Llave de Carraca Reversible

S.O.D.H-System 24

* Renewal Kits → **2749RK-3/8** ➡P298

2749P-3/8

Reversible Ratchet
Llave de Carraca Reversible



S.O.D.H-System 24

* Renewal Kits → **2749RK-3/8** ➡P298

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
2749N-3/8	25	21.9	11.2	125	104	10
2749P-3/8	25	21.9	11.2	125	101	10

⚠ 2749-3/8 series have less strength compared with normal 3/8" ratchet due to the technical design. Make sure to use the ratchet correctly.

3749S

Reversible Ratchet Short
Llave de Carraca Reversible Corta

S.O.D.H-System Two-Step Dog 24

* Renewal Kits → **3749RK** ➡P298

3749SB

Reversible Ratchet with Quick Release Button Short
Llave de Carraca Reversible con botón de extracción rápida Corta

S.O.D.H-System Two-Step Dog 24 Quick Release

* Renewal Kits → **3749BRK** ➡P298



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
3749S	34	24.8	14.1	110	183	5
3749SB	34	24.8	14.1	110	183	5

⚠ Reversible Ratchet with quick release button has less strength compared with normal ratchet due to the technical design. Make sure to use the ratchet correctly.

3749N

Reversible Ratchet
Llave de Carraca Reversible



S.O.D.H-System Two-Step Dog 24

* Renewal Kits → **3749RK** ➡P298

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
3749N	34	24.8	14.1	200	340	1

[L/R Marking]

A pointer and L/R markings on the ratchet head Indicate the turning direction.
The reduced diameter of the head allows easier access in tight spots.

Una flecha y unas marcas L/R en el cabezal de la llave(L = Izquierda / R = Derecha) indican el sentido de giro.
El diámetro reducido del cabezal permite un acceso más fácil en lugares estrechos.

3752N Reversible Ratchet / Llave de Carraca Reversible

* Renewal Kits → 3752RK ➡P298

3752J Reversible Ratchet / Llave de Carraca Reversible

* Renewal Kits → 3752RK ➡P298

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
3752N	33	34.3	23.9	200	310	1
3752J	33	34.3	23.9	200	310	1



3776N Swivel Head Ratchet / Llave de Carraca de Cabeza Giratoria

* Renewal Kits → 3752RK ➡P298

3776P Swivel Head Ratchet / Llave de Carraca de Cabeza Giratoria

* Renewal Kits → 3752RK ➡P298

3776J Swivel Head Ratchet / Llave de Carraca de Cabeza Giratoria

* Renewal Kits → 3752RK ➡P298

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
3776N	44	34.3	23.9	280	565	1
3776P	44	34.3	23.9	280	560	1
3776J	44	34.3	23.9	280	510	1



3753SM
Multi Purpose Ratchet, Reversible
Llave de Carraca de Aplicación General, Reversible



S.O.D.H-System · 2 Two-Step Dog · 24

* Renewal Kits → 3753RK ➡P298

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
3753SM	30.5	26.4	15.7	81	175	5

3753N
Reversible Ratchet
Llave de Carraca Reversible

S.O.D.H-System · 2 Two-Step Dog · 24

* Renewal Kits → 3753RK ➡P298

3753P
Reversible Ratchet
Llave de Carraca Reversible

S.O.D.H-System · 2 Two-Step Dog · 24

* Renewal Kits → 3753RK ➡P298

3753J
Reversible Ratchet
Llave de Carraca Reversible

S.O.D.H-System · 2 Two-Step Dog · 24

* Renewal Kits → 3753RK ➡P298

D3753J
Reversible Ratchet
Llave de Carraca Reversible

S.O.D.H-System · 2 Two-Step Dog · 24

* Renewal Kits → 3753RK ➡P298



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
3753N	30.5	26.4	15.7	200	320	1
3753P	30.5	26.4	15.7	200	286	1
3753J	30.5	26.4	15.7	200	260	1
D3753J	30.5	26.4	15.7	200	260	1

3753P-250
Reversible Ratchet Long
Llave de Carraca Reversible Larga

S.O.D.H-System · 2 Two-Step Dog · 24

* Renewal Kits → 3753RK ➡P298



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
3753P-250	30.5	26.4	15.7	250	335	1

3753SMB

Multi Purpose Ratchet with Quick Release Button
Llave de Carraca de Aplicación General, reversible

* Renewal Kits → 3753BRK ➔P298



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
3753SMB	30.5	26.4	15.7	81	175	5

3753NB

Reversible Ratchet with Quick Release Button
Llave de Carraca Reversible con botón de extracción rápida

* Renewal Kits → 3753BRK ➔P298

3753PB

Reversible Ratchet with Quick Release Button
Llave de Carraca Reversible con botón de extracción rápida

* Renewal Kits → 3753BRK ➔P298

3753JB

Reversible Ratchet with Quick Release Button
Llave de Carraca Reversible con botón de extracción rápida

* Renewal Kits → 3753BRK ➔P298

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
3753NB	30.5	26.4	15.7	200	320	1
3753PB	30.5	26.4	15.7	200	286	1
3753JB	30.5	26.4	15.7	200	260	1



⚠ Reversible Ratchet with quick release button has less strength compared with normal ratchet due to the technical design. Make sure to use the ratchet correctly.

2774PS-3/8

Flexible Ratchet, Reversible
Llave de Carraca Flexible, Reversible

S.O.D.H-System | 24 | Flexible Head

* Renewal Kits → 2749RK-3/8 ➡P298

2774JS-3/8

Flexible Ratchet, Reversible
Llave de Carraca Flexible, Reversible

S.O.D.H-System | 24 | Flexible Head

* Renewal Kits → 2749RK-3/8 ➡P298

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
2774PS-3/8	25	21.9	11.2	120	133	5
2774JS-3/8	25	21.9	11.2	120	113	5

⚠ 2774-3/8 series have less strength compared with normal 3/8" ratchet due to the technical design. Make sure to use the ratchet correctly.

3774PS

Flexible Ratchet, Reversible
Llave de Carraca Flexible, Reversible



S.O.D.H-System | Two-Step Dog | 24 | Flexible Head

* Renewal Kits → 3753RK ➡P298

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
3774PS	30.5	26.4	15.7	175	250	2

3774N

Flexible Ratchet, Reversible
Llave de Carraca Flexible, Reversible

S.O.D.H-System | Two-Step Dog | 24 | Flexible Head | OVAL Shank

* Renewal Kits → 3753RK ➡P298

3774P

Flexible Ratchet, Reversible
Llave de Carraca Flexible, Reversible

S.O.D.H-System | Two-Step Dog | 24 | Flexible Head | OVAL Shank

* Renewal Kits → 3753RK ➡P298

3774J

Flexible Ratchet, Reversible
Llave de Carraca Flexible, Reversible

S.O.D.H-System | Two-Step Dog | 24 | Flexible Head | OVAL Shank

* Renewal Kits → 3753RK ➡P298

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
3774N	30.5	26.4	15.7	265	378	2
3774P	30.5	26.4	15.7	265	378	2
3774J	30.5	26.4	15.7	285	367	1

* Renewal Kits → **3753RK** ➡P298

3774P-SR Speeder Ratchet

	D (mm)	T (mm)	H (mm)	A (mm)	L (mm)	(g)	(pce.)
3774P-SR	30.5	26.4	15.7	34	310	435	1



* Renewal Kits → **3753BRK** ➡P298

3774NB

Flexible Ratchet, Reversible with Quick Release Button
Llave de Carraca Flexible, reversible con botón de extracción rápida

* Renewal Kits → **3753BRK** ➡P298

3774PB

Flexible Ratchet, Reversible with Quick Release Button
Llave de Carraca Flexible, reversible con botón de extracción rápida

* Renewal Kits → **3753BRK** ➡P298

3774JB

Flexible Ratchet, Reversible with Quick Release Button
Llave de Carraca Flexible, reversible con botón de extracción rápida

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
3774NB	30.5	26.4	15.7	265	378	2
3774PB	30.5	26.4	15.7	265	373	2
3774JB	30.5	26.4	15.7	285	367	1



Reversible Ratchet with Quick Release Button :
Sockets and accessories are safely locked.
By pushing the button the sockets or extension bars are released from the ratchet.

Llave de Carraca Reversible con Botón de Extracción Rápida : Los vasos y accesorios se bloquean en posición. Los vasos o las alargaderas se extraen de la llave apretando el botón.



⚠ Reversible Ratchet with quick release button has less strength compared with normal ratchet due to the technical design. Make sure to use the ratchet correctly.

3774NL

Flex-Head Ratchet with Head Lock Button
Llave de Carraca Flexible con Botón de Bloqueo de la Cabeza

S.O.D.H.-System | Two-Step Dog | 24 | Flexible Head | OVAL Shank

* Renewal Kits → 3753RK P298

3774PL

Flex-Head Ratchet with Head Lock Button
Llave de Carraca Flexible con Botón de Bloqueo de la Cabeza

S.O.D.H.-System | Two-Step Dog | 24 | Flexible Head | OVAL Shank

* Renewal Kits → 3753RK P298

3774JL

Flex-Head Ratchet with Head Lock Button
Llave de Carraca Flexible con Botón de Bloqueo de la Cabeza

S.O.D.H.-System | Two-Step Dog | 24 | Flexible Head | OVAL Shank

* Renewal Kits → 3753RK P298

3774JBL

Flex-Head Ratchet with Head Lock Button and Quick Release Button
Llave de Carraca Flexible con Botón de Bloqueo de la Cabeza y Botón de Extracción Rápida

S.O.D.H.-System | Two-Step Dog | 24 | Quick Release | Flexible Head | OVAL Shank

* Renewal Kits → 3753BRK P298



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
3774NL	30.5	26.4	15.7	265	378	2
3774PL	30.5	26.4	15.7	265	378	2
3774JL	30.5	26.4	15.7	285	367	1
3774JBL	30.5	26.4	15.7	285	367	1

Reversible Ratchet with quick release button has less strength compared with normal ratchet due to the technical design. Make sure to use the ratchet correctly.

3755 Ratchet Adaptor
Adaptador de carraca



45

* Renewal Kits → 3755RK P300

	D (mm)	L (mm)	(g)	(pcs.)
3755	30.5	55	146	5

3756 Quick Spinner
Disco de Giro Rápido



	D (mm)	L (mm)	(g)	(pcs.)
3756	30.5	25.5	47	10

3757 Ratchet Wheel
Rueda de carraca





L/R Marking

45

* Renewal Kits → 3752RK P298

	D (mm)	L (mm)	(g)	(pcs.)
3757	50	35	155	5

3762 Flexible Extension Bar
Alargadera Flexible



	D (mm)	L (mm)	(g)	(pcs.)
3762	19.3	300	178	2

3760-32 • -50 • -75 • -125 • -150 • -250 • -300 • -400 • -500 • -600 • -900 • -1000

Extension Bars
Alargaderas



3760	D (mm)	L (mm)	(g)	(pcs.)
32	18	32	27	10
50	18	50	47	10
75	18	75	68	10
125	18	125	106	10
150	18	150	125	10
250	18	250	196	5
300	18	300	291	2
400	18	400	365	1
500	18	500	490	1
600	18	600	538	1
900	18	900	805	1
1000	18	1000	968	1

PK3760/6

Set
Juego

PK3760/6 — 6 Pieces Set/⚖=670g

PLASTIC TRAY

Extension Bars

3760 Extension Bars
32, 50, 75, 125, 150, 250

3763-32 • -50 • -75 • -125 • -150 • -250 • -300

Wobble-Fix Extension Bars
Alargaderas Articuladas-Fijas ⚠



Wobble-Fix

3763	D (mm)	L (mm)	(g)	(pcs.)
32	18	32	26	10
50	18	50	42	10
75	18	75	57	10
125	18	125	80	10
150	18	150	98	10
250	18	250	144	5
300	18	300	170	2

PK3763/6

Set
Juego

PK3763/6 — 6 Pieces Set/⚖=560g

PLASTIC TRAY

Extension Bars

3763 Wobble-Fix Extension Bars
32, 50, 75, 125, 150, 250

Wobble-Fix Extension Bar
Two way usage : one for as a flexible extension bar to provide at 15° angle operation, the other for use as a normal extension bar. This usage is Patent.

Alargadera Articulada-Fija
Dos formas de utilización : Una como alargadera flexible para poder trabajar con un ángulo de 15° y otra para utilizarse como alargadera normal. Esta aplicación está patentada.



⚠ The Wobble-Fix Extension Bar has less strength than normal extension bar due to it's specific design with a reduced square drive. Make sure to use it correctly.

OVAL Shank

3768N-175 Hinge Handle Mango Articulado

* Renewal Kits → 3768RK P300

OVAL Shank

3768N-250 Hinge Handle Mango Articulado

* Renewal Kits → 3768RK P300

OVAL Shank

3768P-250 Hinge Handle Mango Articulado

* Renewal Kits → 3768RK P300

OVAL Shank

3768J-250 Hinge Handle Mango Articulado

* Renewal Kits → 3768RK P300

	D (mm)	L (mm)	(g)	(pcs.)
3768N-175	20.5	175	255	5
3768N-250	20.5	250	290	5
3768P-250	20.5	250	275	5
3768J-250	20.5	250	248	2



OVAL Shank

3768N-300 Hinge Handle Mango Articulado

* Renewal Kits → 3768RK P300

3768P-380 Hinge Handle Mango Articulado ⚠

* Renewal Kits → 3768RK P300

	D (mm)	L (mm)	(g)	(pcs.)
3768N-300	20.5	300	320	2
3768P-380	20.5	380	435	2



⚠ 3768-300, -380 have longer handle than standard, and can be loaded to excessive torque value. In the interest of your own safety always apply load evenly and progressively to avoid breakage and possible injury.

3769N-160 · -230

Spin Type Handle
Mango Tipo Destornillador

3769N	ℓ (mm)	L (mm)	(g)	(pcs.)
160	50	160	96	2
230	120	230	126	2

Plastic or rubber handles are not intended to act as insulation.
Los mangos de plástico o de goma no están previstos para aislamiento.



3769NWF-160 · -230

Spin Type Handle Wobble-Fix
Mango Tipo Destornillador Articulados-Fijos



Wobble-Fix

3769NWF	ℓ (mm)	L (mm)	(g)	(pcs.)
160	50	160	96	2
230	120	230	126	2

Plastic or rubber handles are not intended to act as insulation.
Los mangos de plástico o de goma no están previstos para aislamiento.

Wobble-Fix Extension Bar
Two way usage : one for as a flexible extension bar to provide at 15° angle operation, the other for use as a normal extension bar. This usage is Patent.



Alargadera Articulada-Fija
Dos formas de utilización : Una como alargadera flexible para poder trabajar con un ángulo de 15° y otra para utilizarse como alargadera normal. Esta aplicación está patentada.



3769H

Folding Socket Driver
Llave de Vaso Plegable



	L (mm)	(g)	(pcs.)
3769H	170	210	2



3770

Universal Joint
Articulación Universal



	L (mm)	(g)	(pcs.)
3770	50	66	10
3771	43	46	10

3771

Universal Joint
Articulación Universal



3780 Speed Handle / Manivela Rápida

	L (mm)	(g)	(pce.)
3780	400	432	1



3785 T-Handle / Mango Corredizo

OVAL Shank



Innovative Oval shaped bar provides higher durability and stops the sliding square part turning around the bar.

	L (mm)	(g)	(pcs.)
3785	200	157	5



3322A Adaptor / Adaptador — Warranty 86Nm / Garantía 86Nm

3344A Adaptor / Adaptador

	凹 (sq)	凸 (sq)	L (mm)	(g)	(pcs.)
3322A	3/8"	1/4"	24	18	10
3344A	3/8"	1/2"	30	35	10

Adapting down from bigger square drive to smaller square drive may lead to excessive torque and possibly cause breakage.

La adaptación de mayor a menor de un cuadrado conductor puede conducir a un par excesivo que puede causar roturas.





PK2346/6 Set / Juego

PK2346/6	6 Pieces Set/⚖=460g
PLASTIC TRAY	
Adaptors	
1/4"凹→3/8"凸 2233A	3/8"凹→1/4"凸 3322A
3/8"凹→1/2"凸 3344A	1/2"凹→3/8"凸 4433A-35
1/2"凹→3/4"凸 4466A	3/4"凹→1/2"凸 6644A

2233A	1/4" X 3/8"		
3322A	3/8" X 1/4"	Warranty/Garantia	86Nm
3344A	3/8" X 1/2"		
4433A	1/2" X 3/8"	Warranty/Garantia	290Nm
4466A	1/2" X 3/4"		
6644A	3/4" X 1/2"	Warranty/Garantia	668Nm

3200M · 3200A

Socket Sets
Juegos de Vasos

3200M	18 Pieces Set/⚖=2,250g
METAL CASE:W415×H120×T50mm	
Sockets	**Accessories**
3400M 6-pt. Sockets 6, 8, 9, 10, 11, 12	**3753N**
3405M 12-pt. Sockets 13, 14, 17, 18, 19, 21	**3760-125**
	3760-250
	3768N-250
	3769N-160
	3785

3200A	18 Pieces Set/⚖=2,250g
METAL CASE:W415×H120×T50mm	
Sockets	**Accessories**
3400A 6-pt. Sockets 1/4, 5/16, 3/8, 7/16	**3753N**
3405A 12-pt. Sockets 1/2, 9/16, 19/32, 5/8, 11/16, 3/4, 13/16, 7/8	**3760-125**
	3760-250
	3768N-250
	3769N-160
	3785

3201AMW

Socket Set
Juego de Vasos

3201AMW	42 Pieces Set/⚖=4,700g
METAL CASE:W445×H190×T50mm	
Sockets	**Accessories**
3405M 12-pt. Sockets 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22	**3753N**
3405A 12-pt. Sockets 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 25/32, 13/16, 7/8	**3760-75**
3405W 12-pt. Sockets 1/8, 3/16, 1/4, 5/16, 3/8, 7/16, 1/2	**3760-125**
	3760-250
	3768N-250
	3769N-160
	3770
	3780
	3785
	3344A

3206M

Socket Set
Juego de Vasos

3206M	21 Pieces Set/⚖=2,100g
METAL CASE:W395×H90×T50mm	
Sockets	**Accessories**
3400M 6-pt. Sockets 6, 7, 8, 9, 10, 11, 12	**3753N**
3405M 12-pt. Sockets 13, 14, 15, 16, 17, 18, 19, 21, 22	**3760-125**
	3760-250
	3768N-250
	3785

3206A

Socket Set
Juego de Vasos

3206A	17 Pieces Set/⚖=2,000g
METAL CASE:W395×H90×T50mm	
Sockets	**Accessories**
3400A 6-pt. Sockets 1/4, 5/16, 11/32, 3/8, 7/16	**3753N**
3405A 12-pt. Sockets 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8	**3760-125**
	3760-250
	3768N-250
	3785

3206AM

Socket Set
Juego de Vasos

3206AM	27 Pieces Set/⚖=3,500g
METAL CASE:W445×H190×T50mm	
Sockets	**Accessories**
3405M 12-pt. Sockets 7, 8, 10, 11, 12, 13, 14, 15, 16, 17, 19, 22	**3753N**
3405A 12-pt. Sockets 3/8, 7/16, 1/2, 9/16, 5/8,11/16, 3/4, 13/16, 7/8	**3760-125**
3300C Spark Plug Socket 20.8	**3760-250**
	3768N-250
	3770

3210M

Socket Set
Juego de Vasos

3210M	22 Pieces Set/⚖=2,900g

METAL CASE:W360×H145×T50mm

Sockets	Accessories
3400M 6-pt. Sockets 6, 7, 8, 9, 10, 11, 12	3753N
3405M 12-pt. Sockets 13, 14, 15, 16, 17, 18, 19, 21, 22	3760-125
	3760-250
	3768N-250
	3770
	3785

3215M · 3215A

Socket Sets
Juegos de Vasos

3215M	7 Pieces Set/⚖=430g

PLASTIC BAG

Sockets
3305M 12-pt. Deep Sockets 8, 10, 11, 12, 13, 14, 17

3215A	7 Pieces Set/⚖=430g

PLASTIC BAG

Sockets
3305A 12-pt. Deep Sockets 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 11/16

3217M

Socket Set
Juego de Vasos

3217M	14 Pieces Set/⚖=850g

METAL CASE:W163×H52×T33mm

Sockets
3405M 12-pt. Sockets 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22

3220M

Socket Set
Juego de Vasos

3220M	14 Pieces Set/⚖=2,270g

METAL CASE:W415×H120×T50mm

Sockets	Accessories
3405M 12-pt. Sockets 8, 9, 10, 11, 12, 13, 14, 17, 19, 21, 22	3753N
	3760-125
	3768N-250

3221M

Socket Set
Juego de Vasos

3221M	18 Pieces Set/⚖=2,300g

METAL CASE:W415×H120×T50mm

Sockets	Accessories
3405M 12-pt. Sockets 6, 8, 9, 10, 11, 12, 13, 14, 17, 19, 21, 22	3753N
	3760-125
	3760-250
	3768N-250
	3769N-160
	3785

3244

Socket Set
Juego de Vasos

3244	12 Pieces Set/⚖=1,110g

METAL CASE:W240×H100×T32mm

Sockets	Accessories
3025.50 TORX® Bit Sockets T20, T25, T27, T30, T40, T45, T50	3753N
3425 TORX® Sockets E8, E10, E12	3760-75

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

3240M-00 ◯ Display Stands Expositores
3240M-05 ◯

3240M-00 3240M-05	3400M 67 Pieces Set/=2,800g 3405M 67 Pieces Set/=2,800g

DISPLAY STAND:W410×H160×T500mm

Sockets		
6mm:4pcs	12mm:4pcs	18mm:4pcs
7mm:4pcs	13mm:4pcs	19mm:3pcs
8mm:4pcs	14mm:4pcs	20mm:3pcs
9mm:4pcs	15mm:4pcs	21mm:3pcs
10mm:4pcs	16mm:4pcs	22mm:3pcs
11mm:4pcs	17mm:4pcs	23mm:3pcs

S3240M-00 · S3240A-00 ◯ Display Stands Expositores
S3240M-05 · S3240A-05 ◯

S3240M-00 S3240M-05	3400M 177 Pieces Set/=10,300g 3405M 177 Pieces Set/=10,300g

DISPLAY STAND:W510×H150×T230mm

Sockets		
6mm:12pcs	12mm:12pcs	18mm:8pcs
7mm:12pcs	13mm:11pcs	19mm:8pcs
8mm:12pcs	14mm:11pcs	20mm:7pcs
9mm:12pcs	15mm:10pcs	21mm:7pcs
10mm:12pcs	16mm: 9pcs	22mm:7pcs
11mm:12pcs	17mm: 9pcs	23mm:6pcs

S3240A-00 S3240A-05	3400A 126 Pieces Set/=8,500g 3405A 126 Pieces Set/=8,500g

DISPLAY STAND:W510×H150×T230mm

Sockets		
1/4" :12pcs	9/16":10pcs	25/32":7pcs
5/16":12pcs	19/32":10pcs	13/16":7pcs
3/8" :12pcs	5/8" : 9pcs	7/8" :7pcs
7/16":12pcs	11/16": 9pcs	
1/2" :11pcs	3/4" : 8pcs	

3250M Socket Set Juego de Vasos

3250M	17 Pieces Set/=2,200g

METAL CASE:W415×H120×T50mm

Sockets	Accessories
◯ **3400M** 6-pt. Sockets 7, 8, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19	**3753N** **3760-125** **3760-250** **3770** **3785**

3252M Socket Set Juego de Vasos

3252M	15 Pieces Set/=1,530g

METAL CASE:W310×H90×T48mm

Sockets	Accessories
◯ **3400M** 6-pt. Sockets 5.5, 7, 8, 10, 11, 12 ◯ **3405M** 12-pt. Sockets 13, 14, 17, 19, 22	**3753P** **3760-75** **3760-125** **3770**

P3262M-6P Socket Set Juego de Vasos

P3262M-6P	11 Pieces Set/=1,140g

PLASTIC CASE:W245×H120×T45mm

Sockets	Accessories
◯ **3400M** 6-pt. Sockets 8, 10, 12, 13, 14, 17, 19	**3753N** **3760-75** **3760-125** **3770**

3275 Socket Set
Juego de Vasos

3275	24 Pieces Set/⚖=3,150g

METAL CASE:W400×H147×T50mm

Sockets	Accessories
3400M 6-pt. Sockets 6, 7, 8, 9, 10, 11, 12	**3753N**
3405M 12-pt. Sockets 13, 14, 15, 16, 17, 18, 19, 21, 22	**3760-125**
3300C Spark Plug Sockets 16, 20.8	**3760-250**
	3768N-250
	3770
	3756

3276 Bit Socket Set
Juego de Vasos con Punta

3276	20 Pieces Set/⚖=3,370g

METAL CASE:W310×H150×T50mm

Sockets	Accessories
3000 Bit Sockets 2, 3	**3753N**
3005 Bit Sockets 5, 8	**3763-125**
3010M.62 Hex Bit Sockets 5, 6, 7, 8, 10	
3025.50 TORX®Bit Sockets T10, T15, T20, T25, T27, T30, T40, T45, T50	

3277 Socket Set
Juego de Vasos

3277	29 Pieces Set/⚖=3,240g

METAL CASE:W370×H150×T50mm

Sockets	Accessories
3400M 6-pt. Sockets 8, 9, 10, 11, 12	**3753N**
3405M 12-pt. Sockets 13, 14, 15, 16, 17, 18, 19, 21	**3760-125**
3300M 6-pt. Deep Sockets 8, 9, 10, 11, 12	**3768N-250**
3305M 12-pt. Deep Sockets 13, 14, 15, 16, 17, 18, 19, 21	

3279AM Socket Set
Juego de Vasos

3279AM	35 Pieces Set/⚖=4,200g

METAL CASE:W445×H190×T50mm

Sockets	Accessories
3405M 12-pt. Sockets 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22	**3753N**
3405A 12-pt. Sockets 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 25/32, 13/16, 7/8	**3760-75**
3300S Spark Plug Sockets 16, 20.8	**3760-125**
	3760-250
	3768N-250
	3769N-160
	3770
	3785

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

4400M
6-point Sockets
Vasos Hexagonales



4400M 4405M (mm)	D_1 (mm)	D_2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
6	10.3	21	6	36	42	10
7	11.5	21	7	36	43	10
8	13.2	21	8	36	44	10
9	13.8	21	8.5	37	44	10
10	15.3	21	9	37	45	10
11	16.5	21	9.5	37	46	10
12	17.8	21	10	37	47	10
13	19	22	10.5	37	53	10
14	20.3	22	11	37	56	10
15	21.5	22	11.5	37	57	10
16	22.8	22	12	37	62	10
17	24	23	12.5	37	69	10
18	25	24	13	37	74	10
19	26.5	25	14	38	89	10
20	27.8	26	15	38	92	10
21	29	27	15.5	38	102	10
22	30	28	16	40	113	10
23	31.5	29	16.5	40	128	10
24	32.8	30	17	42	140	5
25	34	31	18	42	164	5
26	35	32	19	42	165	5
27	36.5	33	19.5	43	182	5
28	37.8	34	20	43	198	5
29	39	35	20.5	43	205	5
30	40	36	22	46	222	5
31	41.5	37	22.5	46	246	5
32	42.8	38	23	46	261	5
33	44.2	39	24	47	275	5
34	45.2	40	24	47	315	5
35	46.2	40	24	47	317	5
36	47.2	41	24	47	336	5
37	48.3	42	24	47	360	5
38	49.2	43	24	47	380	5
41	53.1	45	29	57	471	5
46	59.1	48	32	60	567	2

4405M
12-point Sockets
Vasos Bihexagonales



RS4400M/10
RS4405M/10
Socket Set on Rail
Juego de Vasos en Regleta

RS4400M/10	10 Pieces Set/Rail 300mm	(g)
10, 11, 12, 13, 14, 15, 17, 19, 21, 22		717

RS4405M/10	10 Pieces Set/Rail 300mm	(g)
10, 11, 12, 13, 14, 15, 17, 19, 21, 22		717

	6-Point	12-Point	Surface Drive	Nut Grip®	TORX® (E)	TORXPLUS® (EPL)	Double Square	LHSTIX® (LH-S)
1/4"	No. 2400M/A No. 2300M/A No. 2400W-BA No. 2300W-BA No. 2300X series	No. 2405M/A No. 2305M/A No. AS2405A No. AS2305A series	No. 2410M No. 2310M series	No. 2450MS No. 2350M No. 2350X series	No. 2425 No. 2325 series	—	No. 2415M/A series	—
3/8"	No. 3400M/A No. 3300M/A No. 3400W No. 3300W No. 3300X/XA series	No. 3405M/A No. 3305M/A No. 3405W No. 3305W No. 3305X/XA series	No. 3410M No. 3310M series	No. 3450M No. 3350M No. 3350X series	No. 3425 No. 3325 series	—	No. 3415M/A series	No. 3400LH series
1/2"	No. 4400M/A No. 4300M/A No. 4400W series	No. 4405M/A No. 4305M/A No. 4405W series	No. 4410M No. 4310M series	No. 4450M series	No. 4425 No. 4325 series	No. 4425-EPL series	—	No. 4400LH series

4400A

6-point Sockets
Vasos Hexagonales



	4400A 4405A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
New	1/4	10.7	21	6	36	41	10
	5/16	13.2	21	8	36	44	10
	3/8	14.6	21	9	37	45	10
	7/16	16.5	21	9.5	37	46	10
	1/2	19	22	10.5	37	53	10
	9/16	20.3	22	11	37	56	10
	19/32	21.5	22	11.5	37	57	10
	5/8	22.8	22	12	37	62	10
	21/32	24	23	12.5	37	69	10
	11/16	25	24	13	37	74	10
	3/4	26.5	25	14	38	89	10
	25/32	27.8	26	15	38	92	10
	13/16	29	27	15.5	38	102	10
	7/8	30	28	16	40	113	10
	15/16	32.8	30	17	42	140	5
New	31/32	34	31	18	42	165	5
	1	35	32	19	42	165	5
	1 1/16	36.5	33	19.5	43	180	5
	1 1/8	39	35	20.5	43	210	5
	1 3/16	40	36	22	46	222	5
	1 1/4	42.8	38	23	46	261	5
	1 5/16	44.2	39	24	47	275	5
	1 3/8	46.2	40	24	47	317	5
	1 7/16	47.2	41	24	47	336	5
	1 1/2	49.2	43	24	47	380	5

4405A

12-point Sockets
Vasos Bihexagonales



RS4400A/10
RS4405A/10

Socket Set on Rail
Juego de Vasos en Regleta

RS4400A/10	10 Pieces Set/Rail 300mm	(g)
	3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16	809

RS4405A/10	10 Pieces Set/Rail 300mm	(g)
	3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16	809

4400W

6-point Whitworth Sockets
Vasos Whitworth Hexagonales



	4400W 4405W (W)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
	3/16	16.5	21	9.5	37	46	10
	1/4	19	22	10.5	37	54	10
	5/16	21.5	22	11.5	37	54	10
	3/8	25	24	13	37	73	10
	7/16	29	27	15.5	38	87	10
	1/2	31.5	29	16.5	40	133	10
	9/16	35	32	19	42	165	5
	5/8	37.8	34	20	43	191	5
	11/16	40	36	22	46	222	5
	3/4	44.2	39	24	47	280	5

4405W

12-point Whitworth Sockets
Vasos Whitworth Bihexagonales



RS4400W/8
RS4405W/8

Socket Set on Rail
Juego de Vasos en Regleta

Socket Set on Rail
Juego de Vasos en Regleta

RS4400W/8	8 Pieces Set/Rail 250mm	(g)
	3/16, 1/4, 5/16, 3/8, 7/16, 1/2, 9/16, 5/8	860

RS4405W/8	8 Pieces Set/Rail 250mm	(g)
	3/16, 1/4, 5/16, 3/8, 7/16, 1/2, 9/16, 5/8	860

BS W

BS W	BS	3/16BS	1/4BS	5/16BS	3/8BS	7/16BS	1/2BS	9/16BS	5/8BS	11/16BS	3/4BS	7/8BS
	W	1/8W	3/16W	1/4W	5/16W	3/8W	7/16W	1/2W	9/16W	5/8W	11/16W	3/4W
Across Flat	(ref. mm)	8.64	11.30	13.34	15.24	18.03	20.83	23.37	25.65	27.94	30.48	33.35

4410M

Surface Drive Sockets
Vasos Surface Drive (de Contacto Curvo)



4410M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
8	13.2	21	8	36	44	10
9	13.8	21	8.5	37	44	10
10	15.3	21	9	37	45	10
11	16.5	21	9.5	37	46	10
12	17.8	21	10	37	47	10
13	19	22	10.5	37	53	10
14	20.3	22	11	37	56	10
15	21.5	22	11.5	37	52	10
16	22.8	22	12	37	62	10
17	24	23	12.5	37	69	10
18	25	24	13	37	74	10
19	26.5	25	14	38	89	10
20	27.8	26	15	38	92	10
21	29	27	15.5	38	102	10
22	30	28	16	40	113	10
23	31.5	29	16.5	40	128	10
24	32.8	30	17	42	140	5
25	34	31	18	42	164	5
26	35	32	19	42	165	5
27	36.5	33	19.5	43	196	5
28	37.8	34	20	43	198	5
29	39	35	20.5	43	190	5
30	40	36	22	46	222	5
31	41.5	37	22.5	46	257	5
32	42.8	38	23	46	250	5
34	45.2	40	24	47	314	5

RS4410M/10

Socket Set on Rail
Juego de Vasos en Regleta

RS4410M/10	10 Pieces Set/Rail 300mm	(g)
10, 11, 12, 13, 14, 15, 17, 19, 21, 22		717

4425

TORX® Sockets
Vasos TORX®



4425 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
E 8	10.7	21	7	36	41	10
E10	13.2	21	8.2	36	44	10
E11	13.8	21	8.7	37	45	10
E12	14.6	21	9.3	37	47	10
E14	16.5	21	10.6	37	48	10
E16	19	22	11.8	37	57	10
E18	20.3	22	13	37	57	10
E20	22.8	22	14.4	37	63	10
E22	25	24	15.5	37	78	10
E24	26.5	25	17	40	95	5

TORX® (E)



E		E4	E5	E6	E7	E8	E10	E11	E12	E14	E16	E18	E20	E22	E24	E26	E28
S1	(ref. mm)	3.7	4.6	5.6	6.1	7.4	9.3	9.9	11.0	12.8	14.6	16.5	18.3	20.1	22.0	23.7	25.5
S2	(ref. mm)	2.7	3.3	4.0	4.3	5.3	6.8	7.1	7.9	9.2	10.5	11.9	13.2	14.8	15.7	17.5	18.3

RS4425/7

Socket Set on Rail
Juego de Vasos en Regleta

RS4425/7	7 Pieces Set/Rail 200mm	(g)
E10, E12, E14, E16, E18, E20, E24		428

4425-N

TORX® Sockets
Vasos TORX®



4425 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
E10N	13.2	21	8.2	36	47	10
E12N	14.6	21	9.3	37	48	10
E14N	16.5	21	10.6	37	50	10
E16N	19	22	11.8	37	60	10
E18N	20.3	22	13	37	60	10
E20N	22.8	22	14.4	37	65	10

TORX Socket for Nut and low profile bolt
Shallow Chamfer on Socket Opening

A : Flywheel bolt MR20 NISSAN: 4425-E20N
B : Cam sprocket FA20 for TOYOTA/SUBARU: 4425-E16N
C : Connecting rod bolt FA20 for TOYOTA/SUBARU: 4425-E14N

RS4425/6-N

Socket Set on Rail
Juego de Vasos en Regleta

RS4425/6-N	6 Pieces Set/Rail 200mm	(g)
E10N, E12N, E14N, E16N, E18N, E20N		370

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

4425 (EPL)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
10EPL	13.2	21	6.2	36	45	10
12EPL	14.6	21	7.2	37	47	10
14EPL	16.5	21	8.1	37	49	10
16EPL	19	22	9.2	37	60	10
18EPL	20.3	22	10.2	37	60	10
20EPL	22.9	22	11.2	37	65	10

RS4425/6-EPL	6 Pieces Set/Rail 200mm	(g)
10EPL, 12EPL, 14EPL, 16EPL, 18EPL, 20EPL		390

4425-EPL

TORXPLUS® Sockets
Vasos TORXPLUS®

TORX plus®



RS4425/6-EPL

Socket Set on Rail
Juego de Vasos en Regleta

TORX plus®

TORX PLUS
EP/EPL-style

TORX
E-style



Straight Sidewalls & Reduced Recess Fall Away

- **Increase tool engagement**
- **Virtually eliminates camout**
- **Ensures proper torque transfer**
- **Greatly reduces end load requirements**
- **Can reduce worker fatigue and muscular stress during manual assembly**

Elliptically-based Geometry and Lobe Engagement

- **Broadens contact surface to maximize engagement of driver and recess**
- **Eliminates damaging point-to-point contact**

0° Drive Angle

- **Optimises torque transmission**
- **Virtually eliminates radial stresses to increase tool bit life**
- **Enables use of recesses with thinner walls**

Six Lobes with Large Cross-Sectional Areas

- **Enables faster tool engagement**
- **Maximizes torque transfer**
- **Increases torsional strength**

4450M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
10	15.3	21	6	36	44	10
11	16.5	21	6.5	36	46	10
12	17.8	21	7	36	46	10
13	19	22	8	36	57	10
14	20.3	22	8.5	36	54	10
15	21.5	22	9	36	52	10
16	22.8	22	9	36	60	10
17	24	23	9.5	36	68	10
18	25	24	10.5	36	77	10
19	26.5	25	11.5	36	85	10
21	29	27	12	37	110	10
22	30	28	12.5	37	105	10
24	32.8	30	14.5	39	130	5
27	36.5	33	16.5	40	139	5

RS4450M/10	10 Pieces Set/Rail 300mm	(g)
10, 11, 12, 13, 14, 15, 17, 19, 21, 22		717

4400LH (LH-S)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
6S	13.2	21	5.6	36	44	10
8S	16.5	21	6.8	37	46	10
10S	19	22	8	37	53	10
12S	22.8	22	9.2	37	62	10
14S	25	24	10.4	37	74	10
16S	29	27	11.6	38	102	10

RS4400LH/6	6 Pieces Set/Rail 200mm	(g)
6S, 8S, 10S, 12S, 14S, 16S		430

4450M

Nut Grip Sockets **Nut Grip®**
Vasos Sujeta-Tuercas **Nut Grip®**



RS4450M/10

Socket Set on Rail
Juego de Vasos en Regleta

4400LH

LHS Sockets
Vasos LHS



RS4400LH/6

Socket Set on Rail
Juego de Vasos en Regleta

TORX plus® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX plus® es una marca registrada de **Acument Intellectual Properties, LLC.**
LHstix® is a registered trademark of **OSG CORPORATION** System Engineering Department.
LHstix® es una marca registrada de **OSG CORPORATION** System Engineering Department.

4300M · 4300A

6-point Deep Sockets
Vasos Hexagonales Largos



4300M 4305M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
8	13.2	21	9	59	77	76	10
9	13.8	21	10	59	77	82	10
10	15.3	21	11	59	77	82	10
11	16.5	21	12	59	77	86	10
12	17.8	21	13	59	77	92	10
13	19	21.8	14	59	77	106	10
14	20.3	21.8	15	59	77	115	10
15	21.5	21.8	16	59	77	123	10
16	22.8	22	17	59	77	141	10
17	24	23	18	59	77	139	10
18	25	24	19	59	77	149	10
19	26.5	25	20	58	77	165	10
20	27.8	26	21	58	77	183	10
21	29	27	23	58	77	190	10
22	30	28	27	57	77	200	10
23	31.5	29	27	57	77	233	10
24	32.8	30	27	57	77	249	10
25	34	31	27	57	77	270	10
26	35	32	27	56	77	279	10
27	36.5	33	28	56	77	303	10
28	37.8	34	28	56	77	331	10
29	39	35	28	55	77	357	10
30	40	36	34	55	77	342	10
31	41.5	37	34	55	77	384	10
32	42.8	38	34	55	77	405	10
33	44.2	39	35	54	77	420	5
34	45.2	40	35	54	77	442	5
New **35**	46.2	40	35	53	77	458	5
36	47.2	41	35	53	77	484	5
37	48.2	42	38	53	77	475	5
38	49	44	38	53	77	490	5

4305M · 4305A

12-point Deep Sockets
Vasos Bihexagonales Largos



4300A 4305A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
5/16	13.2	21	9	59	77	76	10
3/8	14.6	21	10	59	77	82	10
7/16	16.5	21	12	59	77	86	10
1/2	19	21.8	14	59	77	106	10
9/16	20.3	21.8	15	59	77	115	10
19/32	21.5	21.8	16	59	77	123	10
5/8	22.8	22	17	59	77	141	10
21/32	24	23	18	59	77	139	10
11/16	25	24	19	59	77	149	10
3/4	26.5	25	20	58	77	165	10
25/32	27.8	26	21	58	77	183	10
13/16	29	27	23	58	77	190	10
7/8	30	28	27	57	77	200	10
15/16	32.8	30	27	57	77	249	10
31/32	34	31	27	57	77	270	10
1	35	32	27	56	77	279	10
1. 1/16	36.5	33	28	56	77	303	10
1. 1/8	37.8	34	28	56	77	331	10
1. 3/16	40	36	34	55	77	342	10
1. 1/4	42.8	38	34	55	77	405	10
1. 5/16	44.2	39	35	54	77	420	5
1. 3/8	46.2	40	35	54	77	422	5
1. 7/16	47.2	41	35	53	77	484	5
1. 1/2	49	44	38	53	77	523	5
1.13/16	59	48	38	51	77	791	5

RS4300M/10
RS4305M/10

Socket Set on Rail
Juego de Vasos en Regleta

RS4300M/10 — 10 Pieces Set/Rail 300mm	(g)
10, 11, 12, 13, 14, 15, 17, 19, 21, 22	1,415

RS4305M/10 — 10 Pieces Set/Rail 300mm	(g)
10, 11, 12, 13, 14, 15, 17, 19, 21, 22	1,415

RS4300A/10
RS4305A/10

Socket Set on Rail
Juego de Vasos en Regleta

RS4300A/10 — 10 Pieces Set/Rail 300mm	(g)
3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16	1,600

RS4305A/10 — 10 Pieces Set/Rail 300mm	(g)
3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16	1,600

4300M (L120)

6-point Extra Deep Sockets
Vasos Hexagonales Extra Largos



4300M(L120) (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
8	13.2	21	9	102	120	120	5
10	15.3	21	11	102	120	138	5
12	17.8	21	13	102	120	157	5
14	20.3	21.8	15	102	120	193	5
16	22.8	22	17	102	120	210	5

4310M

Surface Drive Deep Sockets
Vasos Surface Drive (de Contacto Curvo) Largos





4310M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
8	13.2	21	9	59	77	79	10
9	13.8	21	10	59	77	82	10
10	15.3	21	11	59	77	82	10
11	16.5	21	12	59	77	86	10
12	17.8	21	13	59	77	92	10
13	19	21.8	14	59	77	106	10
14	20.3	21.8	15	59	77	115	10
15	21.5	21.8	16	59	77	123	10
16	22.8	22	17	59	77	141	10
17	24	23	18	59	77	139	10
18	25	24	19	59	77	149	10
19	26.5	25	20	58	77	165	10
20	27.8	26	21	58	77	183	10
21	29	27	23	58	77	190	10
22	30	28	27	57	77	200	10
23	31.5	29	27	57	77	233	10
24	32.8	30	27	57	77	249	10
25	34	31	27	57	77	270	10
26	35	32	27	56	77	279	10
27	36.5	33	28	56	77	303	10
28	37.8	34	28	56	77	334	10
29	39	35	28	55	77	357	10
30	40	36	34	55	77	342	10
31	41.5	37	34	55	77	384	10
32	42.8	38	34	55	77	405	10
34	45.2	40	35	54	77	442	5

RS4310M/10

Socket Set on Rail
Juego de Vasos en Regleta

RS4310M/10	10 Pieces Set/Rail 300mm	(g)
10, 11, 12, 13, 14, 15, 17, 19, 21, 22		1,415

4325

TORX® Deep Sockets
Vasos TORX® Largos



4325 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
E 8	10.7	21	7	59	77	68	10
E10	13.2	21	8.2	59	77	99	10
E11	13.8	21	8.7	59	77	84	10
E12	14.6	21	9.3	59	77	99	10
E14	16.5	21	10.6	59	77	103	10
E16	19	21.8	11.8	59	77	107	10
E18	20.3	21.8	13	59	77	118	10
E20	22.8	22	14.4	59	77	141	10
New **E22**	25	24	15.5	59	77	188	10
E24	26.6	25	17	59	77	215	10

RS4325/7

Socket Set on Rail
Juego de Vasos en Regleta

RS4325/7	7 Pieces Set/Rail 200mm	(g)
E10, E12, E14, E16, E18, E20, E24		900

4325 (L140)

TORX® Extra Deep Sockets
Vasos TORX® Extra Largos



4325(L140) (E)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
E 8	10.7	21	7	122	140	110	5
E10	13.2	21	8.2	122	140	140	5
E12	14.6	21	9.3	122	140	160	5
E14	16.5	21	10.6	122	140	180	5

4325 (L140)-2B

TORX® Extra Deep Sockets, **Nut Grip®**
Vasos TORX® Extra Largos, **Nut Grip®**



4325(L140) (2B)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
E 8(2B)	10.7	21	7	122	140	110	5
E10(2B)	13.2	21	8.2	122	140	140	5
E12(2B)	14.6	21	9.3	122	140	160	5
E14(2B)	16.5	21	10.6	122	140	180	5

NUT GRIP®

Twin balls at the 6-point opening hold bolt-nut tightly for safe and reliable work.

Las dos bolas de la boca Hexagonal sujetan el perno-tuerca permitiendo un trabajo seguro y fiable.

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

4440M · 4440A

6-point Universal Sockets
Vasos Hexagonales con Articulación Universal



4440M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
9	14	25	8.3	63	150	10
10	15.3	25	8.8	63	155	10
11	16.5	25	10	65	158	10
12	17.8	25	10.5	65	151	10
13	19	25	11.4	66	152	10
14	20.3	25	11.4	66	151	10
15	21.5	25	13	68	149	10
16	22.8	25	13	68	150	10
17	24	25	14	69	150	10
18	25.3	25	14	69	150	10
19	26.5	25	15	71	170	10
20	27.8	25	15	71	173	5
21	29	25	16	72	176	5
22	30.3	25	16	72	185	5

4440A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
3/8	14.8	25	8.8	63	155	10
7/16	16.5	25	10	65	158	10
1/2	19	25	11.4	66	152	10
9/16	20.3	25	11.4	66	151	10
5/8	22.8	25	13	68	150	10
11/16	24.6	25	14	69	153	10
3/4	26.5	25	15	71	170	10
7/8	30.3	25	16	72	185	5

4440T

TORX® Universal Sockets
Vasos TORX® con Articulación Universal



4440T (E)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
E10	13.2	25	8.2	62	145	10
E12	15	25	9.3	63	147	10
E14	16.3	25	10.6	65	148	10
E16	18.8	25	11.8	65	150	10
E18	20.4	25	13	67	153	10

4117M-125 · -250

Extension Deep Sockets
Vasos con Alargaderas



4117M.125 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pce.)
13	18.7	24	13	59	125	213	1
14	20.2	24	14	59	125	227	1
17	24	24	17	59	125	274	1
19	26.9	24	19	59	125	279	1
21	28.5	24	21	59	125	291	1
22	30	24	22	59	125	323	1
24	32	24	24	59	125	361	1
27	36.5	24	27	59	125	439	1
30	40	24	30	59	125	461	1
32	42	24	32	59	125	498	1

4117M.250 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pce.)
13	18.7	24	13	59	250	412	1
14	20.2	24	14	59	250	423	1
17	24	24	17	59	250	469	1
19	26.9	24	19	59	250	484	1
21	28.5	24	21	59	250	496	1
22	30	24	22	59	250	516	1
24	32	24	24	59	250	560	1
27	36.5	24	27	59	250	641	1
30	40	24	30	59	250	663	1
32	42	24	32	59	250	698	1

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

4000-60 (PH)

Phillips Bit Sockets
Vasos con Punta Phillips

4000 (PH)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
2	22	23.5	60	65	10
3	22	23.5	60	65	10
4	22	23.5	60	67	10



4000-60 (PZ)

PZ Bit Sockets
Vasos con Punta PZ

4000.60 (PZ)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
PZ2	22	23.5	60	65	10
PZ3	22	23.5	60	65	10



4005-60

Slotted Bit Sockets
Vasos con Punta Recta para Cabezas Ranuradas

4005	T×W (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
8	1.2× 8	22	23.5	60	65	10
10	1.6×10	22	23.5	60	75	10
12	2.0×12	23	23.5	60	111	10
14	2.5×14	24	23.5	60	133	10
16	2.5×16	24	23.5	60	133	10



4001

Phillips Bit Sockets
Vasos con Punta Phillips

4001 (PH)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
1	21	38	60	49	10
2	21	38	60	53	10
3	21	38	60	55	10
4	21	38	60	57	10



4006

Slotted Bit Sockets
Vasos con Punta Recta para Cabezas Ranuradas

4006	T×W (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
5	1.0× 5.5	21	38	60	53	10
8	1.2× 8	21	38	60	62	10
10	1.6×10	21	38	60	67	10
12	2.0×12	21	38	60	72	10
14	2.5×14	21	38	60	81	10
16	2.5×16	21	38	60	88	10



4001, 4006 are for hand use only.
Do not use with an impact wrench.

4010M-50 • -75 • -100 • -160
4010A-60

Inhex Bit Sockets
Vasos con Punta Hexagonal





4010M.50 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
4	22	13.5	50	61	10
5	22	13.5	50	62	10
6	22	13.5	50	64	10
7	22	13.5	50	65	10
8	22	13.5	50	66	10
New 9	22	13.5	50	73	10
10	22	13.5	50	75	10
12	23	13.5	50	105	10
13	24	13.5	50	120	10
14	24	13.5	50	120	10
16	25	15	50	150	10
17	25	15	50	150	10
18	27	15	50	200	5
19	27	15	50	200	5

4010M.75 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
4	22	38.5	75	69	10
5	22	38.5	75	70	10
6	22	38.5	75	72	10
7	22	38.5	75	73	10
8	22	38.5	75	74	10
New 9	22	38.5	75	90	10
10	22	38.5	75	92	10
12	23	38.5	75	130	10
13	24	38.5	75	150	10
14	24	38.5	75	150	10
16	25	35	75	180	10
17	25	35	75	180	10
18	27	33	75	230	5
19	27	33	75	230	5

4010M.100 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
4	22	63.5	100	77	10
5	22	63.5	100	78	10
6	22	63.5	100	80	10
7	22	63.5	100	82	10
8	22	63.5	100	84	10
New 9	22	63.5	100	105	10
10	22	63.5	100	109	10
12	23	63.5	100	155	10
13	24	63.5	100	180	5
14	24	63.5	100	180	5
16	25	60	100	250	5
17	25	60	100	250	5
18	27	58	100	300	5
19	27	58	100	300	5

4010M.160 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
4	22	123.5	160	103	10
5	22	123.5	160	104	10
6	22	123.5	160	106	10
7	22	123.5	160	108	10
8	22	123.5	160	110	10
10	22	123.5	160	126	10
12	23	123.5	160	180	5
14	24	123.5	160	260	5
17	25	120	160	360	5
19	27	118	160	415	5

4010A.60 (inch)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
5/32	22	23.5	60	57	10
3/16	22	23.5	60	57	10
7/32	22	23.5	60	59	10
1/4	22	23.5	60	63	10
9/32	22	23.5	60	65	10
5/16	22	23.5	60	67	10
11/32	22	23.5	60	75	10
3/8	22	23.5	60	76	10
7/16	23	23.5	60	101	10
1/2	24	23.5	60	124	10
9/16	25	20	60	127	10
5/8	25	20	60	174	10
3/4	27	18	60	220	5

RS4010M/10-L50
RS4010M/10-L75
RS4010A/10-L60

Socket Set on Rail
Juego de Vasos en Regleta

RS4010M/10-L50	10 Pieces Set/Rail 300mm	(g)
4, 5, 6, 7, 8, 10, 12, 14, 17, 19		968

RS4010M/10-L75	10 Pieces Set/Rail 300mm	(g)
4, 5, 6, 7, 8, 10, 12, 14, 17, 19		1,207

RS4010A/10-L60	10 Pieces Set/Rail 300mm	(g)
3/16, 7/32, 1/4, 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 3/4		1,080

4020-60 · -100 · -120 · -140

XZN Bit Sockets
Vasos con Punta XZN





4020.60 (XZN)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
M 5	22	23.5	60	60	10
M 6	22	23.5	60	61	10
M 8	22	23.5	60	63	10
M10	23	23.5	60	93	10
M12	23	23.5	60	97	10
M14	24	23.5	60	105	10
M16	25	20	60	165	10
M18	27	20	60	215	5

4020.100 (XZN)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
M 5	22	63.5	100	77	10
M 6	22	63.5	100	78	10
M 8	22	63.5	100	80	10
M10	23	63.5	100	132	10
M12	23	63.5	100	136	10
M14	24	63.5	100	144	5
M16	25	60	100	250	5
M18	27	60	100	300	5

4020.120 (XZN)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
M 5	22	83.5	120	86	10
M 6	22	83.5	120	87	10
M 8	22	83.5	120	89	10
M10	23	83.5	120	152	10
M12	23	83.5	120	156	10
M14	24	83.5	120	164	5

4020.140 (XZN)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
M 5	22	103.5	140	95	10
M 6	22	103.5	140	96	10
M 8	22	103.5	140	98	10
M10	23	103.5	140	172	5
M12	23	103.5	140	176	5
M14	24	103.5	140	184	5

XZN



XZN		M4	M5	M6	M8	M10	M12	M14	M16	M18
S_1	(ref. mm)	3.6	4.8	6.1	7.3	9.7	11.5	13.3	15.7	16.9
S_2	(ref. mm)	3.1	4.1	5.1	6.1	8.1	9.7	11.2	13.2	14.2

RS4020/6-L60

Socket Set on Rail
Juego de Vasos en Regleta

RS4020/6-L60	6 Pieces Set/Rail 150mm	(g)
M5, M6, M8, M10, M12, M14		500

	Phillips (PH)	PZ	Slotted	HEX	HEX (ball point)	Triple Square (XZN)	TORX® (T)	TORX® (TH)	TORXplus® (IP)	TORXplus® (IPR)	Ribe-CV
1/4"	No.2000 series	No.2000(PZ) series	No.2005 series	No.2010M/A series	No.2011M series	No.2020 series	No.2025 series	No.2025(TH) series	No.2025(IP) series	No.2025(IPR) series	—
3/8"	No.3000 No.3001 series	No.3000(PZ) series	No.3005 No.3006 series	No.3010M/A No.3012M/A No.3015M series	No.3011M series	No.3020 series	No.3025 series	No.3025(TH) series	No.3025(IP) series	No.3025(IPR) series	No.3027 series
1/2"	No.4000 No.4001 series	No.4000(PZ) series	No.4005 No.4006 series	No.4010M/A No.4012M/A series	—	No.4020 series	No.4025 series	—	No.4025(IP) series	—	No.4027 series

4025-60 · -100 · -140 (T)

TORX® Bit Sockets
Vasos con Punta TORX®



New	4025.60 (T)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
New	**T15**	22	23.5	60	58	10
	T20	22	23.5	60	59	10
	T25	22	23.5	60	60	10
	T27	22	23.5	60	60	10
	T30	22	23.5	60	60	10
	T40	22	23.5	60	62	10
	T45	22	23.5	60	64	10
	T50	22	23.5	60	74	10
	T55	23	23.5	60	96	10
	T60	24	23.5	60	122	10
	T70	24	23.5	60	135	10
	T80	24	20	60	168	10

4025.100 (T)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
T20	22	73.5	100	76	10
T25	22	73.5	100	76	10
T27	22	73.5	100	77	10
T30	22	73.5	100	77	10
T40	22	73.5	100	78	10
T45	22	73.5	100	80	10
T50	22	73.5	100	98	10
T55	23	73.5	100	132	10
T60	24	73.5	100	170	5
T70	24	73.5	100	175	5

4025.140 (T)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
T20	22	103.5	140	94	10
T25	22	103.5	140	95	10
T27	22	103.5	140	95	10
T30	22	103.5	140	95	10
T40	22	103.5	140	97	10
T45	22	103.5	140	99	10
T50	22	103.5	140	129	10
T55	23	103.5	140	175	5
T60	24	103.5	140	229	5
T70	24	103.5	140	245	5
T80	24	100	140	320	5

TORX® (T)



T		T8	T9	T10	T15	T20	T25	T27	T30	T40	T45	T50	T55	T60	T70	T80	T90	T100
S_1	(ref. mm)	2.3	2.5	2.7	3.3	3.9	4.5	5.0	5.6	6.7	7.9	8.9	11.3	13.3	15.6	17.6	20.0	22.2
S_2	(ref. mm)	1.7	1.8	2.0	2.3	2.8	3.2	3.6	4.0	4.8	5.6	6.2	8.0	9.5	11.1	12.7	14.2	15.8

RS4025/9-L60

Socket Set on Rail
Juego de Vasos en Regleta

RS4025/9-L60	9 Pieces Set/Rail 250mm	(g)
T20, T25, T27, T30, T40, T45, T50, T55, T60		700

4025-60-T35

Bit Socket
Vasos con Punta

4025.60 (T)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
T35	22	23.5	60	96	10

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

4025-60 · -100 (IP)

TORXPLUS® Bit Sockets
Vasos con Punta TORXPLUS®





4025.60 (IP)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
20IP	22	23.5	60	60	10
25IP	22	23.5	60	60	10
27IP	22	23.5	60	60	10
30IP	22	23.5	60	60	10
40IP	22	23.5	60	60	10
45IP	22	23.5	60	64	10
50IP	22	23.5	60	74	10
55IP	23	23.5	60	96	10
60IP	24	23.5	60	122	10
70IP	24	23.5	60	170	10

4025.100 (IP)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
40IP	22	63.5	100	79	10
45IP	22	63.5	100	81	10
50IP	22	63.5	100	100	10
55IP	23	63.5	100	133	10
60IP	24	63.5	100	172	5
70IP	25	63.5	100	241	5

RS4025/9-IP	9 Pieces set/Rail 250mm	(g)
20IP, 25IP, 27IP, 30IP, 40IP, 45IP, 50IP, 55IP, 60IP		700

RS4025/9-IP

Socket Set on Rail
Juego de Vasos en Regleta

TORXPLUS® (IP)



IP		8IP	9IP	10IP	15IP	20IP	25IP	27IP	30IP	40IP	45IP	50IP	55IP	60IP	70IP
S_1	(ref. mm)	2.3	2.5	2.7	3.3	3.9	4.5	5.0	5.6	6.7	7.9	8.9	11.3	13.3	15.6
S_2	(ref. mm)	1.7	1.8	2.0	2.3	2.8	3.2	3.6	4.0	4.8	5.6	6.2	8.0	9.5	11.1

4027-60 · -100 · -140

Bit Sockets for Ribe Screws
Vasos con Punta para Tornillos Ribe





4027.60	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
M 5	22	23.5	60	60	10
M 6	22	23.5	60	62	10
M 7	22	23.5	60	63	10
M 8	22	23.5	60	64	10
M 9	22	23.5	60	70	10
M10	22	23.5	60	74	10
M12	23	23.5	60	96	10
M13	24	23.5	60	116	10
M14	24	23.5	60	122	10
M16	24	25	60	135	10

4027.100	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
M 5	22	63.5	100	67	10
M 6	22	63.5	100	68	10
M 7	22	63.5	100	75	10
M 8	22	63.5	100	81	10
M 9	22	63.5	100	90	10
M10	22	63.5	100	101	10
M12	23	63.5	100	134	10
M13	24	63.5	100	155	5
M14	24	63.5	100	173	5
M16	24	60	100	241	5

4027.140	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
M 8	22	103.5	140	98	10
M10	22	103.5	140	127	10
M12	23	103.5	140	171	5
M14	24	103.5	140	226	5
M16	24	100	140	320	5

RS4027/6-L60	6 Pieces set/Rail 200mm	(g)
M5, M6, M8, M10, M12, M14		600

RS4027/6-L60

Socket Set on Rail
Juego de Vasos en Regleta

Ribe CV



CV		M5	M6	M7	M8	M9	M10	M12	M13	M14	M16
W	(ref. mm)	1.2	1.3	1.4	1.8	2.0	2.3	2.6	3.1	3.2	3.6
S_1	(ref. mm)	5.0	6.0	7.0	8.0	9.0	10.0	12.0	13.0	14.0	16.0
S_2	(ref. mm)	3.8	4.5	5.0	6.0	7.1	7.4	9.0	11.0	10.4	11.9

TORXplus is a registered trademark of **Acument Intellectual Properties, LLC.**
TORXplus es una marca registrada de **Acument Intellectual Properties, LLC.**

4012M-43 • -60 • -75 • -100

Inhex Sockets
Vasos con Punta de Hexagonal



4012M.43 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
4	21.1	11.5	23	43	40	10
5	21.1	11.5	23	43	46	10
6	21.1	11.5	23	43	42	10
7	21.1	11.5	23	43	46	10
8	21.1	11.5	23	43	49	10
9	21.1	11.5	23	43	63	10
10	23	11.5	23	43	63	10
11	25	11.5	23	43	74	10
12	25	11.5	23	43	81	10
13	25	11.5	23	43	85	10
14	25	11.5	23	43	88	10
15	26	11.5	23	43	91	10
16	26	11.5	23	43	100	10
17	26	11.5	23	43	101	10
18	26	11.5	23	43	106	10
19	26	11.5	23	43	110	10
20	26	11.5	23	43	130	10
21	26	11.5	23	43	140	10
22	26	11.5	23	43	145	10
23	28	11.5	23	43	167	10
24	28	11.5	23	43	170	10
27	32	11.5	23	43	226	10

4012M.60 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
4	21.1	15.5	38	60	49	10
5	21.1	15.5	38	60	55	10
6	21.1	15.5	38	60	56	10
7	21.1	15.5	38	60	60	10
8	21.1	15.5	38	60	64	10
9	21.1	15.5	38	60	78	10
10	23	15.5	38	60	78	10
11	25	15.5	38	60	100	10
12	25	15.5	38	60	107	10
13	25	15.5	38	60	111	10
14	25	15.5	38	60	122	10
15	26	15.5	38	60	125	10
16	26	15.5	38	60	134	10
17	26	15.5	38	60	141	10
18	26	15.5	38	60	153	10
19	26	15.5	38	60	159	10
21	26	15.5	38	60	197	10
22	26	22.5	38	60	205	10
23	28	22.5	38	60	242	10
24	28	22.5	38	60	245	10

4012M.75 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
4	21.1	15.5	53	75	52	10
5	21.1	15.5	53	75	58	10
6	21.1	15.5	53	75	62	10
7	21.1	15.5	53	75	70	10
8	21.1	15.5	53	75	74	10
9	21.1	15.5	53	75	88	10
10	23	15.5	53	75	94	10
11	25	15.5	53	75	119	10
12	25	15.5	53	75	122	10
13	25	15.5	53	75	137	10
14	25	15.5	53	75	148	10
15	26	15.5	53	75	151	10
16	26	15.5	53	75	171	10
17	26	15.5	53	75	184	10
18	26	15.5	53	75	196	10
19	26	15.5	53	75	212	10
New **22**	26	22.5	53	75	266	10
New **24**	27.9	22.5	53	75	315	10

4012M.100 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
4	24	15.5	78	100	75	10
5	24	15.5	78	100	81	10
6	24	15.5	78	100	85	10
7	24	15.5	78	100	93	10
8	24	15.5	78	100	97	10
9	24	15.5	78	100	111	10
10	24	15.5	78	100	117	10
11	24	15.5	78	100	142	10
12	24	15.5	78	100	143	10
13	24	15.5	78	100	158	10
14	24	15.5	78	100	169	10
15	24	15.5	78	100	172	10
16	24	15.5	78	100	192	5
17	24	15.5	78	100	215	5
18	24	15.5	78	100	227	5
19	24	15.5	78	100	243	5

RS4012M/10-L60

Socket Set on Rail
Juego de Vasos en Regleta

RS4012M/10-L60	10 Pieces set/Rail 300mm	(g)
4, 5, 6, 7, 8, 10, 12, 14, 17, 19		910

4012M/A are for hand use only.
Do not use with an impact wrench.

4012A-43 · -60 · -75 · -100

Inhex Sockets
Vasos Inhex



4012A.43 (inch)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
5/32	21.1	11.5	23	43	40	10
3/16	21.1	11.5	23	43	46	10
7/32	21.1	11.5	23	43	42	10
1/4	21.1	11.5	23	43	43	10
9/32	21.1	11.5	23	43	46	10
5/16	21.1	11.5	23	43	49	10
11/32	21.1	11.5	23	43	63	10
3/8	23	11.5	23	43	59	10
7/16	25	11.5	23	43	74	10
1/2	25	11.5	23	43	85	10
9/16	25	11.5	23	43	88	10
5/8	26	11.5	23	43	100	10
3/4	26	11.5	23	43	110	10
New 7/8	26	11.5	23	43	141	10

4012A.60 (inch)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
5/32	21.1	15.5	38	60	49	10
3/16	21.1	15.5	38	60	55	10
7/32	21.1	15.5	38	60	56	10
1/4	21.1	15.5	38	60	57	10
9/32	21.1	15.5	38	60	60	10
5/16	21.1	15.5	38	60	64	10
11/32	21.1	15.5	38	60	78	10
3/8	23	15.5	38	60	74	10
7/16	25	15.5	38	60	100	10
1/2	25	15.5	38	60	111	10
9/16	25	15.5	38	60	122	10
5/8	26	15.5	38	60	134	10
3/4	26	15.5	38	60	159	10
New 7/8	26	22.5	38	60	202	10

4012A.75 (inch)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
5/32	21.1	15.5	53	75	52	10
3/16	21.1	15.5	53	75	58	10
7/32	21.1	15.5	53	75	62	10
1/4	21.1	15.5	53	75	65	10
9/32	21.1	15.5	53	75	70	10
5/16	21.1	15.5	53	75	74	10
11/32	21.1	15.5	53	75	88	10
3/8	23	15.5	53	75	86	10
7/16	25	15.5	53	75	119	10
1/2	25	15.5	53	75	137	10
9/16	25	15.5	53	75	148	10
5/8	26	15.5	53	75	171	10
3/4	26	15.5	53	75	212	10
New 7/8	26	22.5	53	75	262	10

4012A.100 (inch)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
5/32	24	15.5	78	100	75	10
3/16	24	15.5	78	100	81	10
7/32	24	15.5	78	100	85	10
1/4	24	15.5	78	100	88	10
9/32	24	15.5	78	100	93	10
5/16	24	15.5	78	100	97	10
11/32	24	15.5	78	100	111	10
3/8	24	15.5	78	100	109	10
7/16	24	15.5	78	100	142	10
1/2	24	15.5	78	100	158	10
9/16	24	15.5	78	100	169	10
5/8	24	15.5	78	100	192	5
3/4	24	15.5	78	100	243	5

RS4012A/10-L60

Socket Set on Rail
Juego de Vasos en Regleta

RS4012A/10-L60	10 Pieces set/Rail 300mm	(g)
3/16, 7/32, 1/4, 5/16, 3/8, 7/16, 1/2, 9/16, 5/8, 3/4		950

4012M/A are for hand use only.
Do not use with an impact wrench.

3749S-1/2

Reversible Ratchet Short
Llave de Carraca Reversible Corta

S.O.D.H-System | 2 Two-Step Dog | 24

* Renewal Kits → 3749SRK-1/2 ➡P299

3749SB-1/2

Reversible Ratchet Short with Quick Release Button
Llave de Carraca Reversible corta con botón de extracción rápida ⚠

S.O.D.H-System | 2 Two-Step Dog | 24 | Quick Release

* Renewal Kits → 3749SBRK-1/2 ➡P299



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pcs.)
3749S-1/2	34	29	14.4	110	200	5
3749SB-1/2	34	29	14.4	110	200	5

⚠ Reversible Ratchet with quick release button has less strength compared with normal ratchet due to the technical design. Make sure to use the ratchet correctly.





4749N-250

Reversible Ratchet
Llave de Carraca Reversible

S.O.D.H-System | 2 Two-Step Dog | 24

* Renewal Kits → 4749RK ➡P299



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
4749N-250	44.6	33	18.4	250	616	1

4749N-380

Reversible Ratchet Long
Llave de Carraca Reversible Larga

S.O.D.H-System | 2 Two-Step Dog | 24

* Renewal Kits → 4749RK ➡P299

4749J-380

Reversible Ratchet Long
Llave de Carraca Reversible Larga

S.O.D.H-System | 2 Two-Step Dog | 24

* Renewal Kits → 4749RK ➡P299



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
4749N-380	44.6	33	18.4	380	753	1
4749J-380	44.6	33	18.4	380	743	1



[4750 series]

Two dogs are set in the same axis and the three teeth hold the ratchet gear.
The enlarged contact area produces an about 10% higher torque value and the S.O.D.H system provides smooth and light movements.

Se disponen dos trinquetes en el mismo eje y la rueda de la llave de carraca se bloquea por medio de tres dientes.
El aumento de la superficie de contacto produce un aumento del par de aproximadamente 10% y el sistema S.O.D.H permite movimientos suaves y sin esfuerzo.

4750N
Reversible Ratchet
Llave de Carraca Reversible

S.O.D.H-System® | 3 Three-Step Dog | 30

* Renewal Kits → 4750RK ➡P299

4750P
Reversible Ratchet
Llave de Carraca Reversible

S.O.D.H-System® | 3 Three-Step Dog | 30

* Renewal Kits → 4750RK ➡P299

4750J
Reversible Ratchet
Llave de Carraca Reversible

S.O.D.H-System® | 3 Three-Step Dog | 30

* Renewal Kits → 4750RK ➡P299

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
4750N	38	35.9	21.3	250	548	1
4750P	38	35.9	21.3	250	553	1
4750J	38	35.9	21.3	250	508	1



4750NB
Reversible Ratchet with Quick Release Button
Llave de Carraca con botón de extracción rápida

S.O.D.H-System® | 3 Three-Step Dog | 30 | push Quick Release

* Renewal Kits → 4750BRK ➡P299

4750PB
Reversible Ratchet with Quick Release Button
Llave de Carraca con botón de extracción rápida

S.O.D.H-System® | 3 Three-Step Dog | 30 | push Quick Release

* Renewal Kits → 4750BRK ➡P299

4750JB
Reversible Ratchet with Quick Release Button
Llave de Carraca con botón de extracción rápida

S.O.D.H-System® | 3 Three-Step Dog | 30 | push Quick Release

* Renewal Kits → 4750BRK ➡P299

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
4750NB	38	35.9	21.3	250	548	1
4750PB	38	35.9	21.3	250	553	1
4750JB	38	35.9	21.3	250	508	1



⚠ Reversible Ratchet with quick release button has less strength compared with normal ratchet due to the technical design. Make sure to use the ratchet correctly.

4752N
Reversible Ratchet
Llave de Carraca Reversible

L/R Marking 45

* Renewal Kits → 4752RK ➡P299

4752J
Reversible Ratchet
Llave de Carraca Reversible

L/R Marking 45

* Renewal Kits → 4752RK ➡P299



[L/R Marking]

A pointer and L/R markings on the ratchet head Indicate the turning direction.
The reduced diameter of the head allows easier access in tight spots.

Una flecha y unas marcas L/R en el cabezal de la llave(L = Izquierda / R = Derecha) indican el sentido de giro.
El diámetro reducido del cabezal permite un acceso más fácil en lugares estrechos.

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
4752N	35	38.8	24.5	250	480	1
4752J	35	38.8	24.5	250	470	1

4753N
Reversible Ratchet
Llave de Carraca Reversible

S.O.D.H-System Two-Step Dog 24

* Renewal Kits → 4753RK ➡P299

4753P
Reversible Ratchet
Llave de Carraca Reversible

S.O.D.H-System Two-Step Dog 24

* Renewal Kits → 4753RK ➡P299

4753J
Reversible Ratchet
Llave de Carraca Reversible

S.O.D.H-System Two-Step Dog 24

* Renewal Kits → 4753RK ➡P299

D4753J
Reversible Ratchet
Llave de Carraca Reversible

S.O.D.H-System Two-Step Dog 24

* Renewal Kits → 4753RK ➡P299



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
4753N	38	36.2	21.6	250	595	1
4753P	38	36.2	21.6	250	570	1
4753J	38	36.2	21.6	250	545	1
D4753J	38	36.2	21.6	250	510	1

4753P-410
Reversible Ratchet Long
Llave de Carraca Reversible Larga

S.O.D.H-System Two-Step Dog 24

* Renewal Kits → 4753RK ➡P299



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
4753P-410	38	36.2	21.6	410	790	1

4753NB

Reversible Ratchet with Quick Release Button
Llave de Carraca Reversible con botón de extracción rápida

* Renewal Kits → 4753BRK ➔P299

4753PB

Reversible Ratchet with Quick Release Button
Llave de Carraca Reversible con botón de extracción rápida

* Renewal Kits → 4753BRK ➔P299

4753JB

Reversible Ratchet with Quick Release Button
Llave de Carraca Reversible con botón de extracción rápida

* Renewal Kits → 4753BRK ➔P299

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
4753NB	38	36.2	21.6	250	595	1
4753PB	38	36.2	21.6	250	570	1
4753JB	38	36.2	21.6	250	545	1



⚠ Reversible Ratchet with quick release button has less strength compared with normal ratchet due to the technical design. Make sure to use the ratchet correctly.

Reversible Ratchet with Quick Release Button :
Sockets and accessories are safely locked.
By pushing the button the sockets or extension bars are released from the ratchet.

Llave de Carraca Reversible con Botón de Extracción Rápida : Los vasos y accesorios se bloquean en posición. Los vasos o las alargaderas se extraen de la llave apretando el botón.





GEAR TEETH

4774N

Flexible Ratchet, Reversible
Llave de Carraca Flexible, Reversible

S.O.D.H.-System | Two-Step Dog | 24 | Flexible Head | OVAL Shank

* Renewal Kits → 4753RK ➡P299

4774P

Flexible Ratchet, Reversible
Llave de Carraca Flexible, Reversible

S.O.D.H.-System | Two-Step Dog | 24 | Flexible Head | OVAL Shank

* Renewal Kits → 4753RK ➡P299

4774J

Flexible Ratchet, Reversible
Llave de Carraca Flexible, Reversible

S.O.D.H.-System | Two-Step Dog | 24 | Flexible Head | OVAL Shank

* Renewal Kits → 4753RK ➡P299



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
4774N	38	36.2	21.6	330	700	1
4774P	38	36.2	21.6	330	700	1
4774J	38	36.2	21.6	330	685	1

4774P-450

Flexible Ratchet, Reversible
Llave de Carraca Flexible, Reversible ⚠

S.O.D.H.-System | Two-Step Dog | 24 | Flexible Head | OVAL Shank

* Renewal Kits → 4753RK ➡P299



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
4774P-450	38	36.2	21.6	450	790	1

⚠ 4774P-450 has longer handle than standard, and can be loaded to excessive torque value. In the interest of your own safety always apply load evenly and progressively to avoid breakage and possible injury.

* Renewal Kits → **4753BRK** ➡P299

4774NB

Flexible Ratchet, Reversible with Quick Release Button
Llave de Carraca Flexible, reversible con botón de extracción rápida

* Renewal Kits → **4753BRK** ➡P299

4774PB

Flexible Ratchet, Reversible with Quick Release Button
Llave de Carraca Flexible, reversible con botón de extracción rápida

* Renewal Kits → **4753BRK** ➡P299

4774JB

Flexible Ratchet, Reversible with Quick Release Button
Llave de Carraca Flexible, reversible con botón de extracción rápida

	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
4774NB	38	36.2	21.6	330	700	1
4774PB	38	36.2	21.6	330	700	1
4774JB	38	36.2	21.6	330	685	1



Reversible Ratchet with quick release button has less strength compared with normal ratchet due to the technical design. Make sure to use the ratchet correctly.





Reversible Ratchet with Quick Release Button :
Sockets and accessories are safely locked.
By pushing the button the sockets or extension bars are released from the ratchet.

Llave de Carraca Reversible con Botón de Extracción Rápida : Los vasos y accesorios se bloquean en posición. Los vasos o las alargaderas se extraen de la llave apretando el botón.

4768N-300 Hinge Handle Mango Articulado

* Renewal Kits → 4768RK ➡P300

OVAL Shank

4768N-380 • -450 Hinge Handle Mango Articulado ⚠

* Renewal Kits → 4768RK ➡P300

OVAL Shank

4768P-380 • -450 Hinge Handle Mango Articulado ⚠

* Renewal Kits → 4768RK ➡P300

OVAL Shank

4768J-380 • -450 Hinge Handle Mango Articulado ⚠

* Renewal Kits → 4768RK ➡P300

OVAL Shank



⚠ 4768-450 has longer handle than standard, and can be loaded to excessive torque value. Please use carefully.

	D (mm)	L (mm)	(g)	(pcs.)
4768N-300	28	300	600	2
4768N-380	28	380	696	2
4768N-450	28	450	784	2
4768P-380	28	380	665	2
4768P-450	28	450	748	2
4768J-380	28	380	600	1
4768J-450	28	450	690	1

4768N-600 Hinge Handle Mango Articulado ⚠

* Renewal Kits → 4768RK ➡P300

4768P-600 Hinge Handle Mango Articulado ⚠

* Renewal Kits → 4768RK ➡P300

4768J-600 Hinge Handle Mango Articulado ⚠

* Renewal Kits → 4768RK ➡P300

⚠ 4768-600 has longer handle than standard, and can be loaded to excessive torque value. In the interest of your own safety always apply load evenly and progressively to avoid breakage and possible injury.

	D (mm)	L (mm)	(g)	(pce.)
4768N-600	28	600	1100	1
4768P-600	28	600	1170	1
4768J-600	28	600	1120	1

4781N-450 Flexible Speed Handle / Manivela Rápida Flexible

* Renewal Kits → 4768RK ➡P300

	D (mm)	H (mm)	L (mm)	(g)	(pce.)
4781N-450	28	80	450	1000	1

4755 Ratchet Adaptor / Adaptador de carraca

45

* Renewal Kits → 4755RK ➡P300



	D (mm)	L (mm)	(g)	(pcs.)
4755	33.5	65	270	5

4756 Quick Spinner / Disco de Giro Rápido



	D (mm)	L (mm)	(g)	(pcs.)
4756	38	34.5	95	10

4770 Universal Joint / Articulación Universal





	L (mm)	(g)	(pcs.)
4770	62.4	150	10

4771 Universal Joint / Articulación Universal





	L (mm)	(g)	(pcs.)
4771	57.7	113	10

4760-50 • -75 • -100 • -125 • -150 • -200 • -250 • -300 • -400 • -500 • -600 • -900 • -1000

Extension Bars
Alargaderas



4760	D (mm)	L (mm)	(g)	(pcs.)
50	24	50	92	10
75	24	75	138	10
100	24	100	158	5
125	24	125	194	5
150	24	150	266	5
200	24	200	295	5
250	24	250	358	5
300	24	300	492	2
400	24	400	650	1
500	24	500	808	1
600	24	600	968	1
900	24	900	1430	1
1000	24	1000	1593	1

PK4760/5

Set
Juego

PK4760/5	5 Pieces Set/⚖=1,050g
PLASTIC TRAY	
Extension Bars	
4760 Extension Bars 50, 75, 125, 150, 250	

4763-50 • -75 • -125 • -150 • -250 • -400

Wobble-Fix Extension Bars
Alargaderas Articuladas-Fijas ⚠



Wobble-Fix

4763	D (mm)	L (mm)	(g)	(pcs.)
50	24	50	95	10
75	24	75	111	10
125	24	125	157	5
150	24	150	181	5
250	24	250	357	5
400	24	400	650	1

⚠ The Wobble-Fix Extension Bar has less strength than normal extension bar due to it's specific design with a reduced square drive. Make sure to use it correctly.

PK4763/5

Set
Juego

PK4763/5	5 Pieces Set/⚖=950g
PLASTIC TRAY	
Extension Bars	
4763 Wobble-Fix Extension Bars 50, 75, 125, 150, 250	



Wobble-Fix Extension Bar
Two way usage : one for as a flexible extension bar to provide at 15° angle operation, the other for use as a normal extension bar. This usage is Patent.

Alargadera Articulada-Fija
Dos formas de utilización : Una como alargadera flexible para poder trabajar con un ángulo de 15° y otra para utilizarse como alargadera normal. Esta aplicación está patentada.

4780-400

Speed Handle
Manivela Rápida



	L (mm)	(g)	(pce.)
4780	400	644	1

4785 T-Handle / Mango Corredizo

Innovative Oval shaped bar provides higher durability and stops the sliding square part turning around the bar.

	L (mm)	(g)	(pcs.)
4785	300	410	2



4747 L-Handle / Mango Acodado



	L_1 (mm)	L_2 (mm)	(g)	(pce.)
4747	260	50	470	1



4788-250 · -300 · -450 L-Handles / Mango Acodado



4788	L_1 (mm)	L_2 (mm)	(g)	(pcs.)
250	250	53	417	2
300	300	53	503	1
450	450	53	745	1



4433A-35 · -75 · -125 · -250 · -600

Adaptors / Adaptadores — Warranty 290Nm / Garantia 290Nm

4433A	(sq.)	(sq.)	L (mm)	(g)	(pcs.)
35	1/2"	3/8"	35	50	10
75	1/2"	3/8"	75	120	10
125	1/2"	3/8"	125	164	5
250	1/2"	3/8"	250	275	5
600	1/2"	3/8"	600	530	1



Adapting down from bigger square drive to smaller square drive may lead to excessive torque and possibly cause breakage.

La adaptación de mayor a menor de un cuadrado conductor puede conducir a un par excesivo que puede causar roturas.

4466A Adaptor / Adaptador

	(sq.)	(sq.)	L (mm)	(g)	(pcs.)
4466A	1/2"	3/4"	42	108	10



4222M
Socket Set
Juego de Vasos

4222M	13 Pieces Set/=2,780g
METAL CASE:W415×H120×T50mm	
Sockets	Accessories
4405M 12-pt. Sockets 10, 11, 12, 13, 14, 17, 19, 21, 22, 24	**4753N** **4760-125** **4770**

4223M
Socket Set
Juego de Vasos

4223M	15 Pieces Set/=2,600g
METAL CASE:W415×H120×T50mm	
Sockets	Accessories
4405M 12-pt. Sockets 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22	**4753N** **4760-125** **4770**

4227M
Bit Socket Set
Juego de Vasos con Punta

4227M	10 Pieces Set/=2,550g
METAL CASE:W310×H150×T50mm	
Sockets	Accessories
4012M.75 Hex Bit Sockets 5, 6, 8, 10, 12, 14, 17	**4749N-250** **4760-75** **4760-125**

4230M · 4230A
Socket Sets
Juegos de Vasos

4230M	17 Pieces Set/=3,150g
METAL CASE:W395×H90×T50mm	
Sockets	Accessories
4405M 12-pt. Sockets 9, 10, 12, 13, 14, 15, 16, 17, 18, 19, 21, 23, 26	**4753N** **4760-125** **4768N-380** **4710**

4230A	17 Pieces Set/=3,150g
METAL CASE:W395×H90×T50mm	
Sockets	Accessories
4405A 12-pt. Sockets 3/8, 7/16, 1/2, 9/16, 19/32, 5/8, 11/16, 3/4, 25/32, 13/16, 7/8, 15/16, 1	**4753N** **4760-125** **4768N-380** **4710**

4232M
Socket Set
Juego de Vasos

4232M	16 Pieces Set/=3,300g
METAL CASE:W415×H120×T50mm	
Sockets	Accessories
4405M 12-pt. Sockets 8, 9, 10, 12, 13, 14, 17, 19, 21, 22, 23, 24, 26	**4753N** **4760-125** **4768N-380**

4240M-00 · 4240A-00 ◯ Display Stands Expositores
4240M-05 · 4240A-05 ◯

4240M-00	4400M 32 Pieces Set/△△=4,400g
4240M-05	4405M 32 Pieces Set/△△=4,400g

DISPLAY STAND:W410×H160×T500mm

Sockets (2pcs.each)
10, 11, 12, 13, 14, 15, 16, 17, 19, 21, 22, 23, 24, 27, 30, 32

4240A-00	4400A 32 Pieces Set/△△=4,700g
4240A-05	4405A 32 Pieces Set/△△=4,700g

DISPLAY STAND:W410×H160×T500mm

Sockets (2pcs.each)
3/8, 7/16, 1/2, 9/16, 19/32, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16, 1, 1.1/16, 1.1/8, 1.3/16, 1.1/4

S4240M-00 · S4240A-00 ◯ Display Stands Expositores
S4240M-05 · S4240A-05 ◯

S4240M-00	4400M 117 Pieces Set/△△=13,000g
S4240M-05	4405M 117 Pieces Set/△△=13,000g

DISPLAY STAND:W510×H150×T230mm

Sockets

10mm:9pcs	16mm:9pcs	24mm:6pcs
11mm:9pcs	17mm:8pcs	27mm:5pcs
12mm:9pcs	19mm:7pcs	30mm:5pcs
13mm:9pcs	21mm:7pcs	32mm:4pcs
14mm:9pcs	22mm:6pcs	
15mm:9pcs	23mm:6pcs	

S4240A-00	4400A 103 Pieces Set/△△=13,000g
S4240A-05	4405A 103 Pieces Set/△△=13,000g

DISPLAY STAND:W510×H150×T230mm

Sockets

3/8" :9pcs	11/16":8pcs	1" :5pcs
7/16":9pcs	3/4" :7pcs	1.1/16":5pcs
1/2" :9pcs	13/16":7pcs	1.1/8" :5pcs
9/16":9pcs	7/8" :6pcs	1.3/16":5pcs
5/8" :9pcs	15/16":6pcs	1.1/4" :4pcs

4238AM

Socket Set
Juego de Vasos

4238AM	38 Pieces Set/⚖=8,050g
METAL CASE:W446×H266×T50mm	
Sockets	Accessories
4405M 12-pt. Sockets 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23, 24, 26, 27, 30, 32	**4753N**, **4760-125**, **4760-250**, **4770**, **4780**, **4785**
4405A 12-pt. Sockets 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16, 1.1/16, 1.1/8, 1.1/4	
4300C Spark Plug Socket 20.8	

4241M

Socket Set
Juego de Vasos

4241M	28 Pieces Set/⚖=6,500g
METAL CASE:W445×H190×T50mm	
Sockets	Accessories
4405M 12-pt. Sockets 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 32	**4753N**, **4760-125**, **4760-250**, **4768N-380**, **4770**, **4785**

4241A

Socket Set
Juego de Vasos

4241A	19 Pieces Set/⚖=5,350g
METAL CASE:W445×H190×T50mm	
Sockets	Accessories
4405A 12-pt. Sockets 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16, 1.1/16, 1.1/8, 1.1/4	**4753N**, **4760-125**, **4760-250**, **4768N-380**, **4770**, **4785**

4244M · 4244A

Socket Sets
Juegos de Vasos

4244M	22 Pieces Set/⚖=5,500g
METAL CASE:W445×H190×T50mm	
Sockets	Accessories
4405M 12-pt. Sockets 9, 10, 12, 13, 14, 15, 16, 17, 18, 19, 21, 23, 26, 29, 32	**4753N**, **4760-125**, **4760-250**, **4768N-380**, **4770**, **4785**, **4710**

4244A	22 Pieces Set/⚖=5,650g
METAL CASE:W445×H190×T50mm	
Sockets	Accessories
4405A 12-pt. Sockets 3/8, 7/16, 1/2, 9/16, 19/32, 5/8, 11/16, 3/4, 25/32, 13/16, 7/8, 15/16, 1, 1.1/8, 1.1/4	**4753N**, **4760-125**, **4760-250**, **4768N-380**, **4770**, **4785**, **4710**

4248M Socket Set / Juego de Vasos

4248M 24 Pieces Set/⚖=5,700g

METAL CASE:W445×H190×T50mm

Sockets	Accessories
4405M 12-pt. Sockets 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23, 24, 26, 27, 30, 32	**4753N** **4760-125** **4760-250** **4770** **4780** **4785**

4250M Socket Set / Juego de Vasos

4250M 18 Pieces Set/⚖=3,700g

METAL CASE:W445×H190×T50mm

Sockets	Accessories
4405M 12-pt. Sockets 10, 11, 12, 13, 14, 15, 17, 19, 22, 24, 27, 30, 32	**4753N** **4760-125** **4760-250** **4770** **4785**

4251M · 4251A Socket Sets / Juegos de Vasos

4251M 22 Pieces Set/⚖=3,200g

METAL CASE:W330×H68×T48mm

Sockets
4405M 12-pt. Sockets 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 32

4251A 18 Pieces Set/⚖=2,660g

METAL CASE:W330×H68×T48mm

Sockets
4405A 12-pt. Sockets 3/8, 7/16, 1/2, 9/16, 5/8, 19/32, 21/32, 11/16, 3/4, 25/32, 13/16, 7/8, 15/16, 1, 1.1/16, 1.1/8, 1.3/16, 1.1/4

4252M · 4252A Socket Sets / Juegos de Vasos

4252M 13 Pieces Set/⚖=1,200g

METAL CASE:W168×H60×T42mm

Sockets
4405M 12-pt. Sockets 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22

4252A 13 Pieces Set/⚖=1,300g

METAL CASE:W168×H60×T42mm

Sockets
4405A 12-pt. Sockets 3/8, 7/16, 1/2, 9/16, 19/32, 5/8, 21/32, 11/16, 3/4, 25/32, 13/16, 7/8, 15/16

4254 Socket Set / Juego de Vasos

4254 12 Pieces Set/⚖=1,070g

METAL CASE:W215×H80×T47mm

Sockets	Accessories
3425- E6, E8 **4425-** E10, E12, E14 **3325-** E6, E8 **4325-** E10, E12, E14	**4763-50** **4433A-35**

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

4261M
Socket Set
Juego de Vasos

4261M	18 Pieces Set/=4,870g
METAL CASE:W445×H190×T50mm	
Sockets	Accessories
4405M 12-pt. Sockets 8, 10, 11, 12, 13, 14, 17, 19, 21, 22, 24, 26, 27	**4753N** **4760-125** **4760-250** **4768N-380** **4770**

4263M
Socket Set
Juego de Vasos

4263M	21 Pieces Set/=6,100g
METAL CASE:W445×H190×T50mm	
Sockets	Accessories
4405M 12-pt. Sockets 8, 10, 11, 12, 13, 14, 15, 17, 19, 21, 22, 23, 24, 26, 27	**4753N** **4760-125** **4760-250** **4768N-380** **4770** **4715S**

4273AM
Socket Set
Juego de Vasos

4273AM	30 Pieces Set/=6,940g
METAL CASE:W446×H266×T50mm	
Sockets	Accessories
4405M 12-pt. Sockets 10, 11, 12, 13, 14, 17, 19, 21, 22, 23, 24, 26, 27 **4405A** 12-pt. Sockets 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16, 1	**4753N** **4760-125** **4760-250** **4768N-380** **4770** **4785**

P4241M-00
P4241M-05
Socket Sets
Juegos de Vasos

P4241M-00	28 Pieces Set/=6,400g
PLASTIC CASE:W425×H332×T65mm	
Sockets	Accessories
4400M 6-pt. Sockets 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 32	**4753J** **4760-125** **4760-250** **4768J-380** **4770** **4785**

P4241M-05	28 Pieces Set/=6,400g
PLASTIC CASE:W425×H332×T65mm	
Sockets	Accessories
4405M 12-pt. Sockets 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 32	**4753J** **4760-125** **4760-250** **4768J-380** **4770** **4785**

4275 Socket Set / Juego de Vasos

4275	24 Pieces Set/⚖=5,340g

METAL CASE:W445×H190×T50mm

Sockets	Accessories
4400M 6-pt. Sockets 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 24	4750N
4300C Spark Plug Sockets 16, 20.8	4760-125
4300M Wheel Nut Sockets 17(L60), 19(L60), 21(L60)	4760-250
	4768N-380
	4770
	4785

4276 Socket Set / Juego de Vasos

4276	17 Pieces Set/⚖=2,890g

METAL CASE:W370×H150×T50mm

Sockets	Accessories
4010M.50 Bit Sockets 6, 7, 8, 10, 12, 14	4752N
4025.60 TORX® Bit Sockets T20, T25, T27, T30, T40, T45, T50, T55, T60	4763-125

4277 Socket Set / Juego de Vasos

4277	27 Pieces Set/⚖=5,660g

METAL CASE:W445×H190×T50mm

Sockets	Accessories
4405M 12-pt. Sockets 10, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 24	4750N
4305M 12-pt. Deep Sockets 10, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 24	4760-125
	4768N-380

4279AM Socket Set / Juego de Vasos

4279AM	36 Pieces Set/⚖=6,000g

METAL CASE:W445×H190×T50mm

Sockets	Accessories
4405M 12-pt. Sockets 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23, 24, 26, 27, 30, 32	4753N
4405A 12-pt. Sockets 3/8, 7/16, 1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8, 15/16, 1.1/16, 1.1/8, 1.1/4	4760-125
	4760-250
	4770
	4785

4289M Socket Set / Juego de Vasos

4289M	18 Pieces Set/⚖=4,200g

METAL CASE:W445×H190×T50mm

Sockets	Accessories
4405M 12-pt. Sockets 8, 10, 12, 13, 14, 17, 19, 21, 22, 24, 27, 30, 32	4753N
	4760-125
	4760-250
	4768N-450
	4771

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

6400M · 6400A

6-point Sockets
Vasos Hexagonales



6400M 6405M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
New 14	22.1	34	11	50	160	10
New 16	24.6	34	12	50	167	10
17	26	34	12.5	50	175	5
18	27	34	13	50	178	5
19	28.5	34	13.5	50	179	5
20	29.5	34	14	50	185	5
21	31	34	14.5	50	185	5
22	32	34	15	50	187	5
23	33.5	34	16	50	187	5
24	34.5	34	17	50	200	5
25	36	34	17.5	50	217	5
26	37	34	18	50	222	5
27	38.5	37	19	53	254	5
28	39.5	38	19.5	53	298	5
29	41	38	20	55	292	5
30	42	38	21	55	301	5
31	43.5	38	22	57	294	5
32	44.5	40	23	57	351	5
33	46	40	23.5	57	384	5
34	47	40	24	57	397	5
35	48.5	42	24.5	59	422	5
36	49.5	42	25	59	438	5
37	51	42	25.5	59	484	5
38	52	45	26	59	523	5
39	53.5	45	26.5	59	538	5
40	54.5	45	27	62	550	5
41	56	47	28	62	633	5
42	57	47	28.5	62	652	2
43	58.5	47	29	62	659	2
44	59.5	47	29.5	62	657	2
45	61	47	30	68	734	2
46	62	47	31	68	791	2
47	63.5	48	31.5	68	816	2
48	64.5	45	32	68	800	2
50	67	48	34	68	880	2
52	69.5	53	33	72	925	2
54	72	55	33	72	1040	2
55	73.5	53	36	72	1006	2
56	74.5	53	36	72	1092	2
57	76	53	36	72	1169	2
58	77	53	36	72	1149	2
60	79.5	58	39	76	1402	2
63	83.5	58	39	76	1494	2
65	86	63	42	80	1608	2
70	92	68	45	84	1785	2
75	98.5	73	48	86	2186	1
78	102.1	73	55	86	2425	1
80	104.5	78	52	90	2475	1
85	111	78	52	90	2620	1

6405M · 6405A

12-point Sockets
Vasos Bihexagonales



6400A 6405A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
New 5/8	24.6	34	12	50	168	10
11/16	27	34	13	50	178	5
3/4	28.5	34	13.5	50	179	5
25/32	29.5	34	14	50	185	5
13/16	31	34	14.5	50	185	5
7/8	32	34	15	50	187	5
15/16	34.5	34	17	50	200	5
31/32	36	34	17.5	50	217	5
1	37	34	18	50	222	5
1. 1/16	38.5	37	19	53	254	5
1. 1/8	41	38	20	53	292	5
1. 3/16	42	38	21	55	301	5
1. 1/4	44.5	40	23	57	351	5
1. 5/16	46	40	23.5	57	384	5
1. 3/8	48.5	42	24.5	57	422	5
1. 7/16	51	42	25.5	59	484	5
1. 1/2	52	45	26	59	523	5
1. 9/16	54.5	45	27	59	550	5
1. 5/8	56	47	28	62	633	5
1.11/16	58.5	47	29	62	659	2
1. 3/4	59.5	47	29.5	62	657	2
1.13/16	62	47	31	68	791	2
1. 7/8	64.5	45	32	68	892	2
1.15/16	66	48	32.5	68	870	2
2	68.5	52	34.5	68	949	2
2. 1/16	71	54	33	72	983	2
2. 1/8	72	55	33	72	1040	2
2. 3/16	74.5	53	36	72	1092	2
2. 1/4	76	53	36	72	1169	2
2. 5/16	78.5	53	36	72	1344	2
2. 3/8	79.5	58	39	76	1402	2
2. 7/16	82	58	39	76	1420	2
2. 1/2	84.5	58	39	76	1497	2
2. 9/16	86	63	42	80	1608	2
2. 5/8	88.5	63	42	80	1709	2
2.11/16	89.5	63	42	80	1634	2
2. 3/4	92	68	45	84	1785	2
2.13/16	94.5	68	45	84	2018	2
2. 7/8	96	68	45	84	2062	2
2.15/16	98.5	73	48	86	2186	1
3	101	73	48	86	2309	1
3. 1/8	104.5	78	52	90	2475	1

6425

TORX® Sockets
Vasos TORX®



6425 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
E18	22.1	34	11.9	50	156	5
E20	24.6	34	13.3	50	166	5
E22	27.1	34	14.4	50	178	5
E24	28.6	34	16	50	185	5
E26	31.1	34	17.7	55	217	5
E28	32.1	34	24.1	60	237	5
E30	35	34	24.1	60	242	5
E32	36.1	34	24.1	60	247	5

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

6300M · 6300A

6-point Deep Sockets
Vasos Hexagonales Largos



6300M 6305M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
17	26	34	18	64	90	278	5
18	27	34	19	64	90	281	5
19	28.5	34	20	64	90	292	5
20	29.5	34	21	64	90	334	5
21	31	34	22	64	90	343	5
22	32	34	23	64	90	347	5
23	33.5	34	24	64	90	361	5
24	34.5	34	25	64	90	352	5
25	36	34	26	64	90	369	5
26	37	34	27	64	90	384	5
27	38.5	37	28	64	90	425	5
28	39.5	38	29	63	90	470	5
29	41	38	30	63	90	503	5
30	42	38	31	63	90	503	5
31	43.5	38	32	62	90	517	5
32	44.5	40	34	62	90	544	5
33	46	40	34	62	90	557	5
34	47	40	35	61	90	570	5
35	48.5	42	36	61	90	622	5
36	49.5	42	37	61	90	631	2
38	52	45	39	60	90	710	2
40	54.5	45	41	60	90	742	2
41	56	47	42	59	90	802	2
42	57	47	43	59	90	829	2
44	59.5	47	45	59	90	838	2
46	62	47	47	58	90	906	2
48	64.5	50	49	57	90	998	2
50	67	48	51	57	90	1005	2
52	69.5	53	49	–	100	1270	2
53	71	54	49	–	100	1338	2
54	72	55	49	–	100	1351	2
55	73.5	53	52	–	100	1388	2
56	74.5	53	52	–	100	1389	2
57	76	53	52	–	100	1467	2
58	77	53	52	–	100	1480	2
60	79.5	58	55	–	100	1626	2
63	83.5	58	55	–	100	1740	2
New 65	86	63	65	–	100	1939	2

6305M · 6305A

12-point Deep Sockets
Vasos Bihexagonales Largos

6300A 6305A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
3/4	28.5	34	20	64	90	292	5
25/32	29.5	34	21	64	90	334	5
13/16	31	34	22	64	90	343	5
7/8	32	34	23	64	90	347	5
15/16	34.5	34	25	64	90	352	5
1	37	34	27	64	90	384	5
1. 1/16	38.5	37	28	64	90	425	5
1. 1/8	41	38	30	63	90	503	5
1. 3/16	42	38	31	63	90	503	5
1. 1/4	44.5	40	34	62	90	544	5
1. 5/16	46	40	34	62	90	557	5
1. 3/8	48.5	42	36	61	90	622	5
1. 7/16	51	42	38	61	90	656	2
1. 1/2	52	45	39	60	90	710	2
1. 9/16	54.5	45	41	60	90	742	2
1. 5/8	56	47	42	59	90	802	2
1.11/16	58.5	47	44	59	90	831	2
1. 3/4	59.5	47	45	59	90	838	2
1.13/16	62	47	47	58	90	906	2
2	68.5	52	52	57	90	1061	2
2. 1/16	71	54	49	–	100	1338	2
2. 1/8	72	55	49	–	100	1351	2
2. 3/16	74.5	53	52	–	100	1389	2
2. 1/4	76	53	52	–	100	1467	2
2. 5/16	78.5	53	52	–	100	1787	2
2. 3/8	79.5	58	55	–	100	1626	2
2. 7/16	82	58	55	–	100	1715	2

6012M-75

Inhex Sockets
Vasos con Punta Hexagonal



6012M.75 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
12	35	15.5	40	75	253	10
14	35	15.5	40	75	265	10
15	35	15.5	40	75	271	10
16	35	15.5	40	75	285	10
17	35	15.5	40	75	292	10
18	35	15.5	40	75	302	10
19	35	15.5	40	75	312	10
20	35	15.5	40	75	323	10
New 21	38	15.5	40	75	330	10
22	38	22.5	40	75	340	10
24	38	22.5	40	75	362	10
27	38	22.5	40	75	402	10
30	38	28.5	40	75	445	10
32	38	28.5	40	75	485	10
36	42	28.5	40	75	663	10

6749 Reversible Ratchet
Llave de Carraca Reversible

S.O.D.H.-System | 2 Two-Step Dog | 36

* Renewal Kits→6749RK ➡P299



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
6749	68	49.6	29.6	565	2800	1

6749-1000 Reversible Ratchet
Llave de Carraca Reversible

S.O.D.H.-System | 2 Two-Step Dog | 36

* Renewal Kits→6749RK ➡P299



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
6749-1000	68	49.6	29.6	965	3550	1

6752 Reversible Ratchet
Llave de Carraca Reversible

60

* Renewal Kits→6752RK ➡P299



	D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
6752	67	55.5	35.5	500	2380	1

6755 Ratchet Adaptor
Adaptador de carraca



60

* Renewal Kits → 6755RK P300

	D (mm)	L (mm)	(g)	(pce.)
6755	62	97	1162	1

6760-75 · -100 · -125 · -150 · -200 · -300 · -400 Extension Bars
Alargaderas

6760	D (mm)	L (mm)	(g)	(pcs.)
75	35	75	335	10
100	35	100	434	10
125	35	125	528	10
150	35	150	624	2
200	35	200	815	1
300	35	300	1203	1
400	35	400	1585	1





6768 Hinge Handle Mango Articulado



* Renewal Kits → 6768RK ➔P300

	D (mm)	L (mm)	(g)	(pce.)
6768	42	450	1780	1

6768-600 • -1000 Hinge Handles Mangos Articulados



* Renewal Kits → 6768RK ➔P300

6768	D (mm)	L (mm)	(g)	(pce.)
600	42	600	2900	1
1000	42	1000	3500	1

6785 T-Handle Mango Corredizo

OVAL Shank



	L (mm)	(g)	(pce.)
6785	500	1500	1

6788 L-Handle Mango Acodado



	L (mm)	(g)	(pce.)
6788	330	1200	1

	L (mm)	(g)	(pcs.)
6770	105	500	2

6770 Universal Joint / Articulación Universal





6644A Adaptor / Adaptador — Warranty 668Nm / Garantía 668Nm



6688A Adaptor / Adaptador



	(sq.)	(sq.)	L (mm)	(g)	(pcs.)
6644A	3/4"	1/2"	47	136	5
6688A	3/4"	1"	60	285	5

Adapting down from bigger square drive to smaller square drive may lead to excessive torque and possibly cause breakage.

La adaptación de mayor a menor de un cuadrado conductor puede conducir a un par excesivo que puede causar roturas.

6201M · 6201A

Socket Sets
Juegos de Vasos

6201M — 16 Pieces Set/△△=17,300g

METAL CASE:W580×H200×T85mm

Sockets	Accessories
6405M 12-pt. Sockets 22, 24, 27, 30, 32, 36, 41, 46, 50, 55, 60	**6749** **6760-200** **6760-400** **6768** **6785**

6201A — 18 Pieces Set/△△=17,600g

METAL CASE:W580×H200×T85mm

Sockets	Accessories
6405A 12-pt. Sockets 7/8, 15/16, 1.1/16, 1.1/8, 1.1/4, 1.5/16, 1.7/16, 1.1/2, 1.5/8, 1.11/16, 1.13/16, 1.7/8, 2	**6749** **6760-200** **6760-400** **6768** **6785**

6212M · 6212A

Socket Sets
Juegos de Vasos

6212M — 12 Pieces Set/△△=11,000g

METAL CASE:W580×H124×T70mm

Sockets	Accessories
6405M 12-pt. Sockets 22, 24, 27, 30, 32, 36, 41, 46, 50	**6749** **6760-200** **6785**

6212A — 12 Pieces Set/△△=11,000g

METAL CASE:W580×H124×T70mm

Sockets	Accessories
6405A 12-pt. Sockets 7/8, 15/16, 1.1/16, 1.3/16, 1.1/4, 1.7/16, 1.5/8, 1.13/16, 2	**6749** **6760-200** **6785**

Sockets in sets can be supplied in 6-pt. or 12-pt. format.

6260M · 6260A Socket Sets / Juegos de Vasos

6260M 20 Pieces Set/=15,800g

METAL CASE:W580×H200×T85mm

Sockets	Accessories
6405M 12-pt. Sockets 21, 23, 26, 29, 31, 32, 34, 35, 36, 38, 41, 46, 50	**6749**
6101 Drag Link Socket	**6760-75**
	6760-200
	6760-400
	6770
	6785

6260A 25 Pieces Set/=19,000g

METAL CASE:W580×H200×T85mm

Sockets	Accessories
6405A 12-pt. Sockets 15/16, 31/32, 1, 1.1/16, 1.1/8, 1.3/16, 1.1/4, 1.5/16, 1.3/8, 1.7/16, 1.1/2, 1.9/16, 1.5/8, 1.11/16, 1.3/4, 1.13/16, 1.7/8, 2	**6749**
6101 Drag Link Socket	**6760-75**
	6760-200
	6760-400
	6770
	6785

6268M Socket Sets / Juegos de Vasos

6268M 15 Pieces Set/=12,500g

METAL CASE:W580×H124×T70mm

Sockets	Accessories
6405M 12-pt. Sockets 19, 22, 24, 27, 29, 30, 32, 36, 38, 41, 46, 50	**6749**
	6760-200
	6768

8400M · 8400A

6-point Sockets
Vasos Hexagonales



	8400M 8405M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)
	24	36.5	44	17	60	348	1
	27	40.5	44	19	60	362	1
New	**28**	41.5	44	19.5	60	368	1
New	**29**	43	44	20	60	378	1
	30	44	45	21	65	410	1
	32	46.5	45	23	65	455	1
	33	48	46	23.5	65	485	1
New	**34**	49	46	24	65	500	1
	35	50.5	48	24.5	65	536	1
	36	51.5	48	25	65	600	1
	38	54	50	26	65	624	1
New	**39**	55.5	50	26.5	65	650	1
	40	56.5	53	27	65	686	1
	41	58	53	28	68	747	1
	42	59	53	28.5	68	789	1
New	**43**	60.5	53	29	68	810	1
New	**45**	63	53	30	68	844	1
	46	64	53	31	72	928	1
New	**47**	65.5	53	31.5	72	942	1
New	**48**	66.5	53	32	72	960	1
	50	69	53	34	72	943	1
New	**52**	71.5	53	38	72	987	1
	54	74	55	37	72	1016	1
	55	75.5	53	42	77	1167	1
New	**56**	76.5	53	42	77	1160	1
	58	79	53	41	77	1200	1
	60	81.5	58	46	82	1440	1
New	**62**	84	58	46	82	1510	1
	63	85.5	58	45	82	1470	1
New	**64**	86.5	58	46	82	1540	1
	65	88	63	49	86	1683	1
	67	90.5	63	49	86	1840	1
	68	91.5	63	49	86	1800	1
	70	94	68	50	88	1963	1
	71	95.5	68	50	88	2200	1
New	**72**	96.5	68	51	88	2250	1
	75	100.5	73	53	90	2204	1
	78	104	75	52.5	90	2500	1
	80	106.5	75	58	95	2550	1
	83	110.5	78	57	95	2730	1
	85	113	80	57	95	2680	1
	90	119	80	59	100	3420	1
	95	125.5	85	58	100	4900	1
	100	131.5	85	57	100	4840	1

8405M · 8405A

12-point Sockets
Vasos Bihexagonales



8400A 8405A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)
15/16	36.5	44	17	60	355	1
1. 3/16	44	45	21	65	410	1
1. 1/4	46.5	45	23	65	455	1
1. 5/16	48	46	23.5	65	485	1
1. 3/8	50.5	48	24.5	65	536	1
1. 7/16	53	50	25.5	65	607	1
1. 1/2	54	50	26	65	624	1
1. 9/16	56.5	53	27	65	686	1
1. 5/8	58	53	28	68	747	1
1.11/16	60.5	53	29	68	830	1
1. 3/4	61.5	53	29.5	68	807	1
1.13/16	64	53	31	72	928	1
1. 7/8	66.5	53	32	72	936	1
1.15/16	68	53	32.5	72	941	1
2	70.5	53	37	72	976	1
2. 1/16	73	54	37	72	1027	1
2. 1/8	74	55	37	72	1016	1
2. 3/16	76.5	53	41	77	1192	1
2. 1/4	78	53	41	77	1177	1
2. 5/16	80.5	53	41	77	1292	1
2. 3/8	81.5	58	46	82	1440	1
2. 7/16	84	58	45	82	1495	1
2. 1/2	86.5	58	45	82	1497	1
2. 9/16	88	63	49	86	1683	1
2. 5/8	90.5	63	49	86	1840	1
2.11/16	91.5	63	49	86	1800	1
2. 3/4	94	68	50	88	1963	1
2.13/16	96.5	68	50	88	2035	1
2. 7/8	98	70	50	88	2100	1
2.15/16	100.5	73	53	90	2204	1
3	103	75	53	90	2406	1
3. 1/8	106.5	75	58	95	2550	1
3. 1/4	110.5	78	57	95	2730	1
3. 3/8	114	80	57	95	3050	1
3. 1/2	119	80	59	100	3420	1
3. 3/4	125.5	85	58	100	4900	1

8012M-80

Inhex Sockets
Vasos con Punta de Hexagonal



8012M.80 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
17	44.2	15.5	45	80	400	5
19	44.2	15.5	45	80	410	5
22	47.9	22.5	45	80	436	5
24	47.9	22.5	45	80	471	5
27	47.9	22.5	45	80	526	5
30	47.9	22.5	45	80	658	5
32	47.9	22.5	45	80	715	5
36	54.2	22.5	45	80	945	5

8760-200 • -400

Extension Bars
Alargaderas



8760	D (mm)	L (mm)	(g)	(pce.)
200	44	200	1300	1
400	44	400	2570	1

8770

Universal Joint
Articulación Universal





	L (mm)	(g)	(pce.)
8770	143	1170	1

8866A

Adaptor Warranty 1850Nm
Adaptador Garantía 1850Nm





	□ (mm)	▫ (mm)	L (mm)	(g)	(pcs.)
8866A	1"	3/4"	60	338	5

⚠ Adapting down from bigger square drive to smaller square drive may lead to excessive torque and possibly cause breakage.

La adaptación de mayor a menor de un cuadrado conductor puede conducir a un par excesivo que puede causar roturas.

8749 Reversible Ratchet / Llave de Carraca Reversible



* Renewal Kits → **8749RK** ➡P299

		D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
	8749	70	62.2	36.2	800	4090	1
New	**8749-1000**	70	62.2	36.2	1020	4664	1

8768 Hinge Handle / Mango Articulado



* Renewal Kits → **8768RK** ➡P300

		D (mm)	L (mm)	(g)	(pce.)
	8768	55	600	3190	1
New	**8768-1000**	55	1000	4348	1

8785 T-Handle / Mango Corredizo



		L (mm)	(g)	(pce.)
	8785	550	3190	1
New	**8785-700**	700	3906	1

8788 L-Handle / Mango Acodado





	L (mm)	(g)	(pce.)
8788	600	3600	1





8200M · 8200A

Socket Sets
Juegos de Vasos

8200M 12 Pieces Set/⚖=18,600g

METAL CASE:W600×H150×T110mm

Sockets	Accessories
8405M 12-pt. Sockets 35, 38, 41, 46, 50, 54, 58, 63	**8760-200** **8760-400** **8770** **8785**

8200A 12 Pieces Set/⚖=18,600g

METAL CASE:W600×H150×T110mm

Sockets	Accessories
8405A 12-pt. Sockets 1.7/16, 1.1/2, 1.5/8, 1.13/16, 2, 2.1/8, 2.1/4, 2.1/2	**8760-200** **8760-400** **8770** **8785**

8225M

Socket Set
Juego de Vasos

8225M 15 Pieces Set/⚖=27,000g

METAL CASE:W620×H217×T97mm

Sockets	Accessories
8405M 12-pt. Sockets 32, 33, 36, 41, 46, 50, 55, 60, 65, 70, 75, 80	**8749** **8760-200** **8760-400**

Sockets in sets can be supplied in 6-pt. or 12-pt. format.

Titanium Sockets

TI4261M

Socket Set Titanium
Juego de Vasos de Titanio

TI4261M	18 Pieces Set/△△=4,280g
WOODEN CASE:W445×H190×T60mm	
Sockets	Accessories
TI4400M 6-pt. Sockets 8, 10, 11, 12, 13, 14, 17, 19, 21, 22, 24, 26, 27	**TI4749J** **TI4760-125** **TI4760-250** **TI4768J-380** **TI4770**

Characteristic of Titanium

Light weight : Makes it effective for operating tools.The specific gravity is only about 58% of chrome molybdenum steel which is used for our normal products.
Non-Corrosion : Corrosion Resistance is greatly improved against salt water and any kind of chemical products.
Non-Magnetic : Non-Magnetic material will prevent the tools from magnetizing.

Características del Titanio

Peso ligero : Aumenta la eficiencia de las herramientas de trabajo. El peso específico es aproximadamente sólo el 58% del acero al cromo-molibdeno de nuestros productos normales.
No se oxida : Se aumenta significativamente la resistencia a la corrosión por ambiente salino o por cualquier clase de productos químicos.
No es magnético : Material paramagnético que evita la magnetización de las herramientas.

Pentagonal drive is designed to avoid using with normal square drive items, so that it will provide extra safety and much more strength.

El diseño de conductor pentagonal evita su utilización con conductores normales cuadrados, proporcionando más seguridad y mucha mayor resistencia.

Accessories

4100M · 4100A

Screw and Stud Pullers
Extractores de Espárragos y Tornillos





Screw and Stud Pullers
Hexagon body design can lessen the excessive load on cages and rollers inside the pullers.

Extractores de Tornillos y Espárragos
El diseño hexagonal del cuerpo evita cargas excesivas en las celdas y rodillos internos del extractor.

4100M (mm)		D (mm)	L (mm)	H (mm)	(g)	(pcs.)
5	1/2"	24	65	21	145	10
6		24	65	21	150	10
7		24	65	21	150	10
8		24	65	21	147	10
9		28	75	21	217	10
10		28	75	21	213	10
10.5		28	75	21	202	10
11		28	75	21	218	10
12		28	75	21	220	10
14		34	75	27	340	5
16	–⚠	34	75	27	315	5

4100A (inch)		D (mm)	L (mm)	H (mm)	(g)	(pcs.)
1/4	1/2"	24	65	21	150	10
5/16		24	65	21	147	10
3/8		28	75	21	213	10
7/16		28	75	21	218	10
1/2		28	75	21	191	10
9/16		34	75	27	340	5
5/8	–⚠	34	75	27	315	5

* Renewal Kits → **4100MRK/4100ARK** ➔P301

⚠ 4100M-16 and 4100A-5/8 do not have 1/2" square drive.
Drive the outer hexagon part with 27mm sockets or ring wrenches.

4100M-16 y 4100A-5/8 no tienen conductores cuadrados de 1/2"
Apretar la parte hexagonal exterior con vasos de 27mm o llaves de tuerca.

Tolerance/Tolerancia

4100M (mm)		4100A (inch)	
5	4.7- 5	**1/4**	6 - 6.4
6	5.6- 6	**5/16**	7.6- 8
7	6.6- 7	**3/8**	9 - 9.6
8	7.6- 8	**7/16**	10.5-11.1
9	8.4- 9	**1/2**	12.1-12.7
10	9.4-10	**9/16**	13.5-14.3
10.5	9.9-10.5	**5/8**	15.2-16
11	10.4-11		
12	11.4-12		
14	13.2-14		
16	15.2-16		

4211M · 4211A

Screw and Stud Pullers Sets
Juegos de Extractores de Tornillos y Espárragos

4211M — 4 Pieces Set/⚖=1,040g
METAL CASE:W215×H80×T47mm
PULLER
4100M Stud Pullers
6, 8, 10, 12

4211A — 4 Pieces Set/⚖=1,040g
METAL CASE:W215×H80×T47mm
PULLER
4100A Stud Pullers
1/4, 5/16, 3/8, 1/2

4214M

Screw and Stud Pullers Set
Juegos de Extractores de Tornillos y Espárragos

4214M — 5 Pieces Set/⚖=1,450g
METAL CASE:W215×H80×T47mm
PULLER
4100M Stud Pullers
6, 8, 10, 12, 14

6100M

Screw and Stud Pullers
Extractores de Tornillos y Espárragos

6100M (mm)		D (mm)	L (mm)	H (mm)	(g)	(pce.)
18	3/4"	48	100	36	840	1
20		48	100	36	816	1
22		48	100	36	745	1
24		48	100	36	739	1
27		63	125	46	1707	1
28		63	125	46	1701	1
29		63	125	46	1696	1
30		63	125	46	1691	1

* Renewal Kits → **6100MRK** ➡P301

⚠ 6100M-22 to -30 do not have 3/4" square drive.
Drive the outer hexagon part with sockets or ring wrenches
(size 22-24mm = 36H, 27-30mm = 46H).

6100M-22-30 no tienen conductores cuadrados de 3/4"
Apretar la parte hexagonal exterior con vasos o llaves de tuerca
(medidas 22-24mm = 36H, 27-30mm = 46H)



Tolerance/Tolerancia

6100M (mm)	
18	16.9-18
20	18.8-20
22	20.8-22
24	22.7-24
27	25.7-27
28	26.7-28
29	27.6-29
30	28.6-30

14100M · 14100A

Impact Screw and Stud Pullers
Extractores de Tornillos y Espárragos de Impacto



14100M (mm)		D_1 (mm)	D_2 (mm)	L (mm)	(g)	(pcs.)	
6	1/2"	24	25	48	126	10	*1
7		24	25	48	126	10	*1
8		24	25	48	122	10	*1
9		28	30	48	181	10	*2
10		28	30	48	181	10	*2
12		28	30	48	175	10	*2

14100A (inch)		D_1 (mm)	D_2 (mm)	L (mm)	(g)	(pcs.)	
1/4	1/2"	24	25	48	126	10	*1
5/16		24	25	48	122	10	*1
3/8		28	30	48	181	10	*2
7/16		28	30	48	181	10	*2
1/2		28	30	48	180	10	*2

*1 C-Ring=1401C,Pin/O-Ring=1401A/B
*2 C-Ring=1402C,Pin/O-Ring=1402A/B ➡P250-251

Tolerance/Tolerancia

14100M (mm)		14100A (inch)	
6	5.6- 6	**1/4**	6 - 6.4
7	6.6- 7	**5/16**	7.6- 8
8	7.6- 8	**3/8**	9 - 9.6
9	8.4- 9	**7/16**	10.5-11.1
10	9.4-10	**1/2**	12.1-12.7
12	11.4-12		

141S
Stud Puller Ratchets
Extractores de Espárragos de Carraca

141S (mm)	D (mm)	L (mm)	(g)	(pce.)
6	28	120	150	1
8	28	120	150	1
10	32	120	153	1
12	32	120	152	1

141S (inch)	D (mm)	L (mm)	(g)	(pce.)
5/16	28	120	150	1
3/8	32	120	153	1
1/2	32	120	152	1

141
Stud Puller Ratchets
Extractores de Espárragos de Carraca

141 (mm)	D (mm)	L (mm)	(g)	(pce.)
6	28	205	215	1
8	28	205	215	1
10	32	205	234	1
12	32	205	233	1

141 (inch)	D (mm)	L (mm)	(g)	(pce.)
5/16	28	205	215	1
3/8	32	205	234	1
1/2	32	205	233	1

141P
Stud Puller Ratchets
Extractores de Espárragos de Carraca



141P (mm)	D (mm)	L (mm)	(g)	(pce.)
6	28	205	210	1
8	28	205	210	1
10	32	205	229	1
12	32	205	227	1



The three roller system can protect the studs from damage.

El sistema de tres rodillos puede proteger los espárragos de cualquier daño.

1201
Stud Puller Ratchets Set
Juego de Extractores de Espárragos de Carraca

1201	4 Pieces Set/=973g
METAL CASE:W240×H100×T32mm	
PULLER	
141S Stud Puller Ratchet 6, 8, 10, 12	

4104
Screw and Stud Puller
Extractor de Tornillos y Espárragos



		Tolerance		D (mm)	L (mm)	(g)	(pcs.)
		min	max				
4104	1/2"	ϕ6	ϕ19	54	56	489	2

4103M

Stud Bolt Setters
Vasos para apretar pernos

4103M (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	⚖ (g)	◇ (pcs.)
6(1.0)	1/2"	10.3	22	9	37	54	10
7(1.0)		11.5	22	10	37	58	10
8(1.25)		13.2	22	11	37	60	10
10(1.25)		15.3	23	13	44	86	10
10(1.5)		15.3	23	13	44	86	10
12(1.25)		17.8	23	14	44	86	10
12(1.75)		17.8	23	14	44	86	10



4203M
4203MF

Stud Bolt Setters Set
Juego de Vasos para apretar Pernos

4203M 4 Pieces Set/⚖=530g
METAL CASE:W130×H65×T26mm
Stud Bolt Setter
4103M Stud Bolt Setters
6(1.0), 8(1.25), 10(1.5), 12(1.75)

4203MF 4 Pieces Set/⚖=530g
METAL CASE:W130×H65×T26mm
Stud Bolt Setter
4103M Stud Bolt Setters
6(1.0), 8(1.25), 10(1.25), 12(1.25)



A special socket for installing a stud bolt.
Inside steel ball prevent the stud bolt stuck onto the socket. After installing a stud bolt, turn to anti-clockwise to removing the socket.

13103M

Impact Stud Bolt Setters
Vasos para apretar Pernos de Impacto

13103M (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	⚖ (g)	◇ (pcs.)	
5(0.8)	3/8"	9.5	19	8	32	39	10	*1
6(1.0)		10.8	19	9	32	41	10	*1
7(1.0)		12.5	19	10	32	44	10	*1
8(1.25)		13.5	19	11	35	49	10	*1
10(1.25)		15.8	19	13	35	49	10	*1
10(1.5)		15.8	19	13	35	49	10	*1

*1 C-Ring=1301C, Pin/O-Ring=1301A/B ➡P250-251



14103M

Impact Stud Bolt Setters
Vasos para apretar Pernos de Impacto

14103M (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	⚖ (g)	◇ (pcs.)	
6(1.0)	1/2"	12	25	11	42	75	10	*1
7(1.0)		13.2	25	12	42	78	10	*1
8(1.25)		14.5	25	15	42	81	10	*1
10(1.25)		17	25	18	49	106	10	*1
10(1.5)		17	25	18	49	106	10	*1
12(1.25)		19.5	25	19	49	107	10	*1
12(1.75)		19.5	25	19	49	107	10	*1
14(1.5)		22	25	21	55	128	10	*1
14(2.0)		22	25	21	55	128	10	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➡P250-251



2127 NUTTWISTER® AFLOJA TUERCAS



2127 (mm)	⍁	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	⚖ (g)	◈ (pcs.)
4	1/4"	7	13	4	23	14	10
4.5		7.4	13	4	23	14	10
5		8	13	5	23	14	10
5.5		8.8	13	5	23	14	10
6		9.5	13	6	23	14	10
7		10.9	13	6	23	14	10
8		11.5	13	8	23	14	10
9		13	13	8	23	15	10
9.5		13.8	13	10	23	16	10
10		14.8	13	10	23	17	10

RS2127/6 Socket Set on Rail / Juego de Vasos en Regleta

RS2127/6	6 Pieces Set/Rail 150mm	⚖ (g)
	4, 4.5, 5, 5.5, 6, 7	105

RS2127/10 Socket Set on Rail / Juego de Vasos en Regleta

RS2127/10	10 Pieces Set/Rail 150mm	⚖ (g)
	4, 4.5, 5, 5.5, 6, 7, 8, 9, 9.5,10	180

3127 NUTTWISTER® AFLOJA TUERCAS



3127 (mm)	⍁	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	⚖ (g)	◈ (pcs.)
8	3/8"	11.5	19	8	32	40	10
9		13	19	8	32	40	10
9.5		13.8	19	8	32	41	10
10		14.8	19	10	32	41	10
11		16	19	10	32	43	10
12		17	19	12	32	44	10
13		18.5	19	12	32	46	10
14		19.7	19	14	32	48	10
15		20.7	19	14	32	52	10
16		22.2	22	14	32	66	10
17		23.5	22	16	35	80	10
19		26	22	16	35	92	10

RS3127/8 Socket Set on Rail / Juego de Vasos en Regleta

RS3127/8	8 Pieces Set/Rail 200mm	⚖ (g)
	8, 9, 10, 11, 12, 13, 14, 16	420

3128-80

NUTTWISTER® (Long type)
AFLOJA TUERCAS (Serie Larga)



3128.80 (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	⚖ (g)	◇ (pcs.)
8	3/8"	11.5	19	6	80	58	10
9		13	19	6	80	61	10
10		14.8	19	8	80	66	10
11		16	19	8	80	70	10
12		17	19	10	80	77	10
13		18.5	19	10	80	80	10
14		19.7	19	12	80	82	10

4127

NUTTWISTER®
AFLOJA TUERCAS



4127 (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	⚖ (g)	◇ (pcs.)
14	1/2"	19.7	30	14	42	125	5
17		23.5	30	16	42	137	5
19		26	30	16	42	146	5
21		28	30	17	42	153	5
22		29.5	30	17	42	158	5
24		32	30	18	42	174	5
25.4		33.5	30	18	42	183	5

RS4127/6

Socket Set on Rail
Juego de Vasos en Regleta

RS4127/6 — 6 Pieces Set/Rail 200mm	⚖ (g)
17, 19, 21, 22, 24, 25.4	960

4128-120

NUTTWISTER® (Long type)
AFLOJA TUERCAS (Serie Larga)



4128.120 (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	⚖ (g)	◇ (pcs.)
17	1/2"	23.5	30	16	120	227	10
19		26	30	16	120	247	10
21		28	30	17	120	262	10
22		29.5	30	17	120	259	10

A very effective method and easy solution for removing rounded off nuts, bolts and studs. The sharp edges of the NUTTWISTER® Socket opening will tighten around the nut, bolt or stud and turn it easily off.

Un método muy efectivo y una fácil solución para aflojar tuercas, pernos y espárragos redondeados por desgaste. Las afiladas aristas de la boca del vaso AFLOJA TUERCAS NUTTWISTER®, aprietan contra la tuerca, perno o espárrago, haciéndolo girar fácilmente.

3129-32 BOLTTWISTER® AFLOJA PERNOS



3129.32 (mm)	⊿	D1 (mm)	D2 (mm)	L (mm)	⚖ (g)	◈ (pcs.)
2	3/8"	2	19	32	32	10
3		3	19	32	33	10
4		4	19	32	33	10
6		6	19	32	35	10
8		8	19	32	37	10
10		10	19	32	40	10

RS3129/6-L32 Socket Set on Rail / Juego de Vasos en Regleta



RS3129/6-L32	6 Pieces Set/Rail 150mm	⚖ (g)
	2, 3, 4, 6, 8, 10	250

3129-60 BOLTTWISTER® AFLOJA PERNOS



3129.60 (mm)	⊿	D1 (mm)	D2 (mm)	L (mm)	⚖ (g)	◈ (pcs.)
2	3/8"	2	19	60	38	10
3		3	19	60	42	10
4		4	19	60	44	10
6		6	19	60	47	10
8		8	19	60	53	10
10		10	19	60	64	10

RS3129/6-L60 Socket Set on Rail / Juego de Vasos en Regleta

RS3129/6-L60	6 Pieces Set/Rail 150mm	⚖ (g)
	2, 3, 4, 6, 8, 10	320



Effective method and easy solution for removing twisted off bolt. Drill a hole in the center of bolt and drive BOLTTWISTER® firmly into the hole. The sharp spiral edges will hold the broken bolt and easily remove it.

Un método efectivo y una fácil solución para aflojar pernos rotos. Taladrar un agujero en el centro del perno e introducir el AFLOJA PERNOS BOLTTWISTER® presionando y girando. Las afiladas aristas espirales agarran el perno roto sacándolo.

BOLTTWISTER	Bolt size	Drill size
2	M5	ϕ 2.4– 2.6
3	M6	ϕ 3.2– 3.5
4	M8	ϕ 4.2– 4.5
6	M10–M12	ϕ 6.2– 6.5
8	M14–M16	ϕ 8.2– 8.5
10	M18–M20	ϕ 10.2–10.5
12	M22–M24	ϕ 12.2–12.5
14	M27–M30	ϕ 14.2–14.5
16	M33	ϕ 16.2–16.5

4129-37 BOLTTWISTER® AFLOJA PERNOS

4129.37 (mm)	☐	D_1 (mm)	D_2 (mm)	L (mm)	(g)	(pcs.)
8	1/2"	8	24	37	59	10
10		10	24	37	63	10
12		12	24	37	67	10
14		14	24	37	72	10
16		16	24	37	78	10



RS4129/5-L37 Socket Set on Rail / Juego de Vasos en Regleta

RS4129/5-L37	5 Pieces Set/Rail 150mm	(g)
8, 10, 12, 14, 16		370

4129-75 BOLTTWISTER® AFLOJA PERNOS

4129.75 (mm)	☐	D_1 (mm)	D_2 (mm)	L (mm)	(g)	(pcs.)
8	1/2"	8	24	75	80	10
10		10	24	75	94	10
12		12	24	75	110	10
14		14	24	75	130	10
16		16	24	75	150	10



RS4129/5-L75 Socket Set on Rail / Juego de Vasos en Regleta

RS4129/5-L75	5 Pieces Set/Rail 150mm	(g)
8, 10, 12, 14, 16		600



156M

6-point Deep
Hexagonal Larga



156M (mm)	D (mm)	ℓ (mm)	H (mm)	L1 (mm)	L2 (mm)	(g)	(pce.)
8	12	9	41	355	200	231	1
10	14.5	11	41	355	200	289	1
12	16.8	13	41	355	200	429	1
14	20	16	41	355	200	454	1

104M · 104A

6-point
Hexagonal





104M (mm)	D (mm)	ℓ (mm)	L1 (mm)	L2 (mm)	(g)	(pce.)
6	9.5	8	200	180	150	1
7	11	9	200	180	152	1
8	12	10	250	200	183	1
9	14	12	250	200	188	1
10	14	13	250	200	230	1
11	16	14	250	200	234	1
12	18	15	250	250	384	1
13	18.5	17	300	250	412	1
14	20	18	300	250	428	1
15	21	19	300	250	443	1
16	22.5	21	350	300	528	1
17	24	22	350	300	707	1
18	25	23	350	300	707	1
19	26.5	25	350	300	717	1
21	29	27	350	300	1070	1
22	30	28	350	300	1062	1
24	33	30	350	300	1140	1

104A (inch)	D (mm)	ℓ (mm)	L1 (mm)	L2 (mm)	(g)	(pce.)
1/4	9.5	8	200	180	150	1
5/16	12	10	250	200	183	1
3/8	14	12	250	200	188	1
7/16	16	14	250	200	234	1
1/2	18.5	17	300	250	412	1
9/16	20	18	300	250	428	1
5/8	22.5	21	350	300	528	1
3/4	26.5	25	350	300	717	1

3116M

Universal with 6-point Socket
Con articulación universal con Vaso Hexagonal

3116M (mm)	D (mm)	ℓ (mm)	L1 (mm)	L2 (mm)	(g)	(pce.)
10	14.5	8	800	190	796	1
12	17	10.3	800	190	797	1
13	18	11.3	800	190	797	1
14	19.5	11.3	800	190	797	1
15	21	12.8	800	190	799	1
16	22	12.8	800	190	806	1
17	23.6	13.8	800	190	801	1
18	24	13.8	800	190	809	1

124M-600 (2B)

Ball Joint plus Nut Grip Socket
Con articulación de rótula y Vaso Sujeta Tuerca

124M.600 (mm)	D (mm)	ℓ (mm)	L1 (mm)	L2 (mm)	(g)	(pce.)
8(2B)	12	5	600	200	332	1
10(2B)	14.5	6	600	200	334	1
12(2B)	16.8	7	600	200	424	1
13(2B)	18	8	600	200	425	1
14(2B)	19.5	8.5	600	200	527	1
17(2B)	23.3	9.5	600	200	538	1



NUT GRIP®



Twin balls at the 6-point opening hold bolt-nut tightly for safe and reliable work.

Las dos bolas de la boca Hexagonal sujetan el perno-tuerca permitiendo un trabajo seguro y fiable.

157H

For Inhex Screws
Para Tornillos de Seis Lados en el Interior (Inhex)

157H (mm)	L_1 (mm)	L_2 (mm)	(g)	(pce.)
3	160	100	57	1
4	200	120	70	1
5	250	160	90	1
6	300	190	147	1
7	300	190	193	1
8	300	190	245	1
10	300	190	433	1
12	320	210	662	1
14	340	220	879	1
17	340	220	1369	1

157T (T)

For TORX® Screws
Para Tornillos TORX®

157T (T)	L_1 (mm)	L_2 (mm)	(g)	(pce.)
T25	250	180	95	1
T27	250	180	96	1
T30	250	180	167	1
T40	250	180	168	1
T45	250	180	213	1
T50	250	180	215	1

157P

For Phillips Screws
Para Tornillos Phillips

157S

For Slotted Heads
Para Cabezas Ranuradas



157P (PH)	L_1 (mm)	L_2 (mm)	(g)	(pce.)
2	200	180	84	1
3	300	180	189	1

157S	T×W	L_1 (mm)	L_2 (mm)	(g)	(pce.)
6	1.0×6	200	180	84	1
8	1.2×8	250	180	170	1



TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

2715 T-Handle / Llaves en T

3715 T-Handle / Llaves en T

3715S T-Handle / Llaves en T

3715SL T-Handle / Llaves en T

Wobble-Fix **3716** T-Handle / Llaves en T ⚠

OVAL Shank **3715SLK** T-Handle / Llaves en T





Photo: 3715SLK

	☐	L1 (mm)	L2 (mm)	⚖ (g)	🛍 (pce.)
2715	1/4"	200	120	130	1

	☐	L1 (mm)	L2 (mm)	⚖ (g)	🛍 (pce.)
3715	3/8"	268	240	386	1
3715S		268	190	347	1
3715SL		237	200	325	1
3715SLK		236	200	470	1
3716		268	240	379	1

⚠ 2715/3715/3716
This tool is used sockets in hard to reach places. 3716 has a reduced square drive and similar function as offset extention bars.

4715 T-Handle Llaves en T

4715S T-Handle Llaves en T

4715SL T-Handle Llaves en T



	⊿	L1 (mm)	L2 (mm)	⚖ (g)	👜 (pce.)
4715	1/2"	267	255	475	1
4715S		267	170	402	1
4715SL		250	250	640	1

4711X Spinning Cross Wrench



OVAL Shank

	⊿	L1 (mm)	L2 (mm)	L3 (mm)	⚖ (g)	👜 (pce.)
4711X	1/2"	140	280	350	945	1

3131A

Tap Holder, Adjustable
Adaptadores para machos de terrajas

3131A	☐	S(mm) Min.	S(mm) Max.	L (mm)	(g)	(pcs.)
1	3/8"	2.0	5.0	42	80	5
2		4.5	8.0	47	100	5





160K

Handle
Llave

Tap is not included.



	☐	C (mm)	L (mm)	(g)	(pce.)
160K	3/8"	10	220	130	1
160K-1/2	1/2"	10	220	135	1

3132

Die Holder
Adaptadores

	☐	D (mm)	d (mm)	H (mm)	ℓ_1 (mm)	ℓ_2 (mm)	L (mm)	(g)	(pcs.)
3132-20	3/8"	28	8	17	7	45	60	130	5
4132-25		34	14	22	9	40	60	170	2
4132-38	1/2"	48	18	24	13	60	80	315	2
4132-50		60	30	27	16	85	105	740	2



Die is not included.

4132

Die Holders
Adaptadores

102NM · 102NA

Without Reverse Lever
Sin palanca de inversión



102NM (mm)	L (mm)	D1 (mm)	D2 (mm)	C (mm)	(g)	(pcs.)
6×7	108	15.3	16.4	7.5	60	10
7×8	108	15.3	16.4	7.5	60	10
8×9	134	17.1	19.7	7.5	80	10
8×10	134	17.1	19.7	7.5	80	10
10×11	140	20.1	22.7	7.5	87	10
10×12	140	20.1	22.7	7.5	87	10
New 11×13	145	23.6	24.6	9	112	10
12×13	145	23.6	24.6	9	112	10
12×14	145	23.6	24.6	9	112	10

102NA (inch)	L (mm)	D1 (mm)	D2 (mm)	C (mm)	(g)	(pcs.)
7/32× 1/4	108	15.3	16.4	7.5	60	10
1/4 × 9/32	108	15.3	16.4	7.5	60	10
1/4 × 5/16	108	15.3	16.4	7.5	60	10
5/16×11/32	134	17.1	19.7	7.5	80	10
5/16× 3/8	134	17.1	19.7	7.5	80	10
3/8 × 7/16	140	20.1	22.7	7.5	87	10
7/16× 1/2	145	23.6	24.6	9	112	10
1/2 × 9/16	145	23.6	24.6	9	112	5

102KM · 102KA

Reversible
Reversible



102KM (mm)	L (mm)	D1 (mm)	D2 (mm)	C (mm)	(g)	(pcs.)
6×7	108	15.3	16.4	7.2	51	10
7×8	108	15.3	16.4	7.2	51	10
8×9	134	17	20	9.1	76	10
8×10	134	17	20	9.1	76	10
10×11	141	21	23.5	9.1	84	10
10×12	141	21	23.5	9.1	84	10
12×13	146	24	25	9.1	89	10
12×14	146	24	25	9.1	89	5
13×17	200	27.1	31.8	11.5	190	5
14×17	200	27.1	31.8	11.5	200	5

102KA (inch)	L (mm)	D1 (mm)	D2 (mm)	C (mm)	(g)	(pcs.)
7/32× 1/4	108	15.3	16.4	7.2	51	10
1/4 × 5/16	108	15.3	16.4	7.2	51	10
New 5/16×11/32	134	17	20	9	76	10
3/8 × 7/16	141	21	23.5	9.1	84	10
1/2 × 9/16	146	24	25	9.1	89	5

102KM (BH)

With Twin Openings (Two-in-One)
Con Bocas Gemelas (Dos en Uno)



102KM.BH (mm)	L (mm)	D1 (mm)	D2 (mm)	C (mm)	(g)	(pcs.)
5.5• 6× 7• 8	108	15.3	16.4	10	60	10
8 •10×12•13	141	21	23.5	13	87	10
9 •10×11•12	141	21	23.5	13	87	10
10 •12×13•14	146	24	25	13	98	10
13 •14×15•17	200	27.1	31.8	16	200	5



102KT

Reversible TORX®
Reversible TORX®



102KT (E)	L (mm)	D1 (mm)	D2 (mm)	C (mm)	(g)	(pcs.)
E 4×E 6	108	15.3	16.4	7.5	51	10
E 6×E 8	108	15.3	16.4	7.5	51	10
E10×E12	134	17	20	9	76	10

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

103KM · 103KA
103KA.BH

Reversible
Reversible

Reversible(12P)
Reversible(12P)

103KM (mm)	L (mm)	D_1 (mm)	D_2 (mm)	C (mm)	(g)	(pcs.)
6× 7	108	15.3	16.4	7.5	51	5
7× 8	108	15.3	16.4	7.5	51	5
8× 9	134	17	20	9	76	5
8×10	134	17	20	9	76	5
10×11	140	21	23.5	9	84	5
10×12	140	21	23.5	9	84	5
12×13	145	24	25	9	89	5
12×14	145	24	25	9	89	5

103KA (inch)	L (mm)	D_1 (mm)	D_2 (mm)	C (mm)	(g)	(pcs.)
7/32× 1/4	108	15.3	16.4	7.5	51	5
1/4 × 5/16	108	15.3	16.4	7.5	51	5
5/16×11/32	134	17	20	9	76	5
New **5/16× 3/8**	134	17	20	9	76	5
3/8 × 7/16	140	21	23.5	9	84	5
New **7/16× 1/2**	145	24	25	9	89	5
1/2 × 9/16	145	24	25	9	89	5

103KA.BH (inch)	L (mm)	D_1 (mm)	D_2 (mm)	C (mm)	(g)	(pcs.)
New **1/4×5/16**	108	15.3	16.4	7.5	51	5
New **3/8×7/16**	140	21	23.5	9	84	5
New **1/2×9/16**	145	24	25	9	89	5



103KT

Reversible TORX®
Reversible TORX®

103KT (E)	L (mm)	D_1 (mm)	D_2 (mm)	C (mm)	(g)	(pcs.)
E 4×E 6	104	15.3	16.4	7.5	51	5
E 6×E 8	104	15.3	16.4	7.5	51	5
E10×E12	128	17	20	9	76	5
E14×E16	139	24	25	9	89	5



R810

Reversible
Reversible

R810 (inch)	L (mm)	D_1 (mm)	D_2 (mm)	C (mm)	(g)	(pcs.)
1/4×5/16	108	15.3	16.4	7.5	60	10
3/8×7/16	140	20.1	22.7	7.5	87	10
1/2×9/16	145	23.6	24.6	9	112	10



154M

Push and Pull-Ratchets
Llaves de Carraca de Empuje y Tracción



154M (mm)	L (mm)	D (mm)	C (mm)	(g)	(pcs.)
8	294	17.1	7.5	178	2
10	297	20.1	7.5	183	2
12	300	23.6	9	189	2
13	301	24.6	9	194	2
14	301	24.6	9	194	2



154ML

Push and Pull-Ratchets
Llaves de Carraca de Empuje y Tracción

154ML (mm)	L (mm)	D (mm)	C (mm)	(g)	(pcs.)
10	297	20.1	7.5	230	2
12	300	23.6	9	252	2

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

137

For 1/4" and 3/8" Square Drive Sockets
Para Vasos con Conductor Cuadrado de 1/4" y 3/8"



	L (mm)	D1 (mm)	D2 (mm)	C (mm)	(g)	(pcs.)
137	141	23.5	21	9	104	5

1/4" × 3/8"

138

For Bits 101
Para Puntas 101



	L (mm)	D1 (mm)	D2 (mm)	C (mm)	(g)	(pcs.)
138	141	23.5	21	9	97	10

1/4" × 1/4"

139

For 1/4" Square Drive Sockets
Para Vasos con Conductor Cuadrado de 1/4"



	L (mm)	D (mm)	C (mm)	(g)	(pcs.)
139	125	20.1	7.5	80	10

1/4"

145KM-10H

Reversible, 10mm 6-point
Reversible, 10mm Hexagonal



145KM (mm)	L (mm)	D (mm)	C (mm)	(g)	(pcs.)
10H	125	20.1	7.5	72	10

145KM-10H+150.10H-8 2753N+2400M-8

150-10H

Sockets with 10mm 6-point Drive End
Vasos con Conductor Hexagonal 10mm



150.10H (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
5	12	3.5	11	6	10
6	12	4.5	12.5	7	10
7	12	5	14	7	10
8	12	6	15.5	7	10
9	13	6	16	7	10
10	14.3	7	17	9	10
New **12**	17.4	9	19.5	14	10

1203

Sockets with 10mm 6-point Drive End in Set with Ratchet
Juego de Vasos con Conductor Hex con Llave de Carraca

1203	7 Pieces Set/⚖=250g
METAL CASE:W130×H65×T20mm	
Sockets	Accessory
150.10H 5, 6, 7, 8, 9, 10	**145KM-10H**

R810A

Bit Set
Juego de Puntas

R810A	5 Pieces Set/⚖=208g
METAL CASE:W130×H65×T20mm	
Bits	Accessory
101P Phillips Bits 1, 2, 3	**102NA-1/4x5/16**
101S Slotted Bit 1×7	

R810B

Bit Set
Juego de Puntas

R810B	10 Pieces Set/⚖=268g
METAL CASE:W130×H65×T20mm	
Bits	Accessory
101P Phillips Bits 1, 2, 3	**102NA-1/4x5/16**
101S Slotted Bit 1×7	
128H Hex Bits 3, 4, 5, 6, 8	

R810C

Bit and Socket Set
Juego de Puntas y Vasos

R810C	12 Pieces Set/⚖=227g
METAL CASE:W130×H65×T20mm	
Bits,Sockets	Accessories
101P Phillips Bits 1, 2, 3	**102NA-1/4x5/16**
101S Slotted Bit 1×7	**101A**
2400M Sockets 5, 6, 7, 8, 9, 10	

R810D

Bit and Socket Set
Juego de Puntas y Vasos

R810D	17 Pieces Set/⚖=336g
METAL CASE:W130×H65×T20mm	
Bits,Sockets	Accessories
101P Phillips Bits 1, 2, 3	**102NA-1/4x5/16**
101S Slotted Bit 1×7	**101A**
128H Hex Bits 3, 4, 5, 6, 8	
2400M Sockets 5, 6, 7, 8, 9, 10	

R810E

Socket Set
Juego de Vasos

R810E	9 Pieces Set/⚖=445g
METAL CASE:W130×H65×T20mm	
Sockets	Accessories
2300M Deep Sockets 6, 7, 8, 9, 10, 11, 12	**102NA-1/4x5/16**
	101A

101P

Phillips Bits
Puntas Phillips



101P (PH)	D (mm)	L (mm)	(g)	(pcs.)
1	6.35	20.5	3	10
2	6.35	20.5	4	10
3	6.35	20.5	5	10

101S

Bits for Slotted Head
Puntas Rectas/Planas



101S	D (mm)	L (mm)	(g)	(pcs.)
1.0×7	6.35	15	3	10
1.2×7	6.35	15	3	10

101H

Hex Bits
Puntas Hexagonales



101H (mm)	D (mm)	L (mm)	(g)	(pcs.)
3	6.35	20.5	5	10
4	6.35	20.5	5	10
5	6.35	20.5	5	10
6	6.35	20.5	6	10
7	6.35	20.5	6	10
8	6.35	20.5	7	10

101B

Ball point Hex Bits
Puntas Hexagonales con bola



101B (mm)	D (mm)	L (mm)	(g)	(pcs.)
3	6.35	25	4	10
4	6.35	25	4	10
5	6.35	25	5	10
6	6.35	25	5	10

Ball point bits have less strength due to the special design.
Make sure to use them correctly.

101T (T)

TORX® Bits
Puntas TORX®



101T (T)	D (mm)	L (mm)	(g)	(pcs.)
T 9	6.35	25	4	10
T10	6.35	25	4	10
T15	6.35	25	5	10
T20	6.35	25	5	10
T25	6.35	25	5	10
T27	6.35	25	6	10
T30	6.35	25	6	10

101T (TH)

Tamper-Registant TORX® Bits
Punta TORX®, indeformable



101T (TH)	D (mm)	L (mm)	(g)	(pcs.)
T10H	6.35	25	4	10
T15H	6.35	25	4	10
T20H	6.35	25	5	10
T25H	6.35	25	5	10
T27H	6.35	25	6	10
T30H	6.35	25	6	10

Tamper Resistant TORX® Bits have less strength due to special design.
Make sure to use it correctly.

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

128H

Hex Bits
Puntas Hexagonales

128H (mm)	D (mm)	L (mm)	(g)	(pcs.)
3	8	32	11	10
4	8	32	11	10
5	8	32	12	10
6	8	32	12	10
8	8	32	13	10



128T

TORX® Bits
Puntas TORX®

128T (T)	D (mm)	L (mm)	(g)	(pcs.)
T10	8	32	9	10
T15	8	32	9	10
T20	8	32	9	10
T25	8	32	10	10
T27	8	32	10	10
T30	8	32	11	10



101A

Adaptor
Adaptador

101A	D (mm)	S (mm)	L (mm)	(g)	(pcs.)
	8	6.35	20	8	10



1202

Bit Set
Juego de Puntas

1202 15 Pieces Set/=420g

METAL CASE:W190×H60×T30mm

Bits	Accessory
101P Phillips Bits 1, 2, 3	**138**
101S Slotted Bit 1×7	
101B Ballpoint Hex Bits 3, 4, 5, 6	
101T Torx® Bits T10, T15, T20, T25, T27, T30	

2254M

Bit Set
Juego de Puntas

2254M 12 Pieces Set/=450g

METAL CASE:W160×H100×T28mm

Bits	Accessories
101P Phillips Bits 1, 2, 3	**102NA-1/4×5/16**
101S Slotted Bits 1×7, 1.2×7	**2769F**
101H Hex Bits 3, 4, 5	**101A**
	2137

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

3112N
Attack Driver
Destornillador de Impacto

	☐	L (mm)	(g)	(pce.)
3112N	3/8"	159	730	1
3112G		159	810	1

* Renewal Kits → **3112RK** ➡P301

3112G
Attack Driver
Destornillador de Impacto

	☐	L (mm)	(g)	(pce.)
4112N	1/2"	163	730	1
4112G		163	810	1

* Renewal Kits → **4112RK** ➡P301

4112N
Attack Driver
Destornillador de Impacto

	☐	L (mm)	(g)	(pce.)
6112	3/4"	190	1900	1

* Renewal Kits → **6112RK** ➡P301

Black finished head prevents peeling off the chrome plate by striking the head.

4112G
Attack Driver
Destornillador de Impacto



6112
Attack Driver
Destornillador de Impacto

AN318A
Attack Driver Set
Juego de Destornilladores de Impacto

AN112A

AN318A	6 Pieces Set/=1,070g
METAL CASE:W190×H59×T45mm	
Bits	Accessories
100P.32 Phillips Bits 2, 3	**3112N**
100S.32 Slotted Bits 9, 11	**3138**

AN112A	6 Pieces Set/=1,070g
METAL CASE:W190×H59×T45mm	
Bits	Accessories
100P.32 Phillips Bits 2, 3	**4112N**
100S.32 Slotted Bits 9, 11	**4138**

AG318A
Attack Driver Set
Juego de Destornilladores de Impacto

AG112A

AG318A	6 Pieces Set/=1,150g
METAL CASE:W220×H82×T60mm	
Bits	Accessories
100P.32 Phillips Bits 2, 3	**3112G**
100S.32 Slotted Bits 9, 11	**3138**

AG112A	6 Pieces Set/=1,150g
METAL CASE:W220×H82×T60mm	
Bits	Accessories
100P.32 Phillips Bits 2, 3	**4112G**
100S.32 Slotted Bits 9, 11	**4138**

AN112C
Attack Driver Set
Juego de Destornilladores de Impacto



AN112C	8 Pieces Set/=1,350g
METAL CASE:W220×H82×T60mm	
Bits	Accessories
100P.80 Phillips Bits 1, 2, 3	**4112N**
100S.80 Slotted Bits 7, 9, 12	**4138**

AG112F
Attack Driver Set
Juego de Destornilladores de Impacto

AG112F	25 Pieces Set/=1,530g
METAL CASE:W220×H82×T60mm	
Bits	Accessories
100P.32 Phillips Bits 2, 3	**4112G**
100P.32 PZ Bits PZ2, PZ3	**4138**
100S.32 Slotted Bits 9, 11	
100H.32 Hex Bits 4, 5, 6, 7, 8, 10	
100T.32 TORX® Bits T25, T27, T30, T40, T45, T50	
100X.32 XZN Bits M5, M6, M8, M10, M12	

AG112H
Attack Driver Set
Juego de Destornilladores de Impacto

AG112H	18 Pieces Set/=1,480g
METAL CASE:W220×H82×T60mm	
Bits	Accessories
100P.32 Phillips Bits 2, 3, 4	**4112G**
100S.32 Slotted Bits 8, 9, 10, 12, 14	**4138**
100H.32 Hex Bits 5, 6, 8, 10	
100T.32 TORX® Bits T30, T40, T45, T50	

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

108P-25 • -32 • -50

Phillips Bits
Puntas Phillips



108P.25 (PH)	D (mm)	L (mm)	(g)	(pcs.)
1	6.35	25	5	10
2	6.35	25	5	10
3	6.35	25	6	10

108P.32 (PH)	D (mm)	L (mm)	(g)	(pcs.)
1	6.35	32	7	10
2	6.35	32	7	10
3	6.35	32	8	10

108P.50 (PH)	D (mm)	L (mm)	(g)	(pcs.)
1	6.35	50	10	10
2	6.35	50	11	10
3	6.35	50	11	10

108S-25 • -39

Bits for Slotted head
Puntas Rectas/Planas



108S.25	T×W (mm)	D (mm)	L (mm)	(g)	(pcs.)
3	0.5×3	6.35	25	3	10
4	0.6×4	6.35	25	3	10
4.5	0.6×4.5	6.35	25	4	10
5	0.8×5	6.35	25	5	10
5.5	0.8×5.5	6.35	25	5	10
6	1.0×6	6.35	25	5	10
8	1.2×8	6.35	25	6	10

108S.39	T×W (mm)	D (mm)	L (mm)	(g)	(pcs.)
3	0.5×3	6.35	39	6	10
4	0.6×4	6.35	39	6	10
4.5	0.6×4.5	6.35	39	6	10
5	0.8×5	6.35	39	7	10
5.5	0.8×5.5	6.35	39	8	10
6	1.0×6	6.35	39	9	10
8	1.2×8	6.35	39	12	10

108H-25

Hex Bits
Puntas Hexagonales



108H.25 (mm)	D (mm)	L (mm)	(g)	(pcs.)
3	6.35	25	4	10
4	6.35	25	5	10
5	6.35	25	5	10
6	6.35	25	6	10
7	6.35	25	7	10
8	6.35	25	8	10
10	6.35	25	11	10

108H.25 (inch)	D (mm)	L (mm)	(g)	(pcs.)
1/8	6.35	25	4	10
9/64	6.35	25	5	10
New 5/32	6.35	25	5	10
3/16	6.35	25	5	10
7/32	6.35	25	6	10
1/4	6.35	25	7	10

108T-25 (T)

TORX® Bits
Puntas TORX®



108T.25 (T)	D (mm)	L (mm)	(g)	(pcs.)
New T 8	6.35	25	4	10
T10	6.35	25	4	10
T15	6.35	25	4	10
T20	6.35	25	5	10
T25	6.35	25	6	10
T27	6.35	25	6	10
T30	6.35	25	6	10
T40	6.35	25	6	10

108T-25 (TH)

Tamper-Registant TORX® Bits
Punta TORX®, indeformable



108T.25 (TH)	D (mm)	L (mm)	(g)	(pcs.)
T10H	6.35	25	4	10
T15H	6.35	25	4	10
T20H	6.35	25	5	10
T25H	6.35	25	6	10
T27H	6.35	25	6	10
T30H	6.35	25	6	10
T40H	6.35	25	6	10

Tamper Resistant TORX® Bits have less strength due to special design.
Make sure to use it correctly.

108A

Adaptor
Adaptador



108A.25	D (mm)	L (mm)	(g)	(pcs.)
New 1/4B	6.35	25	10	10

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

2137 Bit Holder Porta-punta

3137 Bit Holder Porta-punta

4137 Bit Holder Porta-punta

		D_1 (mm)	D_2 (mm)	L (mm)	(g)	(pcs.)
2137	1/4"	12	12	22.5	13	10
3137	3/8"	13	16.5	30	30	10
4137	1/2"	13	22	38	53	10





12139 Impact Bit Holder Porta-punta de Impacto

13139 Impact Bit Holder Porta-punta de Impacto

14139 Impact Bit Holder Porta-punta de Impacto

		D_1 (mm)	D_2 (mm)	L (mm)	(g)	(pcs.)	
12139-1/4	1/4"	11	13	26	15	10	*1
13139-1/4	3/8"	11	19	30	32	10	*2
14139-1/4	1/2"	11	25	38	62	10	*3

*1 Pin/O-Ring=1200A/B
*2 C-Ring=1301C,Pin/O-Ring=1301A/B
*3 C-Ring=1401C,Pin/O-Ring=1401A/B
➡P250-251





13142-D6.3 Impact Bit Holder for 1/4" (6.3) Bits
14142-D6.3 Porta-punta de Impacto para Puntas 1/4" (6.3)

		D_1 (mm)	D_2 (mm)	L (mm)	(g)	(pcs.)	
13142-D6.3	3/8"	16	19	45	60	10	*1
14142-D6.3	1/2"	16	25	55	97	10	*2

*1 C-Ring=1301C,Pin/O-Ring=1301A/B
*2 C-Ring=1401C,Pin/O-Ring=1401A/B
➡P250-251

Lock & Quick Release





2749P-1/4HF Reversible Ratchet, for Bits 1/4"
Llave de Carraca Reversible, para Puntas 1/4"

2774P-1/4HF Flexible Ratchet, Reversible, for Bits 1/4"
Llave de Carraca Reversible, para Puntas 1/4"

	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
2749P-1/4HF	25	12	125	96	10
2774P-1/4HF	25	12	165	133	2





100P-32 · -80 · -125

Phillips Bits
Puntas Phillips

100P.32 (PH)	D (mm)	L (mm)	(g)	(pcs.)
1	8	32	11	10
2	8	32	11	10
3	8	32	12	10
4	8	32	12	10

100P.80 (PH)	D (mm)	L (mm)	(g)	(pcs.)
1	8	80	30	10
2	8	80	30	10
3	8	80	31	10
4	8	80	32	10

100P.125 (PH)	D (mm)	L (mm)	(g)	(pcs.)
2	8	125	48	10
3	8	125	49	10

100P-32 (PZ)

PZ Bits
Puntas PZ

100P.32 (PZ)	D (mm)	L (mm)	(g)	(pcs.)
PZ2	8	32	10	10
PZ3	8	32	11	10

100S-32 · -80

Bits for Slotted Head
Puntas Rectas/Planas



100S.32	T×W (mm)	D (mm)	L (mm)	(g)	(pcs.)
6	1 × 6	8	32	10	10
7	1 × 7	8	32	11	10
8	1.2× 8	8	32	12	10
9	1.6× 9	8	32	12	10
10	1.6×10	8	32	13	10
11	1.6×11	8	32	15	10
12	2 ×12	8	32	18	10
14	2 ×14	8	32	21	10

100S.80	T×W (mm)	D (mm)	L (mm)	(g)	(pcs.)
6	1 × 6	8	80	29	10
7	1 × 7	8	80	30	10
8	1.2× 8	8	80	31	10
9	1.6× 9	8	80	32	10
10	1.6×10	8	80	33	10
11	1.6×11	8	80	33	10
12	2 ×12	8	80	34	10
14	2 ×14	8	80	37	10

100H-32

Hex Bits
Puntas Hexagonales

100H.32 (mm)	D (mm)	L (mm)	(g)	(pcs.)
3	8	32	11	10
4	8	32	11	10
5	8	32	12	10
6	8	32	12	10
7	8	32	13	10
8	8	32	13	10
New 9	8	32	16	10
10	8	32	16	10
New 11	8	32	20	10
12	8	32	23	10
14	8	32	29	10

100X-32 (XZN)

XZN Bits
Puntas XZN

100X.32 (XZN)	D (mm)	L (mm)	(g)	(pcs.)
M 5	8	32	10	10
M 6	8	32	11	10
M 8	8	32	12	10
M10	8	32	16	10
M12	8	32	19	10

100T-32 (T)

TORX® Bits
Puntas TORX®

100T.32 (T)	D (mm)	L (mm)	(g)	(pcs.)
T10	8	32	9	10
T15	8	32	9	10
T20	8	32	9	10
T25	8	32	10	10
T27	8	32	10	10
T30	8	32	11	10
T40	8	32	12	10
T45	8	32	12	10
T50	8	32	12	10
T55	8	32	12	10

100T-32 (TH)

Tamper-Registant TORX® Bits
Punta TORX®, indeformable

100T.32 (TH)	D (mm)	L (mm)	(g)	(pcs.)
T10H	8	32	9	10
T15H	8	32	9	10
T20H	8	32	9	10
T25H	8	32	10	10
T27H	8	32	10	10
T30H	8	32	11	10
T40H	8	32	12	10
T45H	8	32	12	10
T50H	8	32	12	10
T55H	8	32	12	10

⚠ Tamper Resistant TORX® Bits have less strength due to special design.
Make sure to use it correctly.

TORX® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX® es una marca registrada de **Acument Intellectual Properties, LLC.**

2138 Bit Holder / Porta-punta

3138 Bit Holder / Porta-punta

		D_1 (mm)	D_2 (mm)	L (mm)	(g)	(pcs.)
2138	1/4"	16	16	26	32	10
3138	3/8"	16	18	38	55	10
4138	1/2"	16	22	38	62	10





4138 Bit Holder / Porta-punta

12140 Impact Bit Holder / Porta-punta de Impacto

13140 Impact Bit Holder / Porta-punta de Impacto

		D_1 (mm)	D_2 (mm)	L (mm)	(g)	(pcs.)	
12140-5/16	1/4"	14	13	26	15	10	*1
13140-5/16	3/8"	14	19	30	32	10	*2
14140-5/16	1/2"	14	25	38	62	10	*3

*1 Pin/O-Ring=1200A/B
*2 C-Ring=1301C,Pin/O-Ring=1301A/B
*3 C-Ring=1401C,Pin/O-Ring=1401A/B
➔P250-251





14140 Impact Bit Holder / Porta-punta de Impacto

2749P-5/16HF Reversible Ratchet, for Bits 5/16" / Llave de Carraca Reversible, para Puntas 5/16"

	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
2749P-5/16HF	25	14	125	96	10
2774P-5/16HF	25	14	165	133	2





2774P-5/16HF Flexible Ratchet, reversible, for Bits 5/16" / Llave de Carraca Reversible, para Puntas 5/16"

131P-80

Phillips Bits
Puntas Phillips



131P.80	⊕	D (mm)	L (mm)	(g)	(pcs.)
1	No.1×No.2	8	80	28	10
2	No.2×No.3	8	80	29	10
3	No.3×No.3	8	80	29	10

131S-80

Bits for Slotted heads
Puntas Rectas/Planas



131S.80	T×W (mm)	D (mm)	L (mm)	(g)	(pcs.)
6	1.0×6	8	80	29	10
7	1.0×7	8	80	29	10
8	1.2×8	8	80	30	10
9	1.6×9	8	80	31	10

131PS-80

Double Ended Bits
Puntas



131PS.80	⊕×⊖	D (mm)	L (mm)	(g)	(pcs.)
2	No.2×No.6	8	80	29	10
3	No.3×No.8	8	80	29	10

131T-80

TORX® Bits
Puntas TORX®



131T.80 (T)	D (mm)	L (mm)	(g)	(pcs.)
T10×T15	8	80	27	10
T20×T25	8	80	27	10
T27×T30	8	80	28	10

3141

Bit Holder, Extra Deep for 131P-80, 131S-80, 131T-80
Porta-punta, extra-largo para 131P-80, 131S-80, 131T-80



4141

Bit Holder, Extra Deep for 131P-80, 131S-80, 131T-80
Porta-punta, extra-largo para 131P-80, 131S-80, 131T-80



	◻	D1 (mm)	D2 (mm)	L (mm)	(g)	(pcs.)
3141	3/8"	16	18	48	60	10
4141	1/2"	16	22	52	70	10

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

123PT-75 · -100

Double Ended Torsion Bits
Puntas Phillips, simétricas, Torsion

123PT (PH)	D (mm)	L (mm)	(g)	(pcs.)
2	6.35	75	18	10
2	6.35	100	24	10





123PN-75 · -100
123PG-75 · -100

Double Ended Bits
Puntas Phillips, simétricas

Magnetic type

123PN.75 123PG.75 (PH)	D (mm)	L (mm)	(g)	(pcs.)
1	6.35	75	16	10
2	6.35	75	16	10
3	6.35	75	17	10

123PN.100 123PG.100 (PH)	D (mm)	L (mm)	(g)	(pcs.)
1	6.35	100	23	10
2	6.35	100	23	10
3	6.35	100	24	10



165LM

Slide Socket with Magnet

165LM.45 (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
8	13.5	3.5	45	55	10
10	16	4.2	45	58	10
12	18.5	5.6	45	65	10
New **13**	20	6	45	68	10
14	21	6.4	45	70	10

Slide the socket by pulling holder, and pull back the socket to lock on the bit groove.
Ring magnet holds a bolt or nut for easy work.



Nut Setter



Phillips Bit



121P-50 · -70 · -100 · -150

Phillips Bits
Puntas Phillips



121P.50 (PH)	D (mm)	R (mm)	L (mm)	(g)	(pcs.)
1	6.35	4.5	50	12	10
2	6.35	5.5	50	12	10
3	6.35	–	50	13	10

121P.70 (PH)	D (mm)	R (mm)	L (mm)	(g)	(pcs.)
1	6.35	4.5	70	15	10
2	6.35	5.5	70	15	10
3	6.35	–	70	16	10

121P.100 (PH)	D (mm)	R (mm)	L (mm)	(g)	(pcs.)
1	6.35	4.5	100	23	10
2	6.35	5.5	100	23	10
3	6.35	–	100	24	10

121P.150 (PH)	D (mm)	R (mm)	L (mm)	(g)	(pcs.)
1	6.35	4.5	150	30	10
2	6.35	5.5	150	35	10
3	6.35	–	150	36	10

121H-50 · -70 · -100 · -150

Hex Bits
Puntas Hexagonales



121H.50 (mm)	D (mm)	R (mm)	L (mm)	(g)	(pcs.)
New 2	6.35	4.0	50	11	10
2.5	6.35	3.0	50	12	10
3	6.35	3.5	50	12	10
4	6.35	4.5	50	12	10
5	6.35	5.6	50	13	10
6	6.35	–	50	14	10

121H.70 (mm)	D (mm)	R (mm)	L (mm)	(g)	(pcs.)
New 2	6.35	4.0	70	13	10
2.5	6.35	4.0	70	15	10
3	6.35	4.0	70	15	10
4	6.35	4.5	70	15	10
5	6.35	5.6	70	16	10
6	6.35	–	70	18	10

121H.100 (mm)	D (mm)	R (mm)	L (mm)	(g)	(pcs.)
New 2	6.35	4.0	100	22	10
2.5	6.35	4.0	100	23	10
3	6.35	4.0	100	23	10
4	6.35	4.5	100	23	10
5	6.35	5.6	100	24	10
6	6.35	–	100	26	10

121H.150 (mm)	D (mm)	R (mm)	L (mm)	(g)	(pcs.)
New 2	6.35	4.0	100	35	10
New 2.5	6.35	4.0	100	35	10
3	6.35	4.5	150	37	10
4	6.35	5.0	150	37	10
5	6.35	6.0	150	38	10
6	6.35	–	150	39	10

121T-50 · -70 · -100 · -150 (T)

TORX® Bits
Puntas TORX®



121T.50 (T)	D (mm)	R (mm)	L (mm)	(g)	(pcs.)
T10	6.35	3.0	50	12	10
T15	6.35	3.5	50	12	10
T20	6.35	4.1	50	12	10
T25	6.35	4.6	50	12	10
T27	6.35	5.2	50	13	10
T30	6.35	5.7	50	13	10
T40	6.35	–	50	14	10

121T.70 (T)	D (mm)	R (mm)	L (mm)	(g)	(pcs.)
T10	6.35	3.5	70	16	10
T15	6.35	3.5	70	16	10
T20	6.35	4.1	70	16	10
T25	6.35	4.6	70	16	10
T27	6.35	5.2	70	17	10
T30	6.35	5.7	70	17	10
T40	6.35	–	70	18	10

121T.100 (T)	D (mm)	R (mm)	L (mm)	(g)	(pcs.)
T10	6.35	3.5	100	24	10
T15	6.35	4.0	100	24	10
T20	6.35	4.1	100	24	10
T25	6.35	4.6	100	24	10
T27	6.35	5.2	100	24	10
T30	6.35	5.7	100	25	10
T40	6.35	–	100	26	10

121T.150 (T)	D (mm)	R (mm)	L (mm)	(g)	(pcs.)
New T10	6.35	3.0	150	35	10
T15	6.35	4.0	150	37	10
T20	6.35	4.5	150	37	10
T25	6.35	5.0	150	37	10
T27	6.35	5.6	150	37	10
T30	6.35	6.0	150	38	10
T40	6.35	–	150	39	10

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

121T-70 · -100 (TH)

Tamper-Registant TORX® Bits
Punta TORX®, indeformable



121T.70 (TH)	D (mm)	R (mm)	L (mm)	(g)	(pcs.)
New T15H	6.35	3.5	70	15	10
T20H	6.35	4.1	70	16	10
T25H	6.35	4.6	70	16	10
T27H	6.35	5.2	70	17	10
T30H	6.35	5.7	70	17	10
T40H	6.35	–	70	18	10

121T.100 (TH)	D (mm)	R (mm)	L (mm)	(g)	(pcs.)
New T15H	6.35	3.5	100	22	10
T20H	6.35	4.1	100	24	10
T25H	6.35	4.6	100	24	10
T27H	6.35	5.2	100	24	10
T30H	6.35	5.7	100	25	10
T40H	6.35	–	100	26	10

Tamper Resistant TORX® Bits have less strength due to special design.
Make sure to use it correctly.

121T-50 · -70 (IP)

TORXPLUS® Bits
Putas TORXPLUS®

TORXplus®



121T.50 (IP)	D (mm)	R (mm)	L (mm)	(g)	(pcs.)
20IP	6.35	4.1	50	12	10
25IP	6.35	4.6	50	12	10
27IP	6.35	5.2	50	13	10
30IP	6.35	5.7	50	13	10
40IP	6.35	–	50	14	10

121T.70 (IP)	D (mm)	R (mm)	L (mm)	(g)	(pcs.)
20IP	6.35	4.1	70	16	10
25IP	6.35	4.6	70	16	10
27IP	6.35	5.2	70	17	10
30IP	6.35	5.7	70	17	10
40IP	6.35	–	70	18	10

13137H

Impact Bit Holder for 1/4"(6.3) Bits
Porta-punta de impacto para Puntas 1/4"(6.3)



		D1 (mm)	D2 (mm)	L (mm)	(g)	(pcs.)	
12137E	1/4"	12	13	36	22	10	*1
13137H	3/8"	13	19	42	77	10	*2
13137E		12	19	40	40	10	*2
14137E	1/2"	12	25	48	70	10	*3

*1 Pin/O-Ring=1200A/B
*2 C-Ring=1301C, Pin/O-Ring=1301A/B ➡P250-251
*3 C-Ring=1401C, Pin/O-Ring=1401A/B

12137E
13137E
14137E

Impact Bit Holder for 1/4"(6.3) Bits
Porta-punta de impacto para Puntas 1/4"(6.3)



		D1 (mm)	D2 (mm)	L (mm)	(g)	(pcs.)	
12142-F6.3	1/4"	16.5	13	36	22	10	*1
13142-F6.3	3/8"	16.5	19	45	60	10	*2
14142-F6.3	1/2"	16.5	25	55	100	10	*3

*1 Pin/O-Ring=1200A/B
*2 C-Ring=1301C, Pin/O-Ring=1301A/B ➡P250-251
*3 C-Ring=1401C, Pin/O-Ring=1401A/B

Lock & Quick Release





12142-F6.3
13142-F6.3
14142-F6.3

Impact Bit Holder for 1/4"(6.3) Bits
Porta-punta de impacto para Puntas 1/4"(6.3)



TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.
TORXplus® is a registered trademark of Acument Intellectual Properties, LLC.
TORXplus® es una marca registrada de Acument Intellectual Properties, LLC.

183H-35 · -75 · -150

Hex Bits
Puntas Hexagonales



	183H.35 (inch)	L (mm)	(g)	(pcs.)
New	3/16	35	15	10
New	7/32	35	16	10
New	1/4	35	18	10
New	5/16	35	20	10
New	3/8	35	26	10
New	7/16	35	28	10
New	1/2	35	38	10

183H.35 (mm)	L (mm)	(g)	(pcs.)
3	35	15	10
4	35	15	10
5	35	15	10
6	35	18	10
New 7	35	19	10
8	35	20	10
10	35	26	10
New 11	35	28	10
12	35	30	10
14	35	35	10
New 16	35	47	10
New 17	35	50	10
New 18	35	53	10
New 19	35	56	10

183H.75 (mm)	L (mm)	R (mm)	(g)	(pcs.)
3	75	6.0	34	10
4	75	6.0	35	10
5	75	6.5	36	10
6	75	7.5	39	10
New 7	75	8.5	44	10
8	75	9.5	47	10
10	75	–	57	10
New 11	75	–	60	10
12	75	–	65	10
14	75	–	79	10

	183H.150 (mm)	L (mm)	R (mm)	(g)	(pcs.)
New	4	150	6.0	51	10
New	5	150	6.5	55	10
New	6	150	7.5	65	10
New	8	150	9.5	87	10
New	10	150	–	118	10
New	12	150	–	136	10

183T-35 · -75 · -150 (T)

TORX® Bits
Puntas TORX®



	183T.35 (T)	L (mm)	(g)	(pcs.)
New	T25	35	18	10
	T30	35	18	10
	T40	35	20	10
	T45	35	22	10
	T50	35	26	10
	T55	35	30	10
	T60	35	38	10

183T.75 (T)	L (mm)	R (mm)	(g)	(pcs.)
T30	75	6.0	35	10
T40	75	6.9	37	10
T45	75	8.0	41	10
T50	75	9.0	45	10
T55	75	11.4	55	10
T60	75	13.5	67	10

	183T.150 (T)	L (mm)	R (mm)	(g)	(pcs.)
New	T30	150	6.0	50	10
New	T40	150	6.9	58	10
New	T45	150	8.0	70	10
New	T50	150	9.0	82	10
New	T55	150	11.4	113	10

183T-35 · -75 (IP)

TORXPLUS® Bits
Puntas TORXPLUS®

TORXplus®



	183T.35 (IP)	L (mm)	(g)	(pcs.)
New	30IP	35	18	10
New	40IP	35	20	10
New	45IP	35	22	10
New	50IP	35	26	10
New	55IP	35	30	10
New	60IP	35	38	10

	183T.75 (IP)	L (mm)	R (mm)	(g)	(pcs.)
New	30IP	75	6.0	35	10
New	40IP	75	6.8	37	10
New	45IP	75	8.0	41	10
New	50IP	75	9.0	45	10
New	55IP	75	11.4	56	10
New	60IP	75	13.5	67	10

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.
TORXplus® is a registered trademark of Acument Intellectual Properties, LLC.
TORXplus® es una marca registrada de Acument Intellectual Properties, LLC.

183X-35 · -75 · -150 (XZN)

XZN Bits
Puntas XZN

	183X.35 (XZN)	L (mm)	(g)	(pcs.)
New	M 4	35	18	10
	M 5	35	18	10
	M 6	35	20	10
	M 8	35	22	10
	M10	35	26	10
	M12	35	30	10
	M14	35	38	10



	183X.75 (XZN)	L (mm)	R (mm)	(g)	(pcs.)
New	M 4	75	6.0	34	10
	M 5	75	6.0	34	10
	M 6	75	6.2	36	10
	M 8	75	7.4	39	10
	M10	75	9.8	54	10
	M12	75	11.7	57	10
	M14	75	13.5	67	10

	183X.150 (XZN)	L (mm)	R (mm)	(g)	(pcs.)
New	M 5	150	6.0	50	10
New	M 6	150	6.2	53	10
New	M 8	150	7.4	64	10
New	M10	150	9.8	93	10
New	M12	150	11.7	121	10

13134 ○
14134 ○
16134 ○

Impact Bit Holder
Porta-punta de Impacto

	◻	D (mm)	L (mm)	(g)	(pcs.)	
13134	3/8"	22	32	70	10	*1
14134	1/2"	25	38	90	10	*2
16134	3/4"	44	52	200	2	*3

*1 C-Ring=1302C,Pin/O-Ring=1302A/B
*2 C-Ring=1401C,Pin/O-Ring=1401A/B ➡P250-251
*3 C-Ring=1600C,Pin/O-Ring=1601A/B



Replacement Screw : M8×5, ⬢ 4mm

For DIN3126 E11.2 Bits



F11.2

13142-F11.2 ○
14142-F11.2 ○

Impact Bit Holder (Quick Release)
Porta-punta de Impacto (Extracción Rápida)

	◻	D₁ (mm)	D₂ (mm)	L (mm)	(g)	(pcs.)	
13142-F11.2	3/8"	18.9	22	46	116	10	*1
14142-F11.2	1/2"	18.9	25	46	207	10	*2

*1 C-Ring=1302C,Pin/O-Ring=1302A/B
*2 C-Ring=1401C,Pin/O-Ring=1401A/B ➡P250-251



For DIN3126 E11.2 Bits



F11.2



113-50 ○ Nut Setters / Vasos para apretar tuercas Hexagonales



113.50 (mm)	D (mm)	ℓ (mm)	L (mm)	⚖ (g)	(pcs.)
5.5	9	4	50	15	10
6	10	5	50	17	10
7	11	5	50	19	10
8	12	6	50	20	10
10	14.2	7	50	31	10
12	17	8	50	39	10
13	18	8	50	42	10
14	19	9	50	46	10

113.50 (inch)	D (mm)	ℓ (mm)	L (mm)	⚖ (g)	(pcs.)
1/4	10	5	50	17	10
5/16	12	6	50	20	10
3/8	14.2	7	50	31	10
1/2	18	8	50	42	10

113-75 · -100 · -150 · -200 · -250 ○ Nut Setters / Vasos para apretar tuercas Hexagonales



113.75 (mm)	D (mm)	ℓ (mm)	L (mm)	⚖ (g)	(pcs.)
7	11.5	5	75	31	10
8	12.7	6	75	32	10
10	14.5	7	75	35	10
12	17	8	75	42	10
13	18	8	75	41	10
14	19	9	75	43	10

113.150 (mm)	D (mm)	ℓ (mm)	L (mm)	⚖ (g)	(pcs.)
7	11.5	5	150	59	10
8	12.7	6	150	60	10
10	14.5	7	150	64	10
12	17	8	150	70	10
13	18	8	150	76	10
14	19	9	150	78	10

113.250 (mm)	D (mm)	ℓ (mm)	L (mm)	⚖ (g)	(pcs.)
7	11.5	5	250	99	10
8	12.7	6	250	100	10
10	14.5	7	250	105	10
12	17	8	250	113	10
13	18	8	250	114	10
14	19	9	250	119	10

113.100 (mm)	D (mm)	ℓ (mm)	L (mm)	⚖ (g)	(pcs.)
7	11.5	5	100	40	10
8	12.7	6	100	41	10
10	14.5	7	100	45	10
12	17	8	100	52	10
13	18	8	100	51	10
14	19	9	100	53	10

113.200 (mm)	D (mm)	ℓ (mm)	L (mm)	⚖ (g)	(pcs.)
7	11.5	5	200	78	10
8	12.7	6	200	79	10
10	14.5	7	200	83	10
12	17	8	200	91	10
13	18	8	200	93	10
14	19	9	200	95	10

113-50 (E) ⬡ Nut Setters, TORX® / Vasos para apretar tuercas, TORX®



113.50 (E)	D (mm)	ℓ (mm)	L (mm)	⚖ (g)	(pcs.)
E 4	6.1	4.5	50	12	10
E 5	7.5	4.5	50	15	10
E 6	8.3	5.0	50	17	10
E 7	8.8	5.8	50	18	10
E 8	10.1	6.6	50	19	10
E10	12	7.4	50	20	10

113-50 (2B) ○ Nut Setters Nut Grip® / Vasos para apretar tuercas con 2 bolas



113.50 (mm)	D (mm)	ℓ (mm)	L (mm)	⚖ (g)	(pcs.)
7(2B)	11	5	50	20	10
8(2B)	12	6	50	21	10
10(2B)	14.2	7	50	26	10
13(2B)	18	8	50	31	10

113.50 (inch)	D (mm)	ℓ (mm)	L (mm)	⚖ (g)	(pcs.)
3/8(2B)	14.2	7	50	26	10

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

115-50 Nut Setters with Magnet
Vasos para tuercas con Imán



115.50 (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
5.5	9	2.1	50	15	10
6	10	2.4	50	17	10
7	11	2.8	50	19	10
8	12	3.5	50	20	10
10	14.2	4.2	50	29	10
12	17	5.6	50	40	10
13	18	6	50	50	10
14	19	6.4	50	60	10

115.50 (inch)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
1/4	10	2.4	50	17	10
5/16	12	3.5	50	20	10
3/8	14.2	4.2	50	29	10
1/2	18	6	50	50	10

115-75 · -100 · -150 · -200 · -250 Nut Setters with Magnet
Vasos para tuercas con Imán



115.75 (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
7	11.5	2.8	75	32	10
8	12.7	3.5	75	33	10
10	14.5	4.2	75	38	10
12	17	5.6	75	46	10
13	18	6	75	49	10
14	19	6.4	75	52	10

115.100 (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
7	11.5	2.8	100	41	10
8	12.7	3.5	100	42	10
10	14.5	4.2	100	50	10
12	17	5.6	100	58	10
13	18	6	100	62	10
14	19	6.4	100	65	10

115.150 (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
7	11.5	2.8	150	60	10
8	12.7	3.5	150	61	10
10	14.5	4.2	150	68	10
12	17	5.6	150	77	10
13	18	6	150	82	10
14	19	6.4	150	85	10

115.200 (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
7	11.5	2.8	200	79	10
8	12.7	3.5	200	80	10
10	14.5	4.2	200	88	10
12	17	5.6	200	97	10
13	18	6	200	102	10
14	19	6.4	200	105	10

115.250 (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
7	11.5	2.8	250	101	10
8	12.7	3.5	250	103	10
10	14.5	4.2	250	110	10
12	17	5.6	250	118	10
13	18	6	250	122	10
14	19	6.4	250	124	10

113UN-100 • -150 • -200

6-point Universal Joint Nut Setters
Vasos para apretar tuercas Hexagonales con Articulación Universal

113UN.100 (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
8	13	7	100	50	10
10	15	8	100	53	10
12	17	10	100	56	10
13	18	10	100	65	10
14	19.2	10	100	67	10



113UN.150 (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
8	13	7	150	65	10
10	15	8	150	70	10
12	17	10	150	77	10
13	18	10	150	92	10
14	19.2	10	150	92	10

113UN.200 (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
8	13	7	200	75	10
10	15	8	200	87	10
12	17	10	200	98	10
13	18	10	200	116	10
14	19.2	10	200	116	10

115G-75 • -100 • -150 • -200 • -250

Nut Setters with sliding Magnet
Vasos para tuercas con Imán Corredizo



115G.75 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
7	11.5	3.5	26	75	34	10
8	12.7	4	26	75	41	10
10	14.5	4.5	26	75	48	10
12	17	6	26	75	65	10
13	18	6.5	25	75	70	10
14	19	7	24	75	73	10

115G.100 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
7	11.5	3.5	26	100	51	10
8	12.7	4	26	100	51	10
10	14.5	4.5	26	100	57	10
12	17	6	26	100	77	10
13	18	6.5	25	100	80	10
14	19	7	24	100	82	10

115G.150 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
7	11.5	3.5	26	150	67	10
8	12.7	4	26	150	70	10
10	14.5	4.5	26	150	77	10
12	17	6	26	150	95	10
13	18	6.5	25	150	100	10
14	19	7	24	150	105	10

115G.200 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
7	11.5	3.5	26	200	86	10
8	12.7	4	26	200	89	10
10	14.5	4.5	26	200	96	10
12	17	6	26	200	119	10
13	18	6.5	25	200	125	10
14	19	7	24	200	128	10

115G.250 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
New **8**	12.7	4	26	250	110	10
New **10**	14.5	4.5	26	250	120	10
New **12**	17	6	26	250	130	10



Sliding magnet system provides bolt clearance and magnetic function at the same time. The item 115G is mainly designed for assembly line work.

El sistema de imán corredizo proporciona espacio para el perno y al mismo tiempo acción magnética. El artículo 115G está diseñado específicamente para líneas de montaje.

110-35B · -50B · -100B · -150B
-35P · -50P · -100P · -150P

Adaptors
Adaptadores



110	⍁	TYPE	L (mm)	(g)	(pcs.)
35B	1/4"	Ball	35	9	10
35P		Pin	35	9	10
50B		Ball	50	15	10
50P		Pin	50	15	10
100B		Ball	100	34	10
100P		Pin	100	34	10
150B		Ball	150	54	10
150P		Pin	150	54	10

⬢ DIN 3126 Form E 6.3

112-50B · -100B · -150B
-50P · -100P · -150P

Adaptors
Adaptadores



112	⍁	TYPE	L (mm)	(g)	(pcs.)
50B	3/8"	Ball	50	21	10
50P		Pin	50	21	10
100B		Ball	100	71	10
100P		Pin	100	71	10
150B		Ball	150	121	10
150P		Pin	150	121	10

⬢ DIN 3126 Form E 6.3



135E-60B · -60P

Adaptors
Adaptadores

135E	⍁	TYPE	L (mm)	(g)	(pcs.)
60B	1/2"	Ball	60	46	10
60P		Pin	60	46	10

⬢ DIN 3126 Form E 6.3

117-50B · -100B
-50P · -100P

Adaptors
Adaptadores

117	⍁	TYPE	L (mm)	(g)	(pcs.)
50B	1/4"	Ball	50	15	10
50P		Pin	50	15	10
100B		Ball	100	71	10
100P		Pin	100	71	10

◗ DIN 3126 Form G7

120-50B · -50P

Adaptors
Adaptadores

120	⍁	TYPE	L (mm)	(g)	(pcs.)
50B	3/8"	Ball	50	27	10
50P		Pin	50	27	10

⬢ DIN 3126 Form E8

186-75P

Adaptors with Pin
Adaptadores con Perno



186-75P	⍁	L (mm)	(g)	(pcs.)
3/8	3/8"	75	65	10
1/2	1/2"	75	85	10

⬢ DIN 3126 Form E11.2



BD022-120P

Hammer Drill Adaptor
Adaptador para Taladro de Percusión



BD022-120P	⍁	L (mm)	(g)	(pcs.)
3/8	3/8"	120	100	10
1/2	1/2"	120	160	10



DIN 3126
Form C6.3



DIN 3126
Form C8



DIN 3126
Form E6.3



DIN 3126
Form G7



DIN 3126
Form E8



DIN 3126
Form E11.2

Screwdrivers

167M · 167A

Socket Drivers
Destornilladores de Vaso



167M (mm)	D (mm)	ℓ (mm)	H1 (mm)	H2 (mm)	L (mm)	(g)	(pcs.)
3	5.8	3	25	125	225	62	6
3.5	5.8	3	25	125	225	62	6
4	6.7	3.5	25	125	225	64	6
4.5	7.2	4.5	25	125	225	65	6
5	7.8	5	25	125	225	66	6
5.5	8.4	5.5	25	125	225	68	6
6	9.1	6	25	125	225	70	6
7	10.9	6.5	25	125	235	101	6
8	12	7	25	125	235	103	6
9	13.2	7.5	25	125	235	107	6
10	14.5	8	25	125	235	111	6
11	15.9	8.5	25	125	245	155	6
12	16.8	9	25	125	245	161	6
13	18.2	9.5	25	125	245	167	6
14	19.2	11	25	125	245	178	6

167A (inch)	D (mm)	ℓ (mm)	H1 (mm)	H2 (mm)	L (mm)	(g)	(pcs.)
1/4	9.1	6	25	125	225	70	6

167C (2B)

Interchangeable Socket Driver, **Nut Grip®**



167C(2B) (mm)	D (mm)	ℓ (mm)	H1 (mm)	H2 (mm)	L (mm)	(g)	(pcs.)
7(2B)	11.5	4	38	122	235	120	6
8(2B)	12.3	5	38	122	235	125	6
10(2B)	14.2	6	38	122	235	130	6
12(2B)	17.3	7	38	122	235	135	6

167C/3-2B	4 Pieces Set/=280g
PLASTIC BAG	
Socket Drivers	
Socket:	7, 8, 10
Grip:	167C-GRIP

168H-B Ball point Hex Screwdrivers

168H (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
3B	80	150	25	6
4B	125	225	60	6
5B	125	235	85	6
6B	125	245	150	6
7B	125	245	151	6
8B	125	245	153	6



Ball point Hex Screwdrivers have less strength due to the special design. Make sure to use them correctly.

168T (TH) Tamper-Resistant TORX® Screwdrivers

168T (TH)	ℓ (mm)	L (mm)	(g)	(pcs.)
T10H	80	150	25	6
T15H	80	150	25	6
T20H	125	225	60	6
T25H	125	225	60	6
T27H	125	235	90	6
T30H	125	235	92	6
T40H	125	245	153	6



Tamper Resistant TORX® Screwdrivers have less strength due to the special design. Make sure to use it correctly.

168T/7 (TH) Set / Juego

168T/7-TH	(g)
168T-T10H, T15H, T20H, T25H, T27H, T30H, T40H	480

168R Square Screwdrivers

168R	ℓ (mm)	L (mm)	(g)	(pcs.)
1	125	225	60	6
2	125	235	85	6



168P (PZ) PZ Screwdrivers



168P (PZ)	ℓ (mm)	L (mm)	(g)	(pcs.)
PZ1	75	175	78	6
PZ2	100	210	129	6
PZ3	150	270	203	6



TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

166P ⊕ 166S ⊖

Screwdrivers (Blade-Through type)
Destornilladores







166P (PH)	ℓ (mm)	L (mm)	⚖ (g)	◈ (pcs.)
1	75	175	78	6
2	100	210	129	6
3	150	270	203	6

166S	ℓ (mm)	L (mm)	⚖ (g)	◈ (pcs.)
5	75	175	78	6
6	100	210	129	6
8	150	270	203	6

166PS/6 ⊕⊖

Set
Juego

166PS/6	6 Pieces Set/⚖=885g
CARDBOARD BOX:W280×H115×T40mm	
Screwdrivers	
⊕ **166P** Screwdrivers 1, 2, 3	
⊖ **166S** Screwdrivers 5, 6, 8	

PK166PS/6 ⊕⊖

Set
Juego

PK166PS/6	6 Pieces Set/⚖=950g
PLASTIC TRAY	
Screwdrivers	
⊕ **166P** Screwdrivers 1, 2, 3	
⊖ **166S** Screwdrivers 5, 6, 8	

168P ⊕ Screwdrivers / Destornilladores
168S ⊖





168P (PH)	ℓ (mm)	L (mm)	⚖ (g)	◇ (pcs.)
1	75	175	59	6
2	100	210	86	6
2(150)	150	260	100	6
2(200)	200	310	111	6
New **2(300)**	300	410	133	6
3	150	270	150	6

168S	ℓ (mm)	L (mm)	⚖ (g)	◇ (pcs.)
5	75	175	59	6
6	100	210	86	6
6(150)	150	260	100	6
6(200)	200	310	111	6
New **6(300)**	300	410	133	6
8	150	270	150	6

168PS/6 6 Pieces Set/⚖=660g

CARDBOARD BOX:W280×H115×T40mm

Screwdrivers

⊕ **168P** Screwdrivers 1, 2, 3

⊖ **168S** Screwdrivers 5, 6, 8

168PS/6 ⊕⊖ Set / Juego

PK168PS/6 6 Pieces Set/⚖=720g

PLASTIC TRAY

Screwdrivers

⊕ **168P** Screwdrivers 1, 2, 3

⊖ **168S** Screwdrivers 5, 6, 8

PK168PS/6 ⊕⊖ Set / Juego



168CS ⊕⊖ Interchangeable Screwdrivers, Stubby

168CS	ℓ (mm)	L (mm)	⚖ (g)	◇ (pcs.)
2×6	22	86	46	6



168C ⊕⊖ Interchangeable Screwdrivers

168C	ℓ (mm)	L (mm)	⚖ (g)	◇ (pcs.)
2×6	100	210	108	6
2×6(150)	150	260	120	6
2×6(200)	200	310	133	6

2769N-150 • -220

Spin Type Handle
Mango Tipo Destornillador

2769N	☐	ℓ (mm)	L (mm)	(g)	(pcs.)
150	1/4"	50	150	68	2
220		120	220	100	2

Plastic or rubber handles are not intended to act as insulation.
Los mangos de plástico o de goma no están previstos para aislamiento.

2769NWF-150 • -220

Spin Type Handle (Wobble-Fix)
Mango Tipo Destornillador (Articulado-Fijo)

2769NWF	☐	ℓ (mm)	L (mm)	(g)	(pcs.)
150	1/4"	50	150	68	2
220		120	220	100	2

Wobble-Fix Extension Bar
Two way usage : One for as a flexible extension bar to provide at 15° angle operation, the other for use as a normal extension bar. This usage is Patent.

Alargadera Articulada-Fija
Dos formas de utilización : Una como alargadera flexible para poder trabajar con un ángulo de 15° y otra para utilizarse como alargadera normal. Esta aplicación está patentada.



3769N-160 • -230

Spin Type Handle
Mango Tipo Destornillador

3769N	☐	ℓ (mm)	L (mm)	(g)	(pcs.)
160	3/8"	50	160	96	2
230		120	230	126	2

3769NWF-160 • -230

Spin Type Handle (Wobble-Fix)
Mangos Tipo Destornillador (Articulado-Fijo)

3769NWF	☐	ℓ (mm)	L (mm)	(g)	(pcs.)
160	3/8"	50	160	96	2
230		120	230	126	2

Impact Sockets

1/4”

3/8”

1/2”

5/8”

3/4”

1”

1-1/2”

2-1/2”

3-1/2”

12400M · 12400A

6-point Sockets
Vasos Hexagonales



FLAT DRIVE®

Flat drive is designed to guarantee a flat surface contact between the socket and the bolt/nut. The Flat contact reduces wear and allows to transmit a higher torque value. The Flat Drive System is also used for the square drive end as well as the hexagonal or bi-hexagonal openings of the socket.

El diseño de contacto plano garantiza una superficie de contacto plana entre el vaso y el perno/tuerca. El contacto plano reduce el desgaste y permite transmitir más par. El Sistema de Contacto Plano se utiliza tanto para el extremo del cuadrado conductor como para la boca del vaso Hex o Bihex.

12400M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
4	7.5	13	4	23	14	10	*1
4.5	8.1	13	4	23	14	10	*1
5	8.8	13	4	23	14	10	*1
5.5	9.4	13	4	23	14	10	*1
6	10	13	5	23	14	10	*1
7	11.3	13	5	23	14	10	*1
8	12.5	13	6	23	14	10	*1
9	13.8	13	7	23	14	10	*1
10	15	13	7	23	15	10	*1
11	16.3	13	8	23	18	10	*1
12	17.5	13	8	23	19	10	*1
13	18.8	13	8	23	19	10	*1
14	20	13	9	23	20	10	*1

12400A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
5/32	7.5	13	4	23	14	10	*1
3/16	8.1	13	4	23	14	10	*1
New **7/32**	9.4	13	4	23	16	10	*1
1/4	10	13	5	23	14	10	*1
9/32	11.3	13	5	23	14	10	*1
5/16	12.5	13	6	23	14	10	*1
11/32	13.8	13	7	23	14	10	*1
3/8	15	13	7	23	15	10	*1
7/16	16.3	13	8	23	18	10	*1
1/2	18.8	13	8	23	19	10	*1
9/16	20	13	9	23	20	10	*1

*1 Pin/O-Ring=1200A/B ➡P251

12400MG · 12400AG

6-point Sockets with Magnet
Vasos Hexagonales con Imán



12400MG (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
4	7.5	13	2.1	23	12	10	*1
4.5	8.1	13	2.1	23	13	10	*1
5	8.8	13	2.1	23	15	10	*1
5.5	9.4	13	2.1	23	15	10	*1
6	10	13	2.4	23	16	10	*1
7	11.3	13	2.8	23	16	10	*1
8	12.5	13	3.5	23	17	10	*1
9	13.8	13	3.8	23	18	10	*1
10	15	13	4.2	23	18	10	*1
11	16.3	13	4.9	23	21	10	*1
12	17.5	13	5.6	25	21	10	*1
13	18.8	13	6	25	21	10	*1
14	20	13	6.4	25	20	10	*1

12400AG (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
3/16	8.1	13	2.1	23	13	10	*1
1/4	10	13	2.4	23	16	10	*1
5/16	12.5	13	3.5	23	17	10	*1
11/32	13.8	13	3.8	23	18	10	*1
3/8	15	13	4.2	23	18	10	*1
7/16	16.3	13	4.9	23	21	10	*1
1/2	18.8	13	6	25	21	10	*1
9/16	20	13	6.4	25	20	10	*1

*1 Pin/O-Ring=1200A/B ➡P251

12410M

Surface Drive Sockets
Vasos Surface Drive (de Contacto Curvo)



SURFACE DRIVE

Surface drive sockets are designed to retain contact with flat sides of nut to transmit high torque and reduce nut wear. These sockets are ideal for use on polished nuts, aluminum nuts and nuts with worn out points.

Los vasos de contacto curvo se diseñan para mantener el contacto con las caras planas de la tuerca y transmitir un alto par reduciendo el desgaste de la tuerca. Estos vasos son ideales para utilizarse en tuercas pulidas, tuercas de aluminio y tuercas con puntas gastadas

12410M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
6	10	13	5	23	14	10	*1
7	11.3	13	5	23	15	10	*1
8	12.5	13	6	23	15	10	*1
9	13.8	13	7	23	14	10	*1
10	15	13	7	23	14	10	*1
11	16.3	13	8	23	17	10	*1
12	17.5	13	8	23	19	10	*1
13	18.8	13	8	23	19	10	*1

*1 Pin/O-Ring=1200A/B ➡P251

12465M

Pathfinder Sockets
Vasos Pathfinder (Guía)



12465M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
10	15	13	8	23	17	10	*1
11	16.3	13	8	23	18	10	*1
12	17.5	13	9	23	18	10	*1
13	18.8	13	9	23	20	10	*1

*1 Pin/O-Ring=1200A/B ➡P251

12425

TORX® Sockets
Vasos TORX®



12425 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
E 4	6.6	13	4.6	23	14	10	*1
E 5	7.7	13	5.2	23	15	10	*1
E 6	8.7	13	5.4	23	15	10	*1
E 7	9.2	13	6.6	23	15	10	*1
E 8	9.7	13	7	23	15	10	*1
E10	12.2	13	8.2	23	15	10	*1

*1 Pin/O-Ring=1200A/B ➡P251

TORX® (E)



E		E4	E5	E6	E7	E8	E10	E11	E12	E14	E16	E18	E20	E22	E24	E26	E28
S1	(ref. mm)	3.7	4.6	5.6	6.1	7.4	9.3	9.9	11.0	12.8	14.6	16.5	18.3	20.1	22.0	23.7	25.5
S2	(ref. mm)	2.7	3.3	4.0	4.3	5.3	6.8	7.1	7.9	9.2	10.5	11.9	13.2	14.8	15.7	17.5	18.3

12460M · 12460A

Sockets with Magnets for Self-Tapping Screws
Vasos con Imán para Tornillos Autorroscantes



12460M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
5.5	9.7	13	4	23	15	10	*1
6	10.3	13	5	23	15	10	*1
7	11.6	13	5	23	16	10	*1
8	12.8	13	6	23	16	10	*1
10	15.3	13	7	23	19	10	*1
13	19.1	13	8	23	23	10	*1

12460A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
1/4	10.3	13	5	23	15	10	*1
5/16	12.8	13	6	23	16	10	*1
3/8	15.3	13	7	23	19	10	*1
1/2	19.1	13	8	23	23	10	*1

*1 Pin/O-Ring=1200A/B ➡P251

12460MG · 12460AG

With Magnet for Self-Tapping Screws
Con Imán para Tornillos Autorroscantes



12460MG (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
5.5	9.7	13	2.1	23	16	10	*1
6	10.3	13	2.4	23	16	10	*1
7	11.6	13	2.8	23	16	10	*1
8	12.8	13	3.5	25	18	10	*1
10	15.3	13	4.2	28	20	10	*1
New **12**	17.9	13	8	30	41	10	*1
13	19.1	13	6	30	23	10	*1
14	20	13	6.4	30	24	10	*1

12460AG (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
1/4	10.3	13	2.4	23	16	10	*1
5/16	12.8	13	3.5	25	18	10	*1
3/8	15.3	13	4.2	28	20	10	*1
7/16	16.6	13	4.9	29	27	10	*1
1/2	19.1	13	6	30	23	10	*1

*1 Pin/O-Ring=1200A/B ➡P251

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

12300M
6-point Sockets, Deep
Vasos Hexagonales Largos



12300M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
6	10	13	6	38	48	26	10	*1
7	11.3	13	7	38	48	30	10	*1
8	12.5	13	8	38	48	32	10	*1
10	15	13	10	37	48	34	10	*1
11	16.3	13	11	37	48	46	10	*1
12	17.5	13	12	37	48	49	10	*1
13	18.8	13	13	37	48	52	10	*1
14	20	13	14	36	48	57	10	*1

*1 Pin/O-Ring=1200A/B ➡P251

12365M
Pathfinder Sockets, Deep
Vasos Pathfinder (Guía) Largos



12365M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
10	15	13	8	37	48	34	10	*1
11	16.3	13	8	37	48	46	10	*1
12	17.5	13	9	37	48	49	10	*1
13	18.8	13	9	37	48	52	10	*1

*1 Pin/O-Ring=1200A/B ➡P251

12300G
Impact Socket with Sliding Magnet
Vasos de Impacto con Imán Corredizo



12300G (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
8	12.5	13	4	22	48	32	10	*1
10	15	13	4.5	20.5	48	34	10	*1
12	17.5	13	6	24.5	48	49	10	*1
13	18.8	13	6.5	23	48	52	10	*1
14	20	13	7	21	48	57	10	*1

*1 Pin/O-Ring=1200A/B ➡P251

12760-55 · -75 · -100 · -150
Extension Bars
Alargaderas



12760	D (mm)	L (mm)	(g)	(pcs.)	
55	13	55	26	10	*1
75	13	75	45	10	*1
100	13	100	50	10	*1
New **150**	13	150	60	10	*1

*1 Pin/O-Ring=1200A/B ➡P251

12222AL
Adaptor (Quick Release)
Adaptador (Extracción Rápida)



	L (mm)	(g)	(pcs.)	
12222AL	35	30	10	*1

*1 Pin/O-Ring=1200A/B ➡P251

12770
Universal Joint
Articulación Universal





Lock & Quick Release



	L (mm)	(g)	(pcs.)	
12770	39	30	10	*1

*1 Pin/O-Ring=1200A/B ➡P251

12233A
Adaptor
Adaptador



	凹 (sq.)	凸 (sq.)	L (mm)	(g)	(pcs.)	
12233A	1/4"	3/8"	22	15	10	*1
12233A-B	1/4"	3/8"	22	15	10	*1
12233A-P	1/4"	3/8"	22	15	10	*1

*1 Pin/O-Ring=1200A/B ➡P251

13400M · 13400A

6-point Sockets
Vasos Hexagonales



13400M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
6	10.8	19	5	32	40	10	*1
7	12	19	5	32	40	10	*1
8	13.3	19	6	32	40	10	*1
9	14.5	19	7	32	40	10	*1
10	15.8	19	7	32	40	10	*1
11	17	19	8	32	41	10	*1
12	18.3	19	9	32	43	10	*1
13	19.5	22	10	32	56	10	*2
14	20.8	22	10	32	56	10	*2
15	22	22	11	32	56	10	*2
16	23.3	22	11	32	57	10	*2
17	24.5	22	12	32	60	10	*2
18	25.8	22	12	32	62	10	*2
19	27	22	12	32	67	10	*2
20	28.3	22	12	32	70	10	*2
21	29.5	22	12	32	71	10	*2
22	30.8	22	13	32	72	10	*2
23	32	22	13	32	75	10	*2
24	33.3	22	13	32	78	10	*2

13400A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
1/4	10.8	19	5	32	40	10	*1
5/16	13.3	19	6	32	40	10	*1
3/8	15.8	19	7	32	40	10	*1
7/16	17	19	8	32	41	10	*1
1/2	19.5	22	10	32	56	10	*2
9/16	20.8	22	10	32	56	10	*2
5/8	23.3	22	11	32	57	10	*2
11/16	24.5	22	12	32	60	10	*2
3/4	27	22	12	32	67	10	*2
13/16	29.5	22	12	32	71	10	*2
7/8	30.8	22	13	32	72	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13405M · 13405A

12-point Sockets
Vasos Bihexagonales



13405M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
8	13.3	19	6	32	40	10	*1
9	14.5	19	7	32	40	10	*1
10	15.8	19	7	32	40	10	*1
New **11**	17	19	8	32	41	10	*1
12	18.3	19	9	32	43	10	*1
13	19.5	22	10	32	56	10	*2
14	20.8	22	10	32	56	10	*2
15	22	22	11	32	56	10	*2
New **16**	23.3	22	11	32	57	10	*2
17	24.5	22	12	32	60	10	*2
New **18**	25.8	22	12	32	62	10	*2
19	27	22	12	32	67	10	*2

13405A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
1/4	10.8	19	5	32	40	10	*1
5/16	13.3	19	6	32	40	10	*1
3/8	15.8	19	7	32	40	10	*1
7/16	17	19	8	32	41	10	*1
1/2	19.5	22	10	32	56	10	*2
9/16	20.8	22	10	32	56	10	*2
5/8	23.3	22	11	32	57	10	*2
11/16	24.5	22	12	32	60	10	*2
3/4	27	22	12	32	67	10	*2
13/16	29.5	22	12	32	71	10	*2
7/8	30.8	22	13	32	72	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13401MS

6-point Short Sockets, Thin-walled.
Vasos Hexagonales de Pared Delgada, Short

thin



13401MS (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
8	12.3	18.5	6	22	25	10	*1
10	14.8	18.5	6	22	25	10	*1
12	17.3	18.5	10	22	20	10	*1
13	18.5	21.5	10	22	30	10	*2
14	19.8	21.5	10	22	30	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

RS13401MS/5

Socket Set on Rail
Juego de Vasos en Regleta

thin

RS13401MS/5	5 Pieces Set/Rail 150mm	(g)
	8, 10, 12, 13, 14	180

13401M · 13401A

6-point Socket, Thin Walled
Vasos Hexagonales de Pared Delgada



13401A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
1/4	9.8	18.5	5	32	28	10	*1
5/16	12.3	18.5	6	32	31	10	*1
3/8	14.8	18.5	7	32	34	10	*1
7/16	16	18.5	8	32	35	10	*1
1/2	18.5	21.5	10	32	43	10	*2
9/16	19.8	21.5	10	32	49	10	*2
5/8	22.3	21.5	11	32	51	10	*2
11/16	23.5	21.5	12	32	54	10	*2
3/4	26	21.5	12	32	60	10	*2
13/16	28.5	21.5	12	32	70	10	*2
7/8	29.8	21.5	13	32	73	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13401M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
6	9.8	18.5	5	32	28	10	*1
7	11	18.5	5	32	30	10	*1
8	12.3	18.5	6	32	31	10	*1
9	13.5	18.5	7	32	32	10	*1
10	14.8	18.5	7	32	34	10	*1
11	16	18.5	8	32	35	10	*1
12	17.3	18.5	9	32	36	10	*1
13	18.5	21.5	10	32	43	10	*2
14	19.8	21.5	10	32	49	10	*2
15	21	21.5	11	32	49	10	*2
16	22.3	21.5	11	32	51	10	*2
17	23.5	21.5	12	32	54	10	*2
18	24.8	21.5	12	32	57	10	*2
19	26	21.5	12	32	60	10	*2
20	27.3	21.5	12	32	65	10	*2
21	28.5	21.5	12	32	70	10	*2
22	29.8	21.5	13	32	73	10	*2
23	31	21.5	13	32	73	10	*2
24	32.3	21.5	13	32	75	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13406M · 13406A

12-point Socket, Thin Walled
Vasos Bihexagonales de Pared Delgada



13406A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
1/4	9.8	18.5	5	32	28	10	*1
5/16	12.3	18.5	6	32	31	10	*1
3/8	14.8	18.5	7	32	34	10	*1
7/16	16	18.5	8	32	35	10	*1
1/2	18.5	21.5	10	32	43	10	*2
9/16	19.8	21.5	10	32	49	10	*2
5/8	22.3	21.5	11	32	51	10	*2
11/16	23.5	21.5	12	32	54	10	*2
3/4	26	21.5	12	32	60	10	*2
13/16	28.5	21.5	12	32	70	10	*2
7/8	29.8	21.5	13	32	73	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13406M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
6	9.8	18.5	5	32	28	10	*1
7	11	18.5	5	32	30	10	*1
8	12.3	18.5	6	32	31	10	*1
9	13.5	18.5	7	32	32	10	*1
10	14.8	18.5	7	32	34	10	*1
11	16	18.5	8	32	35	10	*1
12	17.3	18.5	9	32	36	10	*1
13	18.5	21.5	10	32	43	10	*2
14	19.8	21.5	10	32	49	10	*2
15	21	21.5	11	32	49	10	*2
16	22.3	21.5	11	32	51	10	*2
17	23.5	21.5	12	32	54	10	*2
18	24.8	21.5	12	32	57	10	*2
19	26	21.5	12	32	60	10	*2
20	27.3	21.5	12	32	65	10	*2
21	28.5	21.5	12	32	70	10	*2
22	29.8	21.5	13	32	73	10	*2
23	31	21.5	13	32	73	10	*2
24	32.3	21.5	13	32	75	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

RS13401M/9

Socket Set on Rail
Juego de Vasos en Regleta

RS13401M/9	9 Pieces Set/Rail 250mm	(g)
	8, 10, 12, 13, 14, 17, 19, 21, 22	505

13400MG · 13400AG

6-point Sockets with Magnet
Vasos Hexagonales con Imán



13400MG (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
6	10.8	19	2.4	32	46	10	*1
7	12	19	2.8	32	45	10	*1
8	13.3	19	3.5	32	45	10	*1
9	14.5	19	3.8	32	44	10	*1
10	15.8	19	4.2	32	49	10	*1
11	17	19	4.9	32	50	10	*1
12	18.3	19	5.6	32	55	10	*1
13	19.5	22	6	32	70	10	*2
14	20.8	22	6.4	32	76	10	*2
15	22	22	6.8	32	76	10	*2
16	23.3	22	7	32	88	10	*2
17	24.5	22	7.5	32	95	10	*2
18	25.8	22	7.8	32	105	10	*2
19	27	22	8	32	116	10	*2
21	29.5	22	8	32	125	10	*2
22	30.8	22	9.5	32	135	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13400AG (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
1/4	10.8	19	2.4	32	46	10	*1
5/16	13.3	19	3.5	32	45	10	*1
11/32	14.5	19	3.8	32	44	10	*1
3/8	15.8	19	4.2	32	49	10	*1
7/16	17	19	4.9	32	50	10	*1
1/2	19.5	22	6	32	70	10	*2
9/16	20.8	22	6.4	32	76	10	*2
5/8	23.3	22	7	32	88	10	*2
11/16	24.5	22	7.5	32	95	10	*2
3/4	27	22	8	32	116	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13410M

Surface Drive Sockets
Vasos Surface Drive (de Contacto Curvo)



13410M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
6	10.8	19	5	32	40	10	*1
7	12	19	5	32	40	10	*1
8	13.3	19	6	32	40	10	*1
9	14.5	19	7	32	40	10	*1
10	15.8	19	7	32	40	10	*1
11	17	19	8	32	42	10	*1
12	18.3	19	9	32	50	10	*1
13	19.5	22	10	32	56	10	*2
14	20.8	22	10	32	56	10	*2
15	22	22	11	32	56	10	*2
16	23.3	22	11	32	57	10	*2
17	24.5	22	12	32	60	10	*2
New 18	25.8	22	12	32	62	10	*2
19	27	22	12	32	67	10	*2
22	30.8	22	13	32	72	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13465M

Pathfinder Sockets
Vasos Pathfinder (Guía)



13465M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
8	13.3	19	8	32	40	10	*1
10	15.8	19	8	32	43	10	*1
11	17	19	8	32	44	10	*1
12	18.3	19	9	32	47	10	*1
13	19.5	22	9	32	55	10	*2
14	20.8	22	11	32	56	10	*2
15	22	22	11	32	56	10	*2
16	23.3	22	11	32	57	10	*2
17	24.5	22	12	32	60	10	*2
18	25.8	22	13	32	63	10	*2
19	27	22	13	32	66	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13425

TORX® Sockets
Vasos TORX®



13425 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
E 4	9.7	19	4.6	32	44	10	*1
E 5	10.2	19	5.2	32	43	10	*1
E 6	10.7	19	5.4	32	44	10	*1
E 7	11.2	19	6.6	32	44	10	*1
E 8	11.7	19	7	32	44	10	*1
E10	12.2	19	8.2	32	42	10	*1
E12	14.2	19	9.3	32	43	10	*1
E14	17.2	19	10.6	32	44	10	*1
E16	18.2	19	11.8	32	42	10	*1

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
➡P250-251

13425-EPL

TORXPLUS® Sockets
Vasos TORXPLUS®

TORXplus®



13425-EPL (EPL)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
8EPL	12	19	5.2	32	44	10	*1
10EPL	13.3	19	6.2	32	44	10	*1

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
➡P250-251

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.
TORXplus® is a registered trademark of Acument Intellectual Properties, LLC.
TORXplus® es una marca registrada de Acument Intellectual Properties, LLC.

13460M · 13460A

For Self-Tapping Screws
Para Tornillos Autorroscantes



13460M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
6	11.4	19	5	32	43	10	*1
7	12.8	19	5	32	44	10	*1
8	14.1	19	6	32	44	10	*1
10	16.6	19	7	32	45	10	*1
New **12**	19	19.2	9	32	48	10	*2
13	20.3	22	10	32	60	10	*2

13460A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
1/4	11.4	19	5	32	43	10	*1
3/8	16.6	19	7	32	45	10	*1
1/2	20.3	22	10	32	60	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13460MG · 13460AG

Sockets with Magnets for Self-Tapping Screws
Vasos con Imán para Tornillos Autorroscantes



13460MG (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
6	11.4	19	2.4	32	44	10	*1
7	12.8	19	2.8	32	46	10	*1
8	14.1	19	3.5	32	48	10	*1
10	16.6	19	4.2	33	54	10	*1
13	20.3	22	6	34	81	10	*2

13460AG (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
1/4	11.4	19	2.4	32	44	10	*1
5/16	14.1	19	3.5	32	48	10	*1
3/8	16.6	19	4.2	33	54	10	*1
1/2	20.3	22	6	34	81	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13401LH

LHS Sockets
Vasos LHS



13401LH (LH-S)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
5S	11	19	5	32	32	10	*1
6S	12.3	19	5.6	32	34	10	*1
8S	16	19	6.8	32	36	10	*1
10S	18.5	22	8	32	50	10	*2
12S	22.3	22	9.2	32	58	10	*2
14S	24.8	22	10.4	32	63	10	*2
16S	28.5	22	11.6	32	77	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

LHSTIX®



LH-S		LH-5S	LH-6S	LH-8S	LH-10S	LH-12S	LH-14S	LH-16S
S1	(ref. mm)	5.6	6.8	9.0	11.3	13.6	15.8	18.1
S2	(ref. mm)	7.5	9.0	12.0	15.0	18.0	21.0	24.0

13400-WN

Weld Nut Sockets



13400-WN	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
6WN	15.8	19	6	32	48	10	*1
8WN	18.3	19	8	32	48	10	*1
9WN	19.5	22	9	32	47	10	*2
10WN	20.8	22	10	32	65	10	*2
12WN	24.5	22	12	32	73	10	*2
14WN	27	22	14	32	79	10	*2
17WN	32	22	17	35	110	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

WN



WN		6WN	8WN	9WN	10WN	12WN	14WN	17WN
S	(ref. mm)	6	8	9	10	12	14	17

LHstix® is a registered trademark of **OSG CORPORATION** System Engineering Department.
LHstix® es una marca registrada de **OSG CORPORATION** System Engineering Department.

13301X

6-point Sockets, Semi-Deep
Vasos Hexagonales Medianos de Pared Delgada

thin



New	13301X (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
New	**7**	11	18.5	7	36.5	50	40	10	*1
	8	12.3	18.5	8	36.5	50	40	10	*1
	10	14.8	18.5	10	36.5	50	46	10	*1
	11	16	18.5	11	36.5	50	49	10	*1
	12	17.3	18.5	12	36.5	50	53	10	*1
	13	18.5	21.5	13	36.5	50	67	10	*2
	14	19.8	21.5	14	36.5	50	70	10	*2
	15	21	21.5	15	35.5	50	75	10	*2
	16	22.3	21.5	16	35.5	50	78	10	*2
	17	23.5	21.5	17	35.5	50	82	10	*2
	18	24.8	21.5	18	34.5	50	86	10	*2
	19	26	21.5	19	34.5	50	93	10	*2
	21	28.5	21.5	21	34.5	50	104	10	*2
	22	29.8	21.5	22	33.5	50	110	10	*2
	23	31	21.5	23	33.5	50	115	10	*2
	24	32.3	21.5	24	32.5	50	120	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

RS13301X/9

Socket Set on Rail
Juego de Vasos en Regleta

thin

RS13301X/9	9 Pieces Set/Rail 250mm	(g)
	8, 10, 12, 13, 14, 17, 19, 21, 22	710

13300XG

Impact Sockets with Sliding Magnet
Vasos de Impacto con Imán Corredizo



New	13300XG (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
New	**7**	12	19	3.5	19	50	52	10	*1
	8	13.3	19	4	20.5	50	40	10	*1
	10	15.8	19	4.5	20	50	46	10	*1
	11	17	19	5	20	50	50	10	*1
	12	18.3	19	6	20	50	55	10	*1
	13	19.5	22	6.5	19	50	70	10	*2
	14	20.8	22	7	18	50	75	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13300M · 13300A

6-point Sockets, Deep
Vasos Hexagonales Largos



New	13300M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
	6	10.8	19	6	66.5	80	77	10	*1
	7	12	19	7	66.5	80	82	10	*1
	8	13.3	19	8	66.5	80	82	10	*1
	9	14.5	19	9	66.5	80	88	10	*1
	10	15.8	19	10	66.5	80	94	10	*1
	11	17	19	11	66.5	80	110	10	*1
	12	18.3	19	12	66.5	80	111	10	*1
	13	19.5	22	13	66.5	80	138	10	*2
	14	20.8	22	14	66.5	80	148	10	*2
	15	22	22	15	65.5	80	157	10	*2
	16	23.3	22	16	65.5	80	156	10	*2
	17	24.5	22	17	65.5	80	168	10	*2
	18	25.8	22	18	64.5	80	190	10	*2
	19	27	22	19	64.5	80	192	10	*2
	20	28.3	22	20	64.5	80	224	10	*2
	21	29.5	22	21	64.5	80	226	10	*2
	22	30.8	22	22	63.5	80	231	10	*2
New	**24**	33.2	22	24	63.5	80	242	10	*2

13300A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
1/4	10.8	19	6	66.5	80	77	10	*1
5/16	13.3	19	8	66.5	80	82	10	*1
3/8	15.8	19	10	66.5	80	94	10	*1
7/16	17	19	11	66.5	80	110	10	*1
1/2	19.5	22	13	66.5	80	138	10	*2
9/16	20.8	22	14	66.5	80	148	10	*2
5/8	23.3	22	16	65.5	80	156	10	*2
11/16	24.5	22	17	65.5	80	168	10	*2
3/4	27	22	19	64.5	80	192	10	*2
13/16	29.5	22	21	64.5	80	226	10	*2
7/8	30.8	22	22	63.5	80	231	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13301M · 13301A

6-point Deep Sockets, Thin Walled
Vasos Hexagonales Largos de Pared Delgada

thin



13301M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
6	10	18.5	6	66.5	80	65	10	*1
7	11	18.5	7	66.5	80	66	10	*1
8	12.3	18.5	8	66.5	80	68	10	*1
9	13.5	18.5	9	66.5	80	70	10	*1
10	14.8	18.5	10	66.5	80	72	10	*1
11	16	18.5	11	66.5	80	80	10	*1
12	17.3	18.5	12	66.5	80	85	10	*1
13	18.5	21.5	13	66.5	80	100	10	*2
14	19.8	21.5	14	66.5	80	110	10	*2
15	21	21.5	15	65.5	80	120	10	*2
16	22.3	21.5	16	65.5	80	130	10	*2
17	23.5	21.5	17	65.5	80	136	10	*2
18	24.8	21.5	18	64.5	80	145	10	*2
19	26	21.5	19	64.5	80	155	10	*2
20	27.3	21.5	20	64.5	80	170	10	*2
21	28.5	21.5	21	64.5	80	181	10	*2
22	29.8	21.5	22	63.5	80	190	10	*2
New 24	32.3	21.5	24	63.5	80	216	10	*2

13301A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
1/4	10	18.5	6	66.5	80	65	10	*1
5/16	12.3	18.5	8	66.5	80	68	10	*1
3/8	14.8	18.5	10	66.5	80	72	10	*1
7/16	16	18.5	11	66.5	80	80	10	*1
1/2	18.5	21.5	13	66.5	80	100	10	*2
9/16	19.8	21.5	14	66.5	80	110	10	*2
5/8	22.3	21.5	16	65.5	80	130	10	*2
11/16	23.5	21.5	17	65.5	80	136	10	*2
3/4	26	21.5	19	64.5	80	155	10	*2
13/16	28.5	21.5	21	64.5	80	181	10	*2
7/8	29.8	21.5	22	63.5	80	190	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13305M

12-point Sockets, Deep
Vasos Bihexagonales Largos



13305M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
8	13.3	19	8	66.5	80	82	10	*1
10	15.8	19	10	66.5	80	94	10	*1
New 11	17	19	11	66.5	80	110	10	*1
12	18.3	19	12	66.5	80	111	10	*1
13	19.5	22	13	66.5	80	138	10	*2
14	20.8	22	14	66.5	80	148	10	*2
17	24.5	22	17	65.5	80	168	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13306M

12-point Deep Sockets, Thin-Walled
Vasos Bihexagonales Largos de Pared Delgada

thin



13306M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
New 8	12.3	18.5	8	66.5	80	68	10	*1
New 10	14.8	18.5	10	66.5	80	72	10	*1
New 11	16	18.5	11	66.5	80	80	10	*1
New 12	17.3	18.5	12	66.5	80	85	10	*1
New 13	18.5	21.5	13	66.5	80	100	10	*2
New 14	19.8	21.5	14	66.5	80	110	10	*2
New 17	23.5	215	17	66.5	80	136	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13310M

Surface Drive Sockets, Deep
Vasos Surface Drive (de Contacto Curvo) Largos



13310M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
7	12	19	7	66.5	80	77	10	*1
8	13.3	19	8	66.5	80	90	10	*1
9	14.5	19	9	66.5	80	90	10	*1
10	15.8	19	10	66.5	80	97	10	*1
11	17	19	11	66.5	80	110	10	*1
12	18.3	19	12	66.5	80	105	10	*1
13	19.5	22	13	66.5	80	135	10	*2
14	20.8	22	14	66.5	80	145	10	*2
15	22	22	15	65.5	80	160	10	*2
16	23.3	22	16	65.5	80	156	10	*2
17	24.5	22	17	65.5	80	168	10	*2
New 18	25.8	22	18	64.5	80	190	10	*2
19	27	22	19	64.5	80	190	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13300G

Impact Sockets with Sliding Magnet
Vasos de Impacto con Imán Corredizo



13300G (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
8	13.3	19	4	26.5	80	82	10	*1
10	15.8	19	4.5	26	80	105	10	*1
12	18.3	19	6	26	80	136	10	*1
13	19.5	22	6.5	25	80	165	10	*2
14	20.8	22	7	24	80	186	10	*2
15	22	22	7	24	80	195	10	*2
New 16	23.3	22	8	27	80	210	10	*2
17	24.5	22	8	27	80	220	10	*2
19	27	22	9	28	80	230	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13365M

Pathfinder Sockets deep
Vasos Pathfinder (Guía) Largos



13365M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
New 8	13.3	19	7	66.5	80	90	10	*1
10	15.8	19	8	66.5	80	99	10	*1
11	17	19	8	66.5	80	108	10	*1
12	18.3	19	9	66.5	80	110	10	*1
13	19.5	22	9	66.5	80	142	10	*2
14	20.8	22	11	66.5	80	144	10	*2
15	22	22	11	65.5	80	150	10	*2
16	23.3	22	11	65.5	80	159	10	*2
17	24.5	22	12	65.5	80	170	10	*2
18	25.8	22	13	64.5	80	201	10	*2
19	27	22	13	64.5	80	203	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13325

TORX® Deep Sockets
Vasos TORX® Largos



13325 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
New E 7	11.2	19	6.6	66.5	80	75	10	*1
E 8	11.7	19	7	66.5	80	80	10	*1
E10	12.2	19	8.2	66.5	80	85	10	*1
E12	14.2	19	9.3	66.5	80	90	10	*1
E14	17.2	19	10.6	66.5	80	110	10	*1
E16	18.2	19	11.8	66.5	80	110	10	*1

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
➡P250-251

13440M · 13440A

Universal Sockets
Vasos con Articulación Universal



13440M (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
10	15.8	5	57	115	10	*1
11	17	6	57	115	10	*1
12	18.3	6	57	115	10	*1
13	19.5	6	57	115	10	*1
14	20.8	7	59	120	10	*1
15	22	7	59	120	10	*1
16	23.3	8	59	120	10	*1
17	24.5	8	59	120	10	*1
18	25.8	9	61	126	10	*1
19	27	10	61	130	10	*1
20	29.5	10	61	135	10	*1
New 21	30.7	14	66	175	10	*1
22	32	13	61	185	10	*1
24	34.5	13	63	190	10	*1

13440A (inch)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
3/8	15.8	5	57	115	10	*1
7/16	17	6	57	115	10	*1
1/2	19.5	6	57	115	10	*1
9/16	20.8	7	59	120	10	*1
5/8	23.3	8	59	120	10	*1
11/16	24.5	8	59	120	10	*1
3/4	27	10	61	130	10	*1

*1 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13440T

TORX® Universal Sockets
Vasos TORX® con Articulación Universal



13440T (E)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
E10	13.3	8.2	58	115	10	*1
E12	15.8	9.3	58	115	10	*1
E14	17	10.6	58	115	10	*1

*1 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13430M

Universal Inhex Sockets
Vasos Inhex con Articulación Universal



13430M (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
5	24	15	74	120	10	*1
6	24	15	74	131	10	*1
8	24	20	74	136	10	*1
10	24	20	74	141	10	*1
17	24	7	53	150	10	*1

*1 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

13012M-52

Inhex Sockets
Vasos con Punta Hexagonal



13012M.52 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
New **3**	18	10	34	52	33	10	*1
4	18	15.5	34	52	35	10	*1
5	18	15.5	34	52	35	10	*1
6	18	15.5	34	52	39	10	*1
7	18	15.5	34	52	44	10	*1
8	21	15.5	34	52	60	10	*2
10	21	15.5	34	52	70	10	*2
12	21	15.5	34	52	79	10	*2
14	21	15.5	34	52	92	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13025-50 · -90

TORX® Bit Sockets
Vasos con Punta TORX®



13025.50 (T)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)	
T20	19	23.5	50	35	10	*1
T25	19	23.5	50	35	10	*1
T27	19	23.5	50	35	10	*1
T30	19	23.5	50	35	10	*1
T40	19	23.5	50	39	10	*1
T45	19	23.5	50	60	10	*1
T50	19	23.5	50	70	10	*1
T55	22	23.5	50	79	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

13025.90 (T)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)	
T20	19	63.5	90	43	10	*1
T25	19	63.5	90	45	10	*1
T27	19	63.5	90	47	10	*1
T30	19	63.5	90	50	10	*1
T40	19	63.5	90	58	10	*1
T45	19	63.5	90	66	10	*1
T50	19	63.5	90	80	10	*1
T55	22	63.5	90	120	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

RS13025/8-L50

Socket Set on Rail
Juego de Vasos en Regleta

RS13025/8-L50	8 Pieces Set/Rail 200mm	(g)
	T20, T25, T27, T30, T40, T45, T50, T55	380

13134

Impact Bit Holder
Porta-punta de Impacto



	D (mm)	L (mm)	(g)	(pcs.)	
13134	22	32	70	10	*1

*1 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

Replacement Screw : M8×5, ⬢ 4mm

For DIN3126 E11.2 Bits



F11.2

13142-F11.2

Impact Bit Holder (Quick Release)
Porta-punta de Impacto (Extracción Rápida)



	D1 (mm)	D2 (mm)	L (mm)	(g)	(pcs.)	
13142-F11.2	18.9	22	46	116	10	*1

*1 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

For DIN3126 E11.2 Bits



F11.2



TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

183H-35 · -75 · -150 Hex Bits / Puntas Hexagonales

	183H.35 (inch)	L (mm)	(g)	(pcs.)
New	3/16	35	15	10
New	7/32	35	16	10
New	1/4	35	18	10
New	5/16	35	20	10
New	3/8	35	26	10
New	7/16	35	28	10
New	1/2	35	38	10



	183H.35 (mm)	L (mm)	(g)	(pcs.)
	3	35	15	10
	4	35	15	10
	5	35	15	10
	6	35	18	10
New	7	35	19	10
	8	35	20	10
	10	35	26	10
New	11	35	28	10
	12	35	30	10
	14	35	35	10
New	16	35	47	10
New	17	35	50	10
New	18	35	53	10
New	19	35	56	10

	183H.75 (mm)	L (mm)	R (mm)	(g)	(pcs.)
	3	75	6.0	34	10
	4	75	6.0	35	10
	5	75	6.5	36	10
	6	75	7.5	39	10
New	7	75	8.5	44	10
	8	75	9.5	47	10
	10	75	–	57	10
New	11	75	–	60	10
	12	75	–	65	10
	14	75	–	79	10

	183H.150 (mm)	L (mm)	R (mm)	(g)	(pcs.)
New	4	150	6.0	51	10
New	5	150	6.5	55	10
New	6	150	7.5	65	10
New	8	150	9.5	87	10
New	10	150	–	118	10
New	12	150	–	136	10

183T-35 · -75 · -150 (T) TORX® Bits / Puntas TORX®

	183T.35 (T)	L (mm)	(g)	(pcs.)
New	T25	35	18	10
	T30	35	18	10
	T40	35	20	10
	T45	35	22	10
	T50	35	26	10
	T55	35	30	10
	T60	35	38	10



	183T.75 (T)	L (mm)	R (mm)	(g)	(pcs.)
	T30	75	6.0	35	10
	T40	75	6.9	37	10
	T45	75	8.0	41	10
	T50	75	9.0	45	10
	T55	75	11.4	55	10
	T60	75	13.5	67	10

	183T.150 (T)	L (mm)	R (mm)	(g)	(pcs.)
New	T30	150	6.0	50	10
New	T40	150	6.9	58	10
New	T45	150	8.0	70	10
New	T50	150	9.0	82	10
New	T55	150	11.4	113	10

183T-35 · -75 (IP) TORXPLUS® Bits / Puntas TORXPLUS®

TORXplus®

	183T.35 (IP)	L (mm)	(g)	(pcs.)
New	30IP	35	18	10
New	40IP	35	20	10
New	45IP	35	22	10
New	50IP	35	26	10
New	55IP	35	30	10
New	60IP	35	38	10



	183T.75 (IP)	L (mm)	R (mm)	(g)	(pcs.)
New	30IP	75	6.0	35	10
New	40IP	75	6.8	37	10
New	45IP	75	8.0	41	10
New	50IP	75	9.0	45	10
New	55IP	75	11.4	56	10
New	60IP	75	13.5	67	10

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.
TORXplus® is a registered trademark of Acument Intellectual Properties, LLC.
TORXplus® es una marca registrada de Acument Intellectual Properties, LLC.

183X-35 • -75 • -150 (XZN)

XZN Bits
Puntas XZN



	183X.35 (XZN)	L (mm)	(g)	(pcs.)
New	M 4	35	18	10
	M 5	35	18	10
	M 6	35	20	10
	M 8	35	22	10
	M10	35	26	10
	M12	35	30	10
	M14	35	38	10

	183X.75 (XZN)	L (mm)	R (mm)	(g)	(pcs.)
New	M 4	75	6.0	34	10
	M 5	75	6.0	34	10
	M 6	75	6.2	36	10
	M 8	75	7.4	39	10
	M10	75	9.8	54	10
	M12	75	11.7	57	10
	M14	75	13.5	67	10

	183X.150 (XZN)	L (mm)	R (mm)	(g)	(pcs.)
New	M 5	150	6.0	50	10
New	M 6	150	6.2	53	10
New	M 8	150	7.4	64	10
New	M10	150	9.8	93	10
New	M12	150	11.7	121	10

13134M-52 • -92

Hex Bit Sockets
Vasos con Punta Hexagonal

	13134M-52/-92 (mm)	D (mm)	H (mm)	L (mm)	L (mm)	R (mm)	L=52 (g)	L=92 (g)	(pcs.)	
New	3	22	20.6	52	92	6.0	85	104	10	*1
New	4	22	20.6	52	92	6.0	85	105	10	*1
New	5	22	20.6	52	92	6.5	85	106	10	*1
New	6	22	20.6	52	92	7.5	88	109	10	*1
New	8	22	20.6	52	92	9.5	90	117	10	*1
New	10	22	20.6	52	92	–	96	127	10	*1
New	12	22	20.6	52	92	–	100	135	10	*1
New	14	22	20.6	52	92	–	105	149	10	*1

*1 C-Ring=1302C, Pin/O-Ring=1302A/B ➔P250-251

13134T-52 • -92 (T)

TORX® Bit Sockets
Vasos con Punta TORX®



	13134T-52/-92 (T)	D (mm)	H (mm)	L (mm)	L (mm)	R (mm)	L=52 (g)	L=92 (g)	(pcs.)	
New	T30	22	20.6	52	92	6.0	88	105	10	*1
New	T40	22	20.6	52	92	6.9	90	107	10	*1
New	T45	22	20.6	52	92	8.0	92	111	10	*1
New	T50	22	20.6	52	92	9.0	96	115	10	*1
New	T55	22	20.6	52	92	11.4	100	125	10	*1
New	T60	22	20.6	52	92	13.5	108	137	10	*1

*1 C-Ring=1302C, Pin/O-Ring=1302A/B ➔P250-251

13134T-52 • -92 (IP)

TORXPLUS® Bit Sockets
Vasos con Punta TORXPLUS®



	13134T-52/-92 (IP)	D (mm)	H (mm)	L (mm)	L (mm)	R (mm)	L=52 (g)	L=92 (g)	(pcs.)	
New	30IP	22	20.6	52	92	6.0	88	105	10	*1
New	40IP	22	20.6	52	92	6.8	90	107	10	*1
New	45IP	22	20.6	52	92	8.0	92	111	10	*1
New	50IP	22	20.6	52	92	9.0	96	115	10	*1
New	55IP	22	20.6	52	92	11.4	100	126	10	*1
New	60IP	22	20.6	52	92	13.5	108	139	10	*1

*1 C-Ring=1302C, Pin/O-Ring=1302A/B ➔P250-251

13134X-52 • -92 (XZN)

XZN Bit Sockets
Vasos con Punta XZN



	13134X-52/-92 (XZN)	D (mm)	H (mm)	L (mm)	L (mm)	R (mm)	L=52 (g)	L=92 (g)	(pcs.)	
New	M 5	22	20.6	52	92	6.0	88	104	10	*1
New	M 6	22	20.6	52	92	6.2	90	106	10	*1
New	M 8	22	20.6	52	92	7.4	92	109	10	*1
New	M10	22	20.6	52	92	9.8	96	124	10	*1
New	M12	22	20.6	52	92	11.7	100	129	10	*1
New	M14	22	20.6	52	92	13.5	108	139	10	*1

*1 C-Ring=1302C, Pin/O-Ring=1302A/B ➔P250-251

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.
TORX PLUS® is a registered trademark of Acument Intellectual Properties, LLC.
TORX PLUS® es una marca registrada de Acument Intellectual Properties, LLC.

13145M-100 · -150 · -200 · -250

Extra Long Sockets
Vasos Extra-Largos



13145M.100 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
8	13.3	19	8	100	90	1	*1
10	15.8	19	10	100	92	1	*1
12	18.3	19	12	100	100	1	*1
13	19.5	19	13	100	108	1	*1
14	20.8	19	14	100	112	1	*1
17	24.5	19	17	100	140	1	*1

13145M.150 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
6	10.8	19	6	150	105	1	*1
8	13.3	19	8	150	110	1	*1
10	15.8	19	10	150	120	1	*1
12	18.3	19	12	150	128	1	*1
13	19.5	19	13	150	137	1	*1
14	20.8	19	14	150	146	1	*1
15	22	19	15	150	155	1	*1
17	24.5	19	17	150	163	1	*1

13145M.200 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
6	10.8	19	6	200	136	1	*1
8	13.3	19	8	200	141	1	*1
10	15.8	19	10	200	151	1	*1
12	18.3	19	12	200	159	1	*1
13	19.5	19	13	200	168	1	*1
14	20.8	19	14	200	177	1	*1
15	22	19	15	200	186	1	*1
17	24.5	19	17	200	194	1	*1

13145M.250 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
6	10.8	19	6	250	167	1	*1
8	13.3	19	8	250	172	1	*1
10	15.8	19	10	250	182	1	*1
12	18.3	19	12	250	190	1	*1
13	19.5	19	13	250	199	1	*1
14	20.8	19	14	250	208	1	*1
15	22	19	15	250	217	1	*1
17	24.5	19	17	250	225	1	*1

*1 C-Ring=1301C, Pin/O-Ring=1301A/B ➡P250-251

13145M-100 (12P) · -150 (12P) · -200 (12P)

Extra Long 12-point Sockets
Vasos Bihexagonales, Extra-Largos



13145M.100 (12P) (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
10	15.8	19	10	100	91	1	*1
12	18.3	19	12	100	100	1	*1

13145M.150 (12P) (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
10	15.8	19	10	150	120	1	*1
12	18.3	19	12	150	128	1	*1

13145M.200 (12P) (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
10	15.8	19	10	200	151	1	*1
12	18.3	19	12	200	159	1	*1

*1 C-Ring=1301C, Pin/O-Ring=1301A/B ➡P250-251

13145MG-100 · -150 · -200

Extra Long Sockets with Magnet
Vasos Extra-Largos con Imán



13145MG.100 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
8	13.3	19	3.5	100	90	1	*1
10	15.8	19	4.2	100	93	1	*1
12	18.3	19	5.6	100	105	1	*1
13	19.5	19	6	100	115	1	*1
14	20.8	19	6.4	100	120	1	*1

13145MG.150 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
8	13.3	19	3.5	150	120	1	*1
10	15.8	19	4.2	150	125	1	*1
12	18.3	19	5.6	150	136	1	*1
13	19.5	19	6	150	145	1	*1
14	20.8	19	6.4	150	150	1	*1

13145MG.200 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
10	15.8	19	4.2	200	182	1	*1
12	18.3	19	5.6	200	190	1	*1
13	19.5	19	6	200	208	1	*1
14	20.8	19	6.4	200	225	1	*1

*1 C-Ring=1301C, Pin/O-Ring=1301A/B ➡P250-251

13146M-150 · -200 · -250

Extra Long Universal Sockets
Vasos Extra Largo con Articulación Universal



13146M.150 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
8	12	19	6	150	128	1	*1
10	14.3	19	7	150	131	1	*1
12	18	19	8	150	133	1	*1
13	19.3	19	8.5	150	132	1	*1
14	20	19	9	150	132	1	*1

13146M.200 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
8	12	19	6	200	159	1	*1
10	14.3	19	7	200	162	1	*1
12	18	19	8	200	164	1	*1
13	19.3	19	8.5	200	163	1	*1
14	20	19	9	200	163	1	*1

13146M.250 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
8	12	19	6	250	190	1	*1
10	14.3	19	7	250	193	1	*1
12	18	19	8	250	195	1	*1
13	19.3	19	8.5	250	194	1	*1
14	20	19	9	250	194	1	*1

*1 C-Ring=1301C, Pin/O-Ring=1301A/B ➡P250-251

13147M-150 · -200

Extra Long Universal Inhex Sockets
Vasos Inhex Extra Largos con Articulación Universal



13147M.150 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
4	21	19	15	150	125	1	*1
5	21	19	15	150	128	1	*1
6	21	19	15	150	132	1	*1
8	21	19	15	150	136	1	*1
10	21	19	15	150	140	1	*1

13147M.200 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
4	21	19	15	200	156	1	*1
5	21	19	15	200	159	1	*1
6	21	19	15	200	163	1	*1
8	21	19	15	200	167	1	*1
10	21	19	15	200	171	1	*1

*1 C-Ring=1301C, Pin/O-Ring=1301A/B ➡P250-251

13760-75 · -100 · -125 · -150 · -200 · -250

Extension Bars
Alargaderas



13760	D (mm)	L (mm)	(g)	(pcs.)	
75	22	75	95	10	*1
100	22	100	120	10	*1
125	22	125	141	5	*1
150	22	150	165	5	*1
200	22	200	210	5	*1
250	22	250	260	5	*1

*1 C-Ring=1302C, Pin/O-Ring=1302A/B ➡P250-251

13333AL Adaptor (Quick Release) Adaptador (Extracción Rápida)

	L (mm)	(g)	(pcs.)	
13333AL	45	62	10	*1

*1 C-Ring=1301C, Pin/O-Ring=1301A/B ➡P250-251

Lock & Quick Release





13770 Universal Joint Articulatión Universal

	L (mm)	(g)	(pcs.)	
13770	56	110	10	*1
13770-B	56	110	10	*1
13770-P	56	110	10	*1
13771	48	92	10	*1
13771-B	48	92	10	*1
13771-P	48	92	10	*1

*1 C-Ring=1302C, Pin/O-Ring=1302A/B ➡P250-251



13771 Universal Joint Articulatión Universal









13772-P Universal Double Joint Articulación Universal

	D1 (mm)	D2 (mm)	L (mm)	(g)	(pcs.)	
13772-P	22	19	75	120	5	*1

*1 C-Ring=1301C, Pin/O-Ring=1301A/B ➡P250-251



13322A Adaptor Adaptador ⚠

	(sq.)	(sq.)	L (mm)	(g)	(pcs.)	
13322A	3/8"	1/4"	27	25	10	*1
13322A-B	3/8"	1/4"	27	25	10	*1
13322A-P	3/8"	1/4"	27	25	10	*1

*1 C-Ring=1301C, Pin/O-Ring=1301A/B ➡P250-251

⚠ Adapting down from bigger square drive to smaller square drive may lead to excessive torque load and possibly cause breakage. Always stay within safe torque of the smaller square drive.



13344A Adaptor Adaptador

	(sq.)	(sq.)	L (mm)	(g)	(pcs.)	
13344A	3/8"	1/2"	32.5	53	10	*1
13344A-B	3/8"	1/2"	32.5	53	10	*1
13344A-P	3/8"	1/2"	32.5	53	10	*1

*1 C-Ring=1302C, Pin/O-Ring=1302A/B ➡P250-251



13241M Socket Set Juego de Vasos

13241M — 11 Pieces Set/⚖=850g

METAL CASE:W240×H30×T35mm

Sockets

13400M 6-pt. Sockets
9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19

13242M Socket Set Juego de Vasos

13242M — 11 Pieces Set/⚖=1,140g

METAL CASE:W310×H90×T48mm

Sockets

13400M 6-pt. Sockets
9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19

14400M · 14400A

6-point Sockets
Vasos Hexagonales



14400A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
1/4	12	25	5	38	80	10	*1
5/16	14.5	25	6	38	85	10	*1
3/8	17	25	7	38	85	10	*1
7/16	18.2	25	8	38	85	10	*1
1/2	20.7	25	10	38	85	10	*1
9/16	22	25	10	38	85	10	*1
New 19/32	23.2	30	11	38	130	10	*2
5/8	24.5	30	11	38	130	10	*2
11/16	25.7	30	12	38	130	10	*2
3/4	28.2	30	13	38	125	10	*2
13/16	30.7	30	14	38	120	10	*2
7/8	32	30	14	38	130	10	*2
15/16	34.5	30	14	38	135	10	*2
1	35.7	30	14	38	135	10	*2
1 1/16	38.2	30	16	40	160	10	*2
1 1/8	40.7	30	17	42	190	10	*2
1 3/16	42	30	17	42	190	10	*2
1 1/4	44.5	30	18	42	216	10	*2
1 5/16	45.7	30	19	46	260	5	*2
1 3/8	47	30	19	46	263	5	*2
1 1/2	52	30	20	53	365	5	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

14400M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
8	14.5	25	6	38	85	10	*1
9	15.7	25	7	38	85	10	*1
10	17	25	7	38	85	10	*1
11	18.2	25	8	38	85	10	*1
12	19.5	25	9	38	85	10	*1
13	20.7	25	10	38	85	10	*1
14	22	25	10	38	85	10	*1
15	23.2	30	11	38	130	10	*2
16	24.5	30	11	38	130	10	*2
17	25.7	30	12	38	130	10	*2
18	27	30	13	38	130	10	*2
19	28.2	30	13	38	125	10	*2
20	29.5	30	13	38	127	10	*2
21	30.7	30	14	38	120	10	*2
22	32	30	14	38	130	10	*2
23	33.2	30	14	38	130	10	*2
24	34.5	30	14	38	135	10	*2
25	35.7	30	14	38	135	10	*2
26	37	30	14	38	160	10	*2
27	38.2	30	16	40	160	10	*2
28	39.5	30	16	40	170	10	*2
29	40.7	30	17	42	190	10	*2
30	42	30	17	42	190	10	*2
31	43.2	30	17	42	213	10	*2
32	44.5	30	18	42	216	10	*2
33	45.7	30	19	46	260	5	*2
34	47	30	19	46	263	5	*2
35	48.2	30	19	46	275	5	*2
36	49.5	30	20	46	285	5	*2
New 38	52	30	20	53	360	5	*2
41	55.7	30	21	55	411	2	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

14405M · 14405A

12-point Sockets
Vasos Bihexagonales



14405A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
5/16	14.5	25	6	38	85	10	*1
3/8	17	25	7	38	85	10	*1
7/16	18.2	25	8	38	85	10	*1
1/2	20.7	25	10	38	85	10	*1
9/16	22	25	10	38	85	10	*1
5/8	24.5	30	11	38	130	10	*2
11/16	25.7	30	12	38	130	10	*2
3/4	28.2	30	13	38	125	10	*2
13/16	30.7	30	14	38	120	10	*2
7/8	32	30	14	38	130	10	*2
15/16	34.5	30	14	38	135	10	*2
1	35.7	30	14	38	135	10	*2
1 1/16	38.2	30	16	40	160	10	*2
1 1/8	40.7	30	17	42	190	10	*2
1 3/16	42	30	17	42	190	10	*2
1 1/4	44.5	30	18	42	216	10	*2
1 5/16	45.7	30	19	46	260	5	*2
1 3/8	47	30	19	46	263	5	*2
1 1/2	52	30	20	53	365	5	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

14405M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
8	14.5	25	6	38	85	10	*1
9	15.7	25	7	38	85	10	*1
10	17	25	7	38	85	10	*1
11	18.2	25	8	38	84	10	*1
12	19.5	25	9	38	84	10	*1
13	20.7	25	10	38	84	10	*1
14	22	25	10	38	84	10	*1
15	23.2	30	11	38	130	10	*2
16	24.5	30	11	38	127	10	*2
17	25.7	30	12	38	128	10	*2
18	27	30	13	38	130	10	*2
19	28.2	30	13	38	125	10	*2
20	29.5	30	13	38	127	10	*2
21	30.7	30	14	38	120	10	*2
22	32	30	14	38	130	10	*2
23	33.2	30	14	38	132	10	*2
24	34.5	30	14	38	133	10	*2
26	37	30	14	38	147	10	*2
27	38.2	30	16	40	157	10	*2
28	39.5	30	16	40	170	10	*2
30	42	30	17	42	190	10	*2
32	44.5	30	18	42	216	10	*2
36	49.5	30	20	46	285	5	*2
41	55.7	30	21	55	411	2	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

14401M · 14401A

6-point Sockets, Thin Walled
Vasos Hexagonales de Pared Delgada



14401M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
8	13	24	6	38	57	10	*1
9	14.2	24	7	38	58	10	*1
10	15.5	24	7	38	60	10	*1
11	16.7	24	8	38	62	10	*1
12	18	24	9	38	63	10	*1
13	19.2	24	10	38	65	10	*1
14	20.5	24	10	38	67	10	*1
15	21.7	29	11	38	100	10	*2
16	23	29	11	38	102	10	*2
17	24.2	29	12	38	105	10	*2
18	25.5	29	13	38	105	10	*2
19	26.7	29	13	38	107	10	*2
20	28	29	13	38	108	10	*2
21	29.2	29	14	38	109	10	*2
22	30.5	29	14	38	114	10	*2
23	31.7	29	14	38	118	10	*2
24	33	29	14	38	122	10	*2
25	34.2	29	14	38	129	10	*2
26	35.5	29	14	38	131	10	*2
27	36.7	29	16	40	145	10	*2
28	38	29	16	40	152	10	*2
29	39.2	29	17	42	165	10	*2
30	40.5	29	17	42	178	10	*2
31	41.7	29	17	42	185	10	*2
32	43	29	18	42	188	10	*2
33	44.2	29	19	46	219	5	*2
34	45.5	29	19	46	248	5	*2
New 35	46.7	29	19	46	250	5	*2
36	48	29	20	46	264	5	*2
New 38	50.5	29	20	53	316	5	*2
New 41	54.2	29	21	55	374	2	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

14401A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
1/4	10.5	24	5	38	55	10	*1
5/16	13	24	6	38	57	10	*1
3/8	15.5	24	7	38	60	10	*1
7/16	16.7	24	8	38	62	10	*1
1/2	19.2	24	10	38	65	10	*1
9/16	20.5	24	10	38	67	10	*1
5/8	23	29	11	38	102	10	*2
11/16	24.2	29	12	38	105	10	*2
3/4	26.7	29	13	38	107	10	*2
13/16	29.2	29	14	38	109	10	*2
7/8	30.5	29	14	38	114	10	*2
15/16	33	29	14	38	122	10	*2
1	34.2	29	14	38	129	10	*2
1. 1/16	35.5	29	14	40	131	10	*2
1. 1/8	39.2	29	17	42	165	10	*2
1. 3/16	40.5	29	17	42	178	10	*2
1. 1/4	43	29	18	42	188	10	*2
1. 5/16	44.2	29	19	46	219	5	*2
1. 3/8	45.5	29	19	46	248	5	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

14406M · 14406A

12-point Sockets, Thin Walled
Vasos Bihexagonales de Pared Delgada



14406M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
8	13	24	6	38	57	10	*1
9	14.2	24	7	38	58	10	*1
10	15.5	24	7	38	60	10	*1
11	16.7	24	8	38	62	10	*1
12	18	24	9	38	63	10	*1
13	19.2	24	10	38	65	10	*1
14	20.5	24	10	38	67	10	*1
15	21.7	29	11	38	100	10	*2
16	23	29	11	38	102	10	*2
17	24.2	29	12	38	105	10	*2
18	25.5	29	13	38	105	10	*2
19	26.7	29	13	38	107	10	*2
20	28	29	13	38	108	10	*2
21	29.2	29	14	38	109	10	*2
22	30.5	29	14	38	114	10	*2
23	31.7	29	14	38	118	10	*2
24	33	29	14	38	122	10	*2
25	34.2	29	14	38	129	10	*2
26	35.5	29	14	38	131	10	*2
27	36.7	29	16	40	145	10	*2
28	38	29	16	40	152	10	*2
29	39.2	29	17	42	165	10	*2
30	40.5	29	17	42	178	10	*2
31	41.7	29	17	42	185	10	*2
32	43	29	18	42	188	10	*2
33	44.2	29	19	46	219	5	*2
34	45.5	29	19	46	248	5	*2
36	48	29	20	46	264	5	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

14406A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
1/4	10.5	24	5	38	55	10	*1
5/16	13	24	6	38	57	10	*1
3/8	15.5	24	7	38	60	10	*1
7/16	16.7	24	8	38	62	10	*1
1/2	19.2	24	10	38	65	10	*1
9/16	20.5	24	10	38	67	10	*1
5/8	23	29	11	38	102	10	*2
11/16	24.2	29	12	38	105	10	*2
3/4	26.7	29	13	38	107	10	*2
13/16	29.2	29	14	38	109	10	*2
7/8	30.5	29	14	38	114	10	*2
15/16	33	29	14	38	122	10	*2
1	34.2	29	14	38	129	10	*2
1. 1/16	35.5	29	14	40	131	10	*2
1. 1/8	39.2	29	17	42	165	10	*2
1. 3/16	40.5	29	17	42	178	10	*2
1. 1/4	43	29	18	42	188	10	*2
1. 5/16	44.2	29	19	46	219	5	*2
1. 3/8	45.5	29	19	46	248	5	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

RS14401M/10

Socket Set on Rail
Juego de Vasos en Regleta

RS14401M/10	10 Pieces Set/Rail 300mm	(g)
	10, 12, 13, 14, 17, 19, 21, 22, 24, 27	1,010

14401MS

6-point Short Sockets, Thin-walled.
Vasos Hexagonales de Pared Delgada, Short



14401MS (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
14	20.5	24	10	29	50	10	*1
17	24.2	29	10	29	85	10	*2
19	26.7	29	10	29	85	10	*2
22	30.5	29	10	29	90	10	*2
24	33	29	10	29	90	10	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

RS14401MS/5

Socket Set on Rail
Juego de Vasos en Regleta

RS14401MS/5	5 Pieces Set/Rail 150mm	(g)
New	**14, 17, 19, 22, 24**	420

14400MG

6-point Sockets with Magnet
Vasos Hexagonales con Imán



14400MG (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
8	14.5	25	3.5	38	95	10	*1
10	17	25	4.2	38	95	10	*1
12	19.5	25	5.6	38	100	10	*1
13	20.7	25	6	38	100	10	*1
14	22	25	6.4	38	105	10	*1
15	23.2	30	6.8	38	140	10	*2
16	24.5	30	7	38	145	10	*2
17	25.7	30	7.5	38	145	10	*2
18	27	30	7.8	38	147	10	*2
19	28.2	30	8	38	147	10	*2
21	30.7	30	8	38	165	10	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

14410M

Surface Drive Sockets
Vasos Surface Drive (de Contacto Curvo)

14410M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
10	17	25	7	38	100	10	*1
11	18.2	25	8	38	103	10	*1
12	19.5	25	9	38	110	10	*1
13	20.7	25	10	38	113	10	*1
14	22	25	10	38	115	10	*1
15	23.2	30	11	38	120	10	*2
16	24.5	30	11	38	120	10	*2
17	25.7	30	12	38	126	10	*2
18	27	30	13	38	121	10	*2
19	28.2	30	13	38	124	10	*2
20	29.5	30	13	38	123	10	*2
21	30.7	30	14	38	120	10	*2
22	32	30	14	38	130	10	*2
24	34.5	30	14	38	134	10	*2
25	35.7	30	14	38	135	10	*2
26	37	30	14	38	160	10	*2
27	38.2	30	16	40	160	10	*2
28	39.5	30	16	40	170	10	*2
29	40.7	30	17	42	190	10	*2
30	42	30	17	42	190	10	*2
31	43.2	30	17	42	213	10	*2
32	44.5	30	18	42	216	10	*2
34	47	30	19	46	263	5	*2
36	49.5	30	20	46	263	5	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

SURFACE DRIVE

Surface drive sockets are designed to retain contact with flat sides of nut to transmit high torque and reduce nut wear. These sockets are ideal for use on polished nuts, aluminum nuts and nuts with worn out points.

Los vasos de contacto curvo se diseñan para mantener el contacto con las caras planas de la tuerca y transmitir un alto par reduciendo el desgaste de la tuerca. Estos vasos son ideales para utilizarse en tuercas pulidas, tuercas de aluminio y tuercas con puntas gastadas

14465M

Pathfinder Sockets
Vasos Pathfinder (Guía)

14465M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
10	17	25	8	38	89	10	*1
11	18.2	25	8	38	87	10	*1
12	19.5	25	9	38	87	10	*1
13	20.7	25	9	38	86	10	*1
14	22	25	11	38	86	10	*1
15	23.2	30	11	38	131	10	*2
16	24.5	30	11	38	131	10	*2
17	25.7	30	12	38	132	10	*2
18	27	30	13	38	128	10	*2
19	28.2	30	13	38	128	10	*2
20	29.5	30	14	38	125	10	*2
21	30.7	30	14	38	128	10	*2
22	32	30	15	38	130	10	*2
23	33.2	30	15	38	135	10	*2
24	34.5	30	15	38	135	10	*2
26	37	30	15	38	152	10	*2
27	38.2	30	16	40	169	10	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251



PATHFINDER®

The beveled flats of the 6-point opening of the PATHFINDER socket engage the nut almost immediately.
PATHFINDER sockets are ideal for use with power tools in automatic assembly processes, as the power tool does not have to be totally stopped for the socket to engage the nut.

Las caras biseladas de la boca hexagonal del vaso GUÍA acoplan el vaso inmediatamente.
Los vasos GUÍA son ideales para su utilización con herramientas mecánicas en procesos de montaje automáticos, ya que no es necesario que la herramienta esté completamente parada para acoplar el vaso a la tuerca.

14415M

Double Square Sockets
Vasos Octagonales

14415M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
14	25.7	30	10	38	138	10	*1
15	27	30	11	38	145	10	*1
16	29.5	30	11	38	150	10	*1
17	30.7	30	12	38	155	10	*1
18	32	30	13	38	165	10	*1
19	33.2	30	14	38	170	10	*1
22	38.2	30	14	40	185	10	*1
24	42	30	14	42	215	10	*1
27	45.7	30	16	46	278	5	*1
28	47	30	16	46	285	5	*1
New **29**	49.5	30	17	46	326	5	*2

*1 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251



14425

TORX® Sockets
Vasos TORX®

14425 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
E10	14.2	25	8.2	38	86	10	*1
E11	14.7	25	8.7	38	86	10	*1
E12	15.2	25	9.3	38	85	10	*1
E14	18.2	25	10.6	38	88	10	*1
E16	19.2	25	11.8	38	88	10	*1
E18	22.2	25	13	38	89	10	*1
E20	24.2	30	14.4	38	134	10	*2
E22	26.2	30	15.5	40	140	10	*2
E24	28.2	30	17	40	138	10	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251



14425-EPL

TORXPLUS® Sockets
Vasos TORXPLUS®

TORXplus®

14425-EPL (EPL)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
10EPL	14.5	25	6.2	38	86	10	*1
12EPL	17	25	7.2	38	86	10	*1
14EPL	18.2	25	8.1	38	88	10	*1
16EPL	20.7	25	9.1	38	88	10	*1
18EPL	22	25	10.2	40	90	10	*1
20EPL	24.5	30	11.2	42	135	10	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251



TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.
TORXplus® is a registered trademark of Acument Intellectual Properties, LLC.
TORXplus® es una marca registrada de Acument Intellectual Properties, LLC.

14400-WN Weld Nut Sockets



14400-WN	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
8WN	18.3	25	8	38	93	10	*1
9WN	19.5	25	9	38	93	10	*1
10WN	20.8	25	10	38	92	10	*1
12WN	24.5	30	12	38	139	10	*2
14WN	27	30	14	38	136	10	*2
17WN	32	30	17	40	150	10	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B ➡P250-251

14401LH LHS Sockets / Vasos LHS



14401LH (LH-S)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
6S	13	25	5.6	38	65	10	*1
8S	16.7	25	6.8	38	69	10	*1
10S	19.2	25	8	38	75	10	*1
12S	23	30	9.2	38	115	10	*2
14S	25.5	30	10.4	38	121	10	*2
16S	29.2	30	11.6	38	128	10	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B ➡P250-251

14301X 6-point Sockets, Semi-Deep / Vasos Hexagonales Madianos de pared Delgada

thin



	14301X (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
	8	13	24	8	42	60	72	10	*1
New	**9**	14.2	24	9	42	60	75	10	*1
	10	15.5	24	10	42	60	79	10	*1
	11	16.7	24	11	42	60	82	10	*1
	12	18	24	12	42	60	88	10	*1
	13	19.2	24	13	42	60	92	10	*1
	14	20.5	24	14	42	60	97	10	*1
	15	21.7	29	15	42	60	125	10	*2
	16	23	29	16	42	60	135	10	*2
	17	24.2	29	17	42	60	142	10	*2
	18	25.5	29	18	42	60	148	10	*2
	19	26.7	29	19	41	60	151	10	*2
	21	29.2	29	21	41	60	170	10	*2
	22	30.5	29	22	45	65	187	10	*2
	23	31.7	29	23	45	65	192	10	*2
	24	33	29	24	45	65	202	10	*2
New	**25**	34.2	29	25	44	65	210	10	*2
	26	35.5	29	26	44	65	218	10	*2
	27	36.7	29	27	44	65	231	10	*2
	30	40.5	29	30	44	65	268	10	*2
	32	43	29	32	44	65	296	10	*2
New	**33**	44.2	29	33	44	65	318	2	*2
New	**34**	45.5	29	34	44	65	330	2	*2
	36	48	29	36	44	65	350	2	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B ➡P250-251

RS14301X/10 Socket Set on Rail / Juego de Vasos en Regleta

thin

RS14301X/10	10 Pieces Set/Rail 300mm	(g)
	10, 12, 13, 14, 17, 19, 21, 22, 24, 27	1,585

LHstix® is a registered trademark of **OSG CORPORATION** System Engineering Department.
LHstix® es una marca registrada de **OSG CORPORATION** System Engineering Department.

14300M · 14300A

6-point Deep Sockets
Vasos Hexagonales Largos



14300M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
8	14.5	25	8	62	80	137	10	*1
9	15.7	25	9	62	80	138	10	*1
10	17	25	10	62	80	140	10	*1
11	18.2	25	11	62	80	156	10	*1
12	19.5	25	12	62	80	162	10	*1
13	20.7	25	13	62	80	162	10	*1
14	22	25	14	62	80	174	10	*1
15	23.2	30	15	62	80	220	10	*2
16	24.5	30	16	62	80	232	10	*2
17	25.7	30	17	62	80	232	10	*2
18	27	30	18	62	80	232	10	*2
19	28.2	30	19	61	80	240	10	*2
20	29.5	30	20	61	80	265	10	*2
21	30.7	30	21	61	80	265	10	*2
22	32	30	22	65	85	290	10	*2
23	33.2	30	23	65	85	300	10	*2
24	34.5	30	24	65	85	329	10	*2
25	35.7	30	25	65	85	345	10	*2
26	37	30	26	64	85	350	10	*2
27	38.2	30	27	64	85	385	10	*2
28	39.5	30	28	64	85	390	10	*2
29	40.7	30	29	63	85	416	10	*2
30	42	30	30	63	85	457	10	*2
31	43.2	30	31	63	85	505	10	*2
32	44.5	30	32	63	85	542	10	*2
33	45.7	30	33	62	85	562	2	*2
34	47	30	33	62	85	570	2	*2
35	48.2	30	35	62	85	600	2	*2
36	49.5	30	36	61	85	635	2	*2
New 38	52	30	38	60	85	655	2	*2
41	55.7	30	38	60	85	686	2	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

14300A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
5/16	14.5	25	8	62	80	137	10	*1
3/8	17	25	10	62	80	140	10	*1
7/16	18.2	25	11	62	80	156	10	*1
1/2	20.7	25	13	62	80	162	10	*1
9/16	22	25	14	62	80	174	10	*1
5/8	24.5	30	16	62	80	232	10	*2
11/16	25.7	30	17	62	80	232	10	*2
3/4	28.2	30	19	61	80	259	10	*2
13/16	30.7	30	21	61	80	265	10	*2
7/8	32	30	22	65	85	290	10	*2
15/16	34.5	30	24	65	85	329	10	*2
1	35.7	30	25	65	85	345	10	*2
1. 1/16	38.2	30	27	64	85	385	10	*2
1. 1/8	40.7	30	29	63	85	416	10	*2
1. 3/16	42	30	30	63	85	457	10	*2
1. 1/4	44.5	30	32	63	85	542	10	*2
1. 7/16	50.7	30	37	61	85	580	2	*2
1. 1/2	52	30	38	61	85	600	2	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

14301M · 14301A

thin

6-point Deep Sockets, Thin-walled
Vasos Hexagonales Largos de Pared Delgada



14301M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
8	13	24	8	62	80	87	10	*1
9	14.2	24	9	62	80	92	10	*1
10	15.5	24	10	62	80	98	10	*1
11	16.7	24	11	62	80	104	10	*1
12	18	24	12	62	80	111	10	*1
13	19.2	24	13	62	80	120	10	*1
14	20.5	24	14	62	80	127	10	*1
15	21.7	29	15	62	80	169	10	*2
16	23	29	16	62	80	173	10	*2
17	24.2	29	17	62	80	182	10	*2
18	25.5	29	18	62	80	192	10	*2
19	26.7	29	19	61	80	197	10	*2
20	28	29	20	61	80	203	10	*2
21	29.2	29	21	61	80	218	10	*2
22	30.5	29	22	65	85	244	10	*2
23	31.7	29	23	65	85	253	10	*2
24	33	29	24	65	85	261	10	*2
25	34.2	29	25	65	85	282	10	*2
26	35.5	29	26	64	85	299	10	*2
27	36.7	29	27	64	85	314	10	*2
28	38	29	29	64	85	273	10	*2
29	39.2	29	29	63	85	280	10	*2
30	40.5	29	30	63	85	360	10	*2
31	41.7	29	31	63	85	370	10	*2
32	43	29	32	63	85	380	10	*2
34	45.5	29	34	62	85	411	2	*2
35	46.7	29	35	62	85	450	2	*2
36	48	29	36	61	85	460	2	*2
New 38	50.5	29	38	61	85	508	2	*2
New 41	54.2	29	38	60	85	552	2	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

14301A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
3/8	15.5	24	10	62	80	98	10	*1
7/16	16.7	24	11	62	80	104	10	*1
1/2	19.2	24	13	62	80	120	10	*1
9/16	20.5	24	14	62	80	127	10	*1
5/8	23	29	16	62	80	173	10	*2
11/16	24.2	29	17	62	80	182	10	*2
3/4	26.7	29	19	61	80	197	10	*2
13/16	29.2	29	21	61	80	218	10	*2
7/8	30.5	29	22	65	85	244	10	*2
15/16	33	29	24	65	85	261	10	*2
1. 1/16	36.7	29	27	64	85	314	10	*2
New 1. 1/8	39.2	29	29	63	85	349	10	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

14305M

12-point Deep Sockets
Vasos Bihexagonales Largos



14305M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
8	14.5	25	8	62	80	137	10	*1
10	17	25	10	62	80	140	10	*1
11	18.2	25	11	62	80	156	10	*1
12	19.5	25	12	62	80	162	10	*1
13	20.7	25	13	62	80	162	10	*1
14	22	25	14	62	80	174	10	*1
15	23.2	30	15	62	80	220	10	*2
16	24.5	30	16	62	80	232	10	*2
17	25.7	30	17	62	80	232	10	*2
18	27	30	18	62	80	232	10	*2
19	28.2	30	19	61	80	259	10	*2
20	29.5	30	20	61	80	265	10	*2
21	30.7	30	21	61	80	265	10	*2
22	32	30	22	65	85	290	10	*2
New 23	33.2	30	23	65	85	300	10	*2
24	34.5	30	24	65	85	329	10	*2
New 26	37	30	26	64	85	350	10	*2
27	38.2	30	27	64	85	385	10	*2
28	39.5	30	30	64	85	390	10	*2
New 29	40.7	30	29	63	85	416	10	*2
30	42	30	30	63	85	457	10	*2
32	44.5	30	32	63	85	542	10	*2
New 33	45.7	30	33	62	85	562	2	*2
36	49.5	30	36	61	85	635	2	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

14306M

12-point Deep Sockets, Thin-Walled
Vasos Bihexagonales Largos de Pared Delgada

thin



14306M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
New 8	13	24	8	62	80	88	10	*1
10	15.5	24	10	62	80	98	10	*1
New 11	16.7	24	11	62	80	105	10	*1
12	18	24	12	62	80	111	10	*1
13	19.2	24	13	62	80	120	10	*1
14	20.5	24	14	62	80	127	10	*1
15	21.7	29	15	62	80	169	10	*2
16	23	29	16	62	80	173	10	*2
17	24.2	29	17	62	80	182	10	*2
18	25.5	29	18	62	80	192	10	*2
19	26.7	29	19	61	80	197	10	*2
21	29.2	29	21	61	80	218	10	*2
22	30.5	29	22	65	85	244	10	*2
24	33	29	24	65	85	261	10	*2
New 26	35.5	29	26	64	85	290	10	*2
27	36.7	29	27	64	85	314	10	*2
30	40.5	29	30	63	85	360	10	*2
32	43	29	32	63	85	380	10	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

14310M

Surface Drive Sockets, Deep
Vasos Surface Drive (de Contacto Curvo) Largos



14310M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
10	17	25	10	62	80	136	10	*1
11	18.2	25	11	62	80	148	10	*1
12	19.5	25	12	62	80	156	10	*1
13	20.7	25	13	62	80	158	10	*1
14	22	25	14	62	80	170	10	*1
15	23.2	30	15	62	80	225	10	*2
16	24.5	30	16	62	80	228	10	*2
17	25.7	30	17	62	80	232	10	*2
18	27	30	18	62	80	232	10	*2
19	28.2	30	19	61	80	252	10	*2
20	29.5	30	20	61	80	260	10	*2
21	30.7	30	21	61	80	260	10	*2
22	32	30	22	65	85	290	10	*2
New 23	33.2	30	23	65	85	300	10	*2
24	34.5	30	24	65	85	322	10	*2
25	35.7	30	25	65	85	338	10	*2
26	37	30	26	64	85	350	10	*2
27	38.2	30	27	64	85	380	10	*2
New 28	39.5	30	28	64	85	390	10	*2
30	42	30	30	63	85	450	10	*2
32	44.5	30	32	63	85	535	10	*2
34	47	30	34	62	85	563	2	*2
36	49.5	30	36	61	85	630	2	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

SURFACE DRIVE

Surface drive sockets are designed to retain contact with flat sides of nut to transmit high torque and reduce nut wear. These sockets are ideal for use on polished nuts, aluminum nuts and nuts with worn out points.

Los vasos de contacto curvo se diseñan para mantener el contacto con las caras planas de la tuerca y transmitir un alto par reduciendo el desgaste de la tuerca. Estos vasos son ideales para utilizarse en tuercas pulidas, tuercas de aluminio y tuercas con puntas gastadas

14300G

Impact Socket with Sliding Magnet
Vasos de Impacto con Imán Corredizo

14300G (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)t	L (mm)t	(g)	(pcs.)	
10	17	25	4.5	26	80	139	10	*1
12	19.5	25	6	26	80	165	10	*1
13	20.7	25	6.5	25	80	185	10	*1
14	22	25	7	24	80	189	10	*1
New **15**	23.2	30	7	24	80	240	10	*2
16	24.5	30	7.5	26.5	80	270	10	*2
17	25.7	30	8	26.5	80	272	10	*2
18	27	30	8.5	26.5	80	290	10	*2
19	28.2	30	9	27.5	80	308	10	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251



14365M

Pathfinder Sockets, Deep
Vasos Pathfinder (Guía) Largos

14365M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
10	17	25	8	62	80	138	10	*1
11	18.2	25	8	62	80	144	10	*1
12	19.5	25	9	62	80	165	10	*1
13	20.7	25	9	62	80	170	10	*1
14	22	25	11	62	80	178	10	*1
15	23.2	30	11	62	80	237	10	*2
16	24.5	30	11	62	80	245	10	*2
17	25.7	30	12	62	80	263	10	*2
18	27	30	13	62	80	268	10	*2
19	28.2	30	13	61	80	270	10	*2
20	29.5	30	14	61	80	274	10	*2
21	30.7	30	14	61	80	287	10	*2
22	32	30	15	65	85	314	10	*2
23	33.2	30	15	65	85	320	10	*2
24	34.5	30	15	65	85	335	10	*2
26	37	30	15	64	85	388	10	*2
27	38.2	30	16	64	85	407	10	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251



14325

TORX® Deep Sockets
Vasos TORX® Largos

14325 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
E10	14.2	25	8.2	62	80	136	10	*1
E12	15.2	25	9.3	62	80	141	10	*1
E14	18.2	25	10.6	62	80	147	10	*1
E16	19.2	25	11.8	62	80	151	10	*1
E18	22.2	25	13	62	80	218	10	*1
E20	24.2	30	14.4	62	80	225	10	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251



14440M · 14440A

Universal Sockets
Vasos con Articulación Universal

14440M (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
13	20.7	6	67.5	210	10	*1
14	22	7	69.5	210	10	*1
15	23.2	7	69.5	210	10	*1
16	24.5	8	69.5	206	10	*1
17	25.7	8	69.5	220	10	*1
18	27	9	69.5	218	10	*1
19	28.2	10	73.5	260	10	*1
20	29.5	10	73.5	270	10	*1
21	30.7	11	73.5	280	10	*1
22	32	13	73.5	290	10	*1
24	34.5	14	73.5	300	10	*1

14440A (inch)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
1/2	20.7	6	67.5	210	10	*1
9/16	22	7	69.5	210	10	*1
5/8	24.5	8	69.5	206	10	*1
11/16	25.7	8	69.5	220	10	*1
3/4	28.2	10	73.5	260	10	*1

*1 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251



TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

14012M-60

Inhex Sockets
Vasos Inhex



14012M.60 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
4	25	15.5	38	60	68	10	*1
5	25	15.5	38	60	71	10	*1
6	25	15.5	38	60	74	10	*1
7	25	15.5	38	60	80	10	*1
8	25	15.5	38	60	84	10	*1
10	30	15.5	38	60	140	10	*2
12	30	15.5	38	60	150	10	*2
14	30	15.5	38	60	170	10	*2
New **16**	30	15.5	38	60	180	10	*2
17	30	15.5	38	60	190	10	*2
19	30	15.5	38	60	210	10	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B ➡P250-251

RS14012M/10-L60

Socket Set on Rail
Juego de Vasos en Regleta

RS14012M/10-L60	10 Pieces Set/Rail 300mm	(g)
4, 5, 6, 7, 8, 10, 12, 14, 17, 19		1,300

14025-60 · -100

TORX® Bit Sockets
Vasos con Punta TORX®



14025.100 (T)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)	
T30	25	73.5	100	85	10	*1
T40	25	73.5	100	95	10	*1
T45	25	73.5	100	102	10	*1
T50	25	73.5	100	120	10	*1
T55	25	73.5	100	155	10	*1
T60	30	73.5	100	220	10	*2

14025.60 (T)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)	
T20	25	23.5	60	75	10	*1
T25	25	23.5	60	75	10	*1
T27	25	23.5	60	75	10	*1
T30	25	23.5	60	80	10	*1
T40	25	23.5	60	85	10	*1
T45	25	23.5	60	85	10	*1
T50	25	23.5	60	95	10	*1
T55	25	23.5	60	110	10	*1
T60	30	23.5	60	160	10	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B ➡P250-251

RS14025/6-L60

Socket Set on Rail
Juego de Vasos en Regleta

RS14025/6-L60	6 Pieces Set/Rail 200mm	(g)
T30, T40, T45, T50, T55,T60		650

14134

Impact Bit Holder
Porta-punta de Impacto



	D (mm)	L (mm)	(g)	(pcs.)	
14134	25	38	90	10	*1

*1 C-Ring=1402C, Pin/O-Ring=1402A/B ➡P250-251

Replacement Screw : M8×5, ⬢ 4mm

For DIN3126 E11.2 Bits



14142-F11.2

Impact Bit Holder (Quick Release)
Porta-punta de Impacto (Extracción Rápida)



	D₁ (mm)	D₂ (mm)	L (mm)	(g)	(pcs.)	
14142-F11.2	18.9	25	46	207	10	*1

*1 C-Ring=1402C, Pin/O-Ring=1402A/B ➡P250-251

For DIN3126 E11.2 Bits





TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

183H-35 · -75 · -150 Hex Bits / Puntas Hexagonales



	183H.35 (inch)	L (mm)	(g)	(pcs.)
New	3/16	35	15	10
New	7/32	35	16	10
New	1/4	35	18	10
New	5/16	35	20	10
New	3/8	35	26	10
New	7/16	35	28	10
New	1/2	35	38	10

	183H.35 (mm)	L (mm)	(g)	(pcs.)
	3	35	15	10
	4	35	15	10
	5	35	15	10
	6	35	18	10
New	7	35	19	10
	8	35	20	10
	10	35	26	10
New	11	35	28	10
	12	35	30	10
	14	35	35	10
New	16	35	47	10
New	17	35	50	10
New	18	35	53	10
New	19	35	56	10

	183H.75 (mm)	L (mm)	R (mm)	(g)	(pcs.)
	3	75	6.0	34	10
	4	75	6.0	35	10
	5	75	6.5	36	10
	6	75	7.5	39	10
New	7	75	8.5	44	10
	8	75	9.5	47	10
	10	75	–	57	10
New	11	75	–	60	10
	12	75	–	65	10
	14	75	–	79	10

	183H.150 (mm)	L (mm)	R (mm)	(g)	(pcs.)
New	4	150	6.0	51	10
New	5	150	6.5	55	10
New	6	150	7.5	65	10
New	8	150	9.5	87	10
New	10	150	–	118	10
New	12	150	–	136	10

183T-35 · -75 · -150 (T) TORX® Bits / Puntas TORX®



	183T.35 (T)	L (mm)	(g)	(pcs.)
New	T25	35	18	10
	T30	35	18	10
	T40	35	20	10
	T45	35	22	10
	T50	35	26	10
	T55	35	30	10
	T60	35	38	10

	183T.150 (T)	L (mm)	R (mm)	(g)	(pcs.)
New	T30	150	6.0	50	10
New	T40	150	6.9	58	10
New	T45	150	8.0	70	10
New	T50	150	9.0	82	10
New	T55	150	11.4	113	10

	183T.75 (T)	L (mm)	R (mm)	(g)	(pcs.)
	T30	75	6.0	35	10
	T40	75	6.9	37	10
	T45	75	8.0	41	10
	T50	75	9.0	45	10
	T55	75	11.4	55	10
	T60	75	13.5	67	10

183T-35 · -75 (IP) TORXPLUS® Bits / Puntas TORXPLUS®

TORXplus®



	183T.35 (IP)	L (mm)	(g)	(pcs.)
New	30IP	35	18	10
New	40IP	35	20	10
New	45IP	35	22	10
New	50IP	35	26	10
New	55IP	35	30	10
New	60IP	35	38	10

	183T.75 (IP)	L (mm)	R (mm)	(g)	(pcs.)
New	30IP	75	6.0	35	10
New	40IP	75	6.8	37	10
New	45IP	75	8.0	41	10
New	50IP	75	9.0	45	10
New	55IP	75	11.4	56	10
New	60IP	75	13.5	67	10

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.
TORXplus® is a registered trademark of Acument Intellectual Properties, LLC.
TORXplus® es una marca registrada de Acument Intellectual Properties, LLC.

183X-35 · -75 · -150 (XZN)

XZN Bits
Puntas XZN



	183X.35 (XZN)	L (mm)	(g)	(pcs.)
New	M 4	35	18	10
	M 5	35	18	10
	M 6	35	20	10
	M 8	35	22	10
	M10	35	26	10
	M12	35	30	10
	M14	35	38	10

	183X.75 (XZN)	L (mm)	R (mm)	(g)	(pcs.)
New	M 4	75	6.0	34	10
	M 5	75	6.0	34	10
	M 6	75	6.2	36	10
	M 8	75	7.4	39	10
	M10	75	9.8	54	10
	M12	75	11.7	57	10
	M14	75	13.5	67	10

	183X.150 (XZN)	L (mm)	R (mm)	(g)	(pcs.)
New	M 5	150	6.0	50	10
New	M 6	150	6.2	53	10
New	M 8	150	7.4	64	10
New	M10	150	9.8	93	10
New	M12	150	11.7	121	10

14134M-58 · -98

Hex Bit Sockets
Vasos con Punta Hexagonal

	14134M-58/-98 (mm)	D (mm)	H (mm)	L (mm)	L (mm)	R (mm)	L=58 (g)	L=98 (g)	L=58 (pcs.)	L=98 (pcs.)	
New	3	25	20.6	58	98	6.0	105	124	10	5	*1
New	4	25	20.6	58	98	6.0	105	125	10	5	*1
New	5	25	20.6	58	98	6.5	105	126	10	5	*1
New	6	25	20.6	58	98	7.5	108	129	10	5	*1
New	8	25	20.6	58	98	9.5	110	137	10	5	*1
New	10	25	20.6	58	98	–	116	147	10	5	*1
New	12	25	20.6	58	98	–	120	155	10	5	*1
New	14	25	20.6	58	98	–	125	169	10	5	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➔P250-251

14134T-58 · -98 (T)

TORX® Bit Sockets
Vasos con Punta TORX®



	14134T-58/-98 (T)	D (mm)	H (mm)	L (mm)	L (mm)	R (mm)	L=58 (g)	L=98 (g)	L=58 (pcs.)	L=98 (pcs.)	
New	T30	25	20.6	58	98	6.0	108	125	10	5	*1
New	T40	25	20.6	58	98	6.9	110	127	10	5	*1
New	T45	25	20.6	58	98	8.0	112	131	10	5	*1
New	T50	25	20.6	58	98	9.0	116	135	10	5	*1
New	T55	25	20.6	58	98	11.4	120	145	10	5	*1
New	T60	25	20.6	58	98	13.5	128	157	10	5	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➔P250-251

14134T-58 · -98 (IP)

TORXPLUS® Bit Sockets
Vasos con Punta TORXPLUS®

	14134T-58/-98 (IP)	D (mm)	H (mm)	L (mm)	L (mm)	R (mm)	L=58 (g)	L=98 (g)	L=58 (pcs.)	L=98 (pcs.)	
New	30IP	25	20.6	58	98	6.0	108	125	10	5	*1
New	40IP	25	20.6	58	98	6.8	110	127	10	5	*1
New	45IP	25	20.6	58	98	8.0	112	131	10	5	*1
New	50IP	25	20.6	58	98	9.0	116	135	10	5	*1
New	55IP	25	20.6	58	98	11.4	120	146	10	5	*1
New	60IP	25	20.6	58	98	13.5	128	159	10	5	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➔P250-251

14134X-58 · -98 (XZN)

XZN Bit Sockets
Vasos con Punta XZN

	14134X-58/-98 (XZN)	D (mm)	H (mm)	L (mm)	L (mm)	R (mm)	L=58 (g)	L=98 (g)	L=58 (pcs.)	L=98 (pcs.)	
New	M 5	25	20.6	58	98	6.0	108	124	10	5	*1
New	M 6	25	20.6	58	98	6.2	110	126	10	5	*1
New	M 8	25	20.6	58	98	7.4	112	129	10	5	*1
New	M10	25	20.6	58	98	9.8	116	144	10	5	*1
New	M12	25	20.6	58	98	11.7	120	149	10	5	*1
New	M14	25	20.6	58	98	13.5	128	159	10	5	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➔P250-251

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.
TORX PLUS® is a registered trademark of Acument Intellectual Properties, LLC.
TORX PLUS® es una marca registrada de Acument Intellectual Properties, LLC.

14106

Bit Holder for 107-16
Porta Punta

	D_1 (mm)	D_2 (mm)	L (mm)	(g)	(pcs.)	
14106	28	30	43	160	10	*1

*1 C-Ring=1402C, Pin/O-Ring=1402A/B ➡P250-251

Replacement Screw : M6x8, ⬢3mm



107-16

Bits for Inhex screws
Puntas para Tornillos Inhex





107.16 (mm)	L (mm)	(g)	(pcs.)
10	40	46	10
12	40	52	10
13	40	56	10
14	40	60	10
16	40	69	10
17	40	73	10
18	40	78	10
19	40	80	10
22	40	97	10

107.16 (inch)	L (mm)	(g)	(pcs.)
New **3/8**	40	45	10
1/2	40	56	10
9/16	40	60	10
5/8	40	69	10
3/4	40	80	10

107.16(L100) (mm)	L (mm)	R (mm)	(g)	(pcs.)
New **10**	100	13	122	10
New **12**	100	15	146	10
New **14**	100	–	166	10
New **17**	100	–	193	10
New **19**	100	–	232	10
New **22**	100	–	254	10

107-16 (T)

TORX® Bits
Puntas TORX®





107.16 (T)	L (mm)	(g)	(pcs.)
T55	50	57	10
T60	50	64	10
T70	50	73	10

107.16(L100) (T)	L (mm)	R (mm)	(g)	(pcs.)
New **T55**	100	11.4	108	10
New **T60**	100	13.4	130	10
New **T70**	100	15.7	159	10

107-16 (IP)

TORXPLUS® Bits
Puntas TORXPLUS®



107.16 (IP)	L (mm)	(g)	(pcs.)
55IP	50	57	10
60IP	50	64	10
70IP	50	73	10

107-16 (XZN)

XZN Bits
Puntas XZN





107.16 (XZN)	L (mm)	(g)	(pcs.)
M14	60	83	10
M16	60	93	10
M18	60	103	10

107.16(L100) (XZN)	L (mm)	R (mm)	(g)	(pcs.)
New **M14**	100	13.4	131	10
New **M16**	100	15.8	161	10
New **M18**	100	17.1	177	10

TORX® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX® es una marca registrada de **Acument Intellectual Properties, LLC.**
TORXplus® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORXplus® es una marca registrada de **Acument Intellectual Properties, LLC.**

14145M-100 · -150 · 200 · -250

Extra Long 12-point Sockets
Vasos Bihexagonales, Extra-Largos



14145M.100 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
10	17	25	10	100	155	1	*1
12	19.5	25	12	100	165	1	*1
14	22	25	14	100	180	1	*1
17	25.7	25	17	100	210	1	*1
19	28.2	25	19	100	230	1	*1

14145M.150 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
10	17	25	10	150	190	1	*1
12	19.5	25	12	150	204	1	*1
13	20.7	25	13	150	216	1	*1
14	22	25	14	150	228	1	*1
15	23.2	25	15	150	240	1	*1
16	24.5	25	16	150	245	1	*1
17	25.7	25	17	150	253	1	*1
18	27	25	18	150	260	1	*1
19	28.2	25	19	150	267	1	*1

14145M.200 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
10	17	25	10	200	234	1	*1
12	19.5	25	12	200	248	1	*1
13	20.7	25	13	200	260	1	*1
14	22	25	14	200	272	1	*1
15	23.2	25	15	200	284	1	*1
16	24.5	25	16	200	290	1	*1
17	25.7	25	17	200	297	1	*1
18	27	25	18	200	305	1	*1
19	28.2	25	19	200	311	1	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➡P250-251

14145M.250 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
10	17	25	10	250	278	1	*1
12	19.5	25	12	250	292	1	*1
13	20.7	25	13	250	304	1	*1
14	22	25	14	250	316	1	*1
15	23.2	25	15	250	328	1	*1
16	24.5	25	16	250	335	1	*1
17	25.7	25	17	250	341	1	*1
18	27	25	18	250	350	1	*1
19	28.2	25	19	250	355	1	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➡P250-251

14146M-150 · -200 · -250

Extra Long Universal Sockets
Vasos con Articulación Universal Extra-Largos



14146M.150 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
10	16	25	6.5	150	197	1	*1
12	19.3	25	7.5	150	200	1	*1
13	20	25	8	150	201	1	*1
14	21	25	8.5	150	203	1	*1
15	22	25	9	150	201	1	*1
16	23	25	9.5	150	200	1	*1
17	25	25	9.5	150	200	1	*1
18	26	25	11	150	210	1	*1
19	28	25	11.5	150	210	1	*1

14146M.200 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
10	16	25	6.5	200	241	1	*1
12	19.3	25	7.5	200	244	1	*1
13	20	25	8	200	245	1	*1
14	21	25	8.5	200	247	1	*1
15	22	25	9	200	245	1	*1
16	23	25	9.5	200	244	1	*1
17	25	25	9.5	200	244	1	*1
18	26	25	11	200	250	1	*1
19	28	25	11.5	200	254	1	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➡P250-251

14146M.250 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
10	16	25	6.5	250	285	1	*1
12	19.3	25	7.5	250	288	1	*1
13	20	25	8	250	289	1	*1
14	21	25	8.5	250	291	1	*1
15	22	25	9	250	289	1	*1
16	23	25	9.5	250	288	1	*1
17	25	25	9.5	250	288	1	*1
18	26	25	11	250	290	1	*1
19	28	25	11.5	250	299	1	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➡P250-251

14147M-150 · -200

Extra Long Universal Inhex Sockets
Vasos Inhex con Articulación Universal Extra-Largos



14147M.150 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
6	25	25	15	150	200	1	*1
8	25	25	15	150	205	1	*1
10	25	25	15	150	210	1	*1
12	25	25	15	150	217	1	*1

14147M.200 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
6	25	25	15	200	244	1	*1
8	25	25	15	200	249	1	*1
10	25	25	15	200	254	1	*1
12	25	25	15	200	261	1	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➡P250-251

14760-50 · -75 · -100 · -125 · -150 · -175 · -200 · -250

Extension Bars
Alargaderas





14760	D (mm)	L (mm)	(g)	(pcs.)	
50	30	50	150	10	*1
75	30	75	188	10	*1
100	30	100	240	10	*1
125	30	125	275	5	*1
150	30	150	300	5	*1
175	30	175	358	5	*1
200	30	200	405	5	*1
250	30	250	480	1	*1

*1 C-Ring=1402C, Pin/O-Ring=1402A/B ➡P250-251

14444AL

Adaptor (Quick Release)
Adaptador (Extracción Rápida)



	L (mm)	(g)	(pcs.)	
14444AL	60	128	5	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➡P250-251

Lock & Quick Release



14770

Universal Joint
Articulación Universal



	L (mm)	(g)	(pcs.)	
14770	74	210	5	*1
14770-B	74	210	5	*1
14770-P	74	210	5	*1
14771	65	198	5	*1
14771-B	65	198	5	*1
14771-P	65	198	5	*1

*1 C-Ring=1402C, Pin/O-Ring=1402A/B ➡P250-251

14771

Universal Joint
Articulación Universal







14772-P

Universal Double Joint
Articulación Universal





	D1 (mm)	D2 (mm)	L (mm)	(g)	(pcs.)	
14772-P	27	25	90	230	5	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➡P250-251

14433A Adaptor / Adaptador



	(sq.)	(sq.)	L (mm)	(g)	(pcs.)	
14433A	1/2"	3/8"	37.5	68	10	*1
14433A-B	1/2"	3/8"	37.5	68	10	*1
14433A-P	1/2"	3/8"	37.5	68	10	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➔P250-251

Adapting down to a smaller square drive may lead to excessive torque load and possibly cause breakage. Always stay within limit torque of the smaller square drive.

14455A Adaptor / Adaptador



	(sq.)	(sq.)	L (mm)	(g)	(pcs.)	
14455A	1/2"	5/8"	42	135	10	*1

*1 C-Ring=1402C, Pin/O-Ring=1402A/B ➔P250-251

14466A Adaptor / Adaptador



	(sq.)	(sq.)	L (mm)	(g)	(pcs.)	
14466A	1/2"	3/4"	44	146	10	*1
14466A-B	1/2"	3/4"	44	146	10	*1

*1 C-Ring=1402C, Pin/O-Ring=1402A/B ➔P250-251

14209M Socket Set / Juego de Vasos

New 14209M — 10 Pieces Set/=830g

METAL CASE: W190×H59×T45mm

Bits	Bit Holder
183H.35 Hex Bits 5, 6, 8, 10	**14134** Bit Holder
107.16 Hex Bits 12, 14, 17, 19	**14106** Bit Holder

14210M Socket Set / Juego de Vasos

New 14210M — 18 Pieces Set/=1,250g

METAL CASE: W310×H90×T48mm

Bits	Bit Holder
183H.35 Hex Bits 4, 5, 6, 7, 8, 10, 12, 14	**14134** Bit Holder
183H.75 Hex Bits 4, 5, 6, 7, 8, 10, 12, 14	**168H-4 (40)** Screwdriver

14210T Socket Set / Juego de Vasos

New 14210T — 14 Pieces Set/=1,080g

METAL CASE: W310×H90×T48mm

Bits	Bit Holder
183T.35 TORX® Bits T30, T40, T45, T50, T55, T60	**14134** Bit Holder
183T.75 TORX® Bits T30, T40, T45, T50, T55, T60	**168H-4 (40)** Screwdriver

14210X Socket Set / Juego de Vasos

New 14210X — 14 Pieces Set/=1,040g

METAL CASE: W310×H90×T48mm

Bits	Bit Holder
183X.35 XZN Bits M4, M5, M6, M8, M10, M12	**14134** Bit Holder
183X.75 XZN Bits M4, M5, M6, M8, M10, M12	**168H-4 (40)** Screwdriver

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

14207M ○ Socket Set / Juego de Vasos

14207M	10 Pieces Set/⚖=2,700g

METAL CASE:W310×H90×T48mm

Sockets
○ **14300M** 6-pt Deep Sockets 10, 12, 13, 14, 17, 19, 21, 22, 24, 27

14208M ○ Socket Set / Juego de Vasos

14208M	13 Pieces Set/⚖=3,500g

METAL CASE:W395×H90×T50mm

Sockets
○ **14300M** 6-pt Deep Sockets 10, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 24, 27

14241M ○ Socket Set / Juego de Vasos
14241M-05 ○

14241M	13 Pieces Set/⚖=2,000g

METAL CASE:W196×H100×T45mm

Sockets
○ **14400M** 6-pt. Sockets 10, 11, 12, 13, 14, 15, 16, 17, 19, 21, 22, 24, 27

14241M-05	13 Pieces Set/⚖=2,000g

METAL CASE:W196×H100×T45mm

Sockets
○ **14405M** 12-pt. Sockets 10, 11, 12, 13, 14, 15, 16, 17, 19, 21, 22, 24, 27

14242M ○ Socket Set / Juego de Vasos

14242M	12 Pieces Set/⚖=1,890g

METAL CASE:W310×H90×T48mm

Sockets
○ **14400M** 6-pt. Sockets 10, 11, 12, 13, 14, 15, 16, 17, 19, 21, 22, 27

14245M-6P ○ Socket Set / Juego de Vasos
14245M-12P ○

14245M-6P	18 Pieces Set/⚖=2,250g

METAL CASE:W310×H90×T48mm

Sockets	Accessories
○ **14400M** 6-pt.Sockets 10, 12, 13, 14, 16, 17, 18, 19, 21, 22, 24, 27	**14760-125** **14770** **1401A, 1402A** **1401B, 1402B**

14245M-12P	18 Pieces Set/⚖=2,250g

METAL CASE:W310×H90×T48mm

Sockets	Accessories
○ **14405M** 12-pt. Sockets 10, 12, 13, 14, 16, 17, 18, 19, 21, 22, 24, 27	**14760-125** **14770** **1401A, 1402A** **1401B, 1402B**

S14240M ○ Display Stand / Expositor

S14240M	14400M 98 Pieces Set/⚖=13,690g

DISPLAY STAND:W510×H150×T230mm

○ 10mm:8pcs	15mm:7pcs	22mm:6pcs
11mm:8pcs	16mm:7pcs	23mm:6pcs
12mm:8pcs	17mm:7pcs	24mm:6pcs
13mm:8pcs	19mm:7pcs	27mm:5pcs
14mm:8pcs	21mm:7pcs	

15400M

6-point Sockets
Vasos Hexagonales



15400M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
14	24	35	10	47.5	220	5	*1
17	27.8	35	12	47.5	225	5	*1
19	30.3	35	13	47.5	225	5	*1
21	32.8	35	15	47.5	225	5	*1
22	34	35	15	47.5	225	5	*1
23	35.4	35	16	47.5	225	5	*1
24	36.5	35	16	50.5	245	5	*1
26	39	35	16	50.5	260	1	*1

*1 Pin/O-Ring=1500A/B ➡P251

15400A

6-point Sockets
Vasos Hexagonales



15400A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
9/16	24	35	10	47.5	220	5	*1
5/8	26.5	35	11	47.5	225	5	*1
11/16	27.8	35	12	47.5	225	5	*1
3/4	30.3	35	13	47.5	225	5	*1
13/16	32.8	35	15	47.5	225	5	*1
7/8	34	35	15	47.5	225	5	*1
15/16	36.5	35	16	50.5	245	5	*1

*1 Pin/O-Ring=1500A/B ➡P251

15410M

Surface Drive Sockets
Vasos Surface Drive (de Contacto Curvo)



15410M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
14	24	35	10	47.5	220	5	*1
17	27.8	35	12	47.5	225	5	*1
19	30.3	35	13	47.5	225	5	*1
21	32.8	35	15	47.5	225	5	*1
22	34	35	15	47.5	225	5	*1
23	35.4	35	16	47.5	225	5	*1
24	36.5	35	16	50.5	245	5	*1
26	39	35	16	50.5	260	5	*1

*1 Pin/O-Ring=1500A/B ➡P251

SURFACE DRIVE

Surface drive sockets are designed to retain contact with flat sides of nut to transmit high torque and reduce nut wear. These sockets are ideal for use on polished nuts, aluminum nuts and nuts with worn out points.

Los vasos de contacto curvo se diseñan para mantener el contacto con las caras planas de la tuerca y transmitir un alto par reduciendo el desgaste de la tuerca. Estos vasos son ideales para utilizarse en tuercas pulidas, tuercas de aluminio y tuercas con puntas gastadas

15300M 6-point Deep Sockets / Vasos Hexagonales Largos

15300M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
14	24	35	14	71	90	295	2	*1
17	27.8	35	17	71	90	325	2	*1
19	30.3	35	19	71	90	350	2	*1
21	32.8	35	21	71	90	380	2	*1
22	34	35	22	71	90	390	2	*1

*1 Pin/O-Ring=1500A/B ➡P251



15310M Surface Drive Sockets, Deep / Vasos Surface Drive (de Contacto Curvo) Largos

15310M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
14	24	35	14	71	90	295	2	*1
17	27.8	35	17	71	90	325	2	*1
19	30.3	35	19	71	90	350	2	*1
21	32.8	35	21	71	90	380	2	*1
22	34	35	22	71	90	390	2	*1

*1 Pin/O-Ring=1500A/B ➡P251



15555AL Adaptor (Quick Release) / Adaptador (Extracción Rápida)

	L (mm)	(g)	(pce.)	
15555AL	70	310	1	*1

*1 Pin/O-Ring=1500A/B ➡P251

Lock & Quick Release



15770 Universal Joint / Articulación Universal

	L (mm)	(g)	(pce.)	
15770	88	420	1	*1

*1 Pin/O-Ring=1500A/B ➡P251



15544A Adaptor / Adaptador

	(sq.)	(sq.)	L (mm)	(g)	(pce.)	
15544A	5/8"	1/2"	46	165	1	*1
15544A-P	5/8"	1/2"	46	165	1	*1

*1 Pin/O-Ring=1500A/B ➡P251

⚠ Adapting down from bigger square drive to smaller square drive may lead to excessive torque load and possibly cause breakage. Always stay within safe torque of the smaller square drive.



15566A Adaptor / Adaptador

	(sq.)	(sq.)	L (mm)	(g)	(pce.)	
15566A	5/8"	3/4"	48	200	1	*1

*1 Pin/O-Ring=1500A/B ➡P251



16400M · 16400A

6-point Sockets
Vasos Hexagonales



16400A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
New 5/8	28.8	44	11	50	366	5	*1
11/16	30	44	12	50	355	5	*1
3/4	32.5	44	13	50	360	5	*1
13/16	35	44	15	50	374	5	*1
7/8	36.3	44	15	50	373	5	*1
15/16	38.8	44	16	50	370	5	*1
1	40	44	16	50	374	5	*1
1. 1/16	42.5	44	16	50	375	5	*1
1. 1/8	45	44	18	53	412	5	*1
1. 3/16	46.3	44	18	53	410	5	*1
1. 1/4	48.8	44	19	53	428	5	*1
1. 5/16	51.3	44	20	55	490	5	*1
1. 3/8	52.5	44	20	55	494	5	*1
1. 7/16	55	44	20	55	526	2	*1
1. 1/2	56.3	44	20	57	558	2	*1
1. 9/16	58.8	44	20	57	598	2	*1
1. 5/8	60	44	22	57	572	2	*1
1.11/16	62.5	44	23	62	720	2	*1
1. 3/4	65	44	23	62	757	2	*1
1.13/16	66.3	44	23	62	755	2	*1
1. 7/8	68.8	54	23	62	940	2	*2
1.15/16	70	54	23	62	912	2	*2
2	72.5	54	30	62	969	2	*2
2. 1/16	73.8	54	29	62	1011	2	*2
2. 1/8	76.3	54	29	62	1035	2	*2
2. 3/16	77.5	54	29	62	1056	2	*2
2. 1/4	80	54	32	65	1126	2	*2
2. 5/16	81.3	54	31	65	1163	2	*2
2. 3/8	83.8	54	31	65	1215	2	*2

16400M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
New 16	28.8	44	11	50	367	5	*1
17	30	44	12	50	355	5	*1
18	31.3	44	13	50	372	5	*1
19	32.5	44	13	50	360	5	*1
20	33.8	44	14	50	375	5	*1
21	35	44	15	50	374	5	*1
22	36.3	44	15	50	373	5	*1
23	37.5	44	16	50	373	5	*1
24	38.8	44	16	50	370	5	*1
25	40	44	16	50	374	5	*1
26	41.3	44	16	50	378	5	*1
27	42.5	44	16	50	375	5	*1
28	43.8	44	16	50	383	5	*1
29	45	44	18	53	412	5	*1
30	46.3	44	18	53	410	5	*1
31	47.5	44	18	53	426	5	*1
32	48.8	44	19	53	428	5	*1
33	50	44	20	55	470	5	*1
34	51.3	44	20	55	490	5	*1
35	52.5	44	20	55	494	5	*1
36	53.8	44	20	55	498	5	*1
37	55	44	20	55	526	2	*1
38	56.3	44	20	57	558	2	*1
39	57.5	44	20	57	579	2	*1
40	58.8	44	20	57	598	2	*1
41	60	44	22	57	572	2	*1
42	61.3	44	22	57	617	2	*1
43	62.5	44	23	62	720	2	*1
44	63.8	44	23	62	761	2	*1
45	65	44	23	62	757	2	*1
46	66.3	44	23	62	755	2	*1
47	67.5	54	23	62	805	2	*2
48	68.8	54	23	62	940	2	*2
49	70	54	23	62	912	2	*2
50	71.3	54	30	62	930	2	*2
52	73.8	54	29	62	1011	2	*2
54	76.3	54	29	62	1035	2	*2
55	77.5	54	29	62	1056	2	*2
56	78.8	54	29	62	1091	2	*2
57	80	54	32	65	1126	2	*2
58	81.3	54	31	65	1163	2	*2
59	82.5	54	31	65	1185	2	*2
60	83.8	54	31	65	1215	2	*2
65	90	54	30	65	1325	2	*2
70	96.3	54	34	70	1570	1	*2

*1 C-Ring=1600C, Pin/O-Ring=1601A/B
*2 C-Ring=1801C, Pin/O-Ring=1602A/B
➡P250-251

16405M · 16405A

12-point Sockets
Vasos Bihexagonales



16405A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
3/4	32.5	44	13	50	360	5	*1
13/16	35	44	15	50	374	5	*1
7/8	36.3	44	15	50	373	5	*1
15/16	38.8	44	16	50	370	5	*1
1	40	44	16	50	374	5	*1
1. 1/16	42.5	44	16	50	375	5	*1
1. 1/8	45	44	18	53	412	5	*1
1. 3/16	46.3	44	18	53	410	5	*1
1. 1/4	48.8	44	19	53	428	5	*1
1. 5/16	51.3	44	20	55	490	5	*1
1. 3/8	52.5	44	20	55	494	5	*1
1. 7/16	55	44	20	55	526	2	*1
1. 1/2	56.3	44	20	57	558	2	*1
1. 5/8	60	44	22	57	572	2	*1
1.11/16	62.5	44	23	62	720	2	*1
1. 3/4	65	44	23	62	757	2	*1
1. 7/8	68.8	54	23	62	940	2	*2
2	72.5	54	30	62	969	2	*2

16405M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
17	30	44	12	50	355	5	*1
18	31.3	44	13	50	372	5	*1
19	32.5	44	13	50	360	5	*1
20	33.8	44	14	50	375	5	*1
21	35	44	15	50	374	5	*1
22	36.3	44	15	50	373	5	*1
23	37.5	44	16	50	373	5	*1
24	38.8	44	16	50	370	5	*1
25	40	44	16	50	374	5	*1
26	41.3	44	16	50	378	5	*1
27	42.5	44	16	50	375	5	*1
28	43.8	44	16	50	383	5	*1
29	45	44	18	53	412	5	*1
30	46.3	44	18	53	410	5	*1
32	48.8	44	19	53	428	5	*1
33	50	44	20	55	470	5	*1
34	51.3	44	20	55	490	5	*1
36	53.8	44	20	55	498	5	*1
38	56.3	44	20	57	558	2	*1
41	60	44	22	57	572	2	*1
42	61.3	44	22	57	617	2	*1
46	66.3	44	23	62	755	2	*1
50	71.3	54	30	62	930	2	*2
52	73.8	54	29	62	1011	2	*2
55	77.5	54	29	62	1056	2	*2
60	83.8	54	31	65	1215	2	*2
65	90	54	30	65	1325	2	*2

*1 C-Ring=1600C, Pin/O-Ring=1601A/B
*2 C-Ring=1801C, Pin/O-Ring=1602A/B
➡P250-251

16401M · 16401A

6-point Sockets, Thin Walled
Vasos Hexagonales de Pared Delgada



16401M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
17	28	43	12	50	300	5	*1
18	29.3	43	13	50	300	5	*1
19	30.5	43	13	50	300	5	*1
20	31.8	43	14	50	302	5	*1
21	33	43	15	50	305	5	*1
22	34.3	43	15	50	310	5	*1
23	35.5	43	16	50	315	5	*1
24	36.8	43	16	50	325	5	*1
25	38	43	16	50	326	5	*1
26	39.3	43	16	50	330	5	*1
27	40.5	43	16	50	340	5	*1
28	41.8	43	16	50	345	5	*1
29	43	43	18	53	355	5	*1
30	44.3	43	18	53	365	5	*1
31	45.5	43	18	53	375	5	*1
32	46.8	43	19	53	385	5	*1
33	48	43	20	55	395	5	*1
34	49.3	43	20	55	420	5	*1
35	50.5	43	20	55	430	5	*1
36	51.8	43	20	55	440	5	*1
37	53	43	20	55	460	2	*1
38	54.3	43	20	57	472	2	*1
40	56.8	43	20	57	525	2	*1
41	58	43	22	57	555	2	*1
42	59.3	43	22	57	565	2	*1
New 43	60.5	43	23	62	662	2	*1
44	61.8	43	23	62	670	2	*1
New 45	63	43	23	62	700	2	*1
46	64.3	43	23	62	710	2	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

16401A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
11/16	28	43	12	50	300	5	*1
3/4	30.5	43	13	50	300	5	*1
13/16	33	43	15	50	305	5	*1
7/8	34.3	43	15	50	310	5	*1
15/16	36.8	43	16	50	325	5	*1
1	38	43	16	50	326	5	*1
1. 1/16	40.5	43	16	50	340	5	*1
1. 1/8	43	43	18	53	355	5	*1
1. 3/16	44.3	43	18	53	365	5	*1
1. 1/4	46.8	43	19	53	385	5	*1
1. 5/16	49.3	30	20	55	437	5	*1
1. 3/8	50.5	43	20	55	430	5	*1
1. 7/16	53	43	20	55	460	2	*1
1. 1/2	54.3	43	20	57	472	2	*1
1. 9/16	56.8	43	20	57	525	2	*1
1. 5/8	58	43	22	57	555	2	*1
1.13/16	64.3	43	23	62	710	2	*1
New 1. 7/8	66.8	53	23	62	868	2	*2

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

16410M

Surface Drive Sockets
Vasos Surface Drive (de Contacto Curvo)



16410M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
New 16	28.8	44	11	50	367	5	*1
New 17	30	44	12	50	355	5	*1
New 18	31.3	44	13	50	372	5	*1
New 19	32.5	44	13	50	360	5	*1
New 21	35	44	15	50	374	5	*1
New 22	36.3	44	15	50	373	5	*1
New 24	38.8	44	16	50	370	5	*1
New 27	42.5	44	16	50	375	5	*1
New 30	46.3	44	18	53	410	5	*1
New 32	48.8	44	19	53	428	5	*1
New 33	50	44	20	55	470	5	*1
New 36	53.8	44	20	55	498	5	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

16425

TORX® Sockets
Vasos TORX®



16425 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
E18	26.3	44	13	50	355	5	*1
E20	28.8	44	14.4	50	370	5	*1
E22	31.3	44	15.5	50	390	5	*1
E24	32.5	44	17	50	390	5	*1
E26	35	44	18.8	60	460	5	*1
E28	36.3	44	25.2	60	465	5	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➔P250-251

TORX® (E)



E		E4	E5	E6	E7	E8	E10	E11	E12	E14	E16	E18	E20	E22	E24	E26	E28
S1	(ref. mm)	3.7	4.6	5.6	6.1	7.4	9.3	9.9	11.0	12.8	14.6	16.5	18.3	20.1	22.0	23.7	25.5
S2	(ref. mm)	2.7	3.3	4.0	4.3	5.3	6.8	7.1	7.9	9.2	10.5	11.9	13.2	14.8	15.7	17.5	18.3

16425-EPL

TORXPLUS® Sockets
Vasos TORXPLUS®

TORXplus®



16425-EPL (EPL)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
24EPL	32.5	44	12.2	55	427	5	*1
32EPL	40	44	16.1	62	488	2	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➔P250-251

TORX® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX® es una marca registrada de **Acument Intellectual Properties, LLC.**
TORXplus® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORXplus® es una marca registrada de **Acument Intellectual Properties, LLC.**

16301X

6-point Semi-Deep Sockets, Thin Walled
Vasos Hexagonales Medianos de Pared Delgada

thin



16301X (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
17	28	43	17	49	75	370	2	*1
18	29.3	43	18	49	75	380	2	*1
19	30.5	43	19	49	75	393	2	*1
20	31.8	43	20	49	75	400	2	*1
21	33	43	21	49	75	408	2	*1
22	34.3	43	22	49	75	418	2	*1
23	35.5	43	23	49	75	425	2	*1
24	36.8	43	24	49	75	435	2	*1
25	38	43	25	49	75	449	2	*1
26	39.3	43	26	49	75	455	2	*1
27	40.5	43	27	48	75	464	2	*1
28	41.8	43	28	48	75	479	2	*1
29	43	43	29	48	75	489	2	*1
30	44.3	43	30	48	75	506	2	*1
31	45.5	43	31	47	75	518	2	*1
32	46.8	43	32	47	75	535	2	*1
33	48	43	33	47	75	548	2	*1
35	50.5	43	35	46	75	585	2	*1
36	51.8	43	36	46	75	603	2	*1
37	53	43	37	46	75	645	2	*1
38	54.3	43	38	50	80	691	2	*1
40	56.8	43	38	50	80	725	2	*1
41	58	43	38	49	80	755	2	*1
46	64.3	43	38	48	80	808	2	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

16300M · 16300A

6-point Sockets, Deep
Vasos Hexagonales Largos



	16300M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
New	**14**	26.3	44	14	74	100	497	2	*1
New	**16**	28.8	44	16	74	100	524	2	*1
	17	30	44	17	74	100	544	2	*1
	18	31.3	44	18	74	100	642	2	*1
	19	32.5	44	19	74	100	655	2	*1
	20	33.8	44	20	74	100	680	2	*1
	21	35	44	21	74	100	700	2	*1
	22	36.3	44	22	74	100	700	2	*1
	23	37.5	44	23	74	100	720	2	*1
	24	38.8	44	24	74	100	705	2	*1
	25	40	44	25	74	100	715	2	*1
	26	41.3	44	26	74	100	710	2	*1
	27	42.5	44	27	73	100	710	2	*1
	28	43.8	44	28	73	100	800	2	*1
	29	45	44	29	73	100	835	2	*1
	30	46.3	44	30	73	100	840	2	*1
	31	47.5	44	31	72	100	815	2	*1
	32	48.8	44	32	72	100	875	2	*1
	33	50	44	33	72	100	920	2	*1
	34	51.3	44	34	72	100	950	2	*1
	35	52.5	44	35	71	100	980	2	*1
	36	53.8	44	36	71	100	960	2	*1
	37	55	44	37	71	100	970	2	*1
	38	56.3	44	38	70	100	990	2	*1
New	**39**	57.5	44	38	70	100	1040	2	*1
	40	58.8	44	38	70	100	1060	2	*1
	41	60	44	38	69	100	1120	2	*1
	42	61.3	44	38	69	100	1153	2	*1
	43	62.5	44	38	69	100	1200	2	*1
	46	66.3	44	38	68	100	1305	2	*1
New	**48**	68.8	54	38	68	100	1480	2	*2
	50	71.3	54	61	–	100	1469	2	*2
	55	77.5	54	59	–	100	1620	2	*2
New	**60**	83.8	54	56	–	100	1835	2	*2

*1 C-Ring=1600C, Pin/O-Ring=1601A/B
*2 C-Ring=1801C, Pin/O-Ring=1602A/B ➡P250-251

16300A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
3/4	32.5	44	19	74	100	655	2	*1
13/16	35	44	21	74	100	700	2	*1
7/8	36.3	44	22	74	100	700	2	*1
15/16	38.8	44	24	74	100	705	2	*1
1	40	44	25	74	100	715	2	*1
1. 1/16	42.5	44	27	73	100	765	2	*1
1. 1/8	45	44	29	73	100	835	2	*1
1. 3/16	46.3	44	30	73	100	840	2	*1
1. 1/4	48.8	44	32	72	100	875	2	*1
1. 5/16	51.3	44	34	72	100	950	2	*1
1. 3/8	52.5	44	35	71	100	980	2	*1
1. 7/16	55	44	37	71	100	970	2	*1
1. 1/2	56.3	44	38	70	100	990	2	*1
1. 9/16	58.8	44	38	70	100	1060	2	*1
1. 5/8	60	44	38	69	100	1120	2	*1
1.11/16	62.5	44	38	69	100	1200	2	*1
1. 3/4	65	44	38	68	100	1284	2	*1
1.13/16	66.3	44	38	68	100	1305	2	*1
1. 7/8	68.8	54	38	67	100	1561	2	*2
2	72.5	54	60	–	100	1516	2	*2

*1 C-Ring=1600C, Pin/O-Ring=1601A/B
*2 C-Ring=1801C, Pin/O-Ring=1602A/B ➡P250-251

16301M · 16301A

6-point Deep Sockets, Thin Walled
Vasos Hexagonales Largos de Pared Delgada

thin



	16301M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
New	**16**	26.8	43	16	74	100	435	2	*1
	17	28	43	17	74	100	470	2	*1
	18	29.3	43	18	74	100	475	2	*1
	19	30.5	43	19	74	100	480	2	*1
	20	31.8	43	20	74	100	491	2	*1
	21	33	43	21	74	100	505	2	*1
	22	34.3	43	22	74	100	528	2	*1
	23	35.5	43	23	74	100	542	2	*1
	24	36.8	43	24	74	100	560	2	*1
	25	38	43	25	74	100	581	2	*1
	26	39.3	43	26	74	100	600	2	*1
	27	40.5	43	27	73	100	610	2	*1
	28	41.8	43	28	73	100	639	2	*1
	29	43	43	29	73	100	650	2	*1
	30	44.3	43	30	73	100	670	2	*1
	31	45.5	43	31	72	100	690	2	*1
	32	46.8	43	32	72	100	715	2	*1
	33	48	43	33	72	100	730	2	*1
	34	49.3	43	34	72	100	750	2	*1
	35	50.5	43	35	71	100	785	2	*1
	36	51.8	43	36	71	100	830	2	*1
	37	53	43	37	71	100	850	2	*1
	38	54.3	43	38	70	100	885	2	*1
New	**39**	55.5	43	38	70	100	908	2	*1
	40	56.8	43	38	70	100	925	2	*1
	41	58	43	38	69	100	970	2	*1
	42	59.3	43	38	69	100	990	2	*1
	46	64.3	43	38	68	100	1150	2	*1
New	**50**	69.2	53	62	–	100	1328	2	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

	16301A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
	11/16	28	43	17	74	100	470	2	*1
	3/4	30.5	43	19	74	100	480	2	*1
	13/16	33	43	21	74	100	505	2	*1
	7/8	34.3	43	22	74	100	528	2	*1
	15/16	36.8	43	24	74	100	560	2	*1
	1	38	43	25	74	100	581	2	*1
	1. 1/16	40.5	43	27	73	100	610	2	*1
	1. 1/8	43	43	29	73	100	650	2	*1
	1. 3/16	44.3	43	30	73	100	670	2	*1
	1. 1/4	46.8	43	32	72	100	715	2	*1
New	**1. 5/16**	49.3	43	34	72	100	790	2	*1
	1. 3/8	50.5	43	35	71	100	785	2	*1
	1. 7/16	53	43	37	71	100	850	2	*1
	1. 1/2	54.3	43	38	70	100	885	2	*1
	1. 9/16	56.8	43	38	70	100	925	2	*1
	1. 5/8	58	43	38	69	100	970	2	*1
	1.13/16	64.3	43	38	68	100	1150	2	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

16305M

12-point Sockets, Deep
Vasos Bihexagonales Largos



	16305M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
	14	26.3	44	14	74	100	500	2	*1
New	**16**	28.8	44	16	74	100	522	2	*1
	17	30	44	17	74	100	544	2	*1
New	**18**	31.3	44	18	74	100	600	2	*1
	19	32.5	44	19	74	100	655	2	*1
	21	35	44	21	74	100	700	2	*1
	22	36.3	44	22	74	100	700	2	*1
	23	37.5	44	23	74	100	720	2	*1
	24	38.8	44	24	74	100	715	2	*1
	26	41.3	44	26	74	100	760	2	*1
	27	42.5	44	27	73	100	765	2	*1
	28	43.8	44	28	73	100	800	2	*1
	29	45	44	29	73	100	835	2	*1
	30	46.3	44	30	73	100	840	2	*1
	32	48.8	44	32	72	100	875	2	*1
New	**33**	50	44	33	72	100	920	2	*1
New	**34**	51.3	44	34	72	100	950	2	*1
	35	52.5	44	35	71	100	980	2	*1
	36	53.8	44	36	71	100	960	2	*1
	38	56.3	44	38	70	100	990	2	*1
	41	60	44	38	69	100	1120	2	*1
	46	66.3	44	38	68	100	1305	2	*1
New	**50**	71.3	54	61	–	100	1469	2	*2

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

16310M

Surface Drive Sockets, deep
Vasos Surface Drive (de Contacto Curvo) Largos



	16310M	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
New	**16**	28.8	44	16	74	100	524	2	*1
New	**17**	30	44	17	74	100	544	2	*1
New	**18**	31.3	44	18	74	100	642	2	*1
New	**19**	32.5	44	19	74	100	655	2	*1
New	**21**	35	44	21	74	100	700	2	*1
New	**22**	36.3	44	22	74	100	700	2	*1
New	**24**	38.8	44	24	74	100	705	2	*1
New	**27**	42.5	44	27	73	100	710	2	*1
New	**30**	46.3	44	30	73	100	840	2	*1
New	**32**	48.8	44	32	72	100	875	2	*1
New	**33**	50	44	33	72	100	920	2	*1
New	**36**	53.8	44	34	71	100	960	2	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

16325

TORX® Deep Sockets
Vasos TORX® Largos



	16325 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
	E18	26.3	44	13	74	100	520	2	*1
	E20	28.8	44	14.4	74	100	560	2	*1
	E22	31.3	44	15.5	74	100	600	2	*1
	E24	32.5	44	17	74	100	630	2	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

16106 Bit Holder, For 107-16 Porta Punta



	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
16106	32	44	16	52	370	2	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

Replacement Screw : M6x10, ⬢3mm

107-16 Bits for Inhex Screws Puntas para Tornillos Inhex



	107.16 (mm)	L (mm)	L (mm)	L=40 (g)	L=100 (g)	(pcs.)
New	**10**	40	100	46	122	10
New	**12**	40	100	52	146	10
	13	40	–	56	–	10
New	**14**	40	100	60	166	10
	16	40	–	69	–	10
New	**17**	40	100	73	193	10
	18	40	–	78	–	10
New	**19**	40	100	80	232	10
New	**22**	40	100	97	254	10

	107.16 (inch)	L (mm)	(g)	(pcs.)
New	**3/8**	40	45	10
	1/2	40	56	10
	9/16	40	60	10
	5/8	40	69	10
	3/4	40	80	10

107-16 (T) TORX® Bits Puntas TORX®



	107.16 (T)	L (mm)	L (mm)	L=50 (g)	L=100 (g)	(pcs.)
New	**T55**	50	100	57	108	10
New	**T60**	50	100	64	130	10
New	**T70**	50	100	73	159	10

107-16 (IP) TORXPLUS® Bits Puntas TORXPLUS®



	107.16 (IP)	L (mm)	(g)	(pcs.)
	55IP	50	57	10
	60IP	50	64	10
	70IP	50	73	10

107-16 (XZN) XZN Bits Puntas XZN



	107.16 (XZN)	L (mm)	L (mm)	L=60 (g)	L=100 (g)	(pcs.)
New	**M14**	60	100	83	131	10
New	**M16**	60	100	93	161	10
New	**M18**	60	100	103	177	10

16106-16 Hex Bit Sockets Vasos con Punta Hexagonal



16106.16 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)	
10	44	24	76	416	2	*1
12	44	24	76	422	2	*1
13	44	24	76	426	2	*1
14	44	24	76	430	2	*1
16	44	24	76	439	2	*1
17	44	24	76	443	2	*1
18	44	24	76	448	2	*1
19	44	24	76	450	2	*1
22	44	24	76	473	2	*1

16106.16 (inch)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)	
1/2	44	24	76	426	2	*1
9/16	44	24	76	430	2	*1
5/8	44	24	76	439	2	*1
3/4	44	24	76	450	2	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

TORX® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX® es una marca registrada de **Acument Intellectual Properties, LLC.**
TORX Koken is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX Koken es una marca registrada de **Acument Intellectual Properties, LLC.**

16107-22 Hex Bit Sockets / Vasos con Punta Hexagonal

16107.22 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)	
19	44	28	88	670	2	*1
22	44	28	88	692	2	*1
24	44	28	88	706	2	*1
27	44	28	88	730	2	*1
30	44	28	88	757	2	*1
32	44	28	93	783	2	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251



16107 Bit Holder / Porta Punta

	D_1 (mm)	D_2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
16107	44	44	22	60	530	2	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

Replacement Screw : M8x14, ⬢4mm



107-22 Bits for Inhex Screws / Puntas para Tormillos Inhex

107.22 (mm)	L (mm)	(g)	(pcs.)
17	50	120	10
19	50	140	10
22	50	162	10
24	50	176	10
27	50	200	10
30	50	227	10
32	55	243	10

107.22 (inch)	L (mm)	(g)	(pcs.)
5/8	50	120	10
3/4	50	140	10
7/8	50	162	10
1	50	190	10
1. 1/4	55	243	10



107-22 (T) TORX® Bits / Puntas TORX®

107.22 (T)	L (mm)	(g)	(pcs.)
T 80	60	141	10
T 90	60	155	10
T100	60	170	10



16760-150 · -175 · -200 · -250 · -330

Extension Bars
Alargaderas

16760	D (mm)	L (mm)	(g)	(pce.)	
150	44	150	775	1	*1
175	44	175	870	1	*1
200	44	200	955	1	*1
250	44	250	1150	1	*1
330	44	330	1460	1	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

16666AL
Adaptor (Quick Release)
Adaptador (Extracción Rápida)



	L (mm)	(g)	(pcs.)	
16666AL	75	660	2	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

Lock & Quick Release



16770
Universal Joint
Articulación Universal



16771
Universal Joint
Articulación Universal



	L (mm)	(g)	(pce.)	
16770	106	790	1	*1
16771	95	720	1	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251





16644A · 16655A
Adaptors
Adaptadores

No Warranty
Sin Garantía



	□ (sq.)	◻ (sq.)	L (mm)	(g)	(pcs.)	
16644A	3/4"	1/2"	54	310	5	*1
16644A-B	3/4"	1/2"	54	310	5	*1
16644A-P	3/4"	1/2"	54	310	5	*1

	□ (sq.)	◻ (sq.)	L (mm)	(g)	(pcs.)	
16655A	3/4"	5/8"	55.5	336	5	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

⚠ Adapting down to a smaller square drive may lead to excessive torque load and possibly cause breakage. Always stay within limit torque of the smaller square drive.

16688A
Adaptor
Adaptador



	□ (sq.)	◻ (sq.)	L (mm)	(g)	(pce.)	
16688A	3/4"	1"	62	435	1	*1
16688A-250	3/4"	1"	250	1400	1	*1
16688A-330	3/4"	1"	330	1880	1	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

16688A-250 · -330
Adaptors
Adaptadores

16201M · 16201A

Socket Sets
Juegos de Vasos

16201M 13 Pieces Set/△=6,800g
METAL CASE:W320×H110×T70mm

Sockets
16400M 6-pt. Sockets 19, 21, 22, 23, 24, 26, 27, 30, 32, 33, 36, 38, 41

16201A 11 Pieces Set/△=6,000g
METAL CASE:W320×H110×T70mm

Sockets
16400A 6-pt. Sockets 3/4, 7/8, 15/16, 1, 1.1/16, 1.1/8, 1.1/4, 1.5/16, 1.3/8, 1.7/16, 1.1/2

16201M-01 · 16201A-01

Sockets Sets
Juegos de Vasos

thin

16201M-01 13 Pieces Set/△=6,000g
METAL CASE:W320×H110×T70mm

Sockets
16401M 6-pt. Sockets, Thin-walled 19, 21, 22, 23, 24, 26, 27, 30, 32, 33, 36, 38, 41

16201A-01 11 Pieces Set/△=5,400g
METAL CASE:W320×H110×T70mm

Sockets
16401A 6-pt. Sockets, Thin-walled 3/4, 7/8, 15/16, 1, 1.1/16, 1.1/8, 1.1/4, 1.5/16, 1.3/8, 1.7/16, 1.1/2

16245M

Socket Sets
Juegos de Vasos

16245M 17 Pieces Set/△=12,000g
METAL CASE:W590×H227×T72mm

Sockets	Accessories
16400M 6-pt. Sockets 19, 21, 22, 24, 27, 29, 30, 32, 33, 35, 36, 38, 41, 46, 50	**16760-175** **16760-330**

18400M · 18400A

6-point Sockets
Vasos Hexagonales



18400M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
17	32.8	54	12	57	579	2	*1
18	34	54	13	57	586	2	*1
19	35.3	54	13	57	590	2	*1
New **20**	36.5	54	14	57	600	2	*1
21	37.8	54	15	57	605	2	*1
22	39	54	15	57	620	2	*1
23	40.3	54	16	57	615	2	*1
24	41.5	54	16	57	627	2	*1
25	42.8	54	16	57	620	2	*1
26	44	54	16	57	640	2	*1
27	45.3	54	16	57	627	2	*1
28	46.5	54	16	57	640	2	*1
29	47.8	54	18	57	657	2	*1
30	49	54	21	62	657	2	*1
31	50.3	54	21	62	687	2	*1
32	51.5	54	21	62	685	2	*1
33	52.8	54	21	62	685	2	*1
34	54	54	21	62	690	2	*1
35	55.3	54	21	62	710	2	*1
36	56.5	54	21	62	712	2	*1
37	57.8	54	21	62	735	2	*1
38	59	54	25	66	720	2	*1
New **39**	60.3	54	25	66	820	2	*1
40	61.5	54	25	66	850	2	*1
41	62.8	54	25	66	850	2	*1
42	64	54	25	66	905	2	*1
43	65.3	54	27	68	977	2	*1
44	66.5	54	27	68	970	2	*1
45	67.8	54	27	68	963	2	*1
46	69	54	29	70	1010	2	*1
47	70.3	54	36	70	997	2	*1
48	71.5	54	35	70	990	2	*1
New **49**	72.8	54	36	70	1020	2	*1
50	74	54	35	70	1065	2	*1
New **51**	75.3	54	36	70	1100	2	*1
52	76.5	54	40	75	1185	2	*1
54	79	54	40	75	1252	2	*1
55	80.3	54	39	75	1260	2	*1
56	81.5	54	39	75	1277	2	*1
New **57**	82.8	54	40	75	1300	2	*1
58	84	54	39	75	1340	2	*1
60	86.5	54	39	75	1400	2	*1
62	89	54	38	75	1410	2	*1
63	90.3	54	38	75	1383	2	*1
New **64**	91.5	54	37	75	1580	2	*1
65	92.8	54	38	75	1630	2	*1
New **66**	94	54	36	75	1580	2	*1
67	95.3	54	38	75	1580	2	*1
68	96.5	54	37	75	1583	1	*1
70	99	54	37	75	1625	1	*1
New **74**	104	86	38	80	2650	1	*2
75	105.3	86	37	80	2675	1	*2
New **77**	107.8	86	37	80	2890	1	*2
New **78**	109	86	42	85	2900	1	*2
80	111.5	86	41	85	2996	1	*2
85	117.8	86	37	90	3378	1	*2
90	124	86	40	95	3871	1	*2
95	130.3	86	43	100	4500	1	*2
100	136.5	86	47	105	5000	1	*2

*1 C-Ring=1801C, Pin/O-Ring=1801A/B
*2 C-Ring=1802C, Pin/O-Ring=1802A/B
➡P250-251

18400A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
11/16	32.8	54	12	57	579	2	*1
3/4	35.3	54	13	57	590	2	*1
13/16	37.8	54	15	57	605	2	*1
7/8	39	54	15	57	620	2	*1
15/16	41.5	54	16	57	627	2	*1
1	42.8	54	16	57	620	2	*1
1. 1/16	45.3	54	16	57	627	2	*1
New **1. 3/32**	46.5	54	16	57	642	2	*1
1. 1/8	47.8	54	18	57	657	2	*1
1. 3/16	49	54	21	62	657	2	*1
1. 1/4	51.5	54	21	62	685	2	*1
New **1. 9/32**	52.8	54	21	62	692	2	*1
1. 5/16	54	54	21	62	690	2	*1
1. 3/8	55.3	54	21	62	710	2	*1
1. 7/16	57.8	54	21	62	735	2	*1
New **1.15/32**	57.8	54	21	62	730	2	*1
1. 1/2	59	54	25	66	720	2	*1
1. 9/16	61.5	54	25	66	850	2	*1
1. 5/8	62.8	54	25	66	850	2	*1
1.11/16	65.3	54	27	68	977	2	*1
1. 3/4	67.8	54	27	68	963	2	*1
1.13/16	69	54	29	70	1010	2	*1
1. 7/8	71.5	54	35	70	990	2	*1
1.15/16	72.8	54	35	70	1000	2	*1
2	75.3	54	35	70	1060	2	*1
2. 1/16	76.5	54	40	75	1185	2	*1
2. 1/8	79	54	40	75	1252	2	*1
2. 3/16	80.3	54	39	75	1260	2	*1
2. 1/4	82.8	54	39	75	1337	2	*1
2. 5/16	84	54	39	75	1340	2	*1
2. 3/8	86.5	54	39	75	1400	2	*1
2. 7/16	89	54	38	75	1410	2	*1
2. 1/2	91.5	54	38	75	1498	2	*1
2. 9/16	92.8	54	38	75	1630	2	*1
2. 5/8	95.3	54	38	75	1580	2	*1
2.11/16	96.5	54	37	75	1583	1	*1
2. 3/4	99	54	37	75	1625	1	*1
2.13/16	101.5	86	37	80	2705	1	*2
2. 7/8	102.8	86	38	80	2629	1	*2
2.15/16	105.3	86	37	80	2675	1	*2
3	106.5	86	37	80	2705	1	*2
3. 1/16	109	86	42	85	2967	1	*2
3. 1/8	111.5	86	41	85	2996	1	*2
3. 1/4	115.3	86	44	90	3328	1	*2
3. 3/8	119	86	36	90	3389	1	*2
3. 1/2	124	86	40	95	3871	1	*2
New **3. 3/4**	130.3	86	43	100	4377	1	*2
New **3. 7/8**	135.3	86	47	105	5000	1	*2
New **4**	137.8	86	46	105	5152	1	*2

*1 C-Ring=1801C, Pin/O-Ring=1801A/B
*2 C-Ring=1802C, Pin/O-Ring=1802A/B
➡P250-251

18401M · 18401A

6-point Sockets, Thin Walled
Vasos Hexagonales de Pared Delgada



	18401M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
	17	29.8	53	12	57	481	2	*1
New	18	31	53	13	57	488	2	*1
	19	32.3	53	13	57	492	2	*1
New	20	33.5	53	14	57	505	2	*1
	21	34.8	53	15	57	512	2	*1
	22	36	53	15	57	520	2	*1
	24	38.5	53	16	57	520	2	*1
New	26	41	53	16	57	533	2	*1
	27	42.3	53	16	57	540	2	*1
New	29	44.8	53	18	57	560	2	*1
	30	46	53	21	62	572	2	*1
	32	48.5	53	21	62	600	2	*1
	33	49.8	53	21	62	613	2	*1
	35	52.3	53	21	62	630	2	*1
	36	53.5	53	21	62	635	2	*1
	38	56	53	25	66	705	2	*1
New	40	58.5	53	25	66	725	2	*1
	41	59.8	53	25	66	740	2	*1
New	42	61	53	25	66	803	2	*1
New	43	62.3	53	27	68	835	2	*1
New	45	64.8	53	27	68	888	2	*1
	46	66	53	29	70	900	2	*1
New	47	67.3	53	36	70	915	2	*1
	50	71	53	35	70	940	2	*1

18401A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
11/16	29.8	53	12	57	481	2	*1
3/4	32.3	53	13	57	492	2	*1
13/16	34.8	53	15	57	512	2	*1
7/8	36	53	15	57	520	2	*1
15/16	38.5	53	16	57	520	2	*1
1 1/16	42.3	53	16	57	540	2	*1
1 3/16	46	53	21	62	572	2	*1
1 1/4	48.5	53	21	62	600	2	*1
1 3/8	52.3	53	21	62	630	2	*1
1 1/2	56	53	25	66	705	2	*1
1 5/8	59.8	53	25	66	740	2	*1
1.13/16	66	53	29	70	900	2	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

18405M · 18405A

12-point Sockets
Vasos Bihexagonales



	18405M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
New	24	41.5	54	16	57	627	2	*1
	27	45.3	54	16	57	607	2	*1
	30	49	54	21	62	657	2	*1
	32	51.5	54	21	62	685	2	*1
	33	52.8	54	21	62	690	2	*1
	35	55.3	54	21	62	690	2	*1
	36	56.5	54	21	62	692	2	*1
	38	59	54	25	66	700	2	*1
	40	61.5	54	25	66	830	2	*1
	41	62.8	54	25	66	905	2	*1
	46	69	54	29	70	990	2	*1
	50	74	54	35	70	1021	2	*1
	55	80.3	54	39	75	1234	2	*1
	56	81.5	54	39	75	1250	2	*1
	60	86.5	54	39	75	1400	2	*1
	65	92.8	54	38	75	1600	2	*1
New	70	99	54	37	75	1625	1	*1
New	75	105.3	86	37	80	2675	1	*2
New	80	111.5	86	41	85	2996	1	*2

18405A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
3/4	35.3	54	13	57	590	2	*1
7/8	39	54	15	57	620	2	*1
1	42.8	54	16	57	620	2	*1
1 1/8	47.8	54	18	57	660	2	*1
1 3/16	49	54	21	62	660	2	*1
1 1/4	51.5	54	21	62	690	2	*1
1 3/8	55.3	54	21	62	710	2	*1
1 7/16	57.8	54	21	62	735	2	*1
1 1/2	59	54	25	66	720	2	*1
1 3/4	67.8	54	27	68	970	2	*1
1.15/16	72.8	54	35	70	1000	2	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

18410M

Surface Drive Sockets
Vasos Surface Drive (de Contacto Curvo)



	18410M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
New	24	41.5	54	16	57	627	2	*1
New	27	45.3	54	16	57	627	2	*1
New	30	49	54	21	62	657	2	*1
New	32	51.5	54	21	62	685	2	*1
New	33	52.8	54	21	62	685	2	*1
New	36	56.5	54	21	62	712	2	*1
New	41	62.8	54	25	66	850	2	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

18301X

6-point Semi-Deep Sockets, Thin Walled
Vasos Hexagonales Medianos de Pared Delgada

thin



18301X (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
17	29.8	53	17	48	80	635	2	*1
19	32.3	53	19	48	80	655	2	*1
21	34.8	53	21	48	80	680	2	*1
22	36	53	22	48	80	686	2	*1
24	38.5	53	24	48	80	693	2	*1
27	42.3	53	27	48	80	745	2	*1
30	46	53	30	48	80	761	2	*1
32	48.5	53	32	53	85	770	2	*1
33	49.8	53	33	53	85	781	2	*1
35	52.3	53	35	53	85	800	2	*1
36	53.5	53	36	52	85	808	2	*1
38	56	53	38	52	85	865	2	*1
41	59.8	53	38	51	85	937	2	*1
46	66	53	38	50	85	1032	2	*1
50	71	53	55	–	85	1220	2	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

18300M · 18300A

6-point Sockets, Deep
Vasos Hexagonales Largos



18300M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
New **17**	32.8	54	17	77	108	1000	2	*1
19	35.3	54	19	77	108	1010	2	*1
New **21**	37.8	54	21	77	108	1010	2	*1
22	39	54	22	77	108	1010	2	*1
23	40.3	54	26	77	108	1063	2	*1
24	41.5	54	24	77	108	1060	2	*1
25	42.8	54	25	77	108	1085	2	*1
26	44	54	26	77	108	1133	2	*1
27	45.3	54	27	77	108	1125	2	*1
28	46.5	54	28	77	108	1140	2	*1
29	47.8	54	29	77	108	1120	2	*1
30	49	54	30	77	108	1179	2	*1
31	50.3	54	31	77	108	1125	2	*1
32	51.5	54	32	77	108	1200	2	*1
33	52.8	54	33	77	108	1200	2	*1
34	54	54	34	77	108	1280	2	*1
35	55.3	54	35	77	108	1300	2	*1
36	56.5	54	36	76	108	1280	2	*1
37	57.8	54	37	76	108	1320	2	*1
38	59	54	38	76	108	1423	2	*1
40	61.5	54	38	75	108	1415	2	*1
41	62.8	54	38	75	108	1450	2	*1
42	64	54	38	75	108	1550	2	*1
44	66.5	54	38	74	108	1636	2	*1
45	67.8	54	38	74	108	1660	2	*1
46	69	54	38	74	108	1680	2	*1
48	71.5	54	67	–	108	1500	2	*1
50	74	54	66	–	108	1650	2	*1
52	76.5	54	65	–	108	1770	2	*1
55	80.3	54	63	–	108	1855	2	*1
60	86.5	54	60	–	108	2047	2	*1
65	92.8	54	58	–	108	2310	2	*1
70	99	54	55	–	108	2440	1	*1
75	105.3	86	52	–	108	3646	1	*2
80	111.5	86	49	–	108	4039	1	*2
85	117.8	86	59	–	108	4000	1	*2
90	124	86	57	–	108	4200	1	*2
95	130.3	86	55	–	108	4400	1	*2

*1 C-Ring=1801C, Pin/O-Ring=1801A/B
*2 C-Ring=1802C, Pin/O-Ring=1802A/B ➡P250-251

18300A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
11/16	32.8	54	17	77	108	978	2	*1
3/4	35.3	54	19	77	108	1010	2	*1
7/8	39	54	22	77	108	1010	2	*1
15/16	41.5	54	24	77	108	1060	2	*1
1	42.8	54	25	77	108	1085	2	*1
1. 1/16	45.3	54	27	77	108	1125	2	*1
1. 1/8	47.8	54	29	77	108	1120	2	*1
1. 3/16	49	54	30	77	108	1179	2	*1
1. 1/4	51.5	54	32	77	108	1200	2	*1
1. 5/16	54	54	34	77	108	1280	2	*1
1. 3/8	55.3	54	35	77	108	1300	2	*1
1. 7/16	57.8	54	37	76	108	1320	2	*1
1. 1/2	59	54	38	76	108	1423	2	*1
1. 9/16	61.5	54	38	75	108	1415	2	*1
1. 5/8	62.8	54	38	75	108	1450	2	*1
1.11/16	65.3	54	38	74	108	1577	2	*1
1. 3/4	67.8	54	38	74	108	1660	2	*1
1.13/16	69	54	38	74	108	1680	2	*1
1. 7/8	71.5	54	67	–	108	1500	2	*1
1.15/16	72.8	54	67	–	108	1570	2	*1
2	75.3	54	66	–	108	1605	2	*1
2. 1/16	76.5	54	65	–	108	1770	2	*1
2. 1/8	79	54	64	–	108	1812	2	*1
2. 3/16	80.3	54	63	–	108	1855	2	*1
2. 1/4	82.8	54	62	–	108	1916	2	*1
2. 5/16	84	54	61	–	108	1987	2	*1
2. 3/8	86.5	54	60	–	108	2047	2	*1
2. 7/16	89	54	59	–	108	2041	2	*1
2. 1/2	91.5	54	58	–	108	2250	2	*1
2. 9/16	92.8	54	58	–	108	2310	2	*1
2. 5/8	95.3	54	56	–	108	2370	1	*1
2. 3/4	99	54	55	–	108	2440	1	*1
2. 7/8	102.8	86	53	–	108	3600	1	*2
2.15/16	105.3	86	52	–	108	3646	1	*2
3	106.5	86	51	–	108	3677	1	*2
3. 1/16	109	86	50	–	108	3939	1	*2
3. 1/8	111.5	86	49	–	108	4039	1	*2
3. 3/16	112.8	86	48	–	108	4170	1	*2

*1 C-Ring=1801C, Pin/O-Ring=1801A/B
*2 C-Ring=1802C, Pin/O-Ring=1802A/B ➡P250-251

18301M · 18301A

6-point Deep Sockets, Thin Walled
Vasos Hexagonales Largos de Parad De Igada



	18301M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
	17	29.8	53	17	77	108	692	2	*1
	18	31	53	18	77	108	710	2	*1
	19	32.3	53	19	77	108	725	2	*1
	20	33.5	53	20	77	108	740	2	*1
	21	34.8	53	21	77	108	750	2	*1
	22	36	53	22	77	108	770	2	*1
	23	37.3	53	23	77	108	780	2	*1
	24	38.5	53	24	77	108	800	2	*1
	26	41	53	26	77	108	830	2	*1
	27	42.3	53	27	77	108	860	2	*1
	29	44.8	53	29	77	108	880	2	*1
	30	46	53	30	77	108	910	2	*1
	32	48.5	53	32	77	108	970	2	*1
	33	49.8	53	33	77	108	980	2	*1
	34	51	53	34	77	108	980	2	*1
	35	52.3	53	35	77	108	986	2	*1
	36	53.5	53	36	76	108	992	2	*1
	38	56	53	38	76	108	1025	2	*1
	39	57.3	53	38	76	108	1130	2	*1
	41	59.8	53	38	75	108	1213	2	*1
New	42	61	53	38	75	108	1245	2	*1
	43	62.3	53	38	74	108	1400	2	*1
	46	66	53	38	74	108	1400	2	*1
	50	71	53	38	–	108	1435	2	*1
New	55	77.3	53	62	–	108	1735	2	*1
New	60	83.5	53	59	–	108	1985	2	*1
New	65	89.8	53	56	–	108	2090	2	*1
New	70	96	53	55	–	108	2310	1	*1

	18301A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
	11/16	29.8	53	17	77	108	692	2	*1
	3/4	32.3	53	19	77	108	725	2	*1
	13/16	34.8	53	21	77	108	750	2	*1
	7/8	36	53	22	77	108	770	2	*1
	15/16	38.5	53	24	77	108	800	2	*1
New	1	39.8	53	25	77	108	828	2	*1
	1. 1/16	42.3	53	27	77	108	860	2	*1
New	1. 1/8	44.8	53	29	77	108	909	2	*1
	1. 3/16	46	53	30	77	108	910	2	*1
	1. 1/4	48.5	53	32	77	108	970	2	*1
New	1. 9/32	49.8	53	33	77	108	997	2	*1
New	1. 5/16	51	53	34	77	108	1014	2	*1
	1. 3/8	52.3	53	35	77	108	986	2	*1
New	1. 7/16	54.8	53	37	76	108	1000	2	*1
	1. 1/2	56	53	38	76	108	1025	2	*1
New	1. 9/16	58.5	53	38	75	108	1200	2	*1
	1. 5/8	59.8	53	38	75	108	1213	2	*1
New	1.11/16	62.3	53	38	74	108	1285	2	*1
New	1. 3/4	64.8	53	38	74	108	1360	2	*1
	1.13/16	66	53	38	74	108	1400	2	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

18104M

Extra Long Sockets
Vasos Extra-Largos



	18104M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
	24	41.5	54	24	170	1327	1	*1
	27	45.3	54	27	170	1375	1	*1
	28	46.5	54	28	170	1390	1	*1
	30	49	54	30	170	1407	1	*1
	32	51.5	54	32	170	1537	1	*1
	33	52.8	54	33	170	1590	1	*1
	34	54	54	34	170	1670	1	*1
	36	56.5	54	36	170	1800	1	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

18310M

Surface Drive Sockets, deep
Vasos Surface Drive (de Contacto Curvo) Largos



	18310M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
New	24	41.5	54	24	77	108	1060	2	*1
New	27	45.3	54	27	77	108	1125	2	*1
New	30	49	54	30	77	108	1179	2	*1
New	32	51.5	54	32	77	108	1200	2	*1
New	33	52.8	54	33	77	108	1200	2	*1
New	36	56.5	54	36	76	108	1280	2	*1
New	41	62.8	54	38	75	108	1450	2	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

18106 Bit Holder / Porta Punta



	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
18106	32	54	16	68	640	2	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

Replacement Screw : M6x10, ⬢3mm

107-16 Bits for Inhex Screws / Puntas para Tornillos Inhex







	107.16 (mm)	L (mm)	L (mm)	L=40 (g)	L=100 (g)	(pcs.)
New	10	40	100	46	122	10
New	12	40	100	52	146	10
	13	40	–	56	–	10
New	14	40	100	60	166	10
	16	40	–	69	–	10
New	17	40	100	73	193	10
	18	40	–	78	–	10
New	19	40	100	80	232	10
New	22	40	100	97	254	10

	107.16 (inch)	L (mm)	(g)	(pcs.)
New	3/8	40	45	10
	1/2	40	56	10
	9/16	40	60	10
	5/8	40	69	10
	3/4	40	80	10

107-16 (T) TORX® Bits / Puntas TORX®





	107.16 (T)	L (mm)	L (mm)	L=50 (g)	L=100 (g)	(pcs.)
New	T55	50	100	57	108	10
New	T60	50	100	64	130	10
New	T70	50	100	73	159	10

107-16 (IP) TORXPLUS® Bits / Puntas TORXPLUS®



	107.16 (IP)	L (mm)	(g)	(pcs.)
	55IP	50	57	10
	60IP	50	64	10
	70IP	50	73	10

107-16 (XZN) XZN Bits / Puntas XZN



	107.16 (XZN)	L (mm)	L (mm)	L=60 (g)	L=100 (g)	(pcs.)
New	M14	60	100	83	131	10
New	M16	60	100	93	161	10
New	M18	60	100	103	177	10

18106-16 Hex Bit Sockets / Vasos con Punta Hexagonal



18106.16 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)	
10	54	24	92	686	2	*1
12	54	24	92	692	2	*1
13	54	24	92	696	2	*1
14	54	24	92	700	2	*1
16	54	24	92	709	2	*1
17	54	24	92	713	2	*1
18	54	24	92	718	2	*1
19	54	24	92	764	2	*1
22	54	24	92	781	2	*1

18106.16 (inch)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)	
1/2	54	24	92	696	2	*1
9/16	54	24	92	700	2	*1
5/8	54	24	92	709	2	*1
3/4	54	24	92	764	2	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.
TORX PLUS® is a registered trademark of Acument Intellectual Properties, LLC.
TORX PLUS® es una marca registrada de Acument Intellectual Properties, LLC.

18107-22 Hex Bit Sockets / Vasos con Punta Hexagonal

18107.22 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pcs.)	
19	54	28	98	910	2	*1
22	54	28	98	932	2	*1
24	54	28	98	946	2	*1
27	54	28	98	986	2	*1
30	54	28	98	1008	2	*1
32	54	28	103	1029	2	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251



18107 Bit Holder / Porta Punta

	D_1 (mm)	D_2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
18107	44	54	22	70	770	2	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

Replacement Screw : M8x14, ⬢4mm



107-22 Bits for Inhex Screws / Puntas para Tornillos Inhex

107.22 (mm)	L (mm)	(g)	(pcs.)
17	50	120	10
19	50	140	10
22	50	162	10
24	50	176	10
27	50	200	10
30	50	227	10
32	55	243	10

107.22 (inch)	L (mm)	(g)	(pcs.)
5/8	50	120	10
3/4	50	140	10
7/8	50	162	10
1	50	190	10
1. 1/4	55	243	10



107-22 (T) TORX® Bits / Puntas TORX®

107.22 (T)	L (mm)	(g)	(pcs.)
T 80	60	141	10
T 90	60	155	10
T100	60	170	10



TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

18760-175 · -200 · -250 · -330 Extension Bars Alargaderas



18760	D (mm)	L (mm)	(g)	(pce.)	
175	54	175	1400	1	*1
200	54	200	1580	1	*1
250	54	250	1885	1	*1
330	54	330	2380	1	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

18888AL Adaptor (Quick Release) Adaptador (Extracción Rápida)



	L (mm)	(g)	(pcs.)	
18888AL	95	980	2	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

Lock & Quick Release



18770 Universal Joint Articulación Universal



	L (mm)	(g)	(pce.)	
18770	127	1210	1	*1
18771	115	1210	1	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251



18771 Universal Joint Articulación Universal



18866A Adaptors Adaptadores — No Warranty Sin Garantia

18866A-200

	凹 (sq.)	凸 (sq.)	L (mm)	(g)	(pce.)	
18866A	1"	3/4"	66.5	580	1	*1
18866A-200	1"	3/4"	200	1100	1	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

Adapting down from bigger square drive to smaller square drive may lead to excessive torque load and possibly cause breakage. Always stay within safe torque of the smaller square drive.



18877A Adaptor Adaptador

	凹 (sq.)	凸 (sq.)	L (mm)	(g)	(pce.)	
18877A	1"	1.1/2"	80	935	1	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251



17400M · 17400A

6-point Sockets
Vasos Hexagonales



17400M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
36	62	86	20	77	2126	1	*1
41	68	86	22	80	2346	1	*1
42	70	86	22	80	2330	1	*1
46	74	86	26	84	2360	1	*1
50	79	86	27	84	2400	1	*1
52	82	86	38	84	2340	1	*1
54	84	86	38	84	2340	1	*1
55	85	86	44	90	2450	1	*1
58	88	86	44	90	2510	1	*1
60	91	86	43	90	2640	1	*1
65	97	86	48	95	3050	1	*1
70	103	86	52	100	3350	1	*1
75	108	86	56	105	3700	1	*1
80	115	86	60	110	4240	1	*1
85	122	86	60	110	4550	1	*1
90	128	86	60	112	4840	1	*1
95	135	127	52	112	7660	1	*2
100	140	127	53	115	7700	1	*2
105	146	127	57	120	8000	1	*2
110	153	127	60	124	9200	1	*2
115	160	127	62	128	10700	1	*2
120	166	127	64	132	11200	1	*2
125	173	127	67	136	13000	1	*2
130	180	127	69	140	14200	1	*2
135	186	127	73	145	14940	1	*2
140	190	127	76	150	15600	1	*2
150	200	127	83	160	16500	1	*2

17400A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
1. 5/8	68	86	22	80	2346	1	*1
1.11/16	71	86	22	80	2300	1	*1
1. 3/4	73	86	22	80	2290	1	*1
1.13/16	74	86	26	84	2360	1	*1
1. 7/8	77	86	26	84	2440	1	*1
1.15/16	79	86	27	84	2400	1	*1
2	80	86	27	84	2420	1	*1
2. 1/16	82	86	38	84	2340	1	*1
2. 1/8	84	86	38	84	2340	1	*1
2. 3/16	85	86	44	90	2450	1	*1
2. 1/4	87	86	43	90	2460	1	*1
2. 5/16	88	86	44	90	2510	1	*1
2. 3/8	91	86	43	90	2640	1	*1
2. 7/16	93	86	47	95	2860	1	*1
2. 1/2	96	86	47	95	3000	1	*1
2. 9/16	97	86	48	95	3050	1	*1
2. 5/8	100	86	51	100	3300	1	*1
2.11/16	101	86	51	100	3300	1	*1
2. 3/4	103	86	52	100	3350	1	*1
2.13/16	105	86	55	105	3670	1	*1
2. 7/8	106	86	55	105	3610	1	*1
2.15/16	108	86	56	105	3700	1	*1
3	108	86	55	105	3680	1	*1
3. 1/8	115	86	60	110	4240	1	*1
3. 1/4	118	86	59	110	4370	1	*1
3. 3/8	123	86	60	110	4570	1	*1
3. 1/2	128	86	60	112	4840	1	*1
3. 5/8	132	86	52	112	5500	1	*1
3. 3/4	135	127	52	112	7660	1	*2
3. 7/8	140	127	53	115	7700	1	*2
4	146	127	57	120	8000	1	*2
4. 1/8	146	127	57	120	8000	1	*2
4. 1/4	153	127	60	124	9200	1	*2
4. 1/2	160	127	62	128	10700	1	*2
4. 5/8	166	127	64	132	11200	1	*2
4. 3/4	168	127	64	132	11200	1	*2
4. 7/8	173	127	67	136	13000	1	*2
5	180	127	69	140	14200	1	*2
6	205	127	88	165	16500	1	*2

*1 C-Ring=1700C, Pin/O-Ring=1701A/B
*2 Pin/O-Ring=1702A/B

➡P250-251

17405M · 17405A

12-point Sockets
Vasos Bihexagonales



17405M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
46	74	86	26	84	2360	1	*1
50	79	86	27	84	2400	1	*1
55	85	86	44	90	2450	1	*1
60	91	86	43	90	2640	1	*1
65	97	86	48	95	3050	1	*1
70	103	86	52	100	3350	1	*1
75	108	86	56	105	3700	1	*1
80	115	86	60	110	4240	1	*1
85	122	86	60	110	4550	1	*1
90	128	86	60	112	4840	1	*1
New **95**	135	127	52	112	7660	1	*1
New **100**	140	127	53	115	7700	1	*1

17405A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
1.11/16	71	86	22	80	2300	1	*1
1. 3/4	73	86	22	80	2290	1	*1
1. 7/8	77	86	26	84	2440	1	*1
1.15/16	79	86	27	84	2400	1	*1
2	80	86	27	84	2420	1	*1
2. 1/16	82	86	38	84	2340	1	*1
2. 1/8	84	86	38	84	2340	1	*1
2. 3/16	85	86	44	90	2450	1	*1
2. 1/4	87	86	43	90	2460	1	*1
2. 3/8	91	86	43	90	2640	1	*1
2. 7/16	93	86	47	95	2860	1	*1
2. 1/2	96	86	47	95	3000	1	*1
2. 9/16	97	86	48	95	3050	1	*1
2. 5/8	100	86	51	100	3300	1	*1
New **2.15/16**	108	86	56	105	3700	1	*1

*1 C-Ring=1700C, Pin/O-Ring=1701A/B ➡P250-251

17300M · 17300A

6-point Deep Sockets
Vasos Hexagonales Largos



17300M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pce.)	
New **36**	63	86	26	70.5	115	2800	1	*1
41	68	86	27	70.5	115	3080	1	*1
42	70	86	27	70.5	115	3140	1	*1
46	74	86	28	80.5	125	3440	1	*1
50	79	86	30	90.5	135	3840	1	*1
54	84	86	30	90.5	135	4160	1	*1
55	85	86	33	90.5	135	4130	1	*1
60	91	86	35	90.5	135	4370	1	*1
65	97	86	38	99.5	145	5260	1	*1
70	103	86	40	98.5	145	5780	1	*1
75	108	86	42	107.5	155	6580	1	*1
80	115	86	46	115.5	165	7740	1	*1
85	122	86	49	114.5	165	7420	1	*1
90	128	86	52	122.5	175	9630	1	*1
95	135	127	55	121.5	175	10450	1	*2
100	140	127	58	130.5	185	9741	1	*2
105	146	127	62	138.5	195	10850	1	*2
110	153	127	65	137.5	195	11500	1	*2
115	160	127	68	135.5	195	12160	1	*2
120	166	127	72	144.5	205	13680	1	*2
125	173	127	74	142.5	205	14450	1	*2
130	180	127	76	142.5	205	15190	1	*2

*1 C-Ring=1700C, Pin/O-Ring=1701A/B
*2 Pin/O-Ring=1702A/B ➡P250-251

17300A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pce.)	
1. 5/8	68	86	27	70.5	115	3080	1	*1
1.11/16	71	86	27	70.5	115	3180	1	*1
1. 3/4	73	86	27	70.5	115	3210	1	*1
1.13/16	74	86	28	80.5	125	3440	1	*1
1. 7/8	77	86	28	80.5	125	3550	1	*1
1.15/16	79	86	28	80.5	125	3590	1	*1
2	80	86	30	90.5	135	3916	1	*1
2. 1/16	82	86	30	90.5	135	4030	1	*1
2. 1/8	84	86	30	90.5	135	4160	1	*1
2. 3/16	85	86	33	90.5	135	4200	1	*1
2. 1/4	87	86	33	90.5	135	4160	1	*1
2. 3/8	91	86	35	90.5	135	4370	1	*1
2. 7/16	93	86	35	90.5	135	4490	1	*1
2. 1/2	96	86	35	90.5	135	4630	1	*1
2. 9/16	97	86	38	99.5	145	5260	1	*1
2. 5/8	100	86	38	99.5	145	5320	1	*1
2.11/16	101	86	38	99.5	145	5670	1	*1
2. 3/4	103	86	40	98.5	145	5780	1	*1
2.13/16	105	86	40	98.5	145	6000	1	*1
2. 7/8	106	86	40	98.5	145	6080	1	*1
2.15/16	108	86	42	107.5	155	6580	1	*1
3	108	86	42	107.5	155	6850	1	*1
3. 1/8	115	86	46	115.5	165	7740	1	*1
3. 3/4	135	127	55	121.5	175	12200	1	*2
3. 7/8	140	127	56	120.5	175	11080	1	*2

*1 C-Ring=1700C, Pin/O-Ring=1701A/B
*2 Pin/O-Ring=1702A/B ➡P250-251

17108

Bit Holder, For 107-32
Porta Punta



	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
17108	60	86	30	85	2200	1	*1

*1 C-Ring=1700C, Pin/O-Ring=1701A/B ➡P250-251

Replacement Screw : M8x14, ⬢4mm

107-32

Bit for Inhex Screws
Puntas para Tornillos Inhex



107.32 (mm)	L (mm)	(g)	(pcs.)
19	60	300	10
22	60	320	10
24	60	330	10
27	60	360	10
30	60	390	10
32	60	410	10
36	60	460	10

17108-32

Hex Bit Sockets
Vasos con Punta Hexagonal



17108.32 (mm)	D (mm)	H (mm)	L (mm)	(g)	(pce.)	
19	86	30	115	2500	1	*1
22	86	30	115	2520	1	*1
24	86	30	115	2530	1	*1
27	86	30	115	2560	1	*1
30	86	30	115	2590	1	*1
32	86	30	115	2610	1	*1
36	86	30	115	2660	1	*1

*1 C-Ring=1700C, Pin/O-Ring=1701A/B ➡P250-251

17760-175 · -250 · -330 Extension Bars Alargaderas

17760	D (mm)	L (mm)	(g)	(pce.)	
175	86	175	3300	1	*1
250	86	250	4500	1	*1
330	86	330	5200	1	*1

*1 C-Ring=1700C, Pin/O-Ring=1701A/B ➡P250-251



17770 Universal Joint Articulación Universal

	L (mm)	(g)	(pce.)	
17770	200	4700	1	*1

*1 C-Ring=1700C, Pin/O-Ring=1701A/B ➡P250-251

17788A ⚠ Adaptor Adaptador — No Warranty Sin Garantía

	凹 (sq.)	凸 (sq.)	L (mm)	(g)	(pce.)	
17788A	1.1/2"	1"	98	2600	1	*1

*1 C-Ring=1700C, Pin/O-Ring=1701A/B ➡P250-251

⚠ Adapting down from bigger square drive to smaller square drive may lead to excessive torque load and possibly cause breakage. Always stay within safe torque of the smaller square drive.

17799A Adaptor Adaptador

	凹 (sq.)	凸 (sq.)	L (mm)	(g)	(pce.)	
17799A	1.1/2"	2.1/2"	115	3790	1	*1

*1 C-Ring=1700C, Pin/O-Ring=1701A/B ➡P250-251



19400M · 19400A

6-point Sockets
Vasos Hexagonales



19400M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
50	88	127	39	115	7270	1	*1
55	94	127	42	115	7350	1	*1
60	100	127	45	125	7870	1	*1
65	105	127	48	125	7790	1	*1
70	110	127	51	125	7640	1	*1
75	118	127	54	125	7740	1	*1
80	124	127	57	125	7640	1	*1
85	127	127	61	132	7840	1	*1
90	135	127	64	132	8500	1	*1
95	140	127	71	140	10160	1	*1
100	146	127	71	142	11500	1	*1
105	155	127	74	146	11350	1	*1
110	160	127	76	155	12710	1	*1
115	167	127	78	158	13980	1	*1
120	175	175	79	160	15430	1	*2
125	180	175	82	165	16590	1	*2
130	185	175	85	169	17590	1	*2
135	190	175	89	175	19030	1	*2
140	200	175	93	180	21810	1	*2
145	205	175	95	183	24440	1	*2
150	210	175	97	192	25720	1	*2
160	225	175	102	200	30920	1	*2
165	230	175	105	204	32610	1	*2
170	235	175	106	207	34390	1	*2
175	240	175	109	211	36210	1	*2
180	250	175	110	214	40630	1	*2
185	255	175	113	218	42690	1	*2
190	265	175	113	220	47440	1	*2
200	275	175	116	225	51550	1	*2
210	285	175	123	235	57170	1	*2
215	290	175	126	240	60260	1	*2
225	305	175	133	250	70180	1	*2
235	315	175	140	260	77060	1	*2

19400A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
New **2. 1/8**	92	127	41	115	6665	1	*1
2. 3/8	100	127	45	125	7870	1	*1
2. 7/16	102	127	46	125	7840	1	*1
2. 1/2	103	127	47	125	7810	1	*1
2. 9/16	105	127	48	125	7790	1	*1
2. 5/8	107	127	49	125	7790	1	*1
2.11/16	108	127	50	125	7790	1	*1
2. 3/4	110	127	51	125	7640	1	*1
2.13/16	113	127	52	125	7690	1	*1
2. 7/8	115	127	53	125	7730	1	*1
2.15/16	118	127	54	125	7740	1	*1
3	120	127	55	125	7740	1	*1
3. 1/8	124	127	57	125	7640	1	*1
3. 1/4	125	127	59	125	7740	1	*1
3. 3/8	127	127	61	132	7840	1	*1
3. 1/2	135	127	64	132	8500	1	*1
3. 5/8	138	127	64	132	9330	1	*1
3. 3/4	140	127	71	140	10160	1	*1
3. 7/8	143	127	70	140	10830	1	*1
4	146	127	71	142	11500	1	*1
4. 1/8	155	127	70	142	11250	1	*1
4. 1/4	160	127	76	155	12710	1	*1
New **4. 3/8**	163	127	76	155	13100	1	*1
4. 1/2	167	127	78	158	13980	1	*1
4. 5/8	175	175	79	160	15430	1	*2
4. 7/8	180	175	82	165	16590	1	*2
5	183	175	81	165	17090	1	*2
5. 1/4	190	175	89	175	19030	1	*2
5. 3/8	198	175	94	180	20880	1	*2
5. 1/2	200	175	93	180	21810	1	*2
5. 5/8	203	175	94	182	22480	1	*2
5. 3/4	207	175	103	192	24440	1	*2
6	217	175	100	196	28510	1	*2
6. 1/8	218	175	99	196	29720	1	*2
6. 5/8	233	175	105	205	33500	1	*2
7	248	175	110	213	39160	1	*2

*1 Pin/O-Ring=1901A/B
*2 Pin/O-Ring=1902A/B
➡P251

19300M

6-point Deep Sockets
Vasos Hexagonales Largos

19300M (mm)	D_1 (mm)	D_2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pce.)	
75	118	127	42	129	190	11930	1	*1
80	124	127	46	129	190	12280	1	*1
85	127	127	49	134	195	12480	1	*1
90	135	127	52	144	205	14000	1	*1
95	140	127	55	149	210	14630	1	*1
100	146	127	58	154	215	15520	1	*1
105	155	127	62	146.5	220	18250	1	*1
110	160	127	65	150.5	225	18740	1	*1
115	167	127	68	153.5	230	20940	1	*1
120	175	175	72	157.5	235	23530	1	*2
125	180	175	74	158.5	238	26110	1	*2
130	185	175	76	163.5	243	25320	1	*2
135	190	175	80	165.5	248	26290	1	*2
140	200	175	82	164.5	248	28940	1	*2
145	205	175	84	163.5	248	29520	1	*2
150	210	175	88	168.5	255	30600	1	*2
155	215	175	92	167.5	255	31680	1	*2
160	225	175	95	170.5	260	35560	1	*2
165	230	175	98	169.5	260	36040	1	*2
170	235	175	100	172.5	265	37230	1	*2
175	240	175	102	176.5	270	39420	1	*2

*1 Pin/O-Ring=1901A/B
*2 Pin/O-Ring=1902A/B
➡P251



19760-250 · -500

Extension Bars
Alargaderas

19760	D (mm)	L (mm)	(g)	(pce.)	
250	127	250	17800	1	*1
500	127	500	27800	1	*1

*1 Pin/O-Ring=1901A/B
➡P251



19770

Universal Joint
Articulación Universal

	L (mm)	(g)	(pce.)	
19770	303	21360	1	*1

*1 Pin/O-Ring=1901A/B
➡P251



19977A

Adaptor
Adaptador

No Warranty
Sin Garantía

	□ (sq.)	□ (sq.)	L (mm)	(g)	(pce.)	
19977A	2.1/2"	1.1/2"	145	7210	1	*1

*1 Pin/O-Ring=1901A/B
➡P251

⚠ Adapting down from bigger square drive to smaller square drive may lead to excessive torque load and possibly cause breakage. Always stay within safe torque of the smaller square drive.



10400M · 10400A

6-point Sockets
Vasos Hexagonales



10400M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
105	165	175	86	176	19370	1	*1
110	170	175	88	179	20160	1	*1
115	175	175	90	183	21160	1	*1
120	180	175	91	185	21930	1	*1
125	188	175	94	190	23940	1	*1
130	193	175	97	194	25050	1	*1
135	200	175	101	199	26930	1	*1
140	205	175	105	205	28560	1	*1
145	210	200	106	207	29600	1	*2
150	215	200	109	212	31240	1	*2
160	228	200	114	220	35500	1	*2
165	235	200	117	224	37940	1	*2
170	240	200	118	227	39660	1	*2
175	245	200	121	231	41400	1	*2
180	255	200	122	234	45740	1	*2
185	265	200	125	238	50350	1	*2
190	275	200	125	239	54650	1	*2
200	285	200	128	245	59190	1	*2
210	295	200	135	255	64970	1	*2
215	300	200	138	260	68150	1	*2

10400A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
4.1/8	165	175	86	176	19370	1	*1
4.1/4	168	175	87	178	19770	1	*1
4.3/8	172	175	88	180	20660	1	*1
4.1/2	175	175	89	182	21160	1	*1
4.5/8	178	175	90	183	21550	1	*1
4.3/4	180	175	91	185	21930	1	*1
4.7/8	188	175	94	190	23940	1	*1
5	188	175	95	191	24500	1	*1
5.1/8	193	175	97	194	25050	1	*1
5.1/4	197	175	100	198	25990	1	*1
5.3/8	201	175	102	202	27750	1	*1
5.1/2	205	175	105	205	28560	1	*1
5.5/8	208	200	106	208	30110	1	*2
5.3/4	212	200	108	210	30610	1	*2
5.7/8	215	200	109	212	31240	1	*2
6	219	200	110	214	32460	1	*2
6.1/8	223	200	112	216	33670	1	*2
6.1/4	227	200	114	218	34590	1	*2
6.3/8	231	200	115	221	36720	1	*2
6.1/2	235	200	117	224	37940	1	*2
6.5/8	238	200	118	226	38800	1	*2
6.3/4	241	200	119	228	39870	1	*2
6.7/8	245	200	120	230	40640	1	*2
7	251	200	121	232	43570	1	*2
7.1/8	257	200	122	234	46450	1	*2
7.1/4	263	200	123	236	48400	1	*2
7.3/8	269	200	124	238	52500	1	*2
7.1/2	275	200	125	240	55350	1	*2
7.5/8	278	200	127	242	56050	1	*2
7.3/4	282	200	129	245	57620	1	*2
7.7/8	285	200	130	248	60870	1	*2
8	290	200	132	250	62550	1	*2
8.1/8	293	200	133	251	63760	1	*2
8.1/4	295	200	135	255	64970	1	*2
8.3/8	298	200	136	258	65580	1	*2
8.1/2	300	200	138	260	68150	1	*2
8.5/8	305	200	139	262	70760	1	*2
8.3/4	310	200	140	264	73830	1	*2
8.7/8	313	200	142	267	75780	1	*2

*1 Pin/O-Ring=2001A/B
*2 Pin/O-Ring=2002A/B
➡P251

10099A

Adaptor
Adaptador

No Warranty
Sin Garantía



	(sq.)	(sq.)	L (mm)	(g)	(pce.)	
10099A	3.1/2"	2.1/2"	182	16870	1	*1

*1 Pin/O-Ring=2001A/B
➡P251

Adapting down from bigger square drive to smaller square drive may lead to excessive torque load and possibly cause breakage. Always stay within safe torque of the smaller square drive.

Sleeve Drive Sockets

3/8”

1/2”

3/4”

The deepened drive end of the **Sleeve-Drive** tools prevents the sometimes "wobbly" connection between pulse tool - extension - socket. An O-ring inside **Sleeve-Drive** optimizes the perfect fit of extension bars and sockets on the anvil to the effect, that the exactness of the required torque given by the pulse tool is generally improved. Further, the **Sleeve-Drive** avoids the direct transmission of vibrations on the pulse tool and finally on the operator.

El extremo de accionamiento alargado de las herramientas con **casquillo conductor** evita la unión a veces "holgada" entre la herramienta de percusión-alargadera-vaso. Una junta tórica en el interior del **casquillo conductor** optimiza el ajuste perfecto de las alargaderas y los vasos en el elemento de accionamiento lo que se traduce en la mejora de la exactitud del par requerido suministrado por la herramienta de percusión.



SLEEVE DRIVE SOCKET **PULSE TOOL**



The ***"Sleeve Drive"*** Sockets and accessories are designed for use on Pulse Tools with anvils of certain lengths and diameters as shown hereunder.

Los Vasos y accesorios con Casquillo Conductor se han diseñado para su utilización con Herramientas de Percusión con elementos de accionamiento de cierta longitud y diámetro como se muestra a continuación.

	Anvil Diameter (mm)	Minimum Anvil Length (mm)
3/8"sq.	12	10
1/2"sq.	16	10
3/4"sq.	25	11.8







NV13400

6-point Sockets
Vasos Hexagonales



NV13400 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
10	15.8	19	7	43	53	10	*1
11	17	19	8	43	54	10	*1
12	18.3	19	9	43	55	10	*1
13	19.5	22	10	43	80	10	*2
14	20.8	22	10	43	80	10	*2
15	22	22	11	43	81	10	*2
16	23.3	22	11	43	83	10	*2
17	24.5	22	11	43	85	10	*2
18	25.8	22	11	43	89	10	*2
19	27	22	11	43	98	10	*2
21	29.5	22	11	43	105	10	*2
22	30.8	22	11	43	112	10	*2

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
*2 C-Ring=1302C, Pin/O-Ring=1302A/B
➡P250-251

NV13145-100 · -150 · -200

Extended Sockets
Vasos con Alargadera



NV13145.100 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
6	13	19	6	100	108	10	*1
8	13	19	8	100	110	10	*1
10	15.5	19	10	100	112	10	*1
12	18	19	12	100	120	10	*1
13	19	19	13	100	127	10	*1
14	21	19	14	100	131	10	*1
15	22	19	15	100	133	10	*1
16	24	19	15	100	144	10	*1
17	25	19	15	100	154	10	*1

NV13145.150 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
6	13	19	6	150	163	10	*1
8	13	19	8	150	158	10	*1
10	15.5	19	10	150	165	10	*1
12	18	19	12	150	168	10	*1
13	19	19	13	150	170	10	*1
14	21	19	14	150	175	10	*1
15	22	19	15	150	177	10	*1
16	24	19	15	150	190	10	*1
17	25	19	15	150	203	10	*1

NV13145.200 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
6	13	19	6	200	209	10	*1
8	13	19	8	200	203	10	*1
10	15.5	19	10	200	212	10	*1
12	18	19	12	200	214	10	*1
13	19	19	13	200	218	10	*1
14	21	19	14	200	220	10	*1
15	22	19	15	200	226	10	*1
16	24	19	15	200	235	10	*1
17	25	19	15	200	250	10	*1

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
➡P250-251

NV13760-75 · -125 · -150 · -250
NV13760-75P · -125P · -150P · -250P

Extension Bars
Alargaderas



	NV13760	TYPE	D (mm)	L (mm)	(g)	(pcs.)	
New	**75**	Hole	19	75	95	10	*1
New	**125**	Hole	19	125	125	10	*1
New	**150**	Hole	19	150	150	10	*1
New	**250**	Hole	19	250	255	10	*1

NV13760	TYPE	D (mm)	L (mm)	(g)	(pcs.)	
75P	Pin	19	75	95	10	*1
125P	Pin	19	125	125	10	*1
150P	Pin	19	150	150	10	*1
250P	Pin	19	250	255	10	*1

*1 C-Ring=1301C, Pin/O-Ring=1301A/B
➡P250-251

3/8”,1/2”

183H-35 · -75 · -150

Hex Bits
Puntas Hexagonales



	183H.35 (inch)	L (mm)	(g)	(pcs.)
New	3/16	35	15	10
New	7/32	35	16	10
New	1/4	35	18	10
New	5/16	35	20	10
New	3/8	35	26	10
New	7/16	35	28	10
New	1/2	35	38	10

183H.35 (mm)	L (mm)	(g)	(pcs.)
3	35	15	10
4	35	15	10
5	35	15	10
6	35	18	10
New 7	35	19	10
8	35	20	10
10	35	26	10
New 11	35	28	10
12	35	30	10
14	35	35	10
New 16	35	47	10
New 17	35	50	10
New 18	35	53	10
New 19	35	56	10

183H.75 (mm)	L (mm)	R (mm)	(g)	(pcs.)
3	75	6.0	34	10
4	75	6.0	35	10
5	75	6.5	36	10
6	75	7.5	39	10
New 7	75	8.5	44	10
8	75	9.5	47	10
10	75	–	57	10
New 11	75	–	60	10
12	75	–	65	10
14	75	–	79	10

183H.150 (mm)	L (mm)	R (mm)	(g)	(pcs.)
New 4	150	6.0	51	10
New 5	150	6.5	55	10
New 6	150	7.5	65	10
New 8	150	9.5	87	10
New 10	150	–	118	10
New 12	150	–	136	10

183T-35 · -75 · -150 (T)

TORX® Bits
Puntas TORX®



	183T.35 (T)	L (mm)	(g)	(pcs.)
New	T25	35	18	10
	T30	35	18	10
	T40	35	20	10
	T45	35	22	10
	T50	35	26	10
	T55	35	30	10
	T60	35	38	10

183T.150 (T)	L (mm)	R (mm)	(g)	(pcs.)
New T30	150	6.0	50	10
New T40	150	6.9	58	10
New T45	150	8.0	70	10
New T50	150	9.0	82	10
New T55	150	11.4	113	10

183T.75 (T)	L (mm)	R (mm)	(g)	(pcs.)
T30	75	6.0	35	10
T40	75	6.9	37	10
T45	75	8.0	41	10
T50	75	9.0	45	10
T55	75	11.4	55	10
T60	75	13.5	67	10

183T-35 · -75 (IP)

TORXPLUS® Bits
Puntas TORXPLUS®

TORXplus®



	183T.35 (IP)	L (mm)	(g)	(pcs.)
New	30IP	35	18	10
New	40IP	35	20	10
New	45IP	35	22	10
New	50IP	35	26	10
New	55IP	35	30	10
New	60IP	35	38	10

183T.75 (IP)	L (mm)	R (mm)	(g)	(pcs.)
New 30IP	75	6.0	35	10
New 40IP	75	6.8	37	10
New 45IP	75	8.0	41	10
New 50IP	75	9.0	45	10
New 55IP	75	11.4	56	10
New 60IP	75	13.5	67	10

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.
TORXplus® is a registered trademark of Acument Intellectual Properties, LLC.
TORXplus® es una marca registrada de Acument Intellectual Properties, LLC.

183X-35 · -75 · -150 (XZN)

XZN Bits
Puntas XZN

	183X.35 (XZN)	L (mm)	(g)	(pcs.)
New	M 4	35	18	10
	M 5	35	18	10
	M 6	35	20	10
	M 8	35	22	10
	M10	35	26	10
	M12	35	30	10
	M14	35	38	10



	183X.75 (XZN)	L (mm)	R (mm)	(g)	(pcs.)
New	M 4	75	6.0	34	10
	M 5	75	6.0	34	10
	M 6	75	6.2	36	10
	M 8	75	7.4	39	10
	M10	75	9.8	54	10
	M12	75	11.7	57	10
	M14	75	13.5	67	10

	183X.150 (XZN)	L (mm)	R (mm)	(g)	(pcs.)
New	M 5	150	6.0	50	10
New	M 6	150	6.2	53	10
New	M 8	150	7.4	64	10
New	M10	150	9.8	93	10
New	M12	150	11.7	121	10

NV13134

Bit Holder
Porta Punta

		D_1 (mm)	D_2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
New	NV13134	22.5	22	15	45	100	5	*1

*1 C-Ring=1301C, Pin/O-Ring=1301A/B ➡P250-251

For DIN3126 E11.2 Bits



F11.2

Replacement Screw : M8×5, ⬢ 4mm



NV14134

Bit Holder
Porta Punta

		D_1 (mm)	D_2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
New	NV14134	22.5	25	15	55	130	5	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➡P250-251

For DIN3126 E11.2 Bits



F11.2

Replacement Screw : M8×5, ⬢ 4mm



NV14400

6-point Sockets
Vasos Hexagonales



NV14400 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
12	19.5	25	9	54	120	10	*1
13	20.7	25	10	54	120	10	*1
14	22	25	10	54	120	10	*1
15	23.2	30	11	54	188	10	*2
16	24.5	30	11	54	189	10	*2
17	25.7	30	12	54	190	10	*2
18	27	30	12	54	190	10	*2
19	28.2	30	12	54	190	10	*2
21	30.7	30	12	54	191	10	*2
22	32	30	12	54	192	10	*2
23	33.2	30	12	54	196	10	*2
24	34.5	30	12	54	200	10	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P250-251

NV14145-100 · -150 · -200

Extended Sockets
Vasos con Alargadera



NV14145.100 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
10	15.5	25	10	100	161	1	*1
12	18	25	12	100	178	1	*1
13	19	25	13	100	175	1	*1
14	21	25	14	100	181	1	*1
15	22	25	15	100	185	1	*1
16	24	25	15	100	193	1	*1
17	25	25	15	100	201	1	*1
18	26	25	15	100	211	1	*1
19	28	25	15	100	221	1	*1

NV14145.150 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
10	15.5	25	10	150	200	1	*1
12	18	25	12	150	215	1	*1
13	19	25	13	150	220	1	*1
14	21	25	14	150	225	1	*1
15	22	25	15	150	230	1	*1
16	24	25	15	150	240	1	*1
17	25	25	15	150	250	1	*1
18	26	25	15	150	262	1	*1
19	28	25	15	150	275	1	*1

NV14145.200 (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
10	15.5	25	10	200	236	1	*1
12	18	25	12	200	250	1	*1
13	19	25	13	200	260	1	*1
14	21	25	14	200	270	1	*1
15	22	25	15	200	275	1	*1
16	24	25	15	200	287	1	*1
17	25	25	15	200	300	1	*1
18	26	25	15	200	310	1	*1
19	28	25	15	200	320	1	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
➡P250-251

NV14760-75 · -125 · -175 · -250
NV14760-75P · -125P · -175P · -250P

Extension Bars
Alargaderas



	NV14760	TYPE	D (mm)	L (mm)	(g)	(pcs.)	
New	**75**	Hole	25	75	149	10	*1
New	**125**	Hole	25	125	230	10	*1
New	**175**	Hole	25	175	308	10	*1
New	**250**	Hole	25	250	422	10	*1

NV14760	TYPE	D (mm)	L (mm)	(g)	(pcs.)	
75P	Pin	25	75	149	10	*1
125P	Pin	25	125	230	10	*1
175P	Pin	25	175	308	10	*1
250P	Pin	25	250	422	10	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
➡P250-251

NV14433A-75P · -100P · -150P

Adaptors
Adaptadores

No Warranty
Sin Garantía ⚠



NV14433A	□ (mm)	□ (mm)	L (mm)	(g)	(pcs.)	
75P	1/2"	3/8"	75	120	1	*1
100P	1/2"	3/8"	100	145	1	*1
150P	1/2"	3/8"	150	187	1	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
➡P250-251

⚠ Adapting down from bigger square drive to smaller square drive may lead to excessive torque load and possibly cause breakage. Always stay within safe torque of the smaller square drive.

NV16400

6-point Sockets
Vasos Hexagonales

NV16400 (mm)	D_1 (mm)	D_2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
17	30	44	12	65	448	5	*1
18	31.3	44	13	65	470	5	*1
19	32.5	44	13	65	455	5	*1
21	35	44	15	65	472	5	*1
22	36.3	44	16	65	471	5	*1
23	37.5	44	16	65	471	5	*1
24	38.8	44	16	65	467	5	*1
26	41.3	44	16	65	477	5	*1
27	42.5	44	16	65	473	5	*1
28	43.8	44	16	68	483	5	*1
29	45	44	18	68	464	5	*1
30	46.3	44	18	68	492	5	*1
32	48.8	44	19	70	514	5	*1
33	50	44	20	70	564	5	*1
34	51.3	44	20	70	588	5	*1
35	52.5	44	20	70	593	5	*1
36	53.8	44	20	70	598	5	*1
38	56.3	44	20	72	670	2	*1
41	60	44	22	72	687	2	*1
46	66.3	44	23	77	906	2	*1
50	69	44	23	77	1116	2	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251



NV16760-175 · -250 · -330

Extension Bars
Alargaderas



NV16760	D (mm)	L (mm)	(g)	(pce.)	
175	44	175	870	1	*1
250	44	250	1160	1	*1
330	44	330	1460	1	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

One Piece solid springs steel ring. Simply set by finger pushing and easily removed by puller. Much more convenient and safer than combination of pin and o-ring.

Aro de acero elástico de una pieza. Colocación sencilla apretando con el dedo y fácilmente extraíble con el extractor. Mucho más cómodo y seguro que la combinación de pasador y junta tórica.



C-Ring

No.	◻	Opening (mm)	(pcs.)
1301C	3/8"	≦12	100
1302C	3/8"	>12	100
1401C	1/2"	≦14	100
1402C	1/2"	>14	100
1600C	3/4"	≦46	100
1801C	1"	≦70	100
1802C	1"	>70	50
1700C	1-1/2"	≦90	50



1301C



1302C



1401C



1402C



1600C



1801C

C-Ring Set

Set No.	◻	C-Ring 10pcs.	Puller 1pce.
PK1301C	3/8"	1301C	149
PK1302C	3/8"	1302C	149
PK1401C	1/2"	1401C	149
PK1402C	1/2"	1402C	149
PK1600C	3/4"	1600C	152
PK1801C	1"	1801C	152

Puller

No.	◻		(pcs.)
149	3/8"	1/2"	10
152	3/4"	1"	10

149

152



Pin

No.	⍁	Opening (mm)	D1 (mm)	ℓ (mm)	(pcs.)
1200A	1/4"		1.5	10.2	100
1301A	3/8"	≦ 12	2.5	14.5	100
1302A	3/8"	> 12	2.5	17.5	100
1401A	1/2"	≦ 14	3.5	20	100
1402A	1/2"	> 14	3.5	25	100
1500A	5/8"		4	29	100
1601A	3/4"	≦ 46	5.5	35	100
1602A	3/4"	> 46	5.5	45	100
1801A	1"	≦ 70	6	45	100
1802A	1"	> 70	6	75	50
1701A	1-1/2"	≦ 90	7	75	50
1702A	1-1/2"	> 90	7	110	50
1901A	2-1/2"	≦115	9	110	50
1902A	2-1/2"	>115	9	155	50
2001A	3-1/2"	≦140	13	155	1
2002A	3-1/2"	>140	13	180	1



O-Ring

No.	⍁	Opening (mm)	D2 (mm)	D3 (mm)	(pcs.)
1200B	1/4"		2.5	9	100
1301B	3/8"	≦ 12	3.5	13	100
1302B	3/8"	> 12	3.5	16	100
1401B	1/2"	≦ 14	4	19	100
1402B	1/2"	> 14	4	24	100
1500B	5/8"		5	28	100
1601B	3/4"	≦ 46	5	36	100
1602B	3/4"	> 46	5	45	100
1801B	1"	≦ 70	7	45	100
1802B	1"	> 70	7	75	50
1701B	1-1/2"	≦ 90	10	75	50
1702B	1-1/2"	> 90	10	114	50
1901B	2-1/2"	≦115	10.5	114	50
1902B	2-1/2"	>115	10.5	158	50
2001B	3-1/2"	≦140	15	158	1
2002B	3-1/2"	>140	15	183	1

IMPACT Standard Sockets	Sq.Dr.	1/4"	3/8"		1/2"		3/4"		1"		1-1/2"	
	C-Ring		1301C	1302C	1401C	1402C	1600C	1801C	1801C	1802C	1700C	
size	O-Ring/Pin	1200A/B	1301A/B	1302A/B	1401A/B	1402A/B	1601A/B	1602A/B	1801A/B	1802A/B	1701A/B	1702A/B
4		●										
4.5	3/16	●										
5		●										
5.5		●										
6	1/4	●	●									
7	9/32	●	●									
8	5/16	●	●		●							
9	11/32	●	●		●							
10	3/8	●	●		●							
11	7/16	●	●		●							
12		●	●		●							
13	1/2	●		●	●							
14	9/16	●		●	●							
15				●		●						
16	5/8			●		●	●					
17	11/16			●		●	●		●			
18				●		●	●		●			
19	3/4			●		●	●		●			
20				●		●	●		●			
21	13/16			●		●	●		●			
22	7/8			●		●	●		●			
23				●		●	●		●			
24	15/16			●		●	●		●			
25	1					●	●		●			
26						●	●		●			
27	1- 1/16					●	●		●			
28						●	●		●			
29	1- 1/8					●	●		●			
30	1- 3/16					●	●		●			
31						●	●		●			
32	1- 1/4					●	●		●			
33	1- 5/16					●	●		●			
34	1- 3/8					●	●		●			
36						●	●		●		●	
37	1- 7/16					●	●		●		●	
38	1- 1/2					●	●		●		●	
39						●	●		●		●	
40	1- 9/16					●	●		●		●	
41	1- 5/8					●	●		●		●	
42							●		●		●	
43	1- 11/16						●		●		●	
44							●		●		●	
45	1- 3/4						●		●		●	
46	1- 13/16						●		●		●	
47								●	●		●	
48	1- 7/8							●	●		●	
	1- 15/16							●	●		●	
50								●	●		●	
	2							●	●		●	
52	2- 1/16							●	●		●	
54	2- 1/8							●	●		●	
55	2- 3/16							●	●		●	
56								●	●		●	
	2- 1/4							●	●		●	
58	2- 5/16							●	●		●	
60	2- 3/8							●	●		●	
62	2- 7/16							●	●		●	
63								●	●		●	
	2- 1/2							●	●		●	
65	2- 9/16							●	●		●	
67	2- 5/8							●	●		●	
68	2- 11/16							●	●		●	
70	2- 3/4							●	●		●	
	2- 13/16									●	●	
	2- 7/8									●	●	
75	2- 15/16									●	●	
	3									●	●	
	3- 1/16									●	●	
80	3- 1/8									●	●	
	3- 1/4									●	●	
85										●	●	
	3- 3/8									●	●	
90	3- 1/2									●	●	
	3- 5/8									●	●	
95	3- 3/4									●		●
100	3- 7/8									●		●
105	4									●		●
	4- 1/8											●
110	4- 1/4											●
115	4- 1/2											●
120	4- 5/8											●
	4- 3/4											●
125	4- 7/8											●
130	5											●
135	5- 1/4											●
140												●
150												●
	6											●
	6- 1/2											●

Industrial Sockets

1/4”

3/8”

1/2”

22400M

6-point Sockets
Vasos Hexagonales



22400M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
6	9.2	11.2	5.5	22	9	10
7	10.3	11.2	6	22	9	10
8	11.2	11.7	6.9	22	11	10
10	14.3	12.9	7.7	22	15	10
12	16.8	15.5	9.3	22	23	10
13	18	16.4	9.8	22	23	10

22425

TORX® Sockets
Vasos TORX®



22425 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
E 4	5.4	11.2	4.6	22	7	10
E 5	6.7	11.2	5.2	22	8	10
E 6	7.7	11.2	5.4	22	8	10
E 7	8.3	11.2	6.6	22	9	10
E 8	9.6	11.2	7	22	9	10
E10	11.3	12	8.2	22	10	10

TORX®
(E)



E		E4	E5	E6	E7	E8	E10	E11	E12	E14	E16	E18	E20	E22	E24	E26	E28
S1	(ref. mm)	3.7	4.6	5.6	6.1	7.4	9.3	9.9	11.0	12.8	14.6	16.5	18.3	20.1	22.0	23.7	25.5
S2	(ref. mm)	2.7	3.3	4.0	4.3	5.3	6.8	7.1	7.9	9.2	10.5	11.9	13.2	14.8	15.7	17.5	18.3

22300M · 22300A

6-point Sockets, Deep
Vasos Hexagonales, largos



22300M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
7	10.5	11.2	8	40	50	24	10
8	11.8	11.2	9	40	50	28	10
10	14.3	12.9	11	39	50	33	10
12	16.8	15.5	13	39	50	50	10
13	18	16.4	14	39	50	50	10

22300A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
1/4	9.8	11.2	7	40	50	24	10
5/16	11.8	11.2	9	40	50	28	10
3/8	13.7	12.5	11	40	50	33	10

INDUSTRIAL sockets are thin walled sockets and to be used on electric or pneumatic nut runners for assembly work only.

Los vasos INDUSTRIALES son vasos de pared delgada para su utilización con herramientas eléctricas o neumáticas solamente para trabajos de montaje.

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

23400M · 23400A

6-point Sockets
Vasos Hexagonales

23400M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
6	9.9	17.3	6	26	20	10
7	10.8	17.3	6.5	26	20	10
8	12	17.3	6.9	26	22	10
10	14.5	17.3	8	26	24	10
11	15.8	17.3	9.3	26	25	10
12	16.8	17.3	9	26	25	10
13	18	17	9.4	26	24	10
14	19.5	18.5	11	27	31	10
15	21	19.5	11.5	28	39	10
16	22	20	12	28	42	10
17	23.5	21.5	12.5	29	51	10
18	24.6	22.5	13	30	51	10
19	26	23.5	13.5	30	53	10
21	28	26	14.5	32	77	10



23400A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
5/16	12	17.3	6.9	26	22	10
3/8	13.9	17.3	8	26	22	10
7/16	15.8	17.3	9.3	26	25	10
1/2	18	17	9.4	26	24	10
9/16	19.5	18.5	11	27	31	10
11/16	24.6	22.5	13	30	51	10
3/4	26	23.5	13.5	30	63	10

23405M

12-point Sockets
Vasos Bihexagonales

23405M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
8	12	17.3	6.9	26	22	10
10	14.5	17.3	8	26	24	10
12	16.8	17.3	9	26	25	10
14	19.5	18.5	11	27	31	10



23410M

Surface Drive Sockets
Vasos Surface Drive (de Contacto Curvo)

23410M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
8	12	17.3	6.9	26	22	10
10	14.5	17.3	8	26	24	10
12	16.8	17.3	9	26	25	10
13	18	17	9.4	26	24	10
14	19.5	18.5	11	27	31	10
15	21	19.5	11.5	28	39	10
16	22	20	12	28	42	10
17	23.5	21.5	12.5	29	51	10
18	24.6	22.5	13	30	51	10
19	26	23.5	13.5	30	53	10



23425

TORX® Sockets
Vasos TORX®

23425 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
E 5	7	17.3	5.2	26	20	10
E 6	8.3	17.3	5.4	26	21	10
E 7	8.9	17.3	6.6	26	22	10
E 8	9.9	17.3	7	26	23	10
E10	12	17.3	8.2	26	24	10
E12	14.5	17.3	9.3	26	26	10
E14	15.8	17.3	10.6	26	27	10
E16	18.1	17	11.8	26	27	10



TORX® (E)



E		E4	E5	E6	E7	E8	E10	E11	E12	E14	E16	E18	E20	E22	E24	E26	E28
S1	(ref. mm)	3.7	4.6	5.6	6.1	7.4	9.3	9.9	11.0	12.8	14.6	16.5	18.3	20.1	22.0	23.7	25.5
S2	(ref. mm)	2.7	3.3	4.0	4.3	5.3	6.8	7.1	7.9	9.2	10.5	11.9	13.2	14.8	15.7	17.5	18.3

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

23300M · 23300A

6-point Sockets, Deep
Vasos Hexagonales, largos



23300M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
New **7**	10.6	17.4	8	41.5	55	40	10
8	12	17.4	9	41.5	55	45	10
10	14.5	17.4	11	41.5	55	52	10
11	16	17.2	12	41.5	55	55	10
12	16.8	17.2	13	41.5	55	58	10
13	18	17	14	41.5	55	57	10
14	20	18	16	41.5	55	68	10
15	21	20	16	40.5	55	78	10
16	22	20	17	40.5	55	79	10
17	23.5	22	18	40.5	55	96	10
18	24.5	23	19	39.5	55	96	10
19	25	24	20	39.5	55	102	10

23300A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
5/16	12	17.4	9	41.5	55	45	10
3/8	14	17.4	11	41.5	55	51	10
7/16	16	17.2	12	41.5	55	55	10
1/2	18	17	14	41.5	55	57	10
9/16	20	18	16	41.5	55	68	10
11/16	23.5	22	18	40.5	55	96	10
3/4	25	24	20	39.5	55	102	10

23305M

12-point Deep Sockets
Vasos Bihexagonales Largos



23305M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
8	12	17.4	9	41.5	55	45	10
10	14.5	17.4	11	41.5	55	52	10
12	16.8	17.2	13	41.5	55	58	10
14	20	18	16	41.5	55	68	10

23310M

Surface Drive Sockets, Deep
Vasos Surface Drive (de Contacto Curvo) Largos



23310M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
8	12	17.4	9	41.5	55	45	10
10	14.5	17.4	11	41.5	55	52	10
12	16.8	17.2	13	41.5	55	58	10
13	18	17	14	41.5	55	57	10
14	20	18	16	41.5	55	68	10
15	21	20	16	40.5	55	80	10
17	23.5	22	18	40.5	55	96	10

23325

TORX® Deep Sockets
Vasos TORX®, largos



23325 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
E 5	6.9	17.4	5.2	41.5	55	50	10
E 6	7.9	17.4	5.4	41.5	55	52	10
E 7	8.9	17.4	6.6	41.5	55	55	10
E 8	9.9	17.4	7	41.5	55	58	10
E10	11.8	17.2	8.2	41.5	55	60	10
E12	14.5	17.2	9.3	41.5	55	68	10
E14	15.7	17.2	10.6	41.5	55	77	10
E16	18	17	11.8	41.5	55	80	10

23760-75P · -125P · -250P

Extension Bars
Alargaderas



23760	D (mm)	L (mm)	(g)	(pcs.)
75P	18	75	70	10
125P	18	125	110	10
250P	18	250	200	5

TORX® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX® es una marca registrada de **Acument Intellectual Properties, LLC.**

24400M · 24400A

6-point Sockets
Vasos Hexagonales



24400M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
10	15.3	21	9	37	45	10
11	16.5	21	9.5	37	46	10
12	17.8	21	10	37	47	10
13	19	22	10.5	37	53	10
14	20.3	22	11	37	56	10
15	21.5	22	11.5	37	52	10
16	22.8	22	12	37	62	10
17	24.1	23	12.5	37	69	10
18	25.1	24	13	37	74	10
19	26.6	25	14	38	89	10
20	27.9	26	15	38	92	10
21	29.1	27	15.5	38	102	10
22	30.1	28	16	40	113	10
23	31.5	29	16.5	40	128	10
24	32.9	30	17	42	140	5
26	35	32	19	42	165	5
27	36.5	33	19.5	43	196	5
29	39	35	20.5	43	190	5
30	40	36	22	46	222	5
32	42.8	38	23	46	250	5

24400A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
7/16	16.5	21	9.5	37	46	10
1/2	19	22	10.5	37	53	10
9/16	20.3	22	11	37	56	10
5/8	22.9	22	12	37	62	10
3/4	26.6	25	14	38	89	10
15/16	32.9	30	17	42	140	5

24405M

12-point Sockets
Vasos Bihexagonales



24405M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
10	15.3	21	9	37	45	10
12	17.8	21	10	37	47	10
14	20.3	22	11	37	56	10
17	24.1	23	12.5	37	69	10
19	26.6	25	14	38	89	10

24410M

Surface Drive Sockets
Vasos Surface Drive (de Contacto Curvo)



24410M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
10	15.3	21	9	37	45	10
12	17.8	21	10	37	47	10
13	19	22	10.5	37	53	10
14	20.3	22	11	37	56	10
15	21.5	22	11.5	37	52	10
16	22.8	22	12	37	62	10
17	24.1	23	12.5	37	69	10
18	25.1	24	13	37	74	10
19	26.6	25	14	38	89	10
21	29.1	27	15.5	38	102	10
22	30.1	28	16	40	113	10
24	32.9	30	17	42	140	5

24425

TORX® Sockets
Vasos TORX®



24425 (E)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
E10	13.2	21	8.2	36	68	10
E12	14.6	21	9.3	37	70	10
E14	16.5	21	10.6	37	75	10
E16	19	21.9	11.8	37	80	10
E18	20.3	21.9	13	37	83	10
E20	22.9	22	14.4	37	121	10

TORX® (E)



E		E4	E5	E6	E7	E8	E10	E11	E12	E14	E16	E18	E20	E22	E24	E26	E28
S1	(ref. mm)	3.7	4.6	5.6	6.1	7.4	9.3	9.9	11.0	12.8	14.6	16.5	18.3	20.1	22.0	23.7	25.5
S2	(ref. mm)	2.7	3.3	4.0	4.3	5.3	6.8	7.1	7.9	9.2	10.5	11.9	13.2	14.8	15.7	17.5	18.3

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

24300M · 24300A

6-point Sockets, Deep
Vasos Hexagonales, largos



24300M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
10	15.3	21	11	59	77	91	10
11	16.5	21	12	59	77	95	10
12	17.8	21	13	59	77	99	10
13	19	21.8	14	59	77	107	10
14	20.3	21.8	16	59	77	118	10
15	21.5	21.8	16	59	77	123	10
16	22.8	22	17	59	77	141	10
17	24	23	18	59	77	150	10
18	25	24	19	59	77	164	10
19	26.5	25	20	58	77	177	10
20	27.8	26	21	58	77	178	10
21	29	27	23	58	77	187	10
22	30	28	27	57	77	202	10
24	32.8	30	27	57	77	252	10
27	36.5	33	28	56	77	303	10
30	40	36	34	55	77	342	10
32	42.8	38	34	55	77	405	10

24300A (inch)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
7/16	16.5	21	12	59	77	95	10
1/2	19	21.8	14	59	77	107	10
9/16	20.3	21.8	16	59	77	118	10
5/8	22.8	22	17	59	77	141	10
21/32	24	23	18	59	77	150	10
11/16	25	24	19	59	77	164	10
3/4	26.5	25	20	58	77	177	10
13/16	29	27	23	58	77	187	10
15/16	32.8	30	27	57	77	252	10

24305M

12-point Deep Sockets
Vasos Bihexagonales Largos



24305M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
10	15.3	21	11	59	77	91	10
12	17.8	21	13	59	77	99	10
14	20.3	21.8	16	59	77	118	10
17	24	23	18	59	77	150	10
19	26.5	25	20	58	77	177	10

24310M

Surface Drive Sockets, Deep
Vasos Surface Drive (de Contacto Curvo) Largos



24310M (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
10	15.3	21	11	59	77	91	10
12	17.8	21	13	59	77	99	10
13	19	21.8	14	59	77	107	10
14	20.3	21.8	16	59	77	118	10
15	21.5	21.8	16	59	77	123	10
16	22.8	22	17	59	77	141	10
17	24	23	18	59	77	150	10
18	25	24	19	59	77	160	10
19	26.5	25	20	58	77	177	10
21	29	27	23	58	77	187	10
22	30	28	27	57	77	202	10
24	32.8	30	27	57	77	250	10

24760-75P · -125P · -250P

Extension Bars
Alargaderas



24760	D (mm)	L (mm)	(g)	(pcs.)
75P	24	75	140	10
125P	24	125	200	5
250P	24	250	370	5

TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

3/8”

1/2”

Sockets with Turnable Plastic Protectors

Safety

Turnable plastic protector increases operator's safety during assembly process.

Scratch proof

Protector helps to reduce the possibility giving damage on painted, polished and sensitive surfaces. Protector is free rotation designed.

Protector series are make-to-order manufacturing



13400M-FR

6-point Sockets
Vasos Hexagonales

13400M (FR)	D_1 (mm)	D_2 (mm)	ℓ (mm)	L (mm)	⚖ (g)
8FR	15.7	22	6	33.3	40
10FR	18.2	22	7	33.3	40
12FR	20.8	22	9	33.3	43
13FR	21.8	25	10	33.3	56
14FR	23.6	25	10	33.3	56
16FR	26.1	25	11	33.3	57
17FR	27.3	25	12	33.3	60



13760-125P.FR · -250P.FR

Extension Bars
Alargaderas

13760 (FR)	D (mm)	L (mm)	⚖ (g)
125P.FR	26.2	125	145
250P.FR	26.2	250	220



14400M-FR

6-point Sockets
Vasos Hexagonales

14400M (FR)	D_1 (mm)	D_2 (mm)	ℓ (mm)	L (mm)	⚖ (g)
10FR	19.5	28	7	39.3	90
12FR	22	28	9	39.3	90
13FR	23.2	28	10	39.3	90
14FR	24.8	28	11	39.3	90
16FR	27	33	10	39.3	135
17FR	28.2	33	12	39.3	135
19FR	31	33	13	39.3	130



14760-125P.FR · -250P.FR

Extension Bars
Alargaderas

14760 (FR)	D (mm)	L (mm)	⚖ (g)
125P.FR	34.2	125	280
250P.FR	34.2	250	480



115G-100FR · -150FR · -200FR

Nut Setters with Sliding Magnet
Vasos para tuercas con Imán Corredizo



	115G.100 (FR)	D (mm)	ℓ (mm)	H (mm)	L (mm)	⚖ (g)
	8FR	15.1	4	26	100	55
	10FR	16.9	4.5	26	100	60
	12FR	19.3	6	26	100	80
New	**13FR**	20.4	6.5	25	100	85

	115G.150 (FR)	D (mm)	ℓ (mm)	H (mm)	L (mm)	⚖ (g)
	8FR	15.1	4	26	150	75
	10FR	16.9	4.5	26	150	80
	12FR	19.3	6	26	150	100
New	**13FR**	20.4	6.5	25	150	110

	115G.200 (FR)	D (mm)	ℓ (mm)	H (mm)	L (mm)	⚖ (g)
	8FR	15.1	4	26	200	90
	10FR	16.9	4.5	26	200	100
	12FR	19.3	6	26	200	125
New	**13FR**	20.4	6.5	25	200	135

REPLACEMENT

Remove a damaged Protector and put a new Protector on Socket / Extension bar by pressing.
For your safety, worn out or cracked Protector must be replaced.

Specifications or design of any product in this catalogue are subject to change without notice.

Las especificaciones o el diseño de cualquiera de los productos de este catálogo están sujetos a cambio sin previo aviso.

Automotive Tools

3300C · 4300C

Spark Plug Sockets with Spring Clips
Llaves de Bujía con Presillas



3300C (mm)	◻	D (mm)	ℓ (mm)	L (mm)	H (mm)	⚖ (g)	◈ (pcs.)
13	3/8"	17.5	11	70	17	66	10
14		19	11	70	17	82	10
16		20.5	13	70	17	91	10
18		23.9	12	70	21	140	10
20.8		26.9	13.5	70	22	132	10

4300C (mm)	◻	D (mm)	ℓ (mm)	L (mm)	H (mm)	⚖ (g)	◈ (pcs.)
16	1/2"	21	13	70	21	101	10
18		23.9	12	70	21	132	10
20.8		26.9	13.5	70	22	130	10

3300CB

Spark Plug Socket (BMW)
Llave de Bujía (BMW)



3300CB (mm)	◻	D (mm)	ℓ (mm)	L (mm)	H (mm)	⚖ (g)	◈ (pcs.)
16	3/8"	22.8	13	65	19	118	10



SPARK PLUG SOCKETS with SPRING CLIP
An internal brass guide holds the clips in place, which ensures perfect alignment of the spark plug into the threaded plug hole of the cylinder head, thus preventig thread damage.
The brass guide also eliminates stress loading and possible damage to the ceramic insulator of the spark plug.

3305P

Spark Plug Socket with Magnet, 12-point Opening
Llaves de bujía con Imán, Boca Bihex





3305P (mm)	◻	D (mm)	ℓ (mm)	L (mm)	H (mm)	⚖ (g)	◈ (pcs.)
14	3/8"	19	8	70	17	87	10
16		20.5	8	70	17	100	10

Spark Plug Socket with Magnet, 12-pt. opening: 3305P-14

3300S · 4300S

Spark Plug Sockets with Rubber
Llaves de bujía con Goma



3300S (mm)	◻	D (mm)	ℓ (mm)	L (mm)	H (mm)	⚖ (g)	◈ (pcs.)
16	3/8"	20.9	19	70	17	100	10
18		23.9	21	70	21	145	10
20.8		26.9	27	70	22	140	10

4300S (mm)	◻	D (mm)	ℓ (mm)	L (mm)	H (mm)	⚖ (g)	◈ (pcs.)
16	1/2"	21	19	70	21	100	10
18		23.9	21	70	21	130	10
20.8		26.9	27	70	22	135	10

3300C-180 · -250

Spark Plug Sockets with Spring Clips
Llaves de Bujía con Presillas



3300C.180 (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
14	3/8"	19	18	11	180	205	5
16		20.5	18	13	180	220	5
20.8		26.9	18	13.5	180	260	5

3300C.250 (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
14	3/8"	19	18	11	250	271	5
16		20.5	18	13	250	290	5
20.8		26.9	18	13.5	250	340	5

3305P-250

Spark Plug Socket with Magnet, 12-point Opening
Llave de bujía con Imán, Boca Bihex



3305P.250 (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
14	3/8"	19	18	8	250	250	5

3340C · 4340C

Universal Spark Plug Sockets with Spring Clips
Llaves de bujía con Presillas con Articulación Universal



3340C (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
14	3/8"	19	19	11	88	109	10
16		21	19	13	88	122	10
18		23.9	19	12	88	145	10
20.8		26.8	19	13.5	88	174	10

4340C (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
16	1/2"	21	25	13	100	220	10
20.8		26.8	25	13.5	100	250	10

3345P

Universal Spark Plug Socket with Magnet, 12-point opening
Llave de bujía con Imán con Articulación Universal, Boca Bihex



3345P (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
New **14**	3/8"	19	19	8	88	110	10

127C

T-type Universal Spark Plug Socket Wrench
Llave de Bujías en T con Articulación Universal



127C.315 (mm)	D (mm)	ℓ (mm)	L1 (mm)	L2 (mm)	(g)	(pce.)
14	19	11	315	150	520	1
16	21	13	315	150	530	1
18	23.9	12	315	150	590	1
20.8	26.8	13.5	315	150	590	1

3751N
Torque Ratchet for Spark Plugs
Llave de Bujías Dinamométrica

3751J
Torque Ratchet for Spark Plugs
Llave de Bujías Dinamométrica

TORQUE RATCHET
The torque is set at 25Nm. When the torque is loaded higher than 25Nm, the gear slips and no increased torque is transmitted. Cylinder heads and spark plugs are protected by this mechanism.



		D (mm)	T (mm)	H (mm)	L (mm)	(g)	(pce.)
3751N-25	3/8"	34	57	43	178	320	1
3751J-25		34	57	43	178	320	1

3225A
Set for Torque Controlled Installation of Spark Plugs
Juego de Llaves de Bujías Dinamométricas



3225A — 4 Pieces Set/=960g
METAL CASE:W215×H80×T47mm

Sockets	Accessories
3300C Spark Plug Sockets 16, 20.8	**3751J-25** **3763-125**

3701-20Nm · -30Nm
Torque Adaptors 20Nm / 30Nm
Adaptadores de Par 20Nm / 30Nm



3701		D (mm)	L (mm)	(g)	(pce.)
20Nm	3/8"	25.5	75	178	1
30Nm		28	75	220	1

2350G-12PSG

Sockets for PSG-Glow Plugs
Vasos para PSG-Bujías de pre-calentamiento

2350G-PSG (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	H (mm)	(g)	(pcs.)
12	1/4"	16.5	15.5	12	50	41	41	10



3341G-70 · -89

Universal Glow Plug Sockets with NUT GRIP®
Llaves de Calentador con Articulación Universal con Sujeta-Tuercas (Nut Grip®)

3341G.70 (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
10	3/8"	14.5	19	6	70	76	10
11		15.8	19	6	70	80	10
12		17	19	6	70	85	10

3341G.89 (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
8	3/8"	12	19	7.5	89	82	10
9		13.3	19	7.5	89	87	10
10		14.5	19	6	89	92	10
12(DP52)		17	19	12	89	101	10



GLOW PLUG SOCKETS, NUT GRIP®
Twin balls at the 6-point opening hold bolt/nut tightly for safe and reliable work.
El perno/tuerca se sujeta firmemente por medio de dos bolas en la boca hexagonal para un trabajo seguro y fiable

3342G-150

Deep length universal Glow Plug Socket
Llave de Calentador Larga con Articulación Universal

3342G.150 (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
8	3/8"	12	18	7.5	150	137	10



144KM

For Glow Plugs
Para Calentadores

144KM (mm)	L (mm)	D (mm)	C (mm)	(g)	(pce.)
8	200	22.7	7.5	95	1
12	200	22.7	7.5	102	1



148KM

For Glow Plugs
Para Calentadores

148KM (mm)	L (mm)	D1 (mm)	D2 (mm)	C (mm)	(g)	(pce.)
8S×12	245	23.6	24.6	9	187	1



SP4305M-77

Socket for Diesel Engine Injectors
Vaso para Inyectores de Motor Diesel





SP4305M.77 (mm)	⍁	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	⚖ (g)	◈ (pcs.)
27	1/2"	36.5	33	28	77	212	10

SP4305M.77-27
For fuel injection pump of BMW diesel cars.

4133

Socket for Diesel Engine Injectors
Vaso para Inyectores de Motor Diesel



	⍁	D1 (mm)	D2 (mm)	L (mm)	⚖ (g)	◈ (pcs.)
4133	1/2"	23.9	23	55	86	10

4133
For fuel injection pump of M.B diesel cars.

4122-72

Diesel Injection Holder Nut Socket
Vaso Porta Tuerca de Inyección Diesel



4122.72 (mm)	⍁	D1 (mm)	D2 (mm)	D3 (mm)	L (mm)	⚖ (g)	◈ (pcs.)
22	1/2"	28.5	27	22	72	150	10

4122.72-22
For M.B Trucks, Holder nut of injection post.

SP4122-69

Diesel Injection Holder Nut Socket
Vaso Porta Tuerca de Inyección Diesel



SP4122.69 (mm)	D1 (mm)	D2 (mm)	H1 (mm)	H2 (mm)	L (mm)	⚖ (g)	◈ (pcs.)
22	28.4	22	22	32	69	185	5

3300FN

Flare Nut Sockets
Llaves de vaso para entubar





3300FN (mm)	⍁	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	S (mm)	⚖ (g)	◈ (pcs.)
8		14.5	17.3	6	53	6.4	38	10
9		16	17.3	7	53	6.8	41	10
10		16.8	17.2	7.5	53	7.2	42	10
11		18	17	8.5	53	8.3	42	10
12		20	18	9	53	8.8	50	10
13		21.1	20	9.5	62	9.4	66	10
14	3/8"	22	20	10.5	62	10.5	66	10
15		23	22	11	70	11.5	82	10
16		24	23	11.5	70	12	90	10
17		25	24	12.5	80	13	110	10
18		27	25	13	80	13.5	120	10
19		28	26	14	80	14.5	130	10
22		32	29.5	16	80	16	180	10
24		34.5	31.5	17	80	17	200	10

RS3300FN/6

Socket Set on Rail
Juego de Vasos en Regleta

RS3300FN/6	6 Pieces Set/Rail 150mm	⚖ (g)
	8, 10, 12, 14, 17, 19	450

SP4300M-85
SP4300M-110

Special socket for Lambda Probes
Vaso Especial para Sensores Lambda





	⍁	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	S (mm)	⚖ (g)	◈ (pcs.)
SP4300M.85-22	1/2"	33	30	29	85	8	228	10
SP4300M.110-22		33	30	34	110	8	279	10

FLARE NUT SOCKET
Socket for Lambda Probes
Open section allows for use with wire/connector.

4300H

Oil Pressure Switch Sockets
Vasos para Presostatos de Aceite

4300H (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	H1 (mm)	L (mm)	H2 (mm)	⚖ (g)	◈ (pcs.)
24	1/2"	32.5	27	17	40	57	24	157	10
26		35	27	19	40	57	24	170	10
27		36.1	27	19.5	40	57	24	175	10



4300H series
Removes and installs oil pressure switches

4300H (8P)

8-point Socket
Vaso Octagonales

4300H (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	⚖ (g)	◈ (pcs.)
27(8P)	1/2"	34	27	18.5	37	57	152	10



4300H(8P) series
Socket for Switches, Mercedes Benz and MAN

4010M-100 · -120 (12P)

Bit Sockets for Double Inhex Screws (12-point)
Vasos con Punta para Tornillos Doble Inhex (Bihex)

4010M.100 (mm)	☐	D (mm)	H (mm)	L (mm)	⚖ (g)	◈ (pcs.)
8(12P)	1/2"	23	63.5	100	132	10
10(12P)		23	63.5	100	135	10

4010M.120 (mm)	☐	D (mm)	H (mm)	L (mm)	⚖ (g)	◈ (pcs.)
8(12P)	1/2"	23	83.5	120	151	10
10(12P)		23	83.5	120	155	10



Cylinder head bolt socket for TOYOTA
4010M(12P) is Double Hex bit socket.
XZN(Triple Square) bit socket has different shape.

ST4027-140

Head Bolt Bit Socket for VW/AUDI
Vasos con Punta para Perno de Culata VW/AUDI

	☐	D (mm)	H (mm)	L (mm)	⚖ (g)	◈ (pcs.)
ST4027.140	1/2"	23	103.5	140	155	10



Head Bolt Bit Socket for VW/AUDI
ST4027-140 can not substitute with 3027, 4027-CV bit series.

13145M-150 · -200 (12P)

Extra Long Sockets
Vasos Extra-Largos



13145M.150 (12P) (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	⚖ (g)	◈ (pce.)	
10	3/8"	15.8	19	10	150	120	1	*1
12		18.3	19	12	150	128	1	*1

*1 C-Ring=1301C, Pin/O-Ring=1301A•B ➡P250-251

13145M.200 (12P) (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	⚖ (g)	◈ (pce.)	
10	3/8"	15.8	19	10	200	151	1	*1
12		18.3	19	12	200	159	1	*1

*1 C-Ring=1301C, Pin/O-Ring=1301A/B ➡P250-251

16305M

12-point Sockets, Deep
Vasos Bihexagonales Largos

16305M (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	⚖ (g)	◈ (pcs.)	
14	3/4"	26.3	44	14	74	100	500	2	*1
17		30	44	17	74	100	544	2	*1
19		32.5	44	19	74	100	655	2	*1
22		36.3	44	22	74	100	700	2	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A•B ➡P250-251



4109M

Double Square Sockets
Vasos Octagonales



4109M (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
14	1/2"	26.8	26	11	38	110	10
17		30	28	12.5	40	140	10
19		31.5	29	14	40	150	10
21.5		35	32	16	40	170	10
23		37	34	16.5	43	180	10

4109M series
For Lubrication service

4111M

6-point Socket
Vaso Hexagonales



4111M (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
24	1/2"	32	30	17	40	133	10

4111M
For Lubrication service

4020-60 (MH)

Bit Socket for XZN-Screws with hole
Vaso con Punta para Tornillos XZN con agujero



4020.60 (XZN)	☐	D (mm)	H (mm)	L (mm)	(g)	(pcs.)
MH16	1/2"	24	20	60	135	10

4020-60-MH16
Specially designed for oil drain plug on gearbox of AUDI, VW, PORSCHE.

3110M · 3110A

4-point Male Sockets
Vasos con Macho Cuadrado



3110M (mm)	☐	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
6	3/8"	18	10	28	30	10
8		18	10	28	30	10
10		18	10	28	33	10
12		18	10	28	37	10

3110A (inch)	☐	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
5/16	3/8"	18	10	28	30	10
3/8		18	10	28	33	10
1/2		18	10	28	37	10

4110M · 4110A

4-point Male Sockets
Vasos Macho Cuadrado



4110M (mm)	☐	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
8	1/2"	24	10	32	57	10
10		24	10	32	62	10
10.5		24	10	32	64	10
12		24	10	32	64	10
13		24	10	32	66	10
13.5		24	10	32	67	10
19		25	15	37	101	10
20		26	15	37	114	10

4110A (inch)	☐	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
3/8	1/2"	24	10	32	62	10
1/2		24	10	32	64	10

158

For Lubrication Service
Para Lubricación

158 (mm)	L_1 (mm)	L_2 (mm)	d (mm)	(g)	(pce.)
8S×10S	63	230	13	319	1



3012M-25

Inhex Sockets
Vasos con Punta Hexagonal

3012M.25 (mm)		D (mm)	L (mm)	(g)	(pcs.)
14	3/8"	19	25	30	10
17		19	25	30	10



4202

Drain Plug Keys Set
Juego de Llaves de Tapón de Vaciado

4202	7 Pieces Set/=426g

METAL CASE:W190×H59×T45mm

Sockets

106 Drain Plug Keys
8S×10S, 8H×3/8H, 10H×11H, 12H×13H, 14H×17H, 19H

4102 Drain Plug Key Adaptor

106

4-point / 6-point Male bits
Puntas Macho Cuadrado / Hexagonal

106 (mm)	H (mm)	ℓ_1 (mm)	ℓ_2 (mm)	L (mm)	(g)	(pcs.)
8S×10S	17	8	8	32	40	10
8H×3/8H	17	8	8	32	38	10
10H×11H	17	8	8	32	42	10
12H×13H	17	8	8	32	47	10
14H×17H	17	8	8	32	55	10
19H	17	-	8	24	49	10



4102

Adaptor for 106 Drain Plug Key
Adaptador para llave de tapón de Vaciado 106

4102 (mm)		D_1 (mm)	D_2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
17	1/2"	25	24	16	40	82	10



3400M-24

6-point Sockets
Vasos Hexagonales

3400M.24 (mm)		D_1 (mm)	D_2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
27	3/8"	36.5	21.5	13.5	24	76	10
30		40	25	13.5	24	91	10
32		42.8	28	13.5	24	108	10
36		47.2	32	13.5	24	135	10

3400M.24 Series
For Oil Filter



1206 Push and Pull-Ratchet Set
Juego de Llave de Carraca de Empuje y Tracción

1206	3 Pieces Set/=320g
CARDBOARD BOX	
Sockets	Accessory
150.14H Sockets 12, 14	**154K-14**

154K Push and Pull-Ratchets
Llaves de Carraca de Empuje y Tracción



154K (mm)	L (mm)	D (mm)	C (mm)	(g)	(pce.)
14	480	24.6	9	280	1

150-14H Socket, For 154K
Vasos



150.14H (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
10	16	5	17	16	10
12	17.3	5	18	14	10
14	19.2	7	21	17	10

145LH3/8F Belt Tension Pulley Wrench



145LH3/8F (LH-S)		L (mm)	D (mm)	C (mm)	(g)	(pcs.)
10S	3/8"	100	25	15.5	90	10



Belt Tension Pulley Wrench
For LH-10S bolt on TOYOTA engines 1ZZ (1.8L), 1AZ (2.0L) and 2AZ (2.4L), belt tension pulley.

This item has less strength due to the special design.

4282 Generator Service Set

4282	4 Pieces Set/=449g
PLASTIC BAG	
Sockets	
4020.100-M10 **4020.140-M10**	
4025.100R-T50	
185	

Generator Service Set
For removing and installing belt pulley at the generator.

Lhstix® is a registered trademark of **OSG CORPORATION** System Engineering Department.
Lhstix® es una marca registrada de **OSG CORPORATION** System Engineering Department.

1210 · 1210E Door Hinge Wrench Set / Juego de Llave de Bisagra de Puerta

1210	8 Pieces Set/⚖=450g
PLASTIC BAG	
Sockets	**Accessory**
179B.12H Sockets 10, 12	**145KD-12**
179B.12H XZN Bits M6, M8, M10, M12	
179B.12H TORX® Bit T45	

1210E	11 Pieces Set/⚖=460g
PLASTIC BAG	
Sockets	**Accessory**
179B.12H Sockets 10, 12, 13	**145KD-12**
179B.12H XZN Bits M8, M10, M12	
179B.12H TORX® Bits T40, T45, T50	
179B.12H Hex Bit 8	

3247 Bit Socket Set / Juego de Vasos con Punta ⚠

3247	4 Pieces Set/⚖=385g
PLASTIC BAG	
Sockets	
3025.160 Tamper-resistant TORX® Bit Sockets T27H, T30H, T40H, T50H	



For Air Bag
For air-bag unit in hard to reach places in or around the steering wheel.

⚠ Tamper Resistant TORX® Bit Sockets have less strength.

3300M/4-L120 Socket Set / Juego de Vasos

3300M/4-L120	4 Pieces Set/⚖=477g
PLASTIC BAG	
Sockets	
3300M(L120) 6-pt. Extra Deep Sockets 8, 10, 12, 14	

Extra Deep Socket
Extra deep socket can be used to fasten or loosen longer bolts such as Bumper bolt and Door hinge etc.





3350M/2-L120 Socket Set / Juego de Vasos

3350M/2-L120	2 Pieces Set/⚖=230g
PLASTIC BAG	
Sockets	
3350M(L120) Nut Grip Extra Deep Sockets 10, 12	

Nut Grip Extra Deep Socket



TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

1212

Screwdriver Set
Destornilladores, juego de 4 piezas



1212	4 Pieces Set/=380g
PLASTIC BAG	
Screwdrivers	
168T(250) 20IPR	
168T(250) T20, T25, T30	

Long shank Screw Screwdriver

168T(250) (IPR)	ℓ (mm)	L (mm)	(g)	(pce.)
20IPR	250	350	85	1

168T(250) (T)	ℓ (mm)	L (mm)	(g)	(pce.)
T20	250	350	85	1
T25	250	350	85	1
T30	250	360	120	1

168T (250)

Screwdrivers
Destornilladores

169/2

Door Trim Pad Tool, 2 pieces Set
Herramienta de Forro de Puerta, juego de 2 piezas

169

Door Trim Pad Tool
Herramienta de Forro de Puerta



169/2	2 Pieces Set/=200g
PLASTIC BAG	
Clip Handles	
169 6, 10	

169	ℓ (mm)	L (mm)	(g)	(pcs.)
6	115	215	80	2
10	120	230	110	2



Clip Handle

169WM

Window Molding Remover
Extractor de Burletes de Ventana

	ℓ (mm)	L (mm)	(g)	(pcs.)
169WM	100	210	90	2

Window Molding Remover

169HR/2

Hose Remover, 2 pieces Set
Extractor de Mangueras, juego de 2 piezas

169HR-A

Hose Remover
Extractor de Mangueras



New 169HR/2 — 2 Pieces Set/=180g

PLASTIC BAG

Hose Remover
169HR A, B

169HR	ℓ (mm)	L (mm)	(g)	(pcs.)
A	100	200	75	2
New **B**	100	200	90	2

Hose Remover

169HR-B

Hose Remover
Extractor de Mangueras



169BP	T×W (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
1.8×13	1.8×13	50	150	60	2

169BP

For Battery Screws



For Battery screw

Quick Fastener

TORX® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX® es una marca registrada de **Acument Intellectual Properties, LLC.**
TORX PLUS® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX PLUS® es una marca registrada de **Acument Intellectual Properties, LLC.**

4425-N

TORX® Sockets
For Nut/Low Profile Head Bolt

4425 (E)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
E10N	1/2"	13.2	21	8.2	36	47	10
E12N		14.6	21	9.3	37	48	10
E14N		16.5	21	10.6	37	50	10
E16N		19	22	11.8	37	60	10
E18N		20.3	22	13	37	60	10
E20N		22.8	22	14.4	37	65	10



RS4425/6-N

Socket Set on Rail
Juego de Vasos en Regleta

RS4425/6-N	6 Pieces Set/Rail 200mm	(g)
E10N, E12N, E14N, E16N, E18N, E20N		370

Engine type : QR/MR
Flywheel bolt for NISSAN : E20N

13145A-150
14145A-150

Extra Long Sockets
Vasos Extra-Largos

thin

13145A.150 (inch)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
9/16(D20)	3/8"	20	19	13	150	130	1	*1

*1 C-Ring=1301C, Pin/O-Ring=1301A/B ➡P250-251

14145A.150 (inch)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
9/16(D20)	1/2"	20	25	13	150	200	1	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➡P250-251
For Land Rover Prop Shaft



13772-P
14772-P

Universal Double Joint
Articulación Universal

	☐	D1 (mm)	D2 (mm)	L (mm)	(g)	(pcs.)	
13772-P	3/8"	22	19	75	120	5	*1
14772-P	1/2"	27	25	90	230	1	*2

*1 C-Ring=1301C,Pin/O-Ring=1301A/B
*2 C-Ring=1401C,Pin/O-Ring=1401A/B ➡P250-251





14305M

12-point Deep Sockets
Vasos Bihexagonales Largos

14305M (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)	
30	1/2"	42	30	30	63	85	457	10	*2
32		44.5	30	32	63	85	542	10	*2
36		49.5	30	36	61	85	635	2	*2

*1 C-Ring=1402C, Pin/O-Ring=1402A/B ➡P250-251



TORX® is a registered trademark of Acument Intellectual Properties, LLC.
TORX® es una marca registrada de Acument Intellectual Properties, LLC.

4101 · 6101 Sockets for Slotted Heads / Vasos para Cabeza Ranurada



4101		TxW (mm)	D (mm)	L (mm)	(g)	(pcs.)
1	1/2"	2.7x18.6	22	40	59	10
2		3.7x24	24	40	79	10
3		3.7x30	30	40	128	10

		TxW (mm)	D (mm)	L (mm)	(g)	(pcs.)
6101	3/4"	6.4x33.5	35	50	205	10

155 Tyre Lever / Llave de Neumáticos



	D (mm)	d (mm)	L (mm)	(g)	(pcs.)
155	22	10	170	100	10

For Motor Cycles

4012M-43 Inhex Sockets / Vasos Inhex



4012M.43 (mm)		D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
20	1/2"	26	11.5	43	130	10
21		26	11.5	43	140	10
22		26	11.5	43	145	10
24		28	11.5	43	170	10
27		32	11.5	43	226	10

4400M-DU Rear Wheel Nut Socket
4405M-DU



4400M		D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
41DU	1/2"	53	45	15	28	240	5
46DU		59	48	15	28	280	5

4405M		D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
36DU	1/2"	47.3	41	15	28	200	5
55DU		71	52	16	31	410	5

6405A-MV Rear Wheel Nut Socket



6405A		D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
2.3/16MV	3/4"	74.6	53	23	52	790	2

For:MV AGUSTA

14201M
Wheel Nut Sockets Set
Juego de Vasos para Rueda

14145PM-110
Wheel Nut Sockets
Vasos para Rueda



14201M	3 Pieces Set/⚖=690g

CARDBOARD BOX:W125×H95×T34mm

Sockets

14145PM.110 Impact Wheel Nut Sockets
17, 19, 21

14145PM.110 (mm)	□	D1 (mm)	D2 (mm)	ℓ (mm)	Shaft Color	⚖ (g)	◇ (pcs.)	
17	1/2"	23.7	25.2	21		208	5	*1
19		25.7	27.2	23		219	5	*1
21		27.5	29	25		226	5	*1
22		29	30.5	26		238	5	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➡P250-251

Impact Wheel Nut Sockets-Extra Thin wall
Special design for wheel nut work.
-110mm length gives socket extra reach for nuts recessed deep inside the wheel and ideal for Aluminum wheel nuts where access to nut is very tight.
-Blue (17mm), Red (19mm), Yellow (21mm) and White (22mm), colour coded shafts make size identification easy.
-Plastic insert helps prevent damaged to wheel nut.

⚠ Please note that thin walled design is only for wheel nut work and Torque rating is limited.

198-17 : Spare Plastic Protector for 14145PM.110-17 : **10 pcs.**
198-19 : Spare Plastic Protector for 14145PM.110-19 : **10 pcs.**
198-21 : Spare Plastic Protector for 14145PM.110-21 : **10 pcs.**
198-22 : Spare Plastic Protector for 14145PM.110-22 : **10 pcs.**

A detachable plastic protector is fitted to the socket to prevent damage to the wheel when working in tight areas.
The socket size and Ko-ken mark printed on the shaft makes it easier to see if the socket is still rotating or stopped.

280PM
Adaptor Socket for Low Profile Wheel Nut
Vaso Adaptador para tuercas de Llantas de perfil bajo



280PM (mm)	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	H (mm)	Shaft Color	⚖ (g)	◇ (pcs.)
19	25.7	27.2	13	52	19		150	5
21	27.5	29	13	55	21		180	5

Designed for Low Profile Wheel nut socket.
Detachable plastic protector is fitted to the adaptor to prevent damage to painted or surface treatment area on the wheel.
The Plastic insert locate inside of the adaptor helps prevent damage to wheel nut.
Colour coded band make size identification easy.

Diseñado para Vasos de Tuercas de Llantas de perfil bajo
Protector plástico desmontable es ajustado al adaptador para proteger la superficie pintada o con recubrimiento superficial de la llanta
El inserto plástico localizado dentro del adaptador, protege la tuerca de la llanta
La banda coloreada consigue una fácil identificación de la medida



4300M (L60)

Wheel Nut Sockets
Vasos para Ruedas



4300M(L60) (mm)	⊿	D (mm)	ℓ (mm)	L (mm)	H (mm)	⚖ (g)	◈ (pcs.)
17	1/2"	23.6	25	60	21	98	10
19		25.1	25	60	21	100	10
21		27.1	25	60	21	102	10

Wheel Nut Sockets

⚠ Please note that thin walled design is only for wheel nut work and Torque rating is limited.

4300M (L110)

Wheel Nut Sockets (Long)
Vasos para Ruedas (Largos)



4300M(L110) (mm)	⊿	D₁ (mm)	D₂ (mm)	ℓ (mm)	L (mm)	⚖ (g)	◈ (pcs.)
17	1/2"	23	22	32	110	155	5
19		25.8	22	32	110	170	5
21		26.8	22	32	110	165	5

⚠ Please note that thin walled design is only for wheel nut work and Torque rating is limited.

14118M

Wheel Nut Sockets, Double Ended
Vasos para Rueda, Dos Bocas



14118M (mm)	⊿	D (mm)	ℓ1 (mm)	ℓ2 (mm)	L (mm)	⚖ (g)	◈ (pcs.)
17×19	1/2"	28	15.5	13	48	150	10
19×21		31	17.5	13	57	177	10
19×22		31	17.5	15	57	187	10

14218M

Wheel Nut Sockets, Double Ended with Extension Bar
Vasos para Rueda, Dos Bocas con Alargado

New 14218M 2 Pieces Set/⚖=360g
CARDBOARD BOX

Sockets	Accessory
14118PM 19×21	**14760ST-B**

Interchangeable Wheel Nut Socket of 19mm and 21mm.

AR14300

Impact Sockets with Exchangeable Aluminium Inlets
Vasos de Impacto con Partes Intermas de Aluminio Recambiables



AR14300 (mm)	⊿	D₁ (mm)	D₂ (mm)	ℓ (mm)	L (mm)	⚖ (g)	◈ (pcs.)	
17	1/2"	28	30	21	65	220	10	*1
19		30	30	24	65	223	10	*1
21		33	30	25	65	237	10	*1

*1 C-Ring=1402C, Pin/O-Ring=1402A/B ➡P250-251

AN14300

Impact Sockets, Aluminium Alloyed, for Aluminium Wheel Nuts
Vasos de Impacto, de Aleación de Aluminio, para tuercas de rueda de aluminio



AN14300 (mm)	⊿	D₁ (mm)	D₂ (mm)	ℓ (mm)	H (mm)	L (mm)	⚖ (g)	◈ (pcs.)	
17	1/2"	25.7	30	17	62	80	85	10	*1
19		28.2	30	19	61	80	89	10	*1
21		30.7	30	21	61	80	93	10	*1

*1 C-Ring=1402C, Pin/O-Ring=1402A/B ➡P250-251

14113J

Impact Sockets with Plastic Stops for Hub Cap Screws
Vasos de Impacto con Topes de Plástico para Tornillos de Tapacubos

14113J (mm)	□	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
17	1/2"	25.7	30	14	80	251	10	*1
19		28.2	30	16	80	286	10	*1
21		30.7	30	20	80	309	10	*1

*1 C-Ring=1402C, Pin/O-Ring=1402A/B ➡P250-251



14113M

For Hub Cap Screws
Para Tornillos de Tapacubos

14113M (mm)	□	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
17	1/2"	25.7	30	34	80	230	10	*1
19		28.2	30	38	80	262	10	*1
21		30.7	30	42	80	285	10	*1

*1 C-Ring=1402C, Pin/O-Ring=1402A/B ➡P250-251



14124

Lock Nut Busters (Double Ended)
Tronzador de Tuercas (Dos Bocas)

14124 (mm)	□	D1 (mm)	D2 (mm)	ℓ1 (mm)	ℓ2 (mm)	L (mm)	(g)	(pcs.)
21×24.5	1/2"	28	29.5	24	25	65	157	10
26×27.5		31.5	35	24.5	24.5	65	197	10



14124/3

Juego Tronzador de Tuercas (Dos Bocas)

14124/3 — 3 Pieces Set/=580g
CARDBOARD BOX:W125×H91×T43mm

Sockets	Accessory
14124 21×24.5 26×27.5	**14760-75B**

14124

Lock Nut Busters
Tronzador de Tuercas

14124 (mm)	□	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
17	1/2"	20.5	25	15	50	83	10	*1
18		21	25	15	50	83	10	*1
18.5		23	25	15	50	95	10	*1
19		25	30	20.5	50	140	10	*2
21		28	30	20.5	50	153	10	*2
24.5		29.5	30	23	50	138	10	*2
26		31.5	30	23	50	147	10	*2
27.5		35	30	23	50	181	10	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B ➡P250-251



RS14124/7

Socket Set on Rail
Juego de Vasos en Regleta

RS14124/7	7 Pieces Set/Rail 250mm	(g)
	18, 18.5, 19, 21, 24.5, 26, 27.5	980

KP14101

Torsion Bars (for tightening only)
Barras de Tosión (Solamente para apriete)



KP14101 (mm×Nm)	□	D (mm)	ℓ (mm)	L (mm)	Shaft Color	(g)	(pcs.)	
17×110Nm	1/2"	24	21	204		230	10	*1
19× 90Nm		26	24	259		250	10	*1
19×110Nm		26	24	213		240	10	*1
21×100Nm		28	27	215		255	10	*1
21×110Nm		28	27	216		250	10	*1
21×130Nm		28	27	207		305	10	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➡P250-251

How to use Torsion Bar:

1. Use with a 1/2" Sq. Dr. Pneumatic impact wrench.
2. Set air pressure 0.6MPa, and set impact wrench dial Medium range.
3. Chose a suitable Torsion bar according to wheel nut size and indicated tightening torque.
4. Attach the torsion bar to impact wrench and apply load.
5. Check the actual tightening torque value with torque wrench.
6. Adjust air pressure or torque value according to the results of check 5.
7. Tight other wheel nut in diagonal order.



Torsion Bars

– Designed for tightening wheel nuts with an impact wrench.
– Prevent the excessive torque road.
– Color coded shafts make size identification easy.

KP14101/6S

Display Stand
Expositor

KP14101/6S	6 Pieces Set/⚖=2,230g
DISPLAY STAND	
Torsion Bars	
KP14101 Impact Torsion Bars (Thin walled) 17×110Nm, 19×90Nm, 19×110Nm, 21×100Nm, 21×110Nm, 21×130Nm	



KP14101/6H

Metal-Wall-Hanger for Workshops
Colgador de Pared Metálico para Talleres

KP14101/6H	6 Pieces Set/⚖=2,230g
HANGER	
Torsion Bars	
KP14101 Impact Torsion Bars (Thin walled) 17×110Nm, 19×90Nm, 19×110Nm, 21×100Nm, 21×110Nm, 21×130Nm	

14112 Torsion Extension Bars (for tightening only) Alargaderas de Torsión (solamente para apriete)



14112	◻	D (mm)	L (mm)	(g)	(pce.)	
90NmP	1/2"	25	208	206	1	*1
95NmP		25	202	200	1	*1
100NmP		25	196	198	1	*1
110NmP		25	213	220	1	*1
120NmP		25	201	219	1	*1
140NmP		25	205	230	1	*1
170NmP		25	195	257	1	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➡P250-251

14101M Torsion Bars (for tightening only) Barras de Torsión (solamente para apriete)



14101M (mm×Nm)	◻	D (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
14× 95Nm	1/2"	22	11	208	230	1	*1
15×110Nm		23.2	11	201	230	1	*1
17× 60Nm		25.7	12	216	227	1	*1
17× 75Nm		25.7	12	228	240	1	*1
17× 95Nm		25.7	12	214	256	1	*1
17×110Nm		25.7	12	204	285	1	*1
17×120Nm		25.7	12	200	284	1	*1
19× 60Nm		28.2	13	219	237	1	*1
19× 90Nm		28.2	13	259	275	1	*1
19×110Nm		28.2	13	214	278	1	*1
19×120Nm		28.2	13	203	297	1	*1
19×135Nm		28.2	13	206	339	1	*1
19×170Nm		28.2	13	190	332	1	*1
21×100Nm		30.7	14	214	288	1	*1
21×120Nm		30.7	14	203	288	1	*1
22×160Nm		32	15	209	385	1	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➡P250-251

16101M · 18101M Torsion Bars (for tightening only) Barras de Torsión (solamente para apriete)



16101M (mm×Nm)	◻	D (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
24×180Nm	3/4"	38.8	24	235	850	1	*1
27×450Nm		42.5	27	280	1236	1	*1
32×600Nm		48.8	32	280	1370	1	*1
33×600Nm		50	33	280	1370	1	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

18101M (mm×Nm)	◻	D (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
24×350Nm	1"	43.5	24	300	1380	1	*1
27×350Nm		47	27	300	1401	1	*1
27×450Nm		47	27	300	1579	1	*1
30×500Nm		51	30	300	1563	1	*1
32×450Nm		53.5	32	300	1600	1	*1
32×550Nm		53.5	32	300	1602	1	*1
32×600Nm		53.5	32	300	1602	1	*1
32×700Nm		51.5	32	300	1630	1	*1
33×550Nm		55	33	300	1638	1	*1
33×600Nm		55	33	300	1638	1	*1
36×600Nm		58.5	36	300	1718	1	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

As the torque could vary with the type and the condition of the impact wrench, we strongly recommend the control with a torque wrench.

Como el par puede varia según el estado de la llave de impacto, se recomienda utilizar una llave dinamométrica.

6102M-400
8102M-400

Extra long Sockets for Wheel Nuts
Vasos de para Rueda Extra-largos



6102M.400 (mm)	◻	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)
41W×21W	3/4"	58	40	14	400	1880	1
32		48.5	40	32	400	1480	1
33		49.8	40	32	400	1500	1

8102M.400 (mm)	◻	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)
41W×21W	1"	58	49.9	14	400	2610	1
32		48.5	49.9	32	400	2210	1
33		49.8	49.9	32	400	2220	1

⚠ 6102M/8102M are for hand use only. Do not use with a poweror impact wrench.

Extra long Socket for wheel nut

Combination type.
41W×21W

16102M-270 · -400
18102M-270 · -400

Extra long Sockets for Wheel Nuts
Vasos de Impact para Rueda Extra-largos



16102M.270 (mm)	◻	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
24	3/4"	38.8	44	24	270	1034	1	*1
27		42.5	44	27	270	1088	1	*1
30		46.3	44	30	270	1144	1	*1
32		48.8	44	32	270	1157	1	*1
33		50	44	32	270	1200	1	*1
36		53.8	44	32	270	1250	1	*1
New 38		56.3	44	32	270	1610	1	*1
New 41		60	44	32	270	1640	1	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

16102M.400 (mm)	◻	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
24	3/4"	38.8	44	24	400	1430	1	*1
27		42.5	44	27	400	1460	1	*1
30		46.3	44	30	400	1510	1	*1
32		48.8	44	32	400	1530	1	*1
33		50	44	32	400	1530	1	*1
36		53.8	44	32	400	2180	1	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

18102M.270 (mm)	◻	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
23	1"	37.3	54	23	270	1627	1	*1
24		38.5	54	24	270	1628	1	*1
26		41	54	26	270	1667	1	*1
27		42.3	54	27	270	1680	1	*1
29		44.8	54	29	270	1680	1	*1
30		46	54	30	270	1680	1	*1
32		48.5	54	32	270	1680	1	*1
33		49.8	54	32	270	1700	1	*1
34		51	54	32	270	1750	1	*1
36		53.5	54	32	270	1750	1	*1
38		56	54	32	270	1822	1	*1
New 41		60	54	32	270	1800	1	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

18102M.400 (mm)	◻	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
23	1"	37.3	54	23	400	1865	1	*1
24		38.5	54	24	400	1869	1	*1
26		41	54	26	400	1925	1	*1
27		42.3	54	27	400	2272	1	*1
29		44.8	54	29	400	2278	1	*1
30		46	54	30	400	2266	1	*1
32		48.5	54	32	400	2322	1	*1
33		49.8	54	32	400	2320	1	*1
34		51	54	32	400	2341	1	*1
36		53.5	54	32	400	2442	1	*1
38		56	54	32	400	2550	1	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

PW6 · PW8

Rear Wheel Nut Sockets
Vasos de Tuerca de Rueda Interna

PW6 (mm×mm)	□	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
32×17	3/4"	47	44	12	75	633	2	*1
35×17		50	44	13	75	673	2	*1
38×20		55	44	14	75	708	2	*1
41×19		58	44	14	80	840	2	*1
41×20		58	44	14	80	840	2	*1
41×21		58	44	14	80	831	2	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

PW8 (mm×mm)	□	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
35×17	1"	50	54	13	83	935	2	*1
38×20		55	54	14	83	1038	2	*1
41×19		58	54	14	87	1100	2	*1
41×20		58	54	14	87	1096	2	*1
41×21		58	54	14	87	1089	2	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

SIZE	VEHICLE	
32 × 17	TOYOTA	(～2t)
35 × 17	NISSAN	(～3t)
	MITSUBISHI	(～1t)
	MAZDA	(～2t)
	ISUZU	(～3.5t)
38 × 20	MITSUBISHI	(2～3.5t)

SIZE	VEHICLE	
41 × 19	MAZDA	(3～4t)
41 × 20	TOYOTA	(2t～)
	DAIHATSU	(2～3.5t)
	HINO	(2～3.5t)
41 × 21	NISSAN	(4t～)
	MITSUBISHI	(2t～)
	ISUZU	(4t～)
	HINO	(4t～)



Tightening / Loosening Outer Nut



Tightening / Loosening Inner Nut



PW8P/4

4 Pieces Set/⚖=4,250g

CARDBOARD BOX:W240×H95×T70mm

Sockets

PW8P Impact Rear Wheel Nut Sockets
35×17, 38×20, 41×19, 41×21

PW8P

Socket set of Rear Wheel Nut Sockets
Juego de Vasos de Tuerca de Rueda Interna

Rear Wheel Nut Sockets
Vasos de Tuerca de Rueda Interna

PW8P (mm×mm)	□	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	Shaft Color	(pcs.)	
35×17	1"	50	54	13	83	935		5	*1
38×20		55	54	14	83	1038		5	*1
41×19		58	54	14	87	1100		5	*1
41×21		58	54	14	87	1089		5	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

PW8L

Rear Wheel Nut Socket (long)
Vasos de Tuerca de Rueda Interna (largos)

PW8L (mm×mm)	□	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
41×21	1"	58	54	15	105	1263	1	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251



PS6 · PS8

Rear Wheel Nut Sockets
Vasos de Tuerca de Rueda Interna

PS6 (mm)	□	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
17	3/4"	40	44	19	53	433	5	*1
19		40	44	19	53	419	5	*1
20		44	44	21	55	483	5	*1
21		44	44	23	57	491	5	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

PS8 (mm)	□	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
17	1"	40	54	19	60	621	2	*1
19		43	54	19	60	648	2	*1
20		45	54	21	62	687	2	*1
21		45	54	23	64	696	2	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251



14466A-200B
14488A-B · -200B

Adaptors
Adaptadores

No Warranty
Sin Garantía

		凹 (sq)	凸 (sq)	L (mm)	(g)	(pce.)	
New	14466A-200B	1/2"	3/4"	200	560	1	*1
New	14488A-B	1/2"	1"	58	280	1	*1
New	14488A-200B	1/2"	1"	200	660	1	*1

*1 C-Ring=1402C, Pin/O-Ring=1402A/B ➡P250-251



(PW8P-41X21 + 14488A-200B + 1/2"SQ. Impact wrench)

14466A-B / 14488A-B
Impact Adaptors (凹1/2" SQ.→凸3/4", 1" SQ.)

For temporary fastening a wheel nut socket for large vehicle with a light duty 1/2" SQ. DR. Impact wrench.

⚠ Socket is not completely locked with the Ball-type adaptor connection. Please beware of accidental socket release.



16316M · 16316A
18316M · 18316A

Rear Wheel Nut Sockets
Vasos de Tuerca de Rueda Interna

16316M (mm×mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
35×17	3/4"	52	44	10	90	865	1	*1
38×20		56	44	13	100	952	1	*1
41×19		59	44	12	100	1037	1	*1
41×21		59	44	15	100	963	1	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

18316M (mm×mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
35×17	1"	52	54	10	108	1153	1	*1
38×20		56	54	13	108	1133	1	*1
41×19		59	54	12	108	1200	1	*1
41×21		59	54	15	108	1155	1	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

16316A (inch×inch)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
1.1/2x13/16	3/4"	56	44	13	100	940	1	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

18316A (inch×inch)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
1.1/2x13/16	1"	59	54	13	108	1120	1	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

16317M · 16317A
18317M · 18317A

Rear Wheel Nut Sockets
Vasos de Tuerca de Rueda Interna



16317M (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
17	3/4"	40	44	22.5	67	485	1	*1
19		40	44	22.5	67	462	1	*1
20		44	44	22.5	67	517	1	*1
21		44	44	22.5	67	489	1	*1
22		44	44	22.5	67	482	1	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

18317M (mm)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
17	1"	40	54	22.5	72	682	1	*1
17.5		40	54	22.5	72	677	1	*1
19		43	54	22.5	72	705	1	*1
20		45	54	22.5	72	723	1	*1
20.5		45	54	22.5	72	723	1	*1
21		45	54	22.5	72	703	1	*1
22		45	54	22.5	72	696	1	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

16317A (inch)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
13/16	3/4"	44	44	22.5	67	489	1	*1

*1 C-Ring=1600C, Pin/O-Ring=1601A/B ➡P250-251

18317A (inch)	☐	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pce.)	
13/16	1"	45	54	22.5	72	703	1	*1

*1 C-Ring=1801C, Pin/O-Ring=1801A/B ➡P250-251

Construction

BD014E

12-point Nut Setters, Deep
Vasos Bihex para Apretar Tuercas, largos



BD014E (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
8	12	12	63	104	45	10
10	14	12	63	104	52	10
12	16.5	18	63	104	61	10
13	17.5	18	63	104	65	10
14	19	18	63	104	72	10
17	22.5	18	60	104	80	10
19	24.5	18	60	104	95	10
21	27	18	60	104	110	10
22	28	18	60	104	112	10
24	30.3	18	60	104	123	10

BD014SE

12-point Nut Setters
Vasos Bihex para Apretar Tuercas



BD014SE (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
8	12	12	36	77	35	10
10	14	12	36	77	38	10
12	16.5	14	36	77	48	10
13	17.5	14	36	77	51	10
14	19	14	36	77	54	10
17	22.5	14	36	77	76	10
19	24.5	14	36	77	83	10
21	27	14	34	77	104	10
22	28	14	34	77	120	10
24	30.3	14	34	77	140	10

BD008E-165 (12P)

12-point Nut Setters, Extra Long
Vasos Bihex para Apretar Tuercas



BD008E.165 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
17(12P)	22.5	17	110	165	105	10
19(12P)	24.5	17	110	165	135	10
21(12P)	27	17	110	165	142	10

BD008E-300 · -500 · -700 (12P)

12-point Nut Setters, Extra Long
Vasos Bihex para Apretar Tuercas



BD008E.300 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
17(12P)	22.5	17	245	300	154	2
New **19(12P)**	24.8	17	245	300	204	2
New **21(12P)**	27.3	17	245	300	214	2

BD008E.500 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
17(12P)	22.5	17	445	500	223	2
New **19(12P)**	24.8	17	445	500	293	2

BD008E.700 (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
17(12P)	22.5	17	645	700	292	2

BD014XE (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
8SF	13	12	49	90	40	10
10SF	15	12	49	90	46	10
12SF	17.5	14	48	90	54	10
13SF	18.5	14	48	90	58	10
14SF	19.8	14	47	90	64	10
17SF	23.5	14	46	90	81	10
19SF	25.5	14	46	90	100	10
21SF	28	14	46	90	123	10
24SF	31.5	14	45	90	137	10

BD014XE-SF

Surface Drive Nut Setters, Semi-Deep
Vasos semi-largos con Mango



BD014E (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
17SF	23.5	18	60	104	94	10
19SF	25.5	18	60	104	100	10
21SF	28	18	60	104	110	10

BD014E-SF

Surface Drive Nut Setters
Vasos con Mango



SURFACE DRIVE

Surface drive sockets are designed to retain contact with flat sides of nut to transmit high torque and reduce nut wear. These sockets are ideal for use on polished nuts, aluminum nuts and nuts with worn out points.

Los vasos de contacto curvo se diseñan para mantener el contacto con las caras planas de la tuerca y transmitir un alto par reduciendo el desgaste de la tuerca. Estos vasos son ideales para utilizarse en tuercas pulidas, tuercas de aluminio y tuercas con puntas gastadas

BD011SE (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
10	14	12	35	100	73	10
12	16.5	12	35	100	77	10
13	17.5	12	35	100	79	10
14	19	12	32	100	82	10
17	22.5	14	32	100	87	10
19	24.5	14	30	100	94	10
21	27	14	30	100	103	10
22	28	14	30	100	104	10

BD011SE

12-point Universal Joint Nut Setters
Vasos Bihex para Apretar Tuercas con Articulación Universal





Color Coded

Easy identification for the sizes.

Light Body Design

BD011SE, BD014E and BD014SE are designed 30% light weight for easy handling.

Dark Colour Chrome Plating

Surface treatment is Dark Colour Chrome Plating.
*except BD008E series

12 point Opening / Surface Drive Opening

Socket opening is designed to 12-point opening and surface drive opening to catch a bolt/nut easy.

BD003E-I



	D (mm)	L (mm)	(g)	(pcs.)
BD003E-I	25	70	95	10

BD013E



BD013E (mm)	D (mm)	ℓ (mm)	H (mm)	L (mm)	(g)	(pcs.)
12	17.8	12.5	63	105	69	10

BD017E

Wing Bolt Socket for Electric Drill
Vaso para Tuerca de Orejetas para Taladro eléctrico



	D (mm)	T (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
BD017E	31	7.3	21	104	158	10

BD018

Wing Bolt Socket
Vaso para Tuerca de Orejetas



	☐	D (mm)	T (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
BD018	3/8"	31	7.3	21	45	113	10	*1

*1 C-Ring=1302C, Pin/O-Ring=1401A/B ➡P250-251

3119

Wing Bolt Socket
Vaso para Tuerca de Orejetas



3119 (mm)	☐	T1×T2 (mm)	D1 (mm)	D2 (mm)	d (mm)	L (mm)	(g)	(pcs.)
3 ×5	3/8"	3 ×5	17	17.3	11	30	30	10
5.5×6		5.5×6	21	19.5	14	33	45	10

For Wing Bolt
Para Tuercas de Mariposa

For Drain Plug in Radiator
Para conectores de drenaje en Radiadores

BD023E

Adaptor
Adaptador

BD023E	⍁	D (mm)	L (mm)	⚖ (g)	(pcs.)
3/8	3/8"	12.5	55	27	10
1/2	1/2"	16.5	60	48	10



BD024E

Universal Adaptors
Adaptadores Universal

BD024E	⍁	D (mm)	L (mm)	⚖ (g)	(pcs.)
3/8	3/8"	19.3	78	63	10
1/2	1/2"	19.3	82	73	10



BD030W-1/2

Adaptor (Quick Release)
Adaptador (Extracción Rápida)

BD030W	⍁	D (mm)	L (mm)	⚖ (g)	(pcs.)
New 1/2	1/2"	23	57	115	10



Use an Impact socket.



123PN-65 · -110 · -150
123PG-65 · -110 · -150

Double ended Bits
Puntas Phillips, simétricas

Magnetic type

123PN.65 123PG.65 (PH)	D (mm)	L (mm)	⚖ (g)	(pcs.)
1	6.35	65	13	10
2	6.35	65	13	10
3	6.35	65	14	10

123PN.110 123PG.110 (PH)	D (mm)	L (mm)	⚖ (g)	(pcs.)
1	6.35	110	25	10
2	6.35	110	25	10
3	6.35	110	26	10

123PN.150 123PG.150 (PH)	D (mm)	L (mm)	⚖ (g)	(pcs.)
1	6.35	150	36	10
2	6.35	150	36	10
3	6.35	150	37	10

Groove position: Japanese model



184.64

Drill Chuck Adaptor
Adaptador porta-brocas para Taladro

184.64	D (mm)	ℓ (mm)	L (mm)	H (mm)	⚖ (g)	(pcs.)
3/8×24UNF	12.5	14.5	64	13	34	10
1/2×20UNF	12.5	15.5	64	13	40	10



14184

Drill Chuck Adaptor
Adaptador porta-brocas para Taladro

14184	⍁	D (mm)	ℓ (mm)	L (mm)	H (mm)	⚖ (g)	◇ (pcs.)	◐
3/8×24UNF	1/2"	25	14.5	44	22	85	10	*1
1/2×20UNF		25	15.5	44	22	88	10	*1

*1 C-Ring=1401C, Pin/O-Ring=1401A/B ➡P250-251



BD004 Impact Screw and Stud Setters
Vasos de Impacto para Atornillar Pernos y Espárragos



BD004 (mm)		D1 (mm)	D2 (mm)	L (mm)	(g)	(pcs.)	
12.5×10	1/2"	30	25	70	236	5	*1
12.5×13		38	30	75	388	5	*2
12.5×16		38	30	75	369	5	*2
20 ×19	3/4"	48	44	90	775	2	*3
20 ×22		48	44	90	752	2	*3
20 ×25		62	44	95	1184	2	*3
20 ×29		62	44	95	1148	2	*3

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B ➡P250-251
*3 C-Ring=1600C, Pin/O-Ring=1601A/B



162E Stud Setters
Vasos de Atornillar Espárragos



162E (mm)	D (mm)	L (mm)	(g)	(pcs.)
10	28	66	107	10

162E (inch)	D (mm)	L (mm)	(g)	(pcs.)
1/4	23	66	83	10
5/16	23	66	82	10
3/8	28	66	107	10
1/2	28	66	108	10

*Renewal Kits→**162RK** ➡P301

142 Stud Setters
Vasos de Atornillar Espárragos

142 (inch)	L (mm)	(g)	(pce.)
5/16	190	304	1
3/8	190	361	1
1/2	190	354	1



141S Stud Puller Ratchets
Extractores de Espárragos de Carraca





141S (mm)	D (mm)	L (mm)	(g)	(pce.)
6	28	120	150	1
8	28	120	150	1
10	32	120	153	1
12	32	120	152	1

141S (inch)	D (mm)	L (mm)	(g)	(pce.)
5/16	28	120	150	1
3/8	32	120	153	1
1/2	32	120	152	1

141 Stud Puller Ratchets
Extractores de Espárragos de Carraca



Stud Puller Ratchet (141S/141/141P)
The three roller system can protect the studs from damage.

El sistema de tres rodillos puede proteger los espárragos de cualquier daño

141 (mm)	D (mm)	L (mm)	(g)	(pce.)
6	28	205	215	1
8	28	205	215	1
10	32	205	234	1
12	32	205	233	1

141 (inch)	D (mm)	L (mm)	(g)	(pce.)
5/16	28	205	215	1
3/8	32	205	234	1
1/2	32	205	233	1

141P Stud Puller Ratchets
Extractores de Espárragos de Carraca



141P (mm)	D (mm)	L (mm)	(g)	(pce.)
6	28	205	210	1
8	28	205	210	1
10	32	205	229	1
12	32	205	227	1

1201 Stud Puller Ratchets Set
Juego de Extractores de Espárragos de Carraca

1201	4 Pieces Set/⚖=973g

METAL CASE:W240×H100×T32mm

Pullers

141S Stud Puller Ratchets
6, 8, 10, 12

BD14400MJ

6-point Sockets for Anchor Screws
Vasos Hexagonales para Pernos de Anclaje



BD14400MJ (mm)	⊿	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
13	1/2"	20.7	25	5	38	140	10	*1
15		23.2	30	5	38	145	10	*2
16		24.5	30	6.5	38	145	10	*2
17		25.7	30	6.5	38	145	10	*2
19		28.2	30	7.5	38	145	10	*2
21		30.7	30	9	38	185	10	*2
24		34.5	30	10.5	38	190	10	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P238-239

BD14410MJ

Surface Drive Sockets for Anchor Screws
Vasos Surface Drive para Pernos de Anclaje



	BD14410MJ (mm)	⊿	D1 (mm)	D2 (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)	
New	**13**	1/2"	20.7	25	5	38	140	10	*1
New	**15**		23.2	30	5	38	145	10	*2
New	**16**		24.5	30	6.5	38	145	10	*2
New	**17**		25.7	30	6.5	38	145	10	*2
New	**19**		28.2	30	7.5	38	145	10	*2
New	**21**		30.7	30	9	38	185	10	*2
New	**24**		34.5	30	10.5	38	190	10	*2

*1 C-Ring=1401C, Pin/O-Ring=1401A/B
*2 C-Ring=1402C, Pin/O-Ring=1402A/B
➡P238-239

BD016E
BD016E-SF

6-point Sockets for Anchor Screws
Vasos Hexagonales para Pernos de Anclaje



BD016E (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
13	19.5	4	50	43	10
17	24.5	5	50	56	10
19	27	6	50	68	10

BD016E (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
13SF	19.5	4	50	43	10
17SF	24.5	5	50	56	10
19SF	27	6	50	68	10

BD016JE
BD016JE-SF

6-point Sockets for Anchor Screws
Vasos Hexagonales para Pernos de Anclaje





BD016JE (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
13	19.5	5	60	66	10
17	24.5	6.5	60	80	10
19	27	7.5	60	90	10

BD016JE (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
13SF	19.5	5	60	66	10
17SF	24.5	6.5	60	80	10
19SF	27	7.5	60	90	10

HA001

Stud Setters
Vasos para Atornillar Espárragos

HA001	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
10(1.5)	15.5	13	47	90	10
12(1.25)	17.2	15	49	100	10
16(2.0)	21	18	52	125	10
20(2.5)	24.5	21	56	155	10
22(2.5)	26.5	27	61	175	10
24(3.0)	28	28	62	185	10
W3/8	14.8	13	47	90	10
W1/2	17.6	15	49	105	10



HA002-130 · -160

Socket for HA001
Vaso para HA001

HA002.130 (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
24	34.5	14	130	246	10

HA002.160 (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
24	34.5	14	160	465	10



HA003-100

Socket for HA001
Vaso para HA001

HA003.100 (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
24	34.5	14	100	155	10



HA004

HA004 (mm)	D (mm)	ℓ (mm)	L (mm)	(g)	(pcs.)
24	31	16.5	58	91	10











170S

Spud Handle Ratchets
Llaves de Carraca con Mango de Cola



	170S (mm)	D (mm)	T (mm)	L (mm)	(g)	(pce.)
	10×12	34	38	250	260	1
New	**10×13**	34	38	250	260	1
New	**10×14**	34	38	250	260	1
New	**11×13**	34	38	250	260	1
	12×14	34	38	250	260	1

171S

Spud Handle Ratchets(Short)
Llaves de Carraca con Mango de Cola(Cortas)





	171S (mm)	D (mm)	T (mm)	L (mm)	(g)	(pce.)
New	**13×17**	44.6	50	250	460	1
	14×17	44.6	50	250	460	1
	17×19	44.6	50	250	460	1
	17×21	44.6	50	250	460	1
New	**17×22**	44.6	50	250	460	1
	19×21	44.6	50	250	460	1
New	**19×22**	44.6	50	250	460	1

171

Spud Handle Ratchets(Long)
Llaves de Carraca con Mango de Cola(Largas)



	171 (mm)	D (mm)	T (mm)	L (mm)	(g)	(pce.)
New	**13×17**	44.6	50	380	630	1
	14×17	44.6	50	380	630	1
	17×19	44.6	50	380	630	1
	17×21	44.6	50	380	630	1
New	**17×22**	44.6	50	380	630	1
	19×21	44.6	50	380	630	1
New	**19×22**	44.6	50	380	630	1

172

Spud Handle Ratchets
Llaves de Carraca con Mango de Cola



	172 (mm)	D (mm)	T (mm)	L (mm)	(g)	(pce.)
New	**19×24**	68	58	380	1100	1
	21×26	68	58	380	1100	1
	22×24	68	58	380	1100	1
	23×26	68	58	380	1100	1
	24×27	68	58	380	1100	1
New	**24×30**	68	58	380	1100	1
	26×32	68	63	380	1100	1
New	**27×32**	68	58	380	1100	1
New	**30×32**	68	58	380	1100	1

171SB-1/2

Spud Handle Ratchet with Push Button(short)
Llave de Carraca con Mango de Cola con Botón(corta)

	▱	D (mm)	T (mm)	L (mm)	⚖ (g)	(pce.)
171SB-1/2	1/2"	44.6	33	250	480	1



171B-1/2

Spud Handle Ratchet with Push Button(Long)
Llave de Carraca con Mango de Cola con Botón(larga)

	▱	D (mm)	T (mm)	L (mm)	⚖ (g)	(pce.)
171B-1/2	1/2"	44.6	33	380	650	1



4300TW

6-point Sockets
Vasos Hexagonales

4300TW (mm)	▱	D_1 (mm)	D_2 (mm)	ℓ (mm)	L (mm)	⚖ (g)	◇ (pcs.)
14	1/2"	20.3	21	15	77	120	10
17		24	21.8	18	77	130	10
19		26.5	21.8	20	77	150	10
21		29	21.8	23	77	150	10



1205

Set
Juego

1205 — 5 Pieces Set/⚖=1,200g

BAG

Sockets	Accessory
4300TW Sockets 14, 17, 19, 21	**171B-1/2**



Ko-ken welcomes customer enquiries for special tools.
New items can be designed and manufactured according to customers requirements. Please enquire through your distributors.

Ko-ken da la bienvenida a todas las solicitudes por herramientas especiales de nuestros clientes.
Productos nuevos pueden ser diseñados y fabricados de a cuerdo a sus necesidades. Por favor haga su solicitud a través nuestra red de distribuidores.

Renewal Kits

2749RK

2752RK 2752N

2753RK 2753N, 2753PS, 2753P, 2753P-160, 2753J, 2774PS, 2774JS, 2774N, 2774P, 2774J

2753BRK 2753NB, 2753PB, 2753JB

2725RK 2725Z, 2726Z

2749RK-3/8 2749PS-3/8, 2749N-3/8, 2749P-3/8, 2774PS-3/8, 2774JS-3/8

3749RK 3749S, 3749N

3749BRK 3749SB

3752RK 3752N, 3752J, 3757, 3776N, 3776P, 3776J



3753RK 3753SM, 3753N, 3753P, 3753P-250, 3753J, 3774PS, 3774P-SR D3753J, 3774N, 3774P, 3774J, 3774NL, 3774PL, 3774JL

3753BRK 3753SMB, 3753NB, 3753PB, 3753JB 3774NB, 3774PB, 3774JB, 3774JBL



3725RK 3725Z, 3725ZS, 3726Z, 3726ZS

168T-6IP (40) TORXPLUS® 6IP Screwdriver for 2725RK

168T-8IP (40) TORXPLUS® 8IP Screwdriver for 3725RK

168T-10IP (40) TORXPLUS® 10IP Screwdriver for 4725RK

		(g)	(pce.)
2749RK	1/4"	30	1
2752RK		42	1
2753RK		30	1
2753BRK		31	1
2725RK		30	1
2749RK-3/8	3/8"	45	1
3749RK		70	1
3749BRK		84	1
3752RK		84	1
3753RK		76	1
3753BRK		77	1
3725RK		50	1
168T-6IP(40)	—	20	1
168T-8IP(40)	—	20	1
New 168T-10IP(40)	—	22	1

3749SRK-1/2 3749S-1/2

3749SBRK-1/2 3749SB-1/2

4749RK 4749N-250 4749N-380, 4749J-380

4750RK 4750N, 4750P, 4750J

4750BRK 4750NB, 4750PB, 4750JB



	☐	(g)	(pce.)
3749SRK-1/2	1/2"	120	1
3749SBRK-1/2		120	1
4749RK		130	1
4750RK		130	1
4750BRK		130	1
4752RK		140	1
4753RK		130	1
4753BRK		130	1
4725RK		130	1
6749RK	3/4"	580	1
6752RK		600	1
8749RK	1"	800	1

4752RK 4752N, 4752J

4753RK 4753N, 4753P, 4753P-410, 4753J, D4753J 4774N, 4774P, 4774P-450, 4774J

4753BRK 4753NB, 4753PB, 4753JB 4774NB, 4774PB, 4774JB



4725RK 4725Z

6749RK 6749, 6749-1000

6752RK 6752



8749RK 8749

2755RK

3755RK

4755RK

6755RK

	⍁	⚖ (g)	👜 (pce.)
2755RK	1/4"	40	1
3755RK	3/8"	98	1
4755RK	1/2"	137	1
6755RK	3/4"	550	1

2768RK 2768N, 2768P, 2768J

3768RK 3768N, 3768P, 3768J
3768ZRK 3768Z

4768RK 4768N, 4768P, 4768J, 4781N-450
4768ZRK 4768Z

6768RK 6768

8768RK 8768

	⍁	⚖ (g)	👜 (pce.)
2768RK	1/4"	9	1
3768RK	3/8"	21	1
3768ZRK	3/8"	21	1
4768RK	1/2"	60	1
4768ZRK	1/2"	60	1
6768RK	3/4"	200	1
8768RK	1"	475	1

3112RK

	☐	(pce.)
3112RK	3/8"	1
4112RK	1/2"	1
6112RK	3/4"	1

4112RK

6112RK

4100MRK
4100ARK



4100MRK (mm)	☐	(pce.)
6	1/2"	1
7		1
8		1
9		1
10		1
10.5		1
11		1
12		1
14		1
16		1

4100ARK (inch)	☐	(pce.)
1/4	1/2"	1
5/16		1
3/8		1
7/16		1
1/2		1
9/16		1
5/8		1

6100MRK



6100MRK (mm)	☐	(pce.)
18	3/4"	1
20		1
22		1
24		1
27		1
28		1
29		1
30		1

162RK



162RK	(pce.)
5/16	1
3/8	1
1/2	1
10	1

Standard Socket

Deep Socket





SOCKET		1/4"		3/8"		1/2"		3/4"		1"
		Standard	Deep	Standard	Deep	Standard	Deep	Standard	Deep	Standard
⬡		2400M 2400A	2300M 2300A	3400M 3400A	3300M 3300A	4400M 4400A	4300M 4300A	6400M 6400A	6300M 6300A	8400M 8400A
○		2405M 2405A	2305M 2305A	3405M 3405A	3305M 3305A	4405M 4405A	4305M 4305A	6405M 6405A	6305M 6305A	8405M 8405A
(mm)	(inch)	φD								
3	1/8	2.5	2.5							
4		3	3							
4.5		3.5	3.5							
5	3/16	4	4							
5.5	7/32	4.5	4.5	4.5	4.5					
6	1/4	4.5	5	5	5					
7	9/32	6.2	6	5.5	6					
8	5/16	6.2	7	6	7	6	7			
9	11/32	8.3	8.3	7	8	7	8			
10	3/8	9.4	9	8	9	8	9			
11	7/16	10	10	9	10	9	10			
12		10	11	10	11	10	11			
13	1/2	11.5	12	11	12	11	12			
14	9/16	13	13	13.5	13.5	12	13			
15	19/32			13	14	13	14			
16	5/8			14	15	14	15			
17	21/32			15	16	15	16	15	16	
18	11/16			15	17	15	17	15	17	
19	3/4			16	18	18	18	16	18	
20	25/32			17	19	18	19	17	19	
21	13/16			18	20	18	20	18	20	
22	7/8			19	21	19	21	19	21	
23				20	22	20	22	20	22	
24	15/16			21	23	21	23	21	23	
25				22	24	22	24	22	24	
26	1			23	25	23	25	23	25	
27	1- 1/16				26	23	26	23	26	23
28						24	27	24	27	24
29	1- 1/8					24	28	24	28	24
30	1- 3/16					25	29	25	29	25
31						26	30	26	30	26
32	1- 1/4					27	31	27	31	27
33	1- 5/16					28	32	28	32	28
34						29	33	29	33	29
35	1- 3/8					30	34	30	34	30
36						31	35	31	35	31
37	1- 7/16					31	36	31	36	31
38	1- 1/2					32	37	32	37	32
39								32	38	32
40	1- 9/16							33	39	33
41	1- 5/8							34	40	34
42								34	41	34
43	1-11/16							35	42	35
44	1- 3/4							36	43	36
45								36	44	36
46	1-13/16							37	45	37
47								38	46	38
48	1- 7/8							38	47	38
	1-15/16							39	48	39
50	2							40	49	40
	2- 1/16							40		

Standard Socket

Deep Socket





SOCKET		1/4"	3/8"		1/2"		3/4"		1"	
		Standard	Standard	Deep	Standard	Deep	Standard	Deep	Standard	Deep
		12400M 12400A	13400M 13400A	13300M 13300A	14400M 14400A	14300M 14300A	16400M 16400A	16300M 16300A	18400M 18400A	18300M 18300A
(mm)	(inch)	ϕ D								
4		3								
4.5	3/16	3								
5		4								
5.5		4								
6	1/4	5	5	5						
7	9/32	5	5	6						
8	5/16	6	6	7	6	7				
9	11/32	7	7	8	7	8				
10	3/8	8	8	9	8	9				
11	7/16	9	9	10	9	10				
12		10	10	11	10	11				
13	1/2	11	11	12	11	12				
14	9/16	12	12	13	12	13				
15			13	14	13	14				
16	5/8		14	15	14	15	14	15		
17	11/16		14	16	14	16	14	16		
18			15	17	15	17	15	17		
19	3/4		16	18	16	18	16	18	16	18
20			17	19	17	19	17	19	17	19
21	13/16		18	20	18	20	18	20	18	20
22	7/8		19	21	19	21	19	21	19	21
23			20		20	22	20	22	20	22
24	15/16		20		21	23	21	23	21	23
25	1				22	24	22	24	22	24
26					23	25	23	25	23	25
27	1- 1/16				23	26	23	26	23	26
28					23	27	24	27	24	27
29	1- 1/8				23	28	25	28	25	28
30	1- 3/16				23	29	26	29	26	29
31					23	30	27	30	27	30
32	1- 1/4				23	31	28	31	28	31
33					25	32	29	32	29	32
34	1- 5/16				25	33	30	33	30	33
35	1- 3/8				25	34	31	34	31	34
36					28	35	32	35	32	35
37	1- 7/16						32	36	32	36
38	1- 1/2						34	37	34	37
40	1- 9/16						34	39	34	39
41	1- 5/8						35	40	35	40
42	1-11/16						35	41	35	41
45	1- 3/4						35	44	35	44
46	1-13/16						40	45	40	45
47							40	46		
	1- 7/8						40	47		

Equivalent Standard Bolt Diameters

of German, American, British, Norwegian, French, and Swedish sizes for Wrenches

Socket Opening		Metric sizes												American sizes																		English sizes		
		SW	Thread diameters											Thread diameters																		Thread Diam		
			ISO R272-1968		German Standard				French Standard	Swedish Standards					ISO R272-1962			Nomal Series		Heavy Series		Nuts			Bolts and Screws					Nuts	W	BS	
					metric																													
minimum dimension 1)	maximum dimension 2)	nominal size of wrench mm	standard hexagon	small hexagon	DIN.....2)	DIN561+564	DIN6914+6915	Danish Stand DS 17	NFE 27-111-19303	Metric large SMS 1412	Metric small SMS 1414	Whitworth large SMS 1413	Whitworth small SMS 1415	Nominal Size of Wrench	Bolts	Nuts	Actual A/F	Bolts	Nuts	Bolts	Nuts	a Normal	b Square	c Heavy	d Normal	e Heavy	f Machine Screws	g Set Screws Square	h Machine Screw Nuts	Whitworth Large	BS 916, 1953 and BS 1083, 1968, 1965	Width across flats inch
2.52	2.58	2.5			1																												
3.02	3.08	3			1.2+1.4																												
3.22	3.28	3.2	1.6		1.6																												
3.23	3.35													1/8	No2											No2+3							
3.52	3.60	3.5			1.7																												
4.01	4.14													5/32		No0+1												No0+1					
4.02	4.12	4	2		2				2.5		2.3																						
4.52	4.62	4.5			2.3						2.6																						
4.83	4.95													3/16	No3.4+5	No2+3	19									No4+5	No10	No2+3					
5.02	5.12	5	2.5		2.5+2.6				3		3																						
5.21	5.33													13/64																			
5.52	5.62	5.5	3		3																												
5.59	5.72													7/32													No12						
6.00	6.13													15/64																			
6.03	6.15	6			3.5				3.5	3	3.5																						
6.40	6.53													1/4	No6+8	No4	25									No6+8	1/4	No4					
6.60	6.70																														1/16		.256
6.82	6.97													17/64																			
7.03	7.15	7	4		4				4+4.5	3.5	4																						
7.19	7.32													9/32										No10									
7.60	7.70																														3/32		.297
7.62	7.77													19/64																			
8.03	8.18													5/16	No10+12	No5+6	31									No10+12	5/16	No5+6					
8.03	8.15	8	5		5	6			5	4	5																						
8.41	8.56													21/64																			
8.70	8.80																														1/8	3/16	.340
8.81	8.97													11/32		No8	34											No8					
9.03	9.15	9			6				5.5	5																							
9.60	9.75													3/8		No10	38							※1/4		1/4	3/8	No10					
10.04	10.19	10	6		6	8			6		6																						
10.39	10.55													13/32																			
11.04	11.19	11	7		7			1/4		6	7		1/4																				
11.18	11.33													7/16	1/4	No12.1/4	44	1/4	1/4			1/4	1/4		1/4		7/16	No12.1/4					
11.38	11.45																														3/16	1/4	.445
11.99	12.14													15/32																			
12.04	12.24	12		8					7		8																						
12.80	12.95													1/2	5/16	5/16	50	5/16	5/16		1/4	5/16		1/4	5/16		5/16	1/2					
13.04	13.24	13	8		8	10						1/4	5/16																				
13.44	13.54																														1/4	5/16	.525
13.60	13.77													17/32																			
14.05	14.27	14		10	8※)			5/16	8	8																							
14.38	14.55													9/16	3/8	3/8	56	3/8	3/8		5/16	3/8	5/16	5/16	3/8		3/8	9/16	5/16				
15.05	15.27	15			10※)						10	5/16	3/8																				
15.18	15.36													19/32																			
15.34	15.44																														5/16	3/8	.600
15.98	16.15													5/8	7/16		62	7/16				3/8		7/16			5/8	3/8					
16.05	16.27	16	Spark plug M10x1.0						9																								
16.77	16.95													21/32																			
17.05	17.30	17	10	12	10	12		3/8	10	10																							
17.58	17.75													11/16		7/16	69		7/16		3/8	7/16		3/8									
18.05	18.30	18	Spark plug M12x1.25								12	3/8	7/16																				
18.16	18.29																														3/8	7/16	.710
19.06	19.36	19	12	14	12	16		7/16	11																								
19.18	19.38													3/4	1/2	1/2	75	1/2	1/2		7/16	1/2	7/16	7/16	1/2			3/4					
19.97	20.17													25/32																			
20.06	20.36	20																															
20.78	20.98													13/16	9/16		81	9/16				1/2		9/16									
20.86	21.16	20.8	Spark plug M14x1.25																														
20.95	21.08																														7/16	1/2	.820
21.06	21.36	21							12		14	7/16	1/2																				
22.06	22.36	22	14	16	14		12	1/2		12+14																							
22.35	22.56													7/8		9/16	88		9/16	1/2	1/2	9/16	9/16	1/2			7/8						
23.06	23.36	23							14			1/2																					
23.52	23.67																														1/2	9/16	.920
23.98	24.21													15/16	5/8	5/8	94	5/8	5/8			5/8		9/16	5/8								
24.06	24.36	24	16	18	16	20					16		5/8																				
24.76	24.99													31/32																			
25.06	25.36	25																															
25.55	25.78													1			100					5/8					1						
25.81	25.96																														9/16	5/8	1.010
26.08	26.48	26	Spark plug M18x1.5																														
27.08	27.48	27	18	20	18		16	5/8		16	18																						
27.13	27.36													1 1/16			106			5/8	5/8			5/8									
28.12	28.30																														5/8	11/16	1.100
28.08	28.48	28										5/8	3/4																				
28.75	29.01													1 1/8	3/4	3/4	112	3/4	3/4			3/4	3/4		3/4			1 1/8					
29.08	29.48	29							18																								
30.08	30.48	30	20	22	20	24					20																						
30.34	30.59													1 3/16																			
30.66	30.84																														11/16	3/4	1.200
31.93	32.18													1 1/4			125			3/4	3/4			3/4				1 1/4					
32.08	32.48	32	22	24	22		20	3/4	20	18+20	22																						
33.08	33.48	33										3/4	7/8																				
33.22	33.43																														3/4	7/8	1.300
33.53	33.81													1 5/16	7/8	7/8	131	7/8	7/8			7/8	7/8		7/8								
34.08	34.48	34									24																						
35.10	35.60	35							22																								
35.13	35.41													1 3/8														1 3/8					
35.51	35.71																														13/16	15/16	1.390
36.10	36.60	36	24	27	24	30	22	7/8		22+24																							

Equivalent Standard Bolt Diameters

of German, American, British, Norwegian, French, and Swedish sizes for Wrenches

Socket Opening		Metric sizes												American sizes																	English sizes		
		SW	Thread diameters												Thread diameters																Thread Diam		
			ISO R272-1968		German Standard				French Standard	Swedish Standards					ISO R272-1962																W	BS	
					metric													Nomal Series		Heavy Series		Nuts			Bolts and Screws					Nuts			
minimum dimension 1)	maximum dimension 2)	nominal size of wrench mm	standard hexagon	small hexagon	DIN.....2)	DIN561+564	DIN6914+6915	Danish Stand DS 17	NFE 27-111-19303)	Metric large SMS 1412	Metric small SMS 1414	Whitworth large SMS 1413	Whitworth small SMS 1415	Nominal Size of Wrench	Bolts	Nuts	Actual A/F	Bolts	Nuts	Bolts	Nuts	Normal a	Square b	Heavy c	Normal d	Heavy e	Machine Screws f	Set Screws Square g	Machine Screw Nuts h	Whitworth Large	BS 916, 1953 and BS 1083, 1968, 1965	Width across flats inch
36.73	37.01													1 7/16			144			7/8	7/8			7/8		7/8						
37.10	37.60	37										7/8	1																			
37.82	38.05																													7/8	1	1.480
38.10	38.60	38							24																							
38.30	38.61													1 1/2	1	1	150	1	1			1	1		1			1 1/2				
39.89	40.20													1 9/16																		
40.36	40.59																													15/16	1 1/16	1.580
41.10	41.60	41	27	30	27		24	1		27																						
41.50	41.81													1 5/8			162			1	1			1		1						
42.10	42.60	42							27			1	1 1/8																			
42.67	42.93																													1	1 1/8	1.670
43.08	43.38													1 11/16	1 1/8	1 1/8	169	1 1/8	1 1/8			1 1/8	1 1/8		1 1/8							
44.70	45.03													1 3/4																		
46.10	46.60	46	30	33	30	36	27	1 1/8	30	30																						
46.28	46.61													1 13/16			181			1 1/8	1 1/8			1 1/8		1 1/8						
47.10	47.60	47										1 1/8	1 1/4																			
47.52	47.80																													1 1/8	1 1/4	1.860
47.88	48.21													1 7/8	1 1/4	1 1/4	188	1 1/4	1 1/4			1 1/4	1 1/4		1 1/4							
50.10	50.60	50	33	36	33			1 1/4	33	33																						
51.08	51.44													2			200			1 1/4	1 1/4			1 1/4		1 1/4						
52.10	52.60	52										1 1/4	1 3/8																			
52.37	52.68																													1 1/4	1 3/8	2.050
52.68	53.04													2 1/16	1 3/8	1 3/8	206	1 3/8	1 3/8			1 3/8	1 3/8		1 3/8							
54.12	54.72	54							36																							
54.25	54.61													2 1/8																		
55.12	55.72	55	36	39	36	42		1 3/8		36																						
55.88	56.26													2 3/16			219			1 3/8	1 3/8			1 3/8		1 3/8						
56.12	56.72	56										1 3/8	1 1/2																			
56.72	57.05																													1 3/8	1 1/2	2.220
57.45	57.84													2 1/4	1 1/2	1 1/2	225	1 1/2	1 1/2			1 1/2	1 1/2		1 1/2							
58.12	58.72	58							39																							
60.12	60.72	60	39		39			1 1/2		39		1 1/2	1 5/8																			
60.66	61.06													2 3/8			238			1 1/2	1 1/2			1 1/2		1 1/2						
61.57	61.92																													1 1/2	1 5/8	2.410
62.23	62.64													2 7/16												1 5/8						
63.12	63.72	63							42																							
63.83	64.24													2 1/2																		
65.12	65.72	65	42		42	48		1 3/8		42		1 5/8	1 3/4																			
65.43	65.86													2 9/16			256							1 5/8		1 5/8						
65.91	66.29																													1 5/8	1 3/4	2.580
67.03	67.46													2 5/8	1 3/4	1 3/4	262	1 3/4	1 3/4						1 3/4							
67.12	67.72	67							45																							
70.12	70.72	70	45		45			1 3/4		45		1 3/4	1 7/8																			
70.26	70.69													2 3/4			275			1 3/4	1 3/4			1 3/4		1 3/4						
70.51	70.92																													1 3/4	2	2.760
71.12	71.72	71							48																							
71.81	72.26													2 13/16											1 7/8							
75.03	75.51													2 15/16			294							1 7/8		1 7/8						
75.15	75.85	75	48		48	56		1 7/8		48		1 7/8	2																			
76.61	77.09													3	2	2	300	2	2						2							
77.15	77.85	77							52																							
79.81	80.31													3 1/8			312			2	2			2		2						
80.15	80.85	80	52		52			2	52		2																					
80.47	80.92																													2	2 1/4	3.150
82.15	82.85	82							56																							
85.15	85.85	85	56		56			2 1/4																								
86.18	86.72													3 3/8											2 1/4							
88.15	88.85	88							60																							
89.36	89.92													3 1/2										2 1/4		2 1/4						
90.15	90.85	90	60		60																											
90.60	91.00																														2 1/2	3.550
94.15	94.85	94							64																							
95.15	95.85	95	64		64			2 1/2																								
95.76	96.34													3 3/4											2 1/2							
98.93	99.52													3 7/8										2 1/2		2 1/2						
99.20	99.60																														2 3/4	3.890
100.15	100.85	100	68		68				68																							
105.20	106.00	105	72		72			2 3/4	72																							
105.33	105.67													4 1/8										2 3/4								
106.60	107.00																														3	4.180
108.51	109.14													4 1/4										2 3/4								
110.20	111.00	110	96		76			3	76																							
114.91	115.57													4 1/2											3							
115.20	116.00	115	80		80																											
116.20	117.00	116							80																							
118.08	118.77													4 5/8										3		3						
120.20	121.00	120	85		85			3 1/4																								

1) max-min, dimensions for metric sizes according to DIN 475/2, series 1
2) DIN 439, 555, 601, 609, 610, 917, 931, 933, 934, 935, 936, 937, 960, 961, 979, 980, 985, 986, 1587, 2510/5, 6330, 6331, 7513, 7964, 7967, 7968, 7976, 7990
3) NFE 27-311 is identical to ISO R 272 since Oct.1969
4) Standards prior to 1966
5) Only applicable to Motor industry(M 10 acc.to DIN 70 613 through 70 618)
6) Standards prior to 1963

ANSI B 18.2.2-1972

a) Hex Flat and Hex Flat Jam Nuts
Hex Nuts and Hex Jam Nuts
Hex Slotted Nuts
Hex Thick Nuts
Hex Thick Slotted Nuts
Hex Castle Nuts
b) Square Nuts
c) Heavy Square Nuts
Heavy Hex Flat Nuts
Heavy Hex Flat Jam Nuts
Heavy Hex Nuts
Heavy Hex Jam Nuts
Heavy Hex Slotted Nuts

ANSI B 18.2.1-1972

d) Square Bolts
Hex Bolts
Hex Cap Screws
Lag Screws
e) Heavy Hex Bolts
Heavy Hex Structual Bolts
Heavy Hex Screws

f) ANSI B 18.6.3-1962
g) ANSI B 18.6.2-1956
h) ANSI B 18.6.3-1962
※ Square Bolt and Lag Screw only

Screw dimension	Hexagon Head Bolt			Hexagon Socket Head Cap Screws			TORX		TORXPLUS		Triple Square	LHSTIX	Ref.) Standard Tightning Torque (Nm)				
	Standard	Compact	High Strength	Standard	Button Head / Shoulder Head	Hexagon Socket Set Serews	T	E	IP	EP [EPL]	XZN	LH-S [LH-SS]	Grade 4.6	Grade 6.8	Grade 8.8	Grade 10.9	Grade 12.9
M2	4			1.5		0.9	T6/T8		6IP				0.12	0.24	0.32	0.45	0.54
M2.5	5			2		1.3	T8		8IP		M3		0.25	0.49	0.65	0.92	1.1
M3	5.5			2.5	2	1.5	T10	E4	8IP/10IP	4EP	M3		0.43	0.87	1.16	1.63	1.96
M3.5	(6)						T15		10IP/15IP				0.68	1.37	1.82	2.56	3.08
M4	7			3	2.5	2	T20/T25	E5	15IP/20IP	5EP	M4	LH4S	1.01	2.02	2.7	3.79	4.54
M5	8			4	3	2.5	T25/T27	E6	20IP/25IP /27IP	6EP [8EPL]	M5	LH5S	2.04	4.09	5.47	7.67	9.18
M6	10			5	4	3	T30	E8	27IP/30IP	8EP [10EPL]	M6	LH6S	3.47	6.97	9.27	13	15.6
M7	11						T40	E8	40IP	8EP [12EPL]			5.85	11.6	15.5	21.8	26.2
M8	13	(12)		6	5	4	T40/T45	E10	40IP/45IP	10EP [14EPL]	M8	LH8S	8.41	16.9	22.5	31.6	37.9
M10	16 (17)	(14)		8	6	5	T50	E12	45IP/50IP	12EP [16EPL]	M10	LH10S [LH8SS]	16.7	33.4	44.5	62.6	75.2
M12	18 (19)	(17)	21 (22)	10	8	6	T55	E14	55IP	14EP [20EPL]	M12	LH12S [LH10SS]	29.1	58.3	77.6	109	131
M14	21 (22)	(19)		12			T55/T60	E14/E18	55IP/60IP	18EP [24EPL]	M14	LH14S [LH12SS]	46.4	92.7	124	174	209
M16	24	(22)	27	14	10	8	T60/T70	E16/E20	60IP/70IP	20EP [26EPL]	M16	LH16S [LH14SS]	72.3	145	194	271	325
M18	27	(24)		(14)			T70/T80	E24	80IP	24EP [30EPL]	M18		100	199	266	373	447
M20	30 (32)	(27/29)	32	17	12	10	T80/T90	E24	90IP	24EP [32EPL]			141	282	376	529	635
M22	34 (32/35)	(30/32)	36	(17)			T90/T100	E28	100IP	24EP [36EPL]			192	384	511	720	865
M24	36 (38)	(32/35)	41	19		12	T100	E32	100IP	32EP [40EPL]			244	488	650	915	1100
M27	41	(36)	46	(19)				E32		32EP			358	713	951	1340	1610
M30	46	(41)	50	22				E36		36EP			484	971	1290	1820	2180
M33	50	(46)		(24)				E40		40EP			661	1320	1760	2470	2970
M36	55 (54)	(50)		27				E44		44EP			848	1690	2260	3180	3810
M39	60 (58)	(55)		(27)									1100	2190	2920	4110	4930
M42	65 (63)			32									1350	2710	3610	5080	6080
M45	70 (67)			(32)									1700	3400	4540	6370	7630
M48	75 (71)			36									2030	4060	5440	7620	9120
M52	80 (77)			(36)									2640	5290	7040	9880	11800
M56	85			41									3270	6560	8710	12300	14800
M60	90												4080	8180	10900	15300	18300
M64	95			46									4930	9890	13100	18500	22300
M68	(100)												5970	12000	16000	22500	27000

*Reference: Hexagon Head Bolt: ISO 4014-4018, 8676, 8768
High Strength Hexagon Bolt: JIS B 1196
Hexagon Socket Head Cap Screws: ISO 7380
Hexagon Socket Button Head Screws: ISO 7380
Hexagon Socket Set Screws: ISO 4026-4029
TORX T/E: TORX Standard TMH series
TORXPLUS IP/EP: TORXPLUS Standard CMH series
Triple Square: DIN 2324/2325
LHSTIX LH-S/SS: LH-S/SS Standard

* Standard Tightening Torque: Calculated based on Torque Coefficient (K): 0.2
Axial Force (Ff) : 60% of Proof Strength(σ)

TORX® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX® es una marca registrada de **Acument Intellectual Properties, LLC.**
TORXplus® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORXplus® es una marca registrada de **Acument Intellectual Properties, LLC.**
LHstix® is a registered trademark of **OSG CORPORATION** System Engineering Department.
LHstix® es una marca registrada de **OSG CORPORATION** System Engineering Department.

TORX® / TORX Plus® BITS



		S1 (mm)	S2 (mm)
T6	6IP	1.7	1.2
T7	7IP	2.0	1.4
T8	8IP	2.3	1.7
T9	9IP	2.5	1.8
T10	10IP	2.7	2.0
T15	15IP	3.3	2.3
T20	20IP	3.9	2.8
T25	25IP	4.5	3.2
T27	27IP	5.0	3.6
T30	30IP	5.6	4.0
T40	40IP	6.7	4.8
T45	45IP	7.9	5.6
T50	50IP	8.9	6.2
T55	55IP	11.3	8.0
T60	60IP	13.3	9.5
T70	70IP	15.6	11.1
T80	80IP	17.6	12.7
T90	90IP	20.0	14.2
T100	100IP	22.2	15.8

TORX Plus® With Hole BITS



	S1 (mm)	S2 (mm)
8IPR	2.2	2.0
9IPR	2.4	2.2
10IPR	2.6	2.4
15IPR	3.1	2.8
20IPR	3.6	3.3
25IPR	4.1	3.8
27IPR	4.7	4.3
30IPR	5.2	4.8
40IPR	6.3	5.7
45IPR	7.4	6.7
50IPR	8.4	7.6
55IPR	10.6	9.7

XZN BITS



	S1 (mm)	S2 (mm)
M4	3.6	3.1
M5	4.8	4.1
M6	6.1	5.1
M8	7.3	6.1
M10	9.7	8.1
M12	11.5	9.7
M14	13.3	11.2
M16	15.7	13.2
M18	16.9	14.2

TORX® / TORX Plus® SOCKETS



		S1 (mm)	S2 (mm)
E4	4EP	3.7	2.7
E5	5EP	4.6	3.3
E6	6EP	5.6	4.0
E7	7EP	6.1	4.3
E8	8EP	7.4	5.3
E10	10EP	9.3	6.8
E11	11EP	9.9	7.1
E12	12EP	11.0	7.9
E14	14EP	12.8	9.2
E16	16EP	14.6	10.5
E18	18EP	16.5	11.9
E20	20EP	18.3	13.2
E22	22EP	20.1	14.8
E24	24EP	22.0	15.7
E26	26EP	23.7	17.5
E28	28EP	25.5	18.3
E30	30EP	27.3	20.0
E32	32EP	29.0	21.3

LHstix® (LH-S) SOCKETS



	S1 (mm)	S2 (mm)
LH3S	3.8	4.7
LH4S	4.5	6.0
LH5S	5.6	7.5
LH6S	6.8	9.0
LH7S	7.9	10.5
LH8S	9.0	12.0
LH10S	11.3	15.0
LH12S	13.6	18.0
LH14S	15.8	21.0
LH16S	18.1	24.0

Ribe CV BITS

	W (mm)	S1 (mm)	S2 (mm)
M5	1.2	5.0	3.8
M6	1.3	6.0	4.5
M7	1.4	7.0	5.0
M8	1.8	8.0	6.0
M9	2.0	9.0	7.1
M10	2.3	10.0	7.4
M12	2.6	12.0	9.0
M13	3.1	13.0	11.0
M14	3.2	14.0	10.4
M16	3.6	16.0	11.9

TORX® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX® es una marca registrada de **Acument Intellectual Properties, LLC.**
TORX Plus® is a registered trademark of **Acument Intellectual Properties, LLC.**
TORX Plus® es una marca registrada de **Acument Intellectual Properties, LLC.**
LHstix® is a registered trademark of **OSG CORPORATION** System Engineering Department.
LHstix® es una marca registrada de **OSG CORPORATION** System Engineering Department.

Conversion Table: American Inches-Decimal Inches-Millimeter

in	dec.in.	0"	1"	2"	3"	4"	5"	6"	7"	8"	9"	10"	11"
		Millimeter(mm)											
	0	0	25.4000	50.8000	76.2000	101.6000	127.0000	152.4000	177.8000	203.2000	228.6000	254.0000	279.4000
1/64	0.01563	0.3969	25.7969	51.1969	76.5969	101.9969	127.3969	152.7969	178.1969	203.5969	228.9969	254.3969	279.7969
1/32	0.03125	0.7938	26.1938	51.5938	76.9938	102.3938	127.7938	153.1938	178.5938	203.9938	229.3938	254.7938	280.1938
3/64	0.04688	1.1906	26.5906	51.9906	77.3906	102.7906	128.1906	153.5906	178.9906	204.3906	229.7906	255.1906	280.5906
1/16	0.06250	1.5875	26.9875	52.3875	77.7875	103.1875	128.5875	153.9875	179.3875	204.7875	230.1875	255.5875	280.9875
5/64	0.07813	1.9844	27.3844	52.7844	78.1844	103.5844	128.9844	154.3844	179.7844	205.1844	230.5844	255.9844	281.3844
3/32	0.09375	2.3813	27.7813	53.1813	78.5813	103.9813	129.3813	154.7813	180.1813	205.5813	230.9813	256.3813	281.7813
7/64	0.10938	2.7781	28.1781	53.5781	78.9781	104.3781	129.7781	155.1781	180.5781	205.9781	231.3781	256.7781	282.1781
1/8	0.12500	3.1750	28.5750	53.9750	79.3750	104.7750	130.1750	155.5750	180.9750	206.3750	231.7750	257.1750	282.5750
9/64	0.14063	3.5719	28.9719	54.3719	79.7719	105.1719	130.5719	155.9719	181.3719	206.7719	232.1719	257.5719	282.9719
5/32	0.15625	3.9688	29.3688	54.7688	80.1688	105.5688	130.9688	156.3688	181.7688	207.1688	232.5688	257.9688	283.3688
11/64	0.17188	4.3656	29.7656	55.1656	80.5656	105.9656	131.3656	156.7656	182.1656	207.5656	232.9656	258.3656	283.7656
3/16	0.18750	4.7625	30.1625	55.5625	80.9625	106.3625	131.7625	157.1625	182.5625	207.9625	233.3625	258.7625	284.1625
13/64	0.20313	5.1594	30.5594	55.9594	81.3594	106.7594	132.1594	157.5594	182.9594	208.3594	233.7594	259.1594	284.5594
7/32	0.21875	5.5563	30.9563	56.3563	81.7563	107.1563	132.5563	157.9563	183.3563	208.7563	234.1563	259.5563	284.9563
15/64	0.23438	5.9531	31.3531	56.7531	82.1531	107.5531	132.9531	158.3531	183.7531	209.1531	234.5531	259.9531	285.3531
1/4	0.25000	6.3500	31.7500	57.1500	82.5500	107.9500	133.3500	158.7500	184.1500	209.5500	234.9500	260.3500	285.7500
17/64	0.26563	6.7469	32.1469	57.5469	82.9469	108.3469	133.7469	159.1469	184.5469	209.9469	235.3469	260.7469	286.1469
9/32	0.28125	7.1438	32.5438	57.9438	83.3438	108.7438	134.1438	159.5438	184.9438	210.3438	235.7438	261.1438	286.5438
19/64	0.29688	7.5406	32.9406	58.3406	83.7406	109.1406	134.5406	159.9406	185.3406	210.7406	236.1406	261.5406	286.9406
5/16	0.31250	7.9375	33.3375	58.7375	84.1375	109.5375	134.9375	160.3375	185.7375	211.1375	236.5375	261.9375	287.3375
21/64	0.32813	8.3344	33.7344	59.1344	84.5344	109.9344	135.3344	160.7344	186.1344	211.5344	236.9344	262.3344	287.7344
11/32	0.34375	8.7313	34.1313	59.5313	84.9313	110.3313	135.7313	161.1313	186.5313	211.9313	237.3313	262.7313	288.1313
23/64	0.35938	9.1281	34.5281	59.9281	85.3281	110.7281	136.1281	161.5281	186.9281	212.3281	237.7281	263.1281	288.5281
3/8	0.37500	9.5250	34.9250	60.3250	85.7250	111.1250	136.5250	161.9250	187.3250	212.7250	238.1250	263.5250	288.9250
25/64	0.39063	9.9219	35.3219	60.7219	86.1219	111.5219	136.9219	162.3219	187.7219	213.1219	238.5219	263.9219	289.3219
13/32	0.40625	10.3188	35.7188	61.1188	86.5188	111.9188	137.3188	162.7188	188.1188	213.5188	238.9188	264.3188	289.7188
27/64	0.42188	10.7156	36.1156	61.5156	86.9156	112.3156	137.7156	163.1156	188.5156	213.9156	239.3156	264.7156	290.1156
7/16	0.43750	11.1125	36.5125	61.9125	87.3125	112.7125	138.1125	163.5125	188.9125	214.3125	239.7125	265.1125	290.5125
29/64	0.45313	11.5094	36.9094	62.3094	87.7094	113.1094	138.5094	163.9094	189.3094	214.7094	240.1094	265.5094	290.9094
15/32	0.46875	11.9063	37.3063	62.7063	88.1063	113.5063	138.9063	164.3063	189.7063	215.1063	240.5063	265.9063	291.3063
31/64	0.48438	12.3031	37.7031	63.1031	88.5031	113.9031	139.3031	164.7031	190.1031	215.5031	240.9031	266.3031	291.7031
1/2	0.50000	12.7000	38.1000	63.5000	88.9000	114.3000	139.7000	165.1000	190.5000	215.9000	241.3000	266.7000	292.1000
33/64	0.51563	13.0969	38.4969	63.8969	89.2969	114.6969	140.0969	165.4969	190.8969	216.2969	241.6969	267.0969	292.4969
17/32	0.53125	13.4938	38.8938	64.2938	89.6938	115.0938	140.4938	165.8938	191.2938	216.6938	242.0938	267.4938	292.8938
35/64	0.54688	13.8906	39.2906	64.6906	90.0906	115.4906	140.8906	166.2906	191.6906	217.0906	242.4906	267.8906	293.2906
9/16	0.56250	14.2875	39.6875	65.0875	90.4875	115.8875	141.2875	166.6875	192.0875	217.4875	242.8875	268.2875	293.6875
37/64	0.57813	14.6844	40.0844	65.4844	90.8844	116.2844	141.6844	167.0844	192.4844	217.8844	243.2844	268.6844	294.0844
19/32	0.59375	15.0813	40.4813	65.8813	91.2813	116.6813	142.0813	167.4813	192.8813	218.2813	243.6813	269.0813	294.4813
39/64	0.60938	15.4781	40.8781	66.2781	91.6781	117.0781	142.4781	167.8781	193.2781	218.6781	244.0781	269.4781	294.8781
5/8	0.62500	15.8750	41.2750	66.6750	92.0750	117.4750	142.8750	168.2750	193.6750	219.0750	244.4750	269.8750	295.2750
41/64	0.64063	16.2719	41.6719	67.0719	92.4719	117.8719	143.2719	168.6719	194.0719	219.4719	244.8719	270.2719	295.6719
21/32	0.65625	16.6688	42.0688	67.4688	92.8688	118.2688	143.6688	169.0688	194.4688	219.8688	245.2688	270.6688	296.0688
43/64	0.67188	17.0656	42.4656	67.8656	93.2656	118.6656	144.0656	169.4656	194.8656	220.2656	245.6656	271.0656	296.4656
11/16	0.68750	17.4625	42.8625	68.2625	93.6625	119.0625	144.4625	169.8625	195.2625	220.6625	246.0625	271.4625	296.8625
45/64	0.70313	17.8594	43.2594	68.6594	94.0594	119.4594	144.8594	170.2594	195.6594	221.0594	246.4594	271.8594	297.2594
23/32	0.71875	18.2563	43.6563	69.0563	94.4563	119.8563	145.2563	170.6563	196.0563	221.4563	246.8563	272.2563	297.6563
47/64	0.73438	18.6531	44.0531	69.4531	94.8531	120.2531	145.6531	171.0531	196.4531	221.8531	247.2531	272.6531	298.0531
3/4	0.75000	19.0500	44.4500	69.8500	95.2500	120.6500	146.0500	171.4500	196.8500	222.2500	247.6500	273.0500	298.4500
49/64	0.76563	19.4469	44.8469	70.2469	95.6469	121.0469	146.4469	171.8469	197.2469	222.6469	248.0469	273.4469	298.8469
25/32	0.78125	19.8438	45.2438	70.6438	96.0438	121.4438	146.8438	172.2438	197.6438	223.0438	248.4438	273.8438	299.2438
51/64	0.79688	20.2406	45.6406	71.0406	96.4406	121.8406	147.2406	172.6406	198.0406	223.4406	248.8406	274.2406	299.6406
13/16	0.81250	20.6375	46.0375	71.4375	96.8375	122.2375	147.6375	173.0375	198.4375	223.8375	249.2375	274.6375	300.0375
53/64	0.82813	21.0344	46.4344	71.8344	97.2344	122.6344	148.0344	173.4344	198.8344	224.2344	249.6344	275.0344	300.4344
27/32	0.84375	21.4313	46.8313	72.2313	97.6313	123.0313	148.4313	173.8313	199.2313	224.6313	250.0313	275.4313	300.8313
55/64	0.85938	21.8281	47.2281	72.6281	98.0281	123.4281	148.8281	174.2281	199.6281	225.0281	250.4281	275.8281	301.2281
7/8	0.87500	22.2250	47.6250	73.0250	98.4250	123.8250	149.2250	174.6250	200.0250	225.4250	250.8250	276.2250	301.6250
57/64	0.89063	22.6219	48.0219	73.4219	98.8219	124.2219	149.6219	175.0219	200.4219	225.8219	251.2219	276.6219	302.0219
29/32	0.90625	23.0188	48.4188	73.8188	99.2188	124.6188	150.0188	175.4188	200.8188	226.2188	251.6188	277.0188	302.4188
59/64	0.92188	23.4156	48.8156	74.2156	99.6156	125.0156	150.4156	175.8156	201.2156	226.6156	252.0156	277.4156	302.8156
15/16	0.93750	23.8125	49.2125	74.6125	100.0125	125.4125	150.8125	176.2125	201.6125	227.0125	252.4125	277.8125	303.2125
61/64	0.95313	24.2094	49.6094	75.0094	100.4094	125.8094	151.2094	176.6094	202.0094	227.4094	252.8094	278.2094	303.6094
31/32	0.96875	24.6063	50.0063	75.4063	100.8063	126.2063	151.6063	177.0063	202.4063	227.8063	253.2063	278.6063	304.0063
63/64	0.98438	25.0031	50.4031	75.8031	101.2031	126.6031	152.0031	177.4031	202.8031	228.2031	253.6031	279.0031	304.4031

in.	dec.in.	12"	13"	14"	15"	16"	17"	18"	19"	20"	21"	22"	23"
		Millimeter(mm)											
	0	304.8000	330.2000	355.6000	381.0000	406.4000	431.8000	457.2000	482.6000	508.0000	533.4000	558.8000	584.2000
1/32	0.03125	305.5938	330.9938	356.3938	381.7938	407.1938	432.5938	457.9938	483.3938	508.7938	534.1938	559.5938	584.9938
1/16	0.06250	306.3875	331.7875	357.1875	382.5875	407.9875	433.3875	458.7875	484.1875	509.5875	534.9875	560.3875	585.7875
3/32	0.09375	307.1813	332.5813	357.9813	383.3813	408.7813	434.1813	459.5813	484.9813	510.3813	535.7813	561.1813	586.5813
1/8	0.12500	307.9750	333.3750	358.7750	384.1750	409.5750	434.9750	460.3750	485.7750	511.1750	536.5750	561.9750	587.3750
5/32	0.15625	308.7688	334.1688	359.5688	384.9688	410.3688	435.7688	461.1688	486.5688	511.9688	537.3688	562.7688	588.1688
3/16	0.18750	309.5625	334.9625	360.3625	385.7625	411.1625	436.5625	461.9625	487.3625	512.7625	538.1625	563.5625	588.9625
7/32	0.21875	310.3563	335.7563	361.1563	386.5563	411.9563	437.3563	462.7563	488.1563	513.5563	538.9563	564.3563	589.7563
1/4	0.25000	311.1500	336.5500	361.9500	387.3500	412.7500	438.1500	463.5500	488.9500	514.3500	539.7500	565.1500	590.5500
9/32	0.28125	311.9438	337.3438	362.7438	388.1438	413.5438	438.9438	464.3438	489.7438	515.1438	540.5438	565.9438	591.3438
5/16	0.31250	312.7375	338.1375	363.5375	388.9375	414.3375	439.7375	465.1375	490.5375	515.9375	541.3375	566.7375	592.1375
11/32	0.34375	313.5313	338.9313	364.3313	389.7313	415.1313	440.5313	465.9313	491.3313	516.7313	542.1313	567.5313	592.9313
3/8	0.37500	314.3250	339.7250	365.1250	390.5250	415.9250	441.3250	466.7250	492.1250	517.5250	542.9250	568.3250	593.7250
13/32	0.40625	315.1188	340.5188	365.9188	391.3188	416.7188	442.1188	467.5188	492.9188	518.3188	543.7188	569.1188	594.5188
7/16	0.43750	315.9125	341.3125	366.7125	392.1125	417.5125	442.9125	468.3125	493.7125	519.1125	544.5125	569.9125	595.3125
15/32	0.46875	316.7063	342.1063	367.5063	392.9063	418.3063	443.7063	469.1063	494.5063	519.9063	545.3063	570.7063	596.1063
1/2	0.50000	317.5000	342.9000	368.3000	393.7000	419.1000	444.5000	469.9000	495.3000	520.7000	546.1000	571.5000	596.9000
17/32	0.53125	318.2938	343.6938	369.0938	394.4938	419.8938	445.2938	470.6938	496.0938	521.4938	546.8938	572.2938	597.6938
9/16	0.56250	319.0875	344.4875	369.8875	395.2875	420.6875	446.0875	471.4875	496.8875	522.2875	547.6875	573.0875	598.4875
19/32	0.59375	319.8813	345.2813	370.6813	396.0813	421.4813	446.8813	472.2813	497.6813	523.0813	548.4813	573.8813	599.2813
5/8	0.62500	320.6750	346.0750	371.4750	396.8750	422.2750	447.6750	473.0750	498.4750	523.8750	549.2750	574.6750	600.0750
21/32	0.65625	321.4688	346.8688	372.2688	397.6688	423.0688	448.4688	473.8688	499.2688	524.6688	550.0688	575.4688	600.8688
11/16	0.68750	322.2625	347.6625	373.0625	398.4625	423.8625	449.2625	474.6625	500.0625	525.4625	550.8625	576.2625	601.6625
23/32	0.71875	323.0563	348.4563	373.8563	399.2563	424.6563	450.0563	475.4563	500.8563	526.2563	551.6563	577.0563	602.4563
3/4	0.75000	323.8500	349.2500	374.6500	400.0500	425.4500	450.8500	476.2500	501.6500	527.0500	552.4500	577.8500	603.2500
25/32	0.78125	324.6438	350.0438	375.4438	400.8438	426.2438	451.6438	477.0438	502.4438	527.8438	553.2438	578.6438	604.0438
13/16	0.81250	325.4375	350.8375	376.2375	401.6375	427.0375	452.4375	477.8375	503.2375	528.6375	554.0375	579.4375	604.8375
27/32	0.84375	326.2313	351.6313	377.0313	402.4313	427.8313	453.2313	478.6313	504.0313	529.4313	554.8313	580.2313	605.6313
7/8	0.87500	327.0250	352.4250	377.8250	403.2250	428.6250	454.0250	479.4250	504.8250	530.2250	555.6250	581.0250	606.4250
29/32	0.90625	327.8188	353.2188	378.6188	404.0188	429.4188	454.8188	480.2188	505.6188	531.0188	556.4188	581.8188	607.2188
15/16	0.93750	328.6125	354.0125	379.4125	404.8125	430.2125	455.6125	481.0125	506.4125	531.8125	557.2125	582.6125	608.0125
31/32	0.96875	329.4063	354.8063	380.2063	405.6063	431.0063	456.4063	481.8063	507.2063	532.6063	558.0063	583.4063	608.8063

Koken MAXIMUM TORQUES — DIN ISO STANDARDS — ANSI STANDARDS

1/4" Sq.Dr. Sockets



1/2" Sq.Dr. Sockets



3/8" Sq.Dr. Sockets



Reversible Ratchets



Extension Bars



Hinge Handles



10099A	242
100H	164
100P	164
100P (PZ)	164
100S	164
100T (T)	164
100T (TH)	164
100X (XZN)	164
101A	159
101B	158
101H	158
101P	158
101S	158
101T (T)	158
101T (TH)	158
102KA	154
102KM	154
102KM (BH)	154
102KT	154
102NA	154
102NM	154
103KA	155
103KA.BH	155
103KM	155
103KT	155
10400A	242
10400M	242
104A	148
104M	148
106	271
107-16	211, 224, 232
107-16 (IP)	211, 224, 232
107-16 (T)	211, 224, 232
107-16 (XZN)	211, 224, 232
107-22	225, 233
107-22 (T)	225, 233
107-32	238
108A	162
108H	162
108P	162
108S	162
108T (T)	162
108T (TH)	162
110	175
112	175
113	172
113-50 (2B)	172
113-50 (E)	172
113UN	174
115	173
115G	174
115G-FR	262
117	175
120	175
1201	142, 291
1202	159
1203	156
1205	295
1206	272
1210	273
1210E	273
1212	274
12137E	169
12139	163
12140	165
12142-F6.3	169
121H	168
121P	168
121T (IP)	169
121T (T)	168
121T (TH)	169
12222AL	186
12233A	186
12300G	186
12300M	186
12365M	186
123PG	167, 289
123PN	167, 289
123PT	167
12400A	184
12400AG	184
12400M	184
12400MG	184
12410M	184
12425	185
12460A	185
12460AG	185
12460M	185
12460MG	185
12465M	185
124M (2B)	149
12760	186
12770	186
127C	265
128H	159
128T	159
13012M	194
1301A	251
1301B	251
1301C	250
13025	194
1302A	251
1302B	251
1302C	250
13103M	143
13134	171, 194
13134M	196
13134T (IP)	196
13134T (T)	196
13134X (XZN)	196
13137E	169
13137H	169
13139	163
13140	165
13142-D6.3	163
13142-F11.2	171, 194
13142-F6.3	169
13145A	275
13145M	197
13145M (12P)	197, 269
13145MG	197
13146M	198
13147M	198
131P	166
131PS	166
131S	166
131T	166
13241M	199
13242M	199
13300A	191
13300G	193
13300M	191
13300XG	191
13301A	192
13301M	192
13301X	191
13305M	192
13306M	192
13310M	192
13322A	199
13325	193
13333AL	199
13344A	199
13365M	193
13400A	187
13400AG	189
13400M	187
13400M-FR	261
13400MG	189
13400-WN	190
13401A	188
13401LH	190
13401M	188
13401MS	187
13405A	187
13405M	187
13406A	188
13406M	188
13410M	189
13425	189
13425-EPL	189
13430M	193
13440A	193
13440M	193
13440T	193
13460A	190
13460AG	190
13460M	190
13460MG	190
13465M	189
135E	175
137	156
13760	198
13760-FR	261
13770	199
13771	199
13772-P	199, 275
138	156
139	156
14012M	208
1401A	251
1401B	251
1401C	250
14025	208
1402A	251
1402B	251
1402C	250
141	142, 291
14100A	141
14100M	141
14101M	281
14103M	143
14106	211
14112	281
14113J	279
14113M	279
14118M	278
14124	279
14124/3	279
14134	171, 208
14134M	210
14134T (IP)	210
14134T (T)	210
14134X (XZN)	210
14137E	169
14139	163
14140	165
14142-D6.3	163
14142-F11.2	171, 208
14142-F6.3	169
14145A	275
14145M	212
14145PM	277
14146M	212
14147M	212
14184	289
141P	142, 291
141S	142, 291
142	290
14201M	277
14207M	215
14208M	215
14209M	214
14210M	214
14210T	214
14210X	214
14218M	278
14241M	215
14242M	215
14245M	215
14300A	205
14300G	207
14300M	205
14301A	205
14301M	205
14301X	204
14305M	206, 275
14306M	206
14310M	206
14325	207
14365M	207
14400A	200
14400M	200
14400M-FR	261
14400MG	202
14400-WN	204
14401A	201
14401LH	204
14401M	201
14401MS	202
14405A	200
14405M	200
14406A	201
14406M	201
14410M	202
14415M	203
14425	203
14425-EPL	203
14433A	214
14440A	207
14440M	207
14444AL	213
14455A	214
14465M	203
14466A	214, 284
14488A	284
144KM	267
145KM-10H	156
145LH3/8F	272
14760	213
14760-FR	261
14770	213
14771	213
14772-P	213, 275
148KM	267
149	250
150-10H	156
150-14H	272
152	250
15300M	217
15310M	217
15400A	216
15400M	216
15410M	216
154K	272
154M	155
154ML	155
155	276
15544A	217
15555AL	217
15566A	217
156M	148
15770	217
157H	150
157P	150
157S	150
157T (T)	150
158	271
1600C	250
1601A	251
1601B	251
1602A	251
1602B	251
160K	153
16101M	281
16102M	282
16106	224
16106-16	224
16107	225
16107-22	225
16134	171
16201A	227
16201M	227
16245M	227
162E	290
162RK	301
16300A	221
16300M	221
16301A	222
16301M	222
16301X	221
16305M	222, 269
16310M	223
16316A	284
16316M	284
16317A	284
16317M	284
16325	223

16400A	218
16400M	218
16401A	219
16401M	219
16405A	218
16405M	218
16410M	219
16425	220
16425-EPL	220
165LM	167
16644A	226
16655A	226
16666AL	226
16688A	226
166P	180
166PS/6	180
166S	180
16760	225
16770	226
16771	226
167A	178
167C (2B)	178
167M	178
168C	181
168CS	181
168H-B	179
168P	181
168P (PZ)	179
168PS/6	181
168R	179
168S	181
168T (250)	274
168T (IP)	298
168T (TH)	179
168T/7 (TH)	179
169	274
169/2	274
169BP	274
169HR/2	274
169HR-A	274
169HR-B	274
169WM	274
1700C	250
1701A	251
1701B	251
1702A	251
1702B	251
170S	294
171	294
17108	238
17108-32	238
171B-1/2	295
171S	294
171SB-1/2	295
172	294
17300A	237
17300M	237
17400A	236
17400M	236
17405A	237
17405M	237
17760	239
17770	239
17788A	239
17799A	239
1801A	251
1801B	251
1801C	250
1802A	251
1802B	251
1802C	250
18101M	281
18102M	282
18104M	231
18106	232
18106-16	232
18107	233
18107-22	233
18300A	230
18300M	230
18301A	231
18301M	231
18301X	230
18310M	231
18316A	284
18316M	284
18317A	284
18317M	284
183H	170, 195, 209, 246
183T (IP)	170, 195, 209, 246
183T (T)	170, 195, 209, 246
183X (XZN)	171, 196, 210, 247
184.64	289
18400A	228
18400M	228
18401A	229
18401M	229
18405A	229
18405M	229
18410M	229
186	175
18760	234
18770	234
18771	234
18866A	235
18877A	235
18888AL	234
1901A	251
1901B	251
1902A	251
1902B	251
19300M	241
19400A	240
19400M	240
19760	241
19770	241
19977A	241
2000 (PH)	42
2000 (PZ)	42
2000Z	22
2001A	251
2001B	251
2002A	251
2002B	251
2005	42
2005Z	22
2010A	43
2010M	43
2010MZ	22
2011M	43
2020	44
2025 (IP)	45
2025 (IPR)	45
2025 (T)	44
2025 (TH)	44
2025Z	23
2127	144
2137	163
2138	165
2201AM	52
2203A	52
2203M	52
22300A	254
22300M	254
2233A	51
22400M	254
22425	254
2250A	52
2250M	52
2254M	52, 159
2257M	53
2260M	53
2261M	53
2262M	53
2274A	53
2274M	53
2275	54
2276	54
2277	54
2277A-12P	54
2285ZE	25
2286Z	25
2300A	39
2300M	39
2300MZ	21
2300W-BA	39
2300X	38
2300XZ	21
2305A	39
2305M	39
2310M	40
2325	40
23300A	256
23300M	256
23305M	256
23310M	256
23325	256
23400A	255
23400M	255
23405M	255
23410M	255
23425	255
2350G-12PSG	267
2350M	41
2350X	38
23760	256
2400A	36
2400M	36
2400MZ	21
2400W-BA	37
2405A	36
2405M	36
2410M	37
2415A	37
2415M	37
2425	38
24300A	258
24300M	258
24305M	258
2430M	42
2430T	42
24310M	258
24400A	257
24400M	257
24405M	257
2440A	41
2440M	41
2440T	42
24410M	257
2441M	42
24425	257
2445A	41
2445M	41
2450MS	38
24760	258
2715	151
2725RK	298
2725Z	24
2725Z-3/8	29
2726Z	24
2726Z-3/8	29
2749N-3/8	78
2749P-1/4HF	163
2749P-3/8	78
2749P-5/16HF	165
2749PS-3/8	78
2749RK	298
2749RK-3/8	298
2752N	47
2752RK	298
2753BRK	298
2753J	46
2753JB	47
2753N	46
2753NB	47
2753P	46
2753PB	47
2753PS	46
2753RK	298
2755	48
2755RK	300
2756	48
2756Z	24
2756Z-3/8	24
2760	49
2760Z	24
2762	48
2763	49
2768J	49
2768N	49
2768P	49
2768RK	300
2769F	50
2769H	50
2769N	50, 182
2769NWF	50, 182
2770	51
2771	51
2771Z	24
2772Z	24
2774J	48
2774JS	47
2774JS-3/8	82
2774N	48
2774P	48
2774P-1/4HF	163
2774P-5/16HF	165
2774PS	47
2774PS-3/8	82
2780	51
2785	51
280PM	277
3000 (PH)	68
3000 (PZ)	68
3001	76
3005	68
3006	76
3010A	69
3010M	69
3010MZ	28
3011M	71
3012A	70
3012M	70, 271
3015M	71
3020	72
3025 (IP)	75
3025 (IPR)	75
3025 (T)	73
3025 (TH)	74
3025-100R (T)	73
3025-100R (TH)	74
3025-50-T35	73
3025Z	28
3027	76
3110A	77, 270
3110M	77, 270
3112G	160
3112N	160
3112RK	301
3116M	149
3117M	67
3119	288
3127	144
3128	145
3129	146
3131A	153
3132	153
3137	77, 163
3138	77, 165
3141	77, 166
3200A	90
3200M	90
3201AMW	90
3206A	90
3206AM	90
3206M	90
3210M	91
3215A	91
3215M	91
3217M	91
3220M	91
3221M	91
3225A	266
3240M	92
3244	91
3247	74, 273
3250M	92
3252M	92

3275	93
3276	93
3277	93
3279AM	93
3285Z	32
3285ZA	32
3285ZE	32
3286Z	31
3300A	61
3300C	264, 265
3300CB	264
3300CZ	27
3300FN	64, 268
3300M	61
3300M (L120)	62
3300M/4-L120	62, 273
3300MZ	27
3300S	264
3300W	63
3300X	60
3300XA	60
3300XZ	26
3305A	61
3305M	61
3305M (L120)	62
3305M/4-L120	62
3305P	264, 265
3305PZ	27
3305W	63
3305X	60
3305XA	60
3310M	62
3322A	89
3322AZ	31
3325	63
3340C	265
3340M	66
3341G	267
3342G	267
3344A	89
3345P	265
3350M	64
3350M (L120)	64
3350M/2-L120	64, 273
3350X	60
3400A	56
3400LH	58
3400M	56, 271
3400MZ	26
3400W	57
3405A	56
3405M	56
3405W	57
3410M	57
3415A	58
3415M	58
3425	58
3425 (2B)	59
3430M	67
3440A	65
3440M	65
3440T	66
3441M	66
3445A	65
3445M	65
3445W	65
3450M	59
3701	266
3715	151
3715S	151
3715SL	151
3715SLK	151
3716	151
3725RK	298
3725Z	29
3725ZS	29
3726Z	30
3726ZS	30
3749BRK	298
3749N	78
3749RK	298
3749S	78
3749S-1/2	108
3749SB	78
3749SB-1/2	108
3749SBRK-1/2	299
3749SRK-1/2	299
3751J	266
3751N	266
3752J	79
3752N	79
3752RK	298
3753BRK	298
3753J	80
3753JB	81
3753N	80
3753NB	81
3753P	80
3753PB	81
3753RK	298
3753SM	80
3753SMB	81
3755	85
3755RK	300
3756	85
3756Z	31
3756ZS	31
3757	85
3760	86
3760Z	30
3762	85
3763	86
3768J	87
3768N	87
3768P	87
3768RK	300
3768Z	30
3768ZRK	300
3769H	88
3769N	88, 182
3769NWF	88, 182
3770	88
3771	88
3771Z	31
3772Z	31
3774J	82
3774JB	83
3774JBL	84
3774JL	84
3774N	82
3774NB	83
3774NL	84
3774P	82
3774PB	83
3774PL	84
3774PS	82
3774P-SR	83
3776J	79
3776N	79
3776P	79
3780	89
3785	89
4000 (PH)	101
4000 (PZ)	101
4001	101
4005	101
4006	101
4010A	102
4010M	102
4010M (12P)	269
4012A	107
4012M	106, 276
4020	103
4020 (MH)	270
4025 (IP)	105
4025 (T)	104
4025-60-T35	104
4027	105
4100A	140
4100ARK	301
4100M	140
4100MRK	301
4101	276
4102	271
4103M	143
4104	142
4109M	270
4110A	270
4110M	270
4111M	270
4112G	160
4112N	160
4112RK	301
4117M	100
4122	268
4127	145
4128	145
4129	147
4132	153
4133	268
4137	163
4138	165
4141	166
4202	271
4203M	143
4203MF	143
4211A	140
4211M	140
4214M	140
4222M	118
4223M	118
4227M	118
4230A	118
4230M	118
4232M	118
4238AM	120
4240A	119
4240M	119
4241A	120
4241M	120
4244A	120
4244M	120
4248M	121
4250M	121
4251A	121
4251M	121
4252A	121
4252M	121
4254	121
4261M	122
4263M	122
4273AM	122
4275	123
4276	123
4277	123
4279AM	123
4282	272
4285Z	34
4285ZE	34
4289M	123
4300A	98
4300C	264
4300H	269
4300H (8P)	269
4300M	98
4300M (L110)	278
4300M (L120)	98
4300M (L60)	278
4300S	264
4300TW	295
4305A	98
4305M	98
4310M	99
4325	99
4325 (L140)	99
4325 (L140)-2B	99
4340C	265
4400A	95
4400LH	97
4400M	94
4400M-DU	276
4400MZ	33
4400W	95
4405A	95
4405M	94
4405M-DU	276
4405W	95
4410M	96
4425	96
4425-EPL	97
4425-N	96, 275
4433A	117
4440A	100
4440M	100
4440T	100
4450M	97
4466A	117
4711X	152
4715	152
4715S	152
4715SL	152
4725RK	299
4725Z	33
4747	117
4749J	108
4749N	108
4749RK	299
4750BRK	299
4750J	109
4750JB	109
4750N	109
4750NB	109
4750P	109
4750PB	109
4750RK	299
4752J	110
4752N	110
4752RK	299
4753BRK	299
4753J	110
4753JB	111
4753N	110
4753NB	111
4753P	110
4753PB	111
4753RK	299
4755	115
4755RK	300
4756	115
4756Z	34
4760	116
4760Z	34
4763	116
4768J	114
4768N	114
4768P	114
4768RK	300
4768Z	33
4768ZRK	300
4770	115
4771	115
4771Z	34
4774J	112
4774JB	113
4774N	112
4774NB	113
4774P	112
4774PB	113
4780	116
4781N	115
4785	117
4788	117
6012M	125
6100M	141
6100MRK	301
6101	276
6102M	282
6112	160
6112RK	301
6201A	130
6201M	130
6212A	130
6212M	130
6260A	131
6260M	131
6268M	131
6300A	125
6300M	125

6305A	125
6305M	125
6400A	124
6400M	124
6405A	124
6405A-MV	276
6405M	124
6425	124
6644A	129
6688A	129
6749	126
6749RK	299
6752	126
6752RK	299
6755	127
6755RK	300
6760	127
6768	128
6768RK	300
6770	129
6785	128
6788	128
8012M	133
8102M	282
8200A	136
8200M	136
8225M	136
8400A	132
8400M	132
8405A	132
8405M	132
8749	134
8749RK	299
8760	133
8768	134
8768RK	300
8770	133
8785	134
8788	134
8866A	133
AG112A	161
AG112F	161
AG112H	161
AG318A	161
AN112A	161
AN112C	161
AN14300	278
AN318A	161
AR14300	278
AS2305A	40
AS2405A	36
AS2445A	41
BD003E-I	288
BD004	290
BD008E (12P)	286
BD011SE	287
BD013E	288
BD014E	286
BD014E-SF	287
BD014SE	286
BD014XE-SF	287
BD016E	292
BD016E-SF	292
BD016JE	292
BD016JE-SF	292
BD017E	288
BD018	288
BD022	175
BD023E	289
BD024E	289
BD030W-1/2	289
BD14400MJ	292
BD14410MJ	292
CLIP.P/5	32
D3753J	80
D4753J	110
HA001	293
HA002	293
HA003	293
HA004	293
KP14101	280
KP14101/6H	280
KP14101/6S	280
NV13134	247
NV13145	245
NV13400	245
NV13760	245
NV14134	247
NV14145	248
NV14400	248
NV14433A	248
NV14760	248
NV16400	249
NV16760	249
P2201AM	55
P2251M	55
P2258M	55
P2281A-12P	55
P2285Z	25
P3262M-6P	92
P4241M	122
PK1301C	250
PK1302C	250
PK1401C	250
PK1402C	250
PK1600C	250
PK1601C	250
PK166PS/6	180
PK168PS/6	181
PK1801C	250
PK2346/6	89
PK2760/6	49
PK2763/6	49
PK3760/6	86
PK3763/6	86
PK4760/5	116
PK4763/5	116
PS6	283
PS8	283
PW6	283
PW8	283
PW8L	283
PW8P	283
PW8P/4	283
R810	155
R810A	157
R810B	157
R810C	157
R810D	157
R810E	157
RS13025/8	194
RS13301X/9	191
RS13401M/9	188
RS13401MS/5	187
RS14012M/10	208
RS14025/6	208
RS14124/7	279
RS14301X/10	204
RS14401M/10	201
RS14401MS/5	202
RS2010A/8	43
RS2010M/7	43
RS2025/7	44
RS2025/7-HOLE	44
RS2025/7-IP	45
RS2025/7-IPR	45
RS2025Z/7	23
RS20XXZ/9	22
RS2127/10	144
RS2127/6	144
RS2300A/9	39
RS2300M/11	39
RS2300MZ/12	21
RS2300X/11	38
RS2300XZ/9	21
RS2305A/9	39
RS2305M/11	39
RS2310M/11	40
RS2350M/4	41
RS2350X/4	38
RS2400A/9	36
RS2400M/11	36
RS2400MZ/12	21
RS2400W/9-BA	37
RS2405A/9	36
RS2405M/11	36
RS2410M/11	37
RS2425/6	38
RS2445A/9	41
RS2450MS/6	38
RS3010A/8	69
RS3010M/8	69
RS3010MZ/8	28
RS3012A/8	70
RS3012M/8	70
RS3015M/8	71
RS3020/6	72
RS3020/7	72
RS3025/8	73
RS3025/8-IP	75
RS3025/8-L100R	73
RS3025/8-L100RH	74
RS3025/9-HOLE	74
RS3025/9-IPR	75
RS3025Z/8	28
RS3027/5	76
RS3127/8	144
RS3129/6	146
RS3300A/9	61
RS3300FN/6	64
RS3300FN/6	268
RS3300M/12	61
RS3300M/8	61
RS3300MZ/12	27
RS3300MZ/8	27
RS3300W/7	63
RS3300X/8	60
RS3300XA/9	60
RS3300XZ/12	26
RS3300XZ/8	26
RS3305A/9	61
RS3305M/12	61
RS3305M/8	61
RS3305W/7	63
RS3305X/8	60
RS3305XA/9	60
RS3310M/12	62
RS3325/9	63
RS3340M/8	66
RS3350M/5	64
RS3350X/4	60
RS3400A/9	56
RS3400LH/7	58
RS3400M/12	56
RS3400M/8	56
RS3400MZ/12	26
RS3400MZ/8	26
RS3400W/7	57
RS3405A/9	56
RS3405M/12	56
RS3405M/8	56
RS3405W/7	57
RS3410M/12	57
RS3425/4 (2B)	59
RS3425/9	58
RS3430M/6	67
RS3440A/8	65
RS3440M/8	65
RS3440T/8	66
RS3441M/5	66
RS3445W/7	65
RS3450M/10	59
RS3450M/8	59
RS3X00MZ/12	27
RS4010A/10	102
RS4010M/10	102
RS4012A/10	107
RS4012M/10	106
RS4020/6	103
RS4025/9	104
RS4025/9-IP	105
RS4027/6	105
RS4127/6	145
RS4129/5	147
RS4300A/10	98
RS4300M/10	98
RS4305A/10	98
RS4305M/10	98
RS4310M/10	99
RS4325/7	99
RS4400A/10	95
RS4400LH/6	97
RS4400M/10	94
RS4400MZ/10	33
RS4400W/8	95
RS4405A/10	95
RS4405M/10	94
RS4405W/8	95
RS4410M/10	96
RS4425/6-EPL	97
RS4425/6-N	96, 275
RS4425/7	96
RS4450M/10	97
RSAL	32
RSAL200-1/4×12	32
RSAL200-3/8×8	32
RSAL300-1/2×10	32
RSAL300-3/8×12	32
RSAS2305A/10	40
RSAS2405A/10	36
RSX025/11-IP	75
RSX025/11-IPR	75
S14240M	215
S3240A	92
S3240M	92
S4240A	119
S4240M	119
SP4122	268
SP4300M	268
SP4305M	268
ST4027	269
TI4261M	138

Reproduction in whole or in part without proper and prior authorization is prohibited.
Prohibida la reproducción total o parcial sin la debida autorización previa.

本商品目錄之全部版權,係歸於株式會社山下工業研究所(Koken TOOL CO.,LTD.)所有,不論其部分或全部,未經本公司許可,均不得複製

2017.08

Koken



Copyright © Ko-ken Tool Co., Ltd.
Printed in Japan

EN.ES 2017-18